Initial raw data clean-up

Overview

This notebook describes my initial exploration and cleaning of the raw data from the fall 2026 CURIOSS OSPO survey.

Import packages and utilities

```
library(readxl)
library(dplyr)
```

```
Attaching package: 'dplyr'

The following objects are masked from 'package:stats':

    filter, lag

The following objects are masked from 'package:base':

    intersect, setdiff, setequal, union
```

```
library(docstring)
```

```
Attaching package: 'docstring'

The following object is masked from 'package:utils':

    ?
```

Define functions

```
remove_uninformative_rows <- function(df) {
  #' Removes rows that contain either
  #' an NA object, an empty string, or a whitespace
  #' string ("  ") in every column.
  #'
  #' @param df Data frame to process.
  #' @return A copy of the data frame with
  #' uninformative rows removed.
  #'
  df %>%
    filter(if_any(everything(), function(x) {
      val <- trimws(x) # trim whitespace
      !is.na(val) & val != ""
    }))
}
```

Read data from excel

After receiving the data from Clare, a password-protected .xlsx file, I copied the data into a new excel file without password protection so R's readxl package could read it. That file is called raw_data.xlsx.

```
data <- readxl::read_excel("data/raw_data.xlsx", col_types = "text", na = c(""))
# Using a workaround to preserve distinction between
# "" and "N/A", because by default read_excel converts
# both of these to NA objects.
data[is.na(data)] <- ""
data[data == "N/A"] <- NA
```

Start exploring the data

```
dim(data)
```

```
[1]  36 198
```

```r
names(data)[1:15]
```

```
 [1] "Response ID"
 [2] "Date submitted"
 [3] "Last page"
 [4] "Start language"
 [5] "Seed"
 [6] "Quota exit"
 [7] "Your organization / institution name"
 [8] "Your email"
 [9] "In which region is your organization located?"
[10] "In which region is your organization located? [Other]"
[11] "Which best describes the open source function at your organization?"
[12] "Which best describes the open source function at your organization? [Other]"
[13] "Where is your OSPO located within your university? [University library]"
[14] "Where is your OSPO located within your university? [Central administration (e.g., centr
[15] "Where is your OSPO located within your university? [Technology transfer, innovation, or
```

My plan:
1. Create a text file that contains a single table for all of simple (multiple choice) quantitative questions.
2. For more complex quantitative questions, create one file/table per question.
3. Create a single file/table for all qualitative questions.

Remove uninformative columns

```r
cols_to_remove <- c(
    "Response ID",
    "Date submitted",
    "Last page",
    "Start language",
    "Seed",
    "Quota exit")

data <- data %>% select(-any_of(cols_to_remove))
dim(data)
```

```
[1]  36 192
```

Remove uninformative rows

```r
data <- remove_uninformative_rows(data)
dim(data)
```

```
[1]  26 192
```