`utils.R` Function Reference

Auto-generated on 2026-11-13

---

write_df_to_file: Write data frame to a tsv file

Description

Exports a data frame as a plain, tab-delimited text file. By default, it is saved in the directory specified by the `data_path` variable in config.yml. Specify a different config variable to change the output path. Include .tsv extension when specifying filename.

Usage

```
write_df_to_file(df, filename, path_key = "data_path", cfg_obj = cfg)
```

Arguments

- `df`: A data frame to be written to file.
- `filename`: A character string specifying the destination file name.

Value

`NULL` (called for its side effect of writing a file).

---

remove_uninformative_rows: Remove Uninformative Rows

Description

Removes rows that contain either an NA object, an empty string, or a whitespace string (" ") in every column.

Usage

```
remove_uninformative_rows(df)
```

Arguments

- `df`: Data frame to process.

Value

A copy of the data frame with uninformative rows removed.

---

count_yes_responses: Count Affirmative Responses

Description

Filters a data frame to retain only columns containing strictly binary yes/no values, counts occurrences of the affirmative value per column in descending order, and calculates the total count across all valid columns. Columns containing non-yes/no entries are automatically ignored.

Usage

```
count_yes_responses(data, yes_val = "Yes", no_val = "No")
```

Arguments

- `data`: A data frame or tibble containing response columns.
- `yes_val`: Character string. The affirmative response value to count. Default is `"Yes"`.
- `no_val`: Character string. The negative response value used alongside `yes_val` to identify valid binary columns. Default is `"No"`.

Value

A tibble with three columns: count, tip, nickname

---

consolidate_org_responses_yn: Consolidate Responses from SATA questions by Organization

Description

Aggregates a data frame by a grouping column (e.g., organization) and creates a single composite row per group. A column receives an affirmative value ("Yes") if at least one entry within the group contains that value (case-insensitive); otherwise, it is assigned the negative value ("No").

Usage

```
consolidate_org_responses_yn(
  data,
  group_col = "organization",
  yes_val = "Yes",
  no_val = "No"
)
```

Arguments

- `data`: A data frame or tibble containing response columns to aggregate.
- `group_col`: Character string. The name of the column to group by. Default is `"organization"`.
- `yes_val`: Character string. The affirmative value to search for. Default is `"Yes"`.
- `no_val`: Character string. The fallback value if no affirmative entry exists. Default is `"No"`.

Value

A consolidated data frame or tibble with one row per unique group.

---

consolidate_org_responses_num: Consolidate Responses from Matrix Questions (numeric) by Organization

Description

Groups a data frame or tibble by organization and replaces multiple responses for the same organization with a single composite row calculated from the average of each numeric column.

Usage

```
consolidate_org_responses_num(df, org_col = organization, na.rm = TRUE)
```

Arguments

- `df`: A data frame or tibble containing survey responses.
- `org_col`: Column representing the organization grouping variable (quoted or unquoted). Defaults to `organization`.
- `na.rm`: Logical. Indicates whether missing values (`NA`) should be stripped when computing column means. Defaults to `TRUE`.

Value

A consolidated tibble containing exactly one row per unique organization with averaged numeric values.

---

tally_matrix_vals_by_org: Summarize Matrix Counts and Map Reference Information

Description

Aggregates numeric responses across organizations for each column, matches the aggregated counts with a reference table using the column `nickname`, and returns a tibble with the count, tip description, and nickname.

Usage

```
tally_matrix_vals_by_org(
  df,
  ref_df = codebook,
  count_fn = function(x) sum(x > 0, na.rm = TRUE)
)
```

Arguments

- `df`: A data frame or tibble containing an `organization` column and numeric response columns.
- `ref_df`: A reference data frame containing at least `nickname` and `tip` columns.
- `count_fn`: A function defining how counts are calculated per column (e.g., sum of positive values vs. sum of scores). Defaults to counting positive responses (`sum(x > 0, na.rm = TRUE)`).

Value

A tibble with three columns: `count`, `tip`, and `nickname`.