Repository Structure Documentation

Finanzas SD – Architecture, Flows & SOPs

Arquitectura, Flujos y Procedimientos

November 11, 2025

1 Repository Structure Documentation

Last Updated: November 9, 2025
Module: Finanzas (R1) - Financial Planning & Service Delivery
Status: Pre-production, AWS SDK integration active

1.1 Overview

This repository contains a multi-module enterprise financial planning application with:
- **SDMT Module**: Service delivery cost tracking and forecasting
- **Finanzas Module (R1)**: Budget management (Rubros catalog, allocation rules)

The application is built with React 19, Vite 6, TypeScript, and Tailwind CSS v4, deployed behind CloudFront at `/finanzas/`.

1.2 Directory Structure

```
/
├── src/                          # Application source code
│   ├── api/                      # Real AWS API clients
│   │   └── finanzasClient.ts     # Finanzas module AWS SDK client
│   ├── components/               # Shared UI components
│   │   ├── ui/                   # Shadcn/Radix UI primitives
│   │   ├── AuthProvider.tsx      # Authentication context
│   │   ├── Navigation.tsx        # Main navigation bar
│   │   ├── Protected.tsx         # Route protection HOC
│   │   └── ...                   # Other shared components
│   ├── config/                   # Configuration files
│   │   └── aws.ts                # AWS Cognito/API configuration
│   ├── contexts/                 # React contexts
│   │   └── ProjectContext.tsx    # Project selection state
│   ├── features/                 # Feature modules (domain-driven)
│   │   ├── HomePage.tsx          # Landing page
│   │   ├── pmo/                  # PMO features
│   │   └── sdmt/                 # SDMT features
│   │       └── cost/             # Cost management
│   │           ├── Catalog/      # Line items catalog
│   │           ├── Forecast/     # Budget forecasting
│   │           ├── Reconciliation/ # Invoice reconciliation
```

```
│   │           ├── Cashflow/     # Cash flow analysis
│   │           ├── Scenarios/    # What-if scenarios
│   │           └── Changes/      # Change requests
│   ├── hooks/                    # Custom React hooks
│   ├── lib/                      # Utilities and services
│   │   ├── api.ts               # Mock API service (PMO/SDMT)
│   │   ├── auth.ts              # Auth utilities
│   │   └── utils.ts             # General utilities
│   ├── mocks/                    # Mock data for development
│   │   ├── baseline*.json       # Project baselines (3 projects)
│   │   ├── billing-plan*.json   # Billing schedules
│   │   ├── forecast*.json       # Forecast data
│   │   ├── invoices*.json       # Invoice samples
│   │   └── ikusi-service-catalog.json # Service catalog
│   ├── modules/                  # Independent feature modules
│   │   └── finanzas/            # Finanzas R1 module
│   │       ├── FinanzasHome.tsx  # Finanzas landing
│   │       ├── RubrosCatalog.tsx # Budget items catalog
│   │       ├── AllocationRulesPreview.tsx # Allocation rules
│   │       └── data/            # Static Finanzas data
│   ├── types/                    # TypeScript type definitions
│   │   └── domain.d.ts          # Domain models
│   ├── App.tsx                   # Root application component
│   └── main.tsx                  # Application entry point
│
├── docs/                         # Documentation
│   ├── archive/                  # Historical implementation docs
│   ├── adr/                      # Architecture decision records
│   ├── architecture/             # System architecture docs
│   ├── ops/                      # Operations guides
│   ├── runbooks/                 # Operational runbooks
│   ├── tree.structure.md         # This file
│   └── *.md                      # Current documentation
│
├── infra/                        # Infrastructure as code
│   └── terraform/                # Terraform configurations
│
├── scripts/                      # Build and deployment scripts
│   ├── create-s3-bucket.sh      # S3 bucket creation
```

```
│   └── generate-docs-pdf.cjs    # PDF documentation generator
│
├── services/                     # Backend services
│   └── finanzas-api/            # Finanzas API (AWS SAM)
│
├── openapi/                      # API specifications
│   └── finanzas.yaml            # Finanzas API contract
│
├── public/                       # Static assets
├── .github/                      # GitHub workflows and configs
├── package.json                  # Dependencies and scripts
├── vite.config.ts               # Vite build configuration
├── tsconfig.json                # TypeScript configuration
└── tailwind.config.js           # Tailwind CSS configuration
```

1.3 Key Architecture Decisions

1.3.1 Data Layer Strategy

The application uses **dual data access patterns** based on module:

PMO/SDMT Modules (Mock-based)

- **File**: `src/lib/api.ts`
- **Purpose**: Mock API service for PMO and SDMT features
- **Data Source**: JSON files in `src/mocks/`
- **Usage**: Development and testing of PMO/SDMT workflows
- **Toggle**: `VITE_USE_MOCK_API=true/false` (default: true in dev)
- **Rationale**: PMO/SDMT backend is not yet implemented; mocks enable UI development

Finanzas Module (AWS SDK-based)

- **File**: `src/api/finanzasClient.ts`
- **Purpose**: Real AWS API client for Finanzas module
- **Data Source**: AWS API Gateway → Lambda → DynamoDB
- **Endpoint**: `https://m3g6am67aj.execute-api.us-east-2.amazonaws.com/dev`
- **Auth**: JWT token in localStorage (`finz_jwt`)
- **Rationale**: Finanzas R1 has live backend infrastructure

1.3.2 Module Separation

No centralization needed - The current structure already provides clean separation: - PMO/SDMT features use mock data layer (`lib/api.ts`) - Finanzas module uses real AWS SDK client (`api/finanzasClient.ts`) - Each module imports from its appropriate data source

1.3.3 Feature Organization

Features are organized by **business domain** under `src/features/`: - `pmo/` - Project Management Office features - `sdmt/` - Service Delivery Management Team features - Finanzas is a standalone module under `src/modules/finanzas/`

This structure supports: - Clear ownership boundaries - Independent deployment (via `BUILD_TARGET` env var) - Gradual backend integration

---

1.4 Mock Data Strategy

1.4.1 Purpose

Mock data enables frontend development while backend services are under construction.

1.4.2 Active Mocks (Retained)

All mock files in `src/mocks/` are **actively used** by PMO/SDMT features: - `baseline*.json` (3 variants: healthcare, fintech, retail) - `billing-plan*.json` (3 variants) - `forecast*.json` (3 variants) - `invoices*.json` (3 variants) - `ikusi-service-catalog.json` (service tier definitions)

1.4.3 Usage Pattern

```
[] // src/lib/api.ts imports mocks import baselineData from '@/mocks/baseline.json';
import serviceCatalog from '@/mocks/ikusi-service-catalog.json';
// Components use ApiService import ApiService from '@/lib/api'; const projects =
await ApiService.getProjects();
```

1.4.4 Future Migration

When PMO/SDMT backend is ready: 1. Set `VITE_USE_MOCK_API=false` in production 2. Update `src/lib/api.ts` to call real endpoints 3. Keep mocks for local development and testing

---

1.5 Removed Components (Cleanup)

1.5.1 Development-Only Components (Removed)

- ❌ `src/pages/_diag/FinanzasDiag.tsx` - Diagnostics dashboard
- ❌ `src/components/RoleDebugPanel.tsx` - Role switching panel
- ❌ Route `/_diag` - Diagnostic route

Rationale: These were dev-time debugging tools not needed in production deployment.

1.5.2 Documentation Cleanup

- ✅ Moved 55+ historical implementation docs to `docs/archive/`
- ✅ Retained essential docs in root: README, PRD, SECURITY, LICENSE
- ✅ Kept `docs/` structure for architectural and operational documentation

---

1.6 Build Configuration

1.6.1 Build Targets

The application supports multiple build targets via `BUILD_TARGET` environment variable:

```
[] # Finanzas-only build (default) BUILD_TARGET=finanzas npm run build
# PMO-only build (future) BUILD_TARGET=pmo npm run build
```

1.6.2 Base Path Configuration

- **Vite base**: `/finanzas/` (configured in `vite.config.ts`)
- **Router basename**: `/finanzas` (configured in `App.tsx`)
- **CloudFront path**: `/finanzas/*` (behavior pattern)
- **S3 prefix**: Objects stored under `finanzas/` key prefix

This ensures: - Deep links work correctly (e.g., `/finanzas/catalog/rubros`) - Assets load properly behind CloudFront - SPA routing functions as expected

---

1.7 Environment Variables

1.7.1 Core Settings

```
[] # API Configuration VITE_API_BASE_URL=https://m3g6am67aj.execute-api.us-east-2.amazonaws.com/dev VITE_USE_MOCK_API=false # Use real API (true for local dev with mocks) VITE_FINZ_ENABLED=true # Enable Finanzas module
# Authentication VITE_SKIP_AUTH=true # Skip auth for development VITE_COGNITO_POOL_ID=u
east-2_FyHLtOhiY VITE_COGNITO_CLIENT_ID=dshos5iou44tuach7ta3ici5m
# Deployment VITE_APP_BASENAME=/finanzas
```

See `.env.production` for full production configuration.

1.8 Testing Strategy

1.8.1 Current State

- No unit test framework installed (Vitest planned but not configured)
- Manual verification via:
  - Build success (`npm run build`)
  - Lint pass (`npm run lint`)
  - Local preview (`npm run preview`)
  - Manual UI testing

1.8.2 Test Infrastructure (Future)

- `src/__tests__/basePath.test.ts` - Contains commented-out tests for Vitest
- When Vitest is added, uncomment tests and add to CI/CD

1.9 Deployment Pipeline

1.9.1 CI/CD

- **Workflow**: `.github/workflows/deploy-ui.yml`
- **Trigger**: Push to `main` branch
- **Steps**:
  1. Build with `BUILD_TARGET=finanzas`
  2. Sync to S3 bucket `ukusi-ui-finanzas-prod`
  3. Invalidate CloudFront distribution EPQU7PVDLQXUA

1.9.2 Manual Deployment

[] npm run build:finanzas aws s3 sync dist/ s3://ukusi-ui-finanzas-prod/finanzas/ --delete aws cloudfront create-invalidation --distribution-id EPQU7PVDLQXUA --paths '/finanzas/*'

1.10 Routing Structure

1.10.1 Public Routes

- `/` - Home page (FinanzasHome if `VITE_FINZ_ENABLED=true`, else HomePage)
- `/profile` - User profile

1.10.2 PMO Routes

1.10.3 SDMT Routes

- `/sdmt/cost/catalog` - Line items catalog
- `/sdmt/cost/forecast` - Budget forecasting
- `/sdmt/cost/reconciliation` - Invoice reconciliation
- `/sdmt/cost/cashflow` - Cash flow analysis
- `/sdmt/cost/scenarios` - What-if scenarios
- `/sdmt/cost/changes` - Change requests

1.10.4 Finanzas Routes

- `/catalog/rubros` - Rubros (budget items) catalog
- `/rules` - Allocation rules preview

1.11 Security Considerations

1.11.1 Authentication

- Cognito User Pool: `us-east-2_FyHLtOhiY`
- JWT tokens stored in localStorage (`finz_jwt`)
- Auth can be skipped in dev via `VITE_SKIP_AUTH=true`

1.11.2 Authorization

- Role-based access control (RBAC) implemented at UI level
- Roles: PMO, SDMT, VENDOR, EXEC_RO
- Backend authorization handled by Lambda authorizers (not in UI scope)

1.11.3 Data Protection

- S3 bucket is private (no public access)
- CloudFront + OAC (Origin Access Control)
- HTTPS enforced
- No secrets in source code (environment variables only)

1.12 Next Steps for Finanzas R2

1. **Backend Integration**
   - Complete PMO/SDMT API implementation
   - Replace mock data layer with real API calls
   - Add retry logic and error handling
2. **Testing**
   - Install and configure Vitest
   - Add unit tests for components and utilities
   - Add integration tests for critical workflows
3. **Performance**
   - Implement code splitting (dynamic imports)
   - Optimize bundle size (currently 2.1MB)
   - Add lazy loading for routes
4. **Monitoring**
   - Add CloudWatch RUM for frontend monitoring
   - Implement error tracking (Sentry or similar)
   - Add performance metrics

1.13 Questions & Support

- **Repository**: valencia94/financial-planning-u
- **Branch**: copilot/cleanup-finanzas-module
- **Documentation**: See `docs/` directory for detailed guides
- **Issues**: GitHub Issues for bug reports and feature requests