CYBERSECURITY CAPSTONE PROJECT

External Attack Surface Discovery and Reconnaissance Report

Part 1: Passive Reconnaissance of example.com

Item	Detail
Target domain	example.com (approved for passive reconnaissance)
Collection period	13 - 20 October 2026 (times are WAT, UTC+1)
Platform	Kali Linux 2026.1 in a VirtualBox VM, on a Windows laptop
Tools used	whois (domain and IP), dig, nslookup, whatweb, theHarvester
Prepared by	[Team member names]
Status	Passive phase finished. The lab (active) phase, the attack surface diagram and the repository link still need to be added.

1. Summary

We were asked to work as a junior penetration-testing team and begin with reconnaissance: find out what anyone on the internet can learn about example.com without attacking it. This report covers the passive half of that job. In short:

• example.com is a reserved demo domain that has existed since 1995. IANA holds it, and the registry record shows no owner details.

• Cloudflare sits in front of nearly everything. It hosts the domain's DNS, and the web server that answered us was Cloudflare's. ARIN confirmed that one of the web addresses belongs to Cloudflare, so we never saw the real server behind it.

• The domain is set up to have no email at all. Its MX record says no mail is accepted, and its SPF record says nobody may send mail for it.

• At the registry level the domain has three locks and DNSSEC switched on.

• Searching public sources gave mixed results. One search engine returned nothing. Running theHarvester against all of its sources printed a long list of hostnames, but we could not verify any of them and we think most are junk, because example.com is used as a placeholder all over the internet.

• We did not find any vulnerabilities. Recon produces information, and information on its own is not a vulnerability.

2. Scope

We wrote down the scope before running any tool. For the passive phase it looks like this.

Scope item	Passive phase
Approved domain	example.com
IP range	Not needed for the passive phase. The lab subnet will be added for the active phase.
Exclusions	Every other domain and network. We did not scan or probe any example.com service.
Test dates	13 - 20 October 2026
Techniques allowed	Registry look-ups, DNS queries, searches of public sources, and one light web fingerprint request (whatweb).

A note on scope: while fixing the VM's internet connection we pinged an unrelated website just to test connectivity. That is not part of this assessment and nothing from it is used in this report.

3. Passive and Active Reconnaissance

Passive reconnaissance means collecting information from public sources without sending traffic to the target's own systems. Active reconnaissance means talking to the target directly, for example by scanning it, which can show up in its logs. This report is the passive side. The active side will be done against the lab machine only.

Tool	What it does	Type	Why we classed it that way
whois	Reads public registration records	Passive	It queries a registry database, not the target
dig / nslookup	Asks DNS for A, AAAA, MX, NS and TXT records	Passive	Our resolver talks to DNS servers, not to the target's web or mail services

Tool	What it does	Type	Why we classed it that way
theHarvester	Collects emails and subdomains from public sources	Passive	It relies on search engines and public datasets
whatweb	Identifies web technology from a server's replies	Passive-leaning, light active	It sends normal HTTP and HTTPS requests to the site, so the site could log them

4. Findings

For every finding we give the command, where the data came from and when we collected it. We also say whether each point is a **confirmed fact** (we saw it directly in tool output) or an **assumption** (a sensible guess that we have not proven yet).

4.1 Domain registration (whois)

We ran `whois example.com`. The answer came from the Verisign registry, with a database timestamp of 13 October 2026, 12:02 UTC.

Field	Result	In plain words
Registrar	RESERVED-Internet Assigned Numbers Authority (IANA ID 376)	IANA itself holds the domain; there is no commercial registrar
Created / updated / expires	14 Aug 1995 / 14 Aug 2026 / 13 Aug 2027	The domain is over 30 years old. The expiry date is the registry's sponsorship date
Status	clientDeleteProhibited, clientTransferProhibited, clientUpdateProhibited	Three locks: it can't be deleted, moved or edited until someone removes them
Name servers	ELLIOTT.NS.CLOUDFLARE.COM, HERA.NS.CLOUDFLARE.COM	DNS is hosted at Cloudflare
DNSSEC	signedDelegation (DS record published)	DNS answers are digitally signed, which makes them harder to fake
Registrant details	No name, email or phone shown	No owner data is exposed
Abuse contact	Fields exist but are empty	No public abuse contact in this record

What stands out is how little personal data there is. We would like to call that privacy protection, but the output does not name a privacy service. The more likely reason is simply that IANA holds this domain itself, so we only say that no registrant details are exposed.

Confirmed: every value in the table is visible in the screenshot (Appendix A-1).

4.2 IP addresses (A and AAAA records)

Record	Values	TTL	Source and time
A (IPv4)	104.20.23.154 172.66.147.243	120 s	dig via resolver 192.168.18.1, Fri 16 Oct 2026, 12:05:44 WAT
AAAA (IPv6)	2606:4700:10::6814:179a 2606:4700:10::ac42:93f3	300 s	dig via resolver 192.168.18.1, Fri 16 Oct 2026, 12:05:57 WAT

Two IPv4 and two IPv6 addresses is what you would expect from a site spread across a content delivery network (CDN). nslookup returned the same four addresses (Appendix A-4, A-5 and A-7), so two tools agree. The TTLs are short, which means the addresses can change quickly. We treat them as a snapshot,

not a permanent fact.

Confirmed: the four addresses came back from two tools, and ARIN whois shows that 104.20.23.154 belongs to Cloudflare (section 4.2b). **Assumption:** the other three addresses (172.66.147.243 and the two IPv6 addresses) also belong to Cloudflare. That is likely, but each one needs its own `whois` look-up.

4.2b Who owns the IP address (whois on 104.20.23.154)

We ran `whois 104.20.23.154`. The answer came from ARIN, the registry for North American IP addresses, on Tue 20 Oct 2026 (the screenshot's timestamp).

Field	Result	In plain words
Network range	104.16.0.0 - 104.31.255.255 (104.16.0.0/12)	A big block of roughly a million addresses shared by many sites
Network name	CLOUDFLARENET	The block is named for Cloudflare
Organization	Cloudflare, Inc. (CLOUD14), San Francisco, CA, US	The registered owner
Allocation	Direct Allocation; network registered 2014-03-28	Cloudflare holds the block directly from the registry
Public contacts	Role mailboxes for abuse, network operations and technical contact, and one shared phone number	Normal for a large provider. These are team contacts, not individuals

So the address example.com points to is Cloudflare's own network. From the internet we reach a CDN edge server, not the site's real (origin) server. This also matters for scope: scanning these addresses would mean probing Cloudflare's infrastructure, which we have no permission to do.

Confirmed: 104.20.23.154 is allocated to Cloudflare, Inc. (Appendix A-9). The record tells us nothing about where the origin server is.

4.3 Mail servers (MX record)

dig returned `example.com. 179 IN MX 0 .` on Fri 16 Oct 2026 at 12:07:46 WAT, and nslookup agreed (`mail exchanger = 0 .`). A single dot in place of a mail server is called a null MX. It is the official way to say that a domain does not accept email. There is no mail server to find, and anyone who tries to send mail gets turned away immediately.

Confirmed: both tools show the null MX (Appendix A-1b and A-7).

4.4 Name servers (NS records)

dig returned `hera.ns.cloudflare.com.` and `elliott.ns.cloudflare.com.` with a TTL of 21600 s (Fri 16 Oct 2026, 12:08:03 WAT), and nslookup gave the same two. They match the name servers in the whois record exactly, which is a good sign: the registry and the live DNS agree. It also tells us the DNS provider is Cloudflare, so the security of that provider account now protects this domain's DNS.

Confirmed: whois, dig and nslookup all agree.

4.5 Text records (TXT)

Value	What it is	Status
`"v=spf1 -all"`	An SPF policy saying no server is allowed to send email for this domain	Confirmed
`"_k2n1y4vw3qtb4skdx9e7dxt97qrmmq9 "` (exact string in Appendix A-3)	Looks like a domain-verification token, the kind a third-party service asks you to publish to prove ownership. We do not know which service.	Record confirmed; purpose is an assumption

We collected these with dig on Fri 16 Oct 2026 at 12:10:15 WAT and cross-checked with nslookup. The `-all` in the SPF record is the strictest setting. Together with the null MX it shows the domain is deliberately set to "no email in, no email out", which also makes it harder for someone to spoof the domain in phishing emails.

4.6 Emails and subdomains (theHarvester)

We ran theHarvester 4.10.1 twice: once with `-b duckduckgo` (a single source) and once with `-b all` (every source the tool supports).

Run	What we saw	How we read it
1. duckduckgo only	0 IPs, 0 emails, 0 people, 0 hosts (Appendix A-6)	Nothing found by this one source
2. all sources	A long list of hostnames under example.com. About 40 are visible in our last capture (names from v to z), and some are printed as hostname:IP, for example `vpsny1.example.com` and `yangfan3.tec.02.example.com:5.8.33.119` (Appendix A-6c)	Unverified, low confidence
2. errors	Many sources failed with a missing API key: bevigil, Bitbucket, bufferoverun, BuiltWith, Brave Search, Censys, criminalip and SecurityScorecard (Appendix A-6b)	Those sources gave us nothing, so coverage is incomplete

Many of the hostnames look random, and some seem to contain people's names. The IP addresses attached to them are not in the Cloudflare ranges we saw earlier. example.com is a reserved domain that tutorials, test configurations and datasets use as a placeholder, so data aggregators collect plenty of made-up or mistyped names under it. Our working assumption is that most of the list is noise and does not exist in the real example.com DNS. We have not checked that yet.

Confirmed: theHarvester printed these names (Appendix A-6b, A-6c). **Not confirmed:** that any of them resolve in live DNS, that the domain owner controls them, or that the IPs have any real link to example.com. **Scope:** these hosts and IPs are third-party data, not approved targets, so we must not scan or contact them. **Next step:** run `dig vpsny1.example.com A` on a sample. A status of NXDOMAIN means the name does not exist in live DNS and can be marked as noise.

Finding type	Source	How far to trust it
Subdomains	Certificate-transparency logs (crtsh)	High: based on certificates actually issued, though possibly old
Subdomains	Aggregators (rapiddns, hackertarget and similar)	Low to medium: third-party data, may be stale or fake
Emails	Search engines (duckduckgo)	Low to medium: scraped text, may be outdated or fake

4.7 Web technology (whatweb)

We ran `whatweb example.com` on Fri 16 Oct 2026 and again on Tue 20 Oct 2026, the second time also with `whatweb https://example.com`.

Item	Result
Response	200 OK on both http:// and https://
HTTP server	cloudflare
IP address seen	104.20.23.154 (16 Oct) and 172.66.147.243 (20 Oct). Both match the A records
Allowed methods	GET, HEAD
Page title	Example Domain
Technologies	HTML5, Script
Uncommon headers	cf-cache-status, cf-ray, alt-svc
Country (whatweb GeoIP)	United States (16 Oct); RESERVED / ZZ (20 Oct)

The `cf-ray` and `cf-cache-status` headers are Cloudflare's fingerprints, so web traffic passes through Cloudflare's network. Only GET and HEAD (read-only) methods are advertised, which is a safe setting.

Confirmed: Cloudflare answers web requests, and both IPs we saw match DNS. Seeing a different address on a different day fits a CDN handing out several addresses. **Assumptions:** (1) The country value changed between runs, so it describes the CDN address or the tool's GeoIP data, not where the origin server is. (2) `alt-svc` hints at HTTP/3 support, which we did not test. (3) We cannot tell what the real origin runs, because the CDN hides it.

5. Confirmed Facts and Assumptions

#	Statement	Class	Evidence, or what is still needed
1	Registrar is IANA (reserved); created 1995; expires Aug 2027	Confirmed	whois (A-1)
2	Three registry locks and DNSSEC are set	Confirmed	whois (A-1)
3	Name servers are Cloudflare's	Confirmed	whois (A-1), dig NS (A-1b), nslookup (A-7)
4	example.com has 2 IPv4 and 2 IPv6 addresses	Confirmed	dig (A-2), nslookup (A-4, A-5, A-7)
5	The domain publishes a null MX (accepts no mail)	Confirmed	dig (A-1b), nslookup (A-7)
6	SPF is "-all" (no sender allowed)	Confirmed	dig (A-3), nslookup (A-7)
7	Web traffic is served through Cloudflare	Confirmed	whatweb headers (A-8, A-8b)
8	104.20.23.154 is allocated to Cloudflare, Inc. (CLOUDFLARENET, 104.16.0.0/12)	Confirmed	ARIN whois (A-9, A-9b)
9	The other three IPs (172.66.147.243 and two IPv6) are owned by Cloudflare	Assumption	Run whois on each address
10	The TXT token is a third-party verification code	Assumption	Find the service that issued it
11	The origin server is hidden behind the CDN	Assumption	Cannot be confirmed passively
12	theHarvester (-b all) printed many hostnames under example.com, some with IPs	Confirmed that it printed them; existence not confirmed	A-6b, A-6c; check with dig
13	Those hostnames are real assets of the domain owner	Assumption (likely noise)	dig each name; compare with crt.sh

6. Attack Surface Inventory (Passive Phase)

Asset	Source	Confidence	Possible exposure	Further testing authorized?
example.com (domain)	whois	High	Registry data only; locks and DNSSEC in place	No (passive only)
104.20.23.154	dig A, nslookup, whatweb, ARIN whois	High	Confirmed Cloudflare CDN edge address, not the origin	No
172.66.147.243	dig A, nslookup, whatweb	Medium	Probably a CDN edge address (ownership not yet confirmed)	No
2606:4700:10::6814:179a	dig AAAA, nslookup	Medium	Probably a CDN edge IPv6 address (not yet confirmed)	No
2606:4700:10::ac42:93f3	dig AAAA, nslookup	Medium	Probably a CDN edge IPv6 address (not yet confirmed)	No
hera / elliott .ns.cloudflare.com	whois, dig NS	High	The DNS provider account is a dependency	No
Null MX (no mail host)	dig MX, nslookup	High	None: mail is not accepted	No
TXT verification token	dig TXT, nslookup	Medium	May reveal a third-party service	No
Web service (80/443)	whatweb	High	Cloudflare-fronted site, read-only methods	No

Asset	Source	Confidence	Possible exposure	Further testing authorized?
Subdomains (about 40 seen, e.g. vpsny1.example.com)	theHarvester -b all	Low	Unverified; probably stale or placeholder data	No
IPs attached to some names (e.g. 5.8.33.119)	theHarvester -b all	Low	Unverified third-party addresses	No (out of scope)
Emails / people	theHarvester (duckduckgo and all)	Medium	None reported	No

7. Deeper Analysis: Six Findings

The brief asks for at least five findings, and we looked at six. For each one we ask how a defender could use it, how an attacker might misuse it, and what more we would need to see before calling it a real vulnerability.

Finding 1: Cloudflare sits in front of the site and its DNS

Item	Analysis
Where it came from	A/AAAA records, NS records, whatweb headers, ARIN whois on 104.20.23.154
How a defender can use it	It confirms the CDN is active and that the DNS provider is a key dependency. A team can lock that account down with 2FA and watch for DNS changes.
How an attacker might misuse it	Knowing a CDN is in place, an attacker may try to find the hidden origin server to get around Cloudflare's protection, or go after the DNS provider account instead.
What we would need before calling it a vulnerability	Proof that the origin IP actually leaks (for example in old DNS history or other subdomains) and that the origin accepts traffic from outside Cloudflare. We have seen nothing like that.

Finding 2: Null MX together with SPF "-all"

Item	Analysis
Where it came from	MX and TXT records
How a defender can use it	It shows the domain is deliberately mail-less, which lowers the chance of it being used to spoof email. The same pattern is worth copying on any domain that sends no mail.
How an attacker might misuse it	An attacker learns there is no mail server to attack and would move on. They might still try to spoof the domain if a receiver ignores SPF.
What we would need before calling it a vulnerability	A check of DMARC (`_dmarc.example.com`), which we have not queried, and a test showing that a receiver really accepts spoofed mail.

Finding 3: The TXT verification token

Item	Analysis
Where it came from	TXT record
How a defender can use it	Old tokens can point to services nobody uses any more. A team can review its TXT records and remove the stale ones.
How an attacker might misuse it	An attacker can work out which third-party services the organization uses and plan phishing or supply-chain attacks around them.
What we would need before calling it a vulnerability	We would need to identify the service and show its account is abandoned or can be claimed by someone else. A token on its own is not a vulnerability.

Finding 4: Registry locks and DNSSEC

Item	Analysis
Where it came from	whois status and DNSSEC fields
How a defender can use it	The locks protect against unauthorized deletion, transfer or edits, and DNSSEC protects against forged DNS answers. A team can check that both stay enabled and that DNSSEC keys are rolled over properly.
How an attacker might misuse it	An attacker sees that hijacking the domain through the registry is hard and would look at weaker targets, such as the registrar or DNS account credentials.
What we would need before calling it a vulnerability	Evidence of weak account security (no 2FA, shared passwords) or a DNSSEC mistake that breaks validation. None of that is visible from public data.

Finding 5: Web server fingerprint and headers

Item	Analysis
Where it came from	whatweb output
How a defender can use it	Headers such as cf-ray and alt-svc show what the edge reveals. A team can strip headers that give away unnecessary detail and confirm that only the needed HTTP methods are allowed.
How an attacker might misuse it	Attackers use fingerprints to pick exploits for a specific product or version, and to tell whether they are hitting a CDN or the real server.
What we would need before calling it a vulnerability	A specific vulnerable product and version, confirmed by an authorized test. We only see the CDN, so no exploitable version has been identified.

Finding 6: Many unverified subdomains from third-party sources

Item	Analysis
Where it came from	theHarvester -b all output
How a defender can use it	It shows what public datasets claim about the domain. A team can compare each name with its own DNS and certificate records to find forgotten, stale or unauthorized subdomains and clean them up.
How an attacker might misuse it	An attacker can use the list as a ready-made set of targets or as a wordlist, hoping some names point to forgotten or poorly protected hosts. Too much noise can also hide the few real names.
What we would need before calling it a vulnerability	Proof that a name resolves in live DNS (dig), appears in certificate logs, belongs to the owner and runs something reachable. Only then, with written permission, could testing begin. For example.com we assume most of the names are noise.

8. Recommendations and Hardening Checklist

Items marked **[Verify]** need a check we did not do in this passive phase.

Done?	Recommendation	Why it helps
[ ]	Keep the registry locks (delete, transfer, update) on and review them regularly	Prevents domain hijacking
[ ]	Keep DNSSEC on and watch key rollovers	Stops forged DNS answers; a botched rollover can cause outages
[ ]	Protect the DNS and CDN provider account with 2FA, least-privilege roles and change alerts	The DNS provider is a single point of control
[ ]	Publish a strict DMARC policy on domains that send no mail [Verify]	Completes the SPF and null-MX anti-spoofing setup
[ ]	Review TXT records and remove tokens for services no longer in use	Leaks less information and lowers takeover risk
[ ]	Make sure the origin server only accepts traffic from the CDN [Verify]	Makes bypassing the CDN pointless
[ ]	Remove response headers you do not need and allow only the HTTP methods you use	Less fingerprinting information
[ ]	Keep personal details redacted in WHOIS and keep an abuse contact that works	Gives attackers less to work with while staying reportable
[ ]	Watch certificate-transparency logs for unexpected subdomains	Early warning of shadow IT or impersonation
[ ]	Compare subdomains reported by public datasets with your own DNS records and delete stale entries	Finds forgotten hosts and filters out noise
[ ]	Keep an up-to-date asset inventory (domains, IPs, DNS records, third-party services)	You can't defend what you don't know you have

9. Limitations and Work Still to Do

• **theHarvester output is only partly captured.** Our screenshots show the start and the end of the `-b all` run, not the whole host list, and many sources failed for lack of API keys. We should re-run it with `-f` to save the full output, and check a sample of names with dig.

• **The DNS resolver changed during collection.** The VirtualBox NAT resolver (10.0.2.3) timed out on some queries, so most records came through the local router (192.168.18.1). The answers matched across resolvers and tools.

• **DNS answers are snapshots.** TTLs of 120 to 300 seconds on the address records mean the values can change.


• **Both whatweb screenshots are cropped on the right** (A-8, A-8b), so the page title and headers are not visible in them. We should re-capture with a wider terminal.

• **Only one of the four IP addresses has been checked with whois.** The other three are assumed to be Cloudflare's.


• **Not included yet:** active reconnaissance of the Metasploitable2 lab (nmap), the attack surface diagram, the full passive-versus-active comparison with lab results, and the GitHub repository link.

Appendix A: Evidence Screenshots


Each screenshot is cropped to the terminal text and enlarged so it can be read. The original full-size images are in the evidence folder of the repository.



A-1. whois example.com (registry record, 13 Oct 2026 timestamp). Supports section 4.1.



A-1b. dig MX (12:07:46 WAT) and dig NS (12:08:03 WAT), 16 Oct 2026. Supports sections 4.3 and 4.4.



A-2. dig A (12:05:44 WAT) and dig AAAA (12:05:57 WAT), 16 Oct 2026. Supports section 4.2.

```
┌──(kali㉿kali)-[~]
└─$ dig example.com TXT

; <<>> DiG 9.20.20-1-Debian <<>> example.com TXT
;; global options: +cmd
;; Got answer:
;; ->>HEADER<<- opcode: QUERY, status: NOERROR, id: 54493
;; flags: qr rd ra; QUERY: 1, ANSWER: 2, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 512
;; QUESTION SECTION:
;example.com.                   IN      TXT

;; ANSWER SECTION:
example.com.            300     IN      TXT     "_k2n1y4vw3qtb4skdx9e7dxt97qrmmq9"
example.com.            300     IN      TXT     "v=spf1 -all"

;; Query time: 1119 msec
;; SERVER: 192.168.18.1#53(192.168.18.1) (UDP)
;; WHEN: Fri Oct 16 12:10:15 WAT 2026
;; MSG SIZE  rcvd: 109
```

A-3. dig TXT (12:10:15 WAT), 16 Oct 2026. Supports section 4.5.

```
┌──(kali㉿kali)-[~]
└─$ nslookup example.com
Server:         10.0.2.3
Address:        10.0.2.3#53

Non-authoritative answer:
Name:   example.com
Address: 104.20.23.154
Name:   example.com
Address: 172.66.147.243
Name:   example.com
Address: 2606:4700:10::6814:179a
Name:   example.com
Address: 2606:4700:10::ac42:93f3
```

A-4. nslookup example.com (A and AAAA addresses, resolver 10.0.2.3).

```
┌──(kali㉿kali)-[~]
└─$ nslookup -type=AAAA example.com
Server:         192.168.18.1
Address:        192.168.18.1#53

Non-authoritative answer:
Name:   example.com
Address: 2606:4700:10::6814:179a
Name:   example.com
Address: 2606:4700:10::ac42:93f3
```

A-5. nslookup -type=AAAA example.com (resolver 192.168.18.1).

```
┌──(kali㉿kali)-[~]
└─$ theHarvester -d example.com -b duckduckgo
Read proxies.yaml from /etc/theHarvester/proxies.yaml
*******************************************************************
*  _   _                                            _             *
* | |_| |__   ___    /\  /\__ _ _ ____   _____  ___| |_ ___ _ __  *
* | __|  _ \ / _ \  / /_/ / _` | '__\ \ / / _ \/ __| __/ _ \ '__| *
* | |_| | | |  __/ / __  / (_| | |   \ V /  __/\__ \ ||  __/ |    *
*  \__|_| |_|\___| \/ /_/ \__,_|_|    \_/ \___||___/\__\___|_|    *
*                                                                 *
* theHarvester 4.10.1                                             *
* Coded by Christian Martorella                                   *
* Edge-Security Research                                          *
* cmartorella@edge-security.com                                   *
*                                                                 *
*******************************************************************

[*] Target: example.com

[*] Searching Duckduckgo.

[*] No IPs found.

[*] No emails found.

[*] No people found.

[*] Hosts found: 0
---------------------
```

A-6. theHarvester -d example.com -b duckduckgo: no IPs, emails or people found; hosts found: 0 (section 4.6).



A-6b. theHarvester -d example.com -b all: start of the run, showing sources that failed for missing API keys (section 4.6).


```
vpsny1.example.com
vtcqfc.example.com
vulvinc.example.com
w.barnes.1974329.example.com:45.150.239.126
walkerj235.example.com
walkspup.example.com
whererec1.example.com
winnice911gcinc32.example.com
winnice911gcinc39.example.com
wiser204333c.example.com
wp-teszt.example.com
wymgbhnc.example.com
xa0s3000.example.com
xakep-spike.example.com
xn--80ae9acg.example.com
xu.example.com
xxxxxx.example.com
yaborisoff.example.com
yangfan.tec.02.example.com:5.181.77.54
yangfan10.tec.02.example.com:92.38.149.20
yangfan3.tec.02.example.com:5.8.33.119
yangfan4.tec.02.example.com:5.8.33.177
yangfan6.tec.02.example.com:185.163.2.16
yangfan7.tec.02.example.com:92.38.149.44
yangfan8.tec.02.example.com:92.38.149.54
yangfan9.tec.02.example.com:185.163.2.17
yaroslav16.06maxim.example.com:108.165.201.21
yaroslvozl12.example.com
yellowlightskyblue-vm.example.com
yemotu.example.com
yotaaliya5.example.com
yuilognh.example.com
zachary.freeman.1973.example.com:45.81.33.173
zfivspoz.example.com
zhangdubin.example.com
zsthai039.example.com
zubtzov.example.com
zxflhgfn.example.com

[*] Performing SecurityScorecard scan...
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml
An exception has occurred in SecurityScorecard scanning:
[!] Missing API key for SecurityScorecard.


[*] Performing BuiltWith scan...
Read api-keys.yaml from /etc/theHarvester/api-keys.yaml

[!] Missing API key for BuiltWith.
```


A-6c. theHarvester -b all: end of the host list (names v to z), some printed as hostname:IP. Unverified third-party data (section 4.6).




A-7. nslookup for MX, NS, TXT and A records (resolver 192.168.18.1). Cross-checks the dig results.



A-8. whatweb example.com, 16 Oct 2026 (partial capture, line cut off). Full result in section 4.7.



A-8b. whatweb example.com and whatweb https://example.com, 20 Oct 2026: 200 OK, server cloudflare, IP 172.66.147.243, country RESERVED/ZZ (right edge cut off). Shown in two parts (left, then right) so the text is readable.



A-9. whois 104.20.23.154 (ARIN), part 1: network range, CLOUDFLARENET, Cloudflare, Inc. Supports section 4.2b.

```
OrgRoutingHandle: CLOUD146-ARIN
OrgRoutingName:   Cloudflare-NOC
OrgRoutingPhone:  +1-650-319-8930
OrgRoutingEmail:  noc@cloudflare.com
OrgRoutingRef:    https://rdap.arin.net/registry/entity/CLOUD146-ARIN

OrgAbuseHandle: ABUSE2916-ARIN
OrgAbuseName:   Abuse
OrgAbusePhone:  +1-650-319-8930
OrgAbuseEmail:  abuse@cloudflare.com
OrgAbuseRef:    https://rdap.arin.net/registry/entity/ABUSE2916-ARIN

OrgTechHandle: ADMIN2521-ARIN
OrgTechName:   Admin
OrgTechPhone:  +1-650-319-8930
OrgTechEmail:  rir@cloudflare.com
OrgTechRef:    https://rdap.arin.net/registry/entity/ADMIN2521-ARIN

RAbuseHandle: ABUSE2916-ARIN
RAbuseName:   Abuse
RAbusePhone:  +1-650-319-8930
RAbuseEmail:  abuse@cloudflare.com
RAbuseRef:    https://rdap.arin.net/registry/entity/ABUSE2916-ARIN

RTechHandle: ADMIN2521-ARIN
RTechName:   Admin
RTechPhone:  +1-650-319-8930
RTechEmail:  rir@cloudflare.com
RTechRef:    https://rdap.arin.net/registry/entity/ADMIN2521-ARIN

RNOCHandle: NOC11962-ARIN
RNOCName:   NOC
RNOCPhone:  +1-650-319-8930
RNOCEmail:  noc@cloudflare.com
RNOCRef:    https://rdap.arin.net/registry/entity/NOC11962-ARIN


#
# ARIN WHOIS data and services are subject to the Terms of Use
# available at: https://www.arin.net/resources/registry/whois/tou/
#
# If you see inaccuracies in the results, please report at
# https://www.arin.net/resources/registry/whois/inaccuracy_reporting/
#
# Copyright 1997-2026, American Registry for Internet Numbers, Ltd.
#
```

A-9b. whois 104.20.23.154 (ARIN), part 2: abuse, NOC and technical contacts, end of record.