

PegasusX — Features by App / Role

SOURCE OF TRUTH: CODE ONLY (not other markdown).

Extracted 2026-08-04 from:

- JWT roles: `apps/backend-go/auth/claims.go`
- HTTP mounts: every `apps/backend-go/*routes/routes.go` (612 route registrations scanned)
- Client nav: `*Shell.tsx`, `*Section.kt`, `DriverRoutes`, `RetailerNavigation.kt`
- Apps tree: `apps/*` (stubs noted from their `package.json`)

Companion (also code-grounded): [ROLE_CAPABILITIES_MATH_LOGIC.md](#) · [ORDER_FLOW_AND_EDGE_CASES.md](#)

0. Apps on disk

Dir	Status (from code/package.json)
<code>supplier-portal</code>	Live Next.js + Tauri supplier/ADMIN UI
<code>supplier-app-android</code> / <code>supplier-app-ios</code>	Live
<code>supplier-app-desktop</code>	Redirect stub → <code>supplier-portal</code>
<code>admin-portal</code>	Deprecated stub → <code>supplier-portal</code>
<code>retailer-app-desktop</code> / <code>-android</code> / <code>-ios</code>	Live
<code>warehouse-portal</code> / <code>-android</code> / <code>-ios</code>	Live
<code>factory-portal</code> / <code>-android</code> / <code>-ios</code>	Live
<code>payload-terminal</code> / <code>-android</code> / <code>-ios</code>	Live
<code>driver-app-android</code> / <code>-ios</code>	Live (no portal)
<code>backend-go</code>	API
<code>ai-worker</code>	Workers (import/freeze/synthesis)
<code>handoff-service</code>	Handoff service
<code>marketing-site</code>	Marketing (not ops features)

0.1 JWT roles (`auth/claims.go`)

```
ADMIN, RETAILER, DRIVER, PAYLOAD,  
FACTORY, FACTORY_ADMIN, FACTORY_DRIVER,  
WAREHOUSE_ADMIN, WAREHOUSE
```

Scope fields on claims: `SupplierID`, `HomeNodeType` / `HomeNodeID`, `retailer`

`RetailerOrgID` / `RetailerRole` / `CapabilityPacks` / `ActiveLocationID` . Comment in package: single-tenant `ResolveSupplierID` returns seeded supplier for authenticated callers.

1. Retailer — APIs (`retailerroutes` 145 + related)

Role gate: `RoleRetailer` (plus shared catalog/payment/order/claim routes).

Clients (nav from code)

Client	Evidence	Surfaces
Desktop	<code>RetailerShell.tsx</code> hrefs	<code>/</code> , <code>/dashboard</code> , <code>/catalog</code> , <code>/my-suppliers</code> , <code>/orders</code> , <code>/tracking</code> , <code>/dock</code> , <code>/procurement</code> , <code>/auto-order</code> , <code>/insights</code> , <code>/reports</code> , <code>/hq</code> , <code>/credit</code> , <code>/stock</code> , <code>/stock/local-skus</code> , <code>/pos</code> , <code>/shifts</code> , <code>/sections</code> , <code>/assist</code> , <code>/settings</code>
Android	<code>RetailerNavigation.kt</code> route ids	<code>PROCUREMENT</code> , <code>CONTROL_TOWER</code> , <code>DOCK</code> , <code>ANALYTICS</code> , <code>AUTO_ORDER</code> , <code>CART</code> , <code>NOTIFICATIONS</code> , <code>ACCOUNT_PROFILE</code> , <code>FAMILY_MEMBERS</code> , <code>CAPABILITIES</code> , <code>TEAM</code> , <code>LOCATIONS</code> , <code>STORE_STOCK</code> , <code>LOCAL_SKUS</code> , <code>POS</code> , <code>SHIFTS</code> , <code>SECTIONS</code> , <code>REPORTS_PRO</code> , <code>ASSIST</code> , <code>SETUP_WIZARD</code>
iOS	<code>ContentView.swift</code>	Tab shell (<code>home</code> , <code>insights</code> , ...) + screen modules under <code>Screens/</code>

Feature inventory = registered routes

Auth / identity

Feature	Methods
Login / refresh / register	<code>POST /v1/auth/retailer/{login,refresh,register}</code>
Memberships / select-org / switch-org	<code>GET .../memberships</code> , <code>POST .../select-org</code> , <code>POST .../switch-org</code>
Me + capabilities	<code>GET /v1/retailer/me</code> , <code>GET/POST /v1/retailer/capabilities*</code>
Switch location	<code>POST /v1/auth/retailer/switch-location</code>
Setup / profile	<code>POST /v1/retailer/setup</code> , <code>GET/PUT /v1/retailer/profile</code>
Family members (+ migrate-to-team)	<code>/v1/retailer/family-members*</code>
Org members / locations	<code>/v1/retailer/org/members*</code> , <code>/v1/retailer/locations*</code>
Notifications	<code>/v1/user/notifications*</code>

Procurement

Feature	Methods
Suppliers attach/detach	<code>/v1/retailer/suppliers*</code>
Cart sync	<code>GET/POST /v1/retailer/cart/sync</code>
Checkout quote / promo watch	<code>POST /v1/retailer/checkout/quote</code> , <code>POST /v1/retailer/promotions/watch</code>
Pricing rules (read)	<code>GET /v1/retailer/pricing/rules</code>
Cash/card checkout	<code>POST /v1/order/{cash,card}-checkout</code>
Unified/preview/B2B checkout	<code>POST /v1/checkout/{unified,preview,b2b}</code> (<code>paymentroutes</code>)
Catalog browse	<code>GET /v1/catalog/*</code> , <code>GET /v1/products</code> (<code>catalogroutes</code>)
Saved cards	<code>/v1/retailer/card*</code> , <code>GET /v1/retailer/cards</code>

Orders / delivery / AI

Feature	Methods
Order list	GET /v1/orders , GET /v1/retailers/{id}/orders
Cancel / request-cancel	POST /v1/order/cancel , POST /v1/orders/request-cancel
Preorder confirm/edit/reject	POST /v1/orders/{confirm,edit,reject}-preorder
Delivery proposal accept/reject	POST /v1/orders/{accept,reject}-delivery-proposal
Shop-closed respond	POST /v1/retailer/shop-closed-response , POST /v1/retailer/orders/{id}/shop-closed/respond
Confirm cash (doorstep)	POST /v1/delivery/confirm-cash (orderroutes , RoleRetailer)
Tracking / active fulfillment / pending payments	GET /v1/retailer/{tracking,active-fulfillment,pending-payments}
Pulse / control-tower pulse	GET /v1/retailer/pulse , GET /v1/retailer/control-tower/pulse
Auto-order settings + run	/v1/retailer/settings/auto-order* including .../run
AI predictions / confirm / reject	/v1/retailer/ai/predictions , /v1/ai/* , POST /v1/retailer/orders/{confirm,reject}-ai
Reorder suggestions / sell-through	GET /v1/retailer/reorder-suggestions , GET /v1/retailer/insights/sell-through
Claims file/list/eligibility	/v1/orders/{id}/claims* , claim-eligibility (orderroutes)
Receipt / QR / timeline / status-context	orderroutes retailer GETs
Credit profile / relationships / AR	creditroutes : /v1/retailer/credit-profile , credit-relationships , ar/invoices

Retail OS

Feature	Methods
Store stock	/v1/retailer/stock* (receive/transfer/adjust/counts)
Local SKUs	/v1/retailer/local-skus*
POS	/v1/retailer/registers , /v1/retailer/pos/*
Time / shifts	/v1/retailer/time/* , /v1/retailer/shifts*
Sections	/v1/retailer/sections*
Assist tickets	/v1/retailer/assist/tickets*
Reports	/v1/retailer/reports/*
Franchise HQ	/v1/retailer/hq/*
Analytics expenses	/v1/retailer/analytics/{expenses,detailed}

Parity gaps (nav vs routes)

Observation	Code basis
/hq in desktop shell; not in Android route ids	Shell vs RetailerNavigation.kt

Observation	Code basis
<code>/credit</code> in desktop shell; Android exposes profile/credit via account, not a <code>CREDIT</code> section id	Shell vs Android ids
<code>CONTROL_TOWER</code> on Android; desktop has pulse API but no <code>/control-tower</code> in shell href list	Shell hrefs vs Android
AR invoices routes exist; no shell href <code>/ar</code>	<code>creditroutes</code> vs shells

2. Supplier (ADMIN) — APIs (`supplierroutes` + finance packs)

Clients

Client	Evidence	Surfaces (abbrev.)
Portal	<code>SupplierShell.tsx</code>	dashboard, orders, dispatch, fleet, <i>manifests</i> , <i>exceptions</i> , <i>catalog</i> , <i>inventory(+import)</i> , <i>pricing</i> , <i>promotions</i> , <i>topology/factories/warehouses/zones/lanes</i> , <i>ledger/payments/chargebacks/reconciliation/treasury/earnings/compliance</i> , <i>credit</i> , <i>control-tower</i> , <i>playbooks</i> , <i>planning</i> , <i>segmentation</i> , <i>tax-regimes</i> , <i>AI</i> , <i>analytics</i> , <i>replenishment*</i> , <i>returns</i> , <i>org-fleet</i> , <i>activity</i> , <i>ops/map</i> , ...
Android	<code>SupplierSection.kt</code>	DASHBOARD , ORDERS , FLEET* , MANIFESTS , DISPATCH_PREVIEW , ACTIVITY , ORG_FLEET , TREASURY_HUB , LEDGER , PAYMENTS , CHARGEBACKS , RECONCILIATION , OPERATIONS , ANALYTICS , AI_RECOMMENDATIONS , <i>topology/catalog/inventory/pricing/promotions/returns/earnings/profile/setup</i> , ...
Desktop	<code>supplier-app-desktop/package.json</code>	redirect only

Feature inventory (route groups)

Domain	Route prefix / examples
Auth / setup	<code>/v1/auth/supplier/*</code> , <code>/v1/supplier/{configure,business/setup,billing/setup,profile,settings}</code>
Dashboard / activity / pulse	<code>/v1/supplier/{dashboard,activity}</code> , <code>/v1/supplier/pulse</code>
Orders	<code>/v1/supplier/orders</code> , <code>.../vet</code> , <code>.../payment-bypass</code> , <code>receipts</code>
Shop-closed ops	<code>/v1/supplier/shop-closed/{active,resolve}</code>
Negotiations	<code>/v1/supplier/negotiations/pending</code> , <code>.../negotiate/resolve</code>
Early-complete	<code>/v1/supplier/route/approve-early-complete</code>
Reassign	<code>/v1/supplier/{recommend-reassign,reassign-order}</code>
Dispatch / fleet	<code>/v1/supplier/dispatch/*</code> , <code>/v1/supplier/fleet/*</code>

Domain	Route prefix / examples
Manifests / exceptions	/v1/supplier/manifests , exceptions* , manifest-exceptions , ops/exception-map
Catalog CRUD	catalogroutes POST/PUT products (RoleAdmin)
Inventory + import + audit	/v1/supplier/inventory*
Pricing / promotions	/v1/supplier/pricing/* , /v1/supplier/promotions*
Topology	/v1/supplier/topology , supply-lanes , factories/warehouses via supplier APIs
Finance	/v1/payment/{ledger,chargeback*,settlement/authority,reconciliation/mismatches} , claim-chargebacks, cash-reconciliations, credit-notes
Credit program	/v1/supplier/credit-{profiles,program*,relationships*} , admin disable
Claims adjudicate	/v1/supplier/claims , /v1/claims/{id}/{approve,reject}
Compliance	/v1/compliance/* , tax-regimes
Planning / AI / MEIO / twin	/v1/supplier/{ai,planning,meio,segmentation,knowledge-graph}* , twin routes, replenishment*
Control tower	/v1/control-tower/* , zone-overrides
Returns / broadcast	/v1/supplier/returns* , /v1/supplier/broadcast
Demand signals	demandroutes /v1/demand/signals*

Parity gaps (portal shell vs Android section)

Portal-only hrefs with no matching Android section enum: /control-tower , /settings/playbooks , /settings/segmentation , /settings/tax-regimes , /credit/policy , /credit/admin-disable , /analytics/demand/flywheel , /demand/payday-calendar , /settings/planning (Android has analytics/AI/ops subset instead).

3. Warehouse — APIs (warehouseroutes 78 + returns/creditnote/claims)

Roles: WAREHOUSE , WAREHOUSE_ADMIN (many ops routes require Admin/WarehouseAdmin).

Clients

Client	Evidence
Portal	WarehouseShell.tsx : / , dispatch* , orders , preorders , tomorrow-board , drivers/vehicles , inventory , stock-commitments , products , manifests , fleet-live-map , replenishment , demand-forecast , supply-requests , transfers , returns , claims , exceptions , rescues , analytics , crm , treasury , payment-config , staff , settings , operations , control-tower , dispatch-locks

Client	Evidence
Android	WarehouseSection.kt : DASHBOARD , ORDERS , DRIVERS , VEHICLES , INVENTORY , DISPATCH , ANALYTICS , TREASURY , STAFF , MANIFESTS , DISPATCH_SETTINGS , FLEET_LIVE_MAP , TRANSFER_ACTIONS , PRODUCTS , PREORDERS , TOMORROW_BOARD , STOCK_COMMITMENTS , SUPPLY_REQUESTS , REPLENISHMENT , DEMAND_FORECAST , RETAILERS , RETURNS , EXCEPTIONS , CLAIMS , RESCUES , PAYMENT_CONFIG , OPS_SETTINGS , LOCATION_SETTINGS , NOTIFICATIONS , PORTAL_* handoff

Feature inventory

Domain	Routes
Auth / setup	/v1/auth/warehouse/* , /v1/warehouse/setup
Dispatch	/v1/warehouse/ops/dispatch/{preview,execute,settings,runs*} , rescue preview/propose, tracking, dispatch-locks
Reassign	/v1/warehouse/{recommend-reassign,reassign-order}
Orders / preorders	delay/reject/overflow/propose-delivery; preorder edit/reject
Board / exceptions / broadcast	/ops/board , /ops/exceptions , broadcast templates
Fleet	drivers/vehicles/staff, live-map
Inventory / commitments / products / settings / location	/ops/inventory* , stock-commitments, products, settings, location
Replenishment / demand / supply / transfers	insights, demand/forecast, supply-requests, transfers emergency/receive/force-receive
Returns inbound	returnsroutes /v1/returns/inbound* (+ /ops/returns)
Reverse logistics	GET/POST /v1/warehouse/reverse-logistics* (RequireRole Warehouse only)
Return policy	GET/PUT /v1/warehouse/return-policy (WarehouseAdmin/Admin)
Claims	shared orderroutes claims approve/reject (WarehouseAdmin)
Treasury / financials / payment-config / CRM / analytics	/ops/{treasury,financials,payment-config,crm,analytics}
Pulse	/v1/warehouse/ops/pulse

Parity gaps

Observation	Code
Control Tower in portal shell; absent from Android section enum	shells vs WarehouseSection.kt
PORTAL_SETUP / PORTAL_PROFILE / PORTAL_SEARCH on Android	explicit portal handoff
Return-policy routes; no shell href /return-policy	warehouseroutes vs WarehouseShell
Reverse-logistics role = WAREHOUSE not WAREHOUSE_ADMIN	creditnoteroutes

4. Factory — APIs (factoryroutes 39)

Roles: `FACTORY` , `FACTORY_ADMIN` (+ `ADMIN`). `FACTORY_DRIVER` uses driver routes.

Clients

Client	Evidence
Portal	<code>FactoryShell.tsx</code> : <code>/</code> , <code>loading-bay</code> , <code>manifests</code> , <code>manifest-exceptions</code> , <code>payload-override</code> , <code>transfers</code> , <code>supply-requests</code> , <code>fleet</code> , <code>staff</code> , <code>insights</code> , <code>analytics</code> , <code>settings/location</code>
Android	<code>FactorySection.kt</code> : <code>DASHBOARD</code> , <code>LOADING_BAY</code> , <code>TRANSFERS</code> , <code>FLEET</code> , <code>STAFF</code> , <code>LOCATION</code> , <code>SUPPLY_REQUESTS</code> , <code>PAYLOAD_OVERRIDE</code> , <code>MANIFESTS</code> , <code>MANIFEST_EXCEPTIONS</code> , <code>INSIGHTS</code> , <code>ANALYTICS</code> , <code>NOTIFICATIONS</code>

Feature inventory

Domain	Routes
Auth / setup / profile / location	<code>/v1/auth/factory/*</code> , <code>/v1/factory/setup</code> , <code>profile</code> , <code>ops/location</code>
Dashboard / analytics / pulse	<code>/v1/factory/{dashboard,analytics/overview}</code> , <code>/v1/factory/pulse</code>
Manifest lifecycle	<code>start-loading</code> , <code>seal</code> , <code>dispatch</code> , <code>complete</code> ; <code>factory dispatch</code>
Rebalance / cancel	<code>manifests rebalance</code> , <code>cancel-transfer</code> , <code>cancel</code>
Exceptions	<code>manifest-exceptions list/resolve</code>
Transfers / supply-requests	<code>create/transition</code> ; <code>accept/fulfill-options/patch</code>
Fleet / staff	<code>fleet</code> , <code>drivers</code> , <code>vehicles</code> , <code>staff CRUD</code>
Insights	clients call <code>/v1/warehouse/replenishment/insights</code> (<code>warehouse route</code> allows <code>factory roles</code> in <code>handler gate</code>)

No dedicated `FACTORY_DRIVER` app directory — role allowed on `driverroutes` .

5. Payload — APIs (`payloaderroutes` 27)

Role: `PAYLOAD` (+ `ADMIN`).

Clients

Client	Evidence
Terminal	<code>apps/payload-terminal</code> Expo app
Android	<code>PayloadRoot.kt</code> (<code>home</code> + <code>inbound</code>)
iOS	<code>Root home</code> + <code>inbound views</code>

Feature inventory

Feature	Routes
Auth	<code>/v1/auth/payloader/{login,refresh}</code>

Feature	Routes
Board	/v1/payloader/{trucks,orders,manifests}
Load / seal	start-loading, seal, seal-completed, seal-all, /v1/payload/seal
Inject	.../inject-order
Reassign	recommend-reassign, reassign-order, /v1/fleet/reassign
Exceptions	/v1/payload/manifest-exception , list, /v1/delivery/exception-report
Capacity	GET /v1/payload/capacity/{vehicleID}
Alias supplier manifests	/v1/supplier/manifests* same handlers
Pulse / notifications	/v1/payloader/pulse , user notifications
Inbound returns	returnsroutes (PAYLOAD allowed on inbound)

seal-all is registered; client usage must be verified per app (not assumed from docs).

6. Driver — APIs (driverroutes 49 + orderroutes doorstep + telemetry)

Roles: DRIVER , FACTORY_DRIVER .

Clients

Client	Evidence
Android	DriverRoutes : LOGIN , MAIN , SCANNER , NOTIFICATIONS , CORRECTION , OFFLOAD_REVIEW , PAYMENT_WAITING , CASH_COLLECTION , SHOP_CLOSED_WAITING , OFFLINE_VERIFIER , SYNC_QUEUE , SUPPLY_TRANSFERS
iOS	Matching Views under driver-app-ios
Portal	none under apps/

Feature inventory

Domain	Routes
Auth / profile / availability / pulse	/v1/auth/driver/login , /v1/driver/{profile,availability,pulse,history,earnings}
Manifest / fleet	manifest, manifest-gate, /v1/fleet/{manifest,orders} , geometry, depart, return-complete, reorder, request-early-complete
Telemetry	POST /v1/telemetry/location
Doorstep (orderroutes)	arrive, proximity-unlock, shop-closed, partial-offload, scan-qr, deliver, confirm-offload, collect-cash, complete, fiscal/retry
Doorstep (driverroutes aliases)	shop-closed, partial-offload, credit-leave, validate-qr, amend, negotiate, credit-delivery, missing-items, exception-report, split-payment, confirm-payment-bypass, bypass-offload
Sync offline	POST /v1/sync/batch
Supply transfers	/v1/driver/supply-transfers*
Rescue	/v1/driver/ops/rescue/{request,respond}

Domain	Routes
Cash recon	/v1/driver/cash-reconciliations
Return goods	GET /v1/driver/return-goods
Open fiscal / pending collections	/v1/driver/open-fiscal , pending-collections
Handshake	deliveryroutes verify-handshake, update-order-during-delivery
Force-complete	not driver — RoleAdmin , RoleWarehouseAdmin only

7. Platform routes (all roles)

Package	Routes
platformroutes	client-policy/config, media upload-ticket, device-token, auth refresh
webhookroutes	global-pay, adyen, stripe, payme, click
updateroutes	iOS plist + desktop updater.json
infraroutes	healthz/ready
etaroutes / laborcapacityroutes	ETA + labor capacity helpers

8. How this file was built

1. Listed apps/* and stub package.json descriptions.
2. Parsed every .(Get|Post|Put|Patch|Delete)("") in *routes/routes.go .
3. Read shell href arrays / Kotlin section enums / DriverRoutes.
4. Did **not** copy feature lists from ECOSYSTEM_FEATURES_BY_ROLE.md or other docs.

If a feature is not a route above and not a client nav id above, it is not claimed here.