

Neural Networks

Steve Cygu

January 23, 2019

OUTLINE

Introduction

- Why Machine Learning?
- Neural Networks and Human Brain

Neural Networks

- Components
- Types of Neural Networks

Fitting Neural Networks

- Feed-forward
- Back propagation
- Gradient descent

Some Issues in Training Neural Networks

References


Why Machine Learning?

Can we write algorithm to correctly identify each of the objects?


504192



Neural Networks and Human Brain



The Neuron and information transmission



Components

Layers

- ▶ **Input nodes**
No computation
- ▶ **Hidden nodes (Neurons)**
Intermediate processing and computation and transfers (another hidden layer or output).
- ▶ **Output nodes**
Uses a function (not necessarily activation function) to map the input from other layers to desired output format.
 - ▶ Sigmoid
 - ▶ Softmax

Synapse/Connections

- ▶ Transfers the output of neuron i to the input of neuron j .
- ▶ Each connection is assigned weight, W_{ij}

Activation function

Introduces **nonlinearity** into the neuron output.

- ▶ Sigmoid (Logistic Activation Function)

$$a(z) = \frac{1}{1 + \exp(-z)}$$



- ▶ Tanh (hyperbolic tangent Activation Function)

$$a(z) = \tanh(z) = \frac{2}{1 + \exp(-2z)} - 1 = 2\text{sigmoid}(2z) - 1$$

- ▶ ReLU (Rectified Linear Unit Activation Function)

$$a(z) = \max(0, z)$$


Sigmoid and Tanh Activation Functions



Types of Neural Networks

Single-layer Perceptron


- ▶ No hidden layer, a single neuron.



Types of Neural Networks


Single-layer Perceptron

- No hidden layer, a single neuron.



$$\hat{y} = b + \sum_{i=1}^n x_i w_i$$

Multi-layer perceptron (MLP)



Other types

- ▶ Convolutional Neural Network (CNN)
- ▶ Recurrent neural networks

Fitting Neural Networks

Weights are the parameters. The generic approach is by **gradient descent**.

- ▶ Forward-propagation (feed-forward)
- ▶ Backward-propagation

Feed-forward

Consider,

$$Z_1^i = X_1 W_{1,1}^i + X_2 W_{2,1}^i + X_3 W_{3,1}^i + X_4 W_{4,1}^i$$

Feed-forward

Consider,

$$Z_1^i = X_1 W_{1,1}^i + X_2 W_{2,1}^i + X_3 W_{3,1}^i + X_4 W_{4,1}^i$$

$$Z_2^i = X_1 W_{1,2}^i + X_2 W_{2,2}^i + X_3 W_{3,2}^i + X_4 W_{4,2}^i$$

Feed-forward

Consider,

$$Z_1^i = X_1 W_{1,1}^i + X_2 W_{2,1}^i + X_3 W_{3,1}^i + X_4 W_{4,1}^i$$

$$Z_2^i = X_1 W_{1,2}^i + X_2 W_{2,2}^i + X_3 W_{3,2}^i + X_4 W_{4,2}^i$$

\vdots

Feed-forward

Consider,

$$Z_1^i = X_1 W_{1,1}^i + X_2 W_{2,1}^i + X_3 W_{3,1}^i + X_4 W_{4,1}^i$$

$$Z_2^i = X_1 W_{1,2}^i + X_2 W_{2,2}^i + X_3 W_{3,2}^i + X_4 W_{4,2}^i$$

\vdots

Z^i 'component' is the **sum of weighted inputs** to each neuron.

$$Z^i = XW^i \tag{1}$$

Feed-forward

Apply activation function to 1

$$a^i = a(Z^i) \quad (2)$$

Propagate 2 to the output layer

$$Z^j = a^i W^j \quad (3)$$

$$\implies \hat{y} = a^j = a^*(Z^j) \quad (4)$$

Back propagation

- ▶ Estimate weights that ensures the model fits the training data well.

$$J = \sum \frac{1}{2} (y - \hat{y})^2 \quad (5)$$


Back propagation

- ▶ Estimate weights that ensures the model fits the training data well.


$$J = \sum \frac{1}{2} (y - \hat{y})^2 \quad (5)$$

$$J(W) = \frac{1}{2} \sum (y - a(a(XW^i)W^j))^2 \quad (6)$$

Gradient descent



Gradient descent



$$W_{t+1} = W_t - \gamma \Delta J(W_t)$$

Gradient descent

Compute $\frac{\partial J}{\partial W^i}$ and $\frac{\partial J}{\partial W^j}$

$$\begin{aligned}\frac{\partial J}{\partial W^j} &\approx - (y - \hat{y}) \frac{\partial \hat{y}}{\partial W^j} \\ \Rightarrow \frac{\partial J}{\partial W^j} &= -\mathbf{a}^{iT} (y - \hat{y}) a'(Z^j)\end{aligned}$$

$$\frac{\partial J}{\partial W^i} \approx - (y - \hat{y}) \frac{\partial \hat{y}}{\partial W^i}$$

$$\Rightarrow \frac{\partial J}{\partial W^i} = -X^T (y - \hat{y}) a'(Z^j) W^{jT} a'(Z^i)$$

Some Issues in Training Neural Networks

1. Starting values

- ▶ Starting weights are random numbers near zero.
- ▶ However, near weights collapses NN into approximately linear model.
- ▶ Exactly zero weights leads to zero derivatives and perfect symmetry.
- ▶ Large weights lead to poor results.

Some Issues in Training Neural Networks

1. Starting values

- ▶ Starting weights are random numbers near zero.
- ▶ However, near weights collapses NN into approximately linear model.
- ▶ Exactly zero weights leads to zero derivatives and perfect symmetry.
- ▶ Large weights lead to poor results.

2. Overfitting and Stopping Criterion


- ▶ **Reduce training error** to some predetermined threshold \rightarrow **overfitting**.
- ▶ Regularization by *weight decay* (analogous to ridge regression)

$$J(W) = \sum \frac{1}{2}(y - \hat{y})^2/n + \frac{1}{2}\lambda \left(\sum W_1^2 + \sum W_2^2 \right)$$

$\lambda \geq 0$ - Is tuning parameter. Larger values of λ shrinks weights toward zero.

- ▶ Cross-validation is used to estimate λ .

3. Convergence at the Local Minima



References

- [1] Trevor, H., Robert, T., & JH, F. (2009). The elements of statistical learning: data mining, inference, and prediction. *Springer series in statistics*. Second Edition
- [2] Tom M. Mitchell. (1997). Machine Learning *McGraw-Hill International Editions*.
- [3] Internet sources (2019).