



concordance=TRUE concordance=TRUE

# Neural Networks

Steve

January 10, 2019





# Components

- ▶ **Layers** - Input, Hidden and Output
  - ▶ **Neuron/Node/Unit** - Receives input and **computes** and output
- ▶ **Synapse** - Associated weights.
- ▶ **Activation function** - Introduces **nonlinearity** into the neuron output.
  - ▶ Sigmoid (Logistic Activation Function)
$$a(x) = \frac{1}{1 + \exp(-x)}$$
  - ▶ Tanh (hyperbolic tangent Activation Function)
$$a(x) = \tanh(x) = \frac{2}{1 + \exp(-2x)} - 1 = 2\text{sigmoid}(2x) - 1$$
  - ▶ ReLU (Rectified Linear Unit Activation Function)
$$a(x) = \max(0, x)$$

```
##
## Attaching package: 'dplyr'
## The following objects are masked from
'package:stats':
##
##      filter, lag
## The following objects are masked from
'package:base':
##
##      intersect, setdiff, setequal, union
## -- Attaching packages
----- tidyverse
1.2.1 --
## v tibble  2.0.0      v purrr  0.2.5
## v readr   1.3.1      v stringr 1.3.1
## v tibble  2.0.0      v forcats 0.3.0
## -- Conflicts
-----
tidyverse_conflicts() --
```

# Feed-forward

Consider,

$$H_1^{(1)} = X_1 W_{1,1}^{(1)} + X_2 W_{2,1}^{(1)} + X_3 W_{3,1}^{(1)} + X_4 W_{4,1}^{(1)}$$

# Feed-forward

Consider,

$$H_1^{(1)} = X_1 W_{1,1}^{(1)} + X_2 W_{2,1}^{(1)} + X_3 W_{3,1}^{(1)} + X_4 W_{4,1}^{(1)}$$

$$H_2^{(1)} = X_1 W_{1,2}^{(1)} + X_2 W_{2,2}^{(1)} + X_3 W_{3,2}^{(1)} + X_4 W_{4,2}^{(1)}$$



# Feed-forward

Consider,

$$H_1^{(1)} = X_1 W_{1,1}^{(1)} + X_2 W_{2,1}^{(1)} + X_3 W_{3,1}^{(1)} + X_4 W_{4,1}^{(1)}$$

$$H_2^{(1)} = X_1 W_{1,2}^{(1)} + X_2 W_{2,2}^{(1)} + X_3 W_{3,2}^{(1)} + X_4 W_{4,2}^{(1)}$$

$\vdots$

# Feed-forward

Consider,

$$H_1^{(1)} = X_1 W_{1,1}^{(1)} + X_2 W_{2,1}^{(1)} + X_3 W_{3,1}^{(1)} + X_4 W_{4,1}^{(1)}$$

$$H_2^{(1)} = X_1 W_{1,2}^{(1)} + X_2 W_{2,2}^{(1)} + X_3 W_{3,2}^{(1)} + X_4 W_{4,2}^{(1)}$$

$\vdots$

$H^2$  'component' is the **sum of weighted inputs** to each neuron.

$$H^{(1)} = XW^{(1)} \tag{1}$$

# Feed-forward

Apply activation function to 1

$$a^{(1)} = a(H^{(1)}) \quad (2)$$

Propagate 2 to the output layer

$$H^{(2)} = a^{(1)} W^{(2)} \quad (3)$$

$$\implies \hat{y} = a^{(2)} = a(H^{(2)}) \quad (4)$$

# Back propagation

- Estimate weights that ensures the model fits the training data well.

$$J = \sum \frac{1}{2} (y - \hat{y})^2 \quad (5)$$


# Back propagation

- Estimate weights that ensures the model fits the training data well.

$$J = \sum \frac{1}{2} (y - \hat{y})^2 \quad (5)$$

$$J(W) = \frac{1}{2} \sum \left( y - a(a(XW^{(1)})W^{(2)}) \right)^2 \quad (6)$$

# Gradient descent



# Gradient descent

$$W_{t+1} = W_t - \gamma \Delta J(W_t)$$

Compute  $\frac{\partial J}{\partial W^{(1)}}$  and  $\frac{\partial J}{\partial W^{(2)}}$

$$\begin{aligned}\frac{\partial J}{\partial W^{(2)}} &\approx -(y - \hat{y}) \frac{\partial \hat{y}}{\partial W^{(2)}} \\ &= -(y - \hat{y}) \frac{\partial \hat{y}}{\partial H^{(2)}} \frac{\partial H^{(2)}}{\partial W^{(2)}} \\ &= -(y - \hat{y}) \mathbf{a}'(H^{(2)}) \frac{\partial H^{(2)}}{\partial W^{(2)}} \\ &= -(y - \hat{y}) \mathbf{a}'(H^{(2)}) \frac{\partial H^{(2)}}{\partial W^{(2)}} \\ \implies \frac{\partial J}{\partial W^{(2)}} &= -\mathbf{a}^{(1)T} (y - \hat{y}) \mathbf{a}'(H^{(2)})\end{aligned}$$

# Gradient descent

$$\begin{aligned}\frac{\partial J}{\partial W^{(1)}} &\approx -(y - \hat{y}) \frac{\partial \hat{y}}{\partial W^{(1)}} \\&= -(y - \hat{y}) \frac{\partial \hat{y}}{\partial H^{(2)}} \frac{\partial H^{(2)}}{\partial W^{(1)}} \\&= -(y - \hat{y}) a'(H^{(2)}) \frac{\partial H^{(2)}}{\partial W^{(1)}} \\&= -(y - \hat{y}) a'(H^{(2)}) \frac{\partial H^{(2)}}{\partial a^{(1)}} \frac{\partial a^{(1)}}{\partial W^{(1)}} \\&= -(y - \hat{y}) a'(H^{(2)}) W^{(2)T} \frac{\partial a^{(1)}}{\partial W^{(1)}} \\&= -(y - \hat{y}) a'(H^{(2)}) W^{(2)T} \frac{\partial a^{(2)}}{\partial H^{(2)}} \frac{\partial H^{(2)}}{\partial W^{(1)}} \\ \implies \frac{\partial J}{\partial W^{(1)}} &= -X^T (y - \hat{y}) a'(H^{(2)}) W^{(2)T} a'(H^{(1)})\end{aligned}$$



# Remarks

1. Starting values
2. Overfitting and Stopping Criterion
  - ▶ Reduce training error to some predetermined threshold  $\longrightarrow$  overfitting.
  - ▶ Regularization

$$J(W) = \sum \frac{1}{2}(y - \hat{y})^2/n + \frac{1}{2}\lambda \left( \sum w_1 + \sum w_2 \right)$$

$\lambda$  - Regularization hyper parameter

# Remarks

## 3. Convergence and Local Minima

