


Git




Cyrus Wong

In case of fire



Github




StackOverflow



My code



When you can't find the right
Stack Overflow answer



**The code will be executed successfully
or
You will be executed successfully**



imgflip.com



这图做的还可以



GAOXIAOGIF.COM

Create a Repository

From scratch -- Create a new local repository

```
$ git init [project name]
```

Download from an existing repository

```
$ git clone my_url
```

Observe your Repository

List new or modified files not yet committed

```
$ git status
```

Show the changes to files not yet staged

```
$ git diff
```

Show the changes to staged files

```
$ git diff --cached
```

Show all staged and unstaged file changes

```
$ git diff HEAD
```

Show the changes between two commit ids

```
$ git diff commit1 commit2
```

List the change dates and authors for a file

```
$ git blame [file]
```

Show the file changes for a commit id and/or file

```
$ git show [commit]:[file]
```

Show full change history

```
$ git log
```

Show change history for file/directory including diffs

```
$ git log -p [file/directory]
```

Working with Branches

List all local branches

```
$ git branch
```

List all branches, local and remote

```
$ git branch -av
```

Switch to a branch, my_branch, and update working directory

```
$ git checkout my_branch
```

Create a new branch called new_branch

```
$ git branch new_branch
```

Delete the branch called my_branch

```
$ git branch -d my_branch
```

Merge branch_a into branch_b

```
$ git checkout branch_b
```

```
$ git merge branch_a
```

Tag the current commit

```
$ git tag my_tag
```

Make a change

Stages the file, ready for commit

```
$ git add [file]
```

Stage all changed files, ready for commit

```
$ git add .
```

Commit all staged files to versioned history

```
$ git commit -m "commit message"
```

Commit all your tracked files to versioned history

```
$ git commit -am "commit message"
```

Unstages file, keeping the file changes

```
$ git reset [file]
```

Revert everything to the last commit

```
$ git reset --hard
```

Synchronize

Get the latest changes from origin (no merge)

```
$ git fetch
```

Fetch the latest changes from origin and merge

```
$ git pull
```

Fetch the latest changes from origin and rebase

```
$ git pull --rebase
```

Push local changes to the origin


```
$ git push
```

Finally!

When in doubt, use git help

```
$ git command --help
```

Or visit <https://training.github.com/> for official GitHub training.



Git

- We use Git to keep track of changes to our code.

Git

- We use Git to keep track of changes to our code.

```
a = 1  
b = 2  
c = 3
```

Create file

Git

- We use Git to keep track of changes to our code.

```
a = 1  
b = 2  
c = 3
```

Create file

```
a = 1  
b = 2  
c = 3  
d = 4
```

Add a line

Git

- We use Git to keep track of changes to our code.

```
a = 1  
b = 2  
c = 3
```

Create file

```
a = 1  
b = 2  
c = 3  
d = 4
```

Add a line

```
a = 1  
b = 2  
d = 4
```

Delete a line

Git

- We also use Git to synchronize code across multiple devices.


Git

- We also use Git to synchronize code across multiple devices.

```
a = 1  
b = 2
```

Git

- We also use Git to synchronize code across multiple devices.



Git

- We also use Git to synchronize code across multiple devices.


```
a = 1  
b = 2
```

```
a = 1  
b = 2  
c = 3
```

```
a = 1  
b = 2  
d = 4
```


Git

- We also use Git to synchronize code across multiple devices.



Git

- We also use Git to synchronize code across multiple devices.



Git

- We also use Git to synchronize code across multiple devices.


```
a = 1  
b = 2  
c = 3  
d = 4
```

```
a = 1  
b = 2  
c = 3
```

```
a = 1  
b = 2  
d = 4
```

Git

- We also use Git to synchronize code across multiple devices.




Git

- Git allows us to test changes to our code without losing the original.

Git


- Git allows us to test changes to our code without losing the original.



```
a = 1  
b = 2  
c = 3
```



Git

- Git allows us to test changes to our code without losing the original.




Git

- Git allows us to test changes to our code without losing the original.




Git

- Git allows us to test changes to our code without losing the original.



Git

- Git allows us to test changes to our code without losing the original.



Git

- We can go back in time to prior versions of our code.

Git

- We can go back in time to prior versions of our code.

```
a = 1  
b = 2  
c = 3
```

Create file

```
a = 1  
b = 2  
c = 3  
d = 4
```

Add a line

```
a = 1  
b = 2  
d = 4
```

Delete a line

Git

- We can go back in time to prior versions of our code.

```
a = 1  
b = 2  
c = 3
```

Create file

```
a = 1  
b = 2  
c = 3  
d = 4
```

Add a line

GitHub

Microsoft to acquire GitHub for \$7.5 billion

June 4, 2018 | Microsoft News Center




From left: Chris Wanstrath, Github CEO and co-founder; Satya Nadella, Microsoft CEO; and Nat Friedman, Microsoft corporate vice president, Developer Services

Acquisition will empower developers, accelerate GitHub's growth and advance Microsoft services with new audiences



GitHub

- A central hub on the internet for you to store, view, and contribute to your own and others' repositories.
- A “repository” is Git/GitHub terminology for a collection of related code.
- You will likely find it easiest to first create a repository on GitHub's web interface, before working on it at the command line.



git clone

- Used to initially get a local copy of a repository stored elsewhere (e.g. GitHub).

git clone


- Used to initially get a local copy of a repository stored elsewhere (e.g. GitHub).

```
a = 1  
b = 2
```




git clone

- Used to initially get a local copy of a repository stored elsewhere (e.g. GitHub).



git clone

- Used to initially get a local copy of a repository stored elsewhere (e.g. GitHub).



git clone

- Used to initially get a local copy of a repository stored elsewhere (e.g. GitHub).

```
git clone <url>
```

git add

- Used to let Git know which files we want it to look at when we prepare our next “snapshot” of the repository.

git add

- Used to let Git know which files we want it to look at when we prepare our next “snapshot” of the repository.

```
a = 1  
b = 2
```

```
a = 1  
b = 2
```

git add

- Used to let Git know which files we want it to look at when we prepare our next “snapshot” of the repository.

```
a = 1  
b = 2  
c = 3
```

```
a = 1  
b = 2
```


git add

- Used to let Git know which files we want it to look at when we prepare our next “snapshot” of the repository.

```
a = 1  
b = 2  
c = 3
```

```
a = 1  
b = 2
```

git add

- Used to let Git know which files we want it to look at when we prepare our next “snapshot” of the repository.

```
a = 1  
b = 2  
c = 3
```

```
a = 1  
b = 2
```

git add

- Used to let Git know which files we want it to look at when we prepare our next “snapshot” of the repository.

```
a = 1  
b = 2
```

```
a = 1  
b = 2  
c = 3
```

git add

- Used to let Git know which files we want it to look at when we prepare our next “snapshot” of the repository.

```
git add <filename>
```

```
git add -A
```

git status

- Used to let you know the current state of your directory (i.e., what's changed)

git commit


- Used to tell Git that it's time to take that next “snapshot” of the repository.

```
a = 1  
b = 2  
c = 3
```

```
a = 1  
b = 2
```

git commit

- Used to tell Git that it's time to take that next “snapshot” of the repository.




```
a = 1  
b = 2
```

git commit

- Used to tell Git that it's time to take that next “snapshot” of the repository.

```
a = 1  
b = 2
```



Add a line

git commit

- Used to tell Git that it's time to take that next “snapshot” of the repository.

```
git commit -m "message"  
git commit -m "Add a line"
```


git push

- Used to take all of the snapshots and changes made locally and send them to your “remote” (i.e., GitHub).

git push

- Used to take all of the snapshots and changes made locally and send them to your “remote” (i.e., GitHub).


```
a = 1  
b = 2
```



Add a line


git push

- Used to take all of the snapshots and changes made locally and send them to your “remote” (i.e., GitHub).




git push

- Used to take all of the snapshots and changes made locally and send them to your “remote” (i.e., GitHub).



Add a line



Add a line

git pull

- Used to get all of the snapshots and changes that are stored on your “remote” (i.e., GitHub) onto your local machine.

git pull

- Used to get all of the snapshots and changes that are stored on your “remote” (i.e., GitHub) onto your local machine.

a = 1	a = 1	a = 1
b = 2	b = 2	c = 3
	c = 3	

Add a line


Delete line

a = 1	a = 1
b = 2	b = 2
	c = 3

Add a line


git pull

- Used to get all of the snapshots and changes that are stored on your “remote” (i.e., GitHub) onto your local machine.



git pull

- Used to get all of the snapshots and changes that are stored on your “remote” (i.e., GitHub) onto your local machine.




Conflicts

- A conflict can occur when locally saved changes are incompatible with changes on the remote.

```
a = 1  
b = 2  
c = 3  
d = 4
```

```
a = 1  
b = 2  
c = 5  
d = 4
```



Conflicts

- A conflict can occur when locally saved changes are incompatible with changes on the remote.

```
a = 1  
b = 2  
c = 3  
d = 4
```

```
a = 1  
b = 2  
c = 5  
d = 4
```

CONFLICT (content): Merge conflict in foo.py
Automatic merge failed; fix conflicts and
then commit the result.

Conflicts

- A conflict can occur when locally saved changes are incompatible with changes on the remote.

```
a = 1
b = 2
<<<<< HEAD
c = 3
=====
c = 5
>>>>> 2828abcdef0123456789
d = 4
```

Conflicts

- A conflict can occur when locally saved changes are incompatible with changes on the remote.

```
a = 1
b = 2
<<<<< HEAD
c = 3
=====
c = 5
>>>>> 2828abcdef0123456789
d = 4
```

Conflicts

- A conflict can occur when locally saved changes are incompatible with changes on the remote.

```
a = 1
b = 2
<<<<< HEAD
c = 3
=====
c = 5
>>>>> 2828abcdef0123456789
d = 4
```

git log

- Used to get a history of all of the commits you've made locally.

git reset

- Used to jump back in time to a prior version of your code (perhaps because the current version is broken).

git reset

- Used to jump back in time to a prior version of your code (perhaps because the current version is broken).

```
git reset --hard <commit>
```


```
git reset --hard origin/master
```

Git

- We use Git commits to create a history of how our code evolves.

Git


- We use Git commits to create a history of how our code evolves.



initial
commit


Git

- We use Git commits to create a history of how our code evolves.




Git

- We use Git commits to create a history of how our code evolves.




Git

- We use Git commits to create a history of how our code evolves.




Git

- We use Git commits to create a history of how our code evolves.




Git

- We use Git commits to create a history of how our code evolves.




Git

- We use Git commits to create a history of how our code evolves.




Git

- We use Git commits to create a history of how our code evolves.



Git

- We use Git commits to create a history of how our code evolves.




git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.

git branch


- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.



initial
commit


git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.




git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.




git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.




git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.




git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.




git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.




git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.




git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.




git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.



git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.



git branch

- Used to get an identical copy of your repository that can be edited and tested separately without impacting production environments.


```
git branch
```

```
git branch <name>
```


```
git checkout <name>
```

```
git merge <name>
```



Original



After "git merge"





After "git rebase"



Remotes


Remotes

- Recall that there's a distinction between code on your local device and code on the “remote”, e.g. GitHub.




Remotes

- Recall that there's a distinction between code on your local device and code on the “remote”, e.g. GitHub.




`git fetch`




Remotes

- Recall that there's a distinction between code on your local device and code on the “remote”, e.g. GitHub.




Remotes

- Recall that there's a distinction between code on your local device and code on the “remote”, e.g. GitHub.




```
git fetch  
git merge origin/master
```




Remotes

- Recall that there's a distinction between code on your local device and code on the “remote”, e.g. GitHub.




```
git fetch  
git merge origin/master
```





Remotes

- Recall that there's a distinction between code on your local device and code on the “remote”, e.g. GitHub.



`git pull`





Forks

No description, website, or topics provided. Edit

Add topics

1 commit 1 branch 0 releases 1 contributor

Branch: master, ... New pull request Create new file Upload files Find file Clone or download ...

s33a-student Create index.html Latest commit 75b1836 3 minutes ago

index.html Create index.html 3 minutes ago

Help people interested in this repository understand your project by adding a README. Add a README

- Code
- Issues
- Pull requests
- Projects
- Wiki
- Insights
- Settings

No description, website, or topics provided. Edit

Add topics

1 commit 1 branch 0 releases 1 contributor

Branch: master, ... New pull request Create new file Upload files Find file Clone or download ...

s33a-student Create index.html Latest commit 75b1836 3 minutes ago

index.html Create index.html 3 minutes ago

Help people interested in this repository understand your project by adding a README. Add a README

Pull Requests

Pull Requests

- A ***pull request*** is GitHub-specific terminology that arises when someone other than the original contributor wishes to propose modifications to someone else's repository.

Pull Requests

- A ***pull request*** is GitHub-specific terminology that arises when someone other than the original contributor wishes to propose modifications to someone else's repository.
- They typically arise after someone has forked their own copy of a repository, tested out a change, and wants to incorporate it back in to the original codebase.

Pull Requests

- A ***pull request*** is GitHub-specific terminology that arises when someone other than the original contributor wishes to propose modifications to someone else's repository.
- They typically arise after someone has forked their own copy of a repository, tested out a change, and wants to incorporate it back in to the original codebase.
- It's also possible to use PRs to merge your own branches.

GitHub Pages

GitHub Pages

- So far, all of the code we've written has only been “run” locally, on my own machine or IDE.
- GitHub Pages is a feature of GitHub that effectively allows you to deploy the contents of a repository to live on the internet.