

A diagram showing a circular cross-section of a beam. The cross-section is divided into concentric regions by three circles. The outermost region is shaded gray. A vertical dashed line passes through the center of the circles. At the top and bottom of the vertical line, there are horizontal arrows pointing outwards, labeled 'A'.

Technical drawing of a mechanical part, likely a bracket or support, showing dimensions and tolerances. The part has a central rectangular hole and two side flanges. Dimensions include diameters (ϕ 18.00, ϕ 15.00, ϕ 8.40, ϕ 13.00), radii (R 2.0), and various angles ($0.30 \times 45^\circ$, $1.00 \times 30^\circ$). Tolerances are specified for several dimensions, such as $+0.05/-0.02$ for the outer diameter and $+0.10/-0.10$ for the hole diameter.

1. ALL EDGES AND CORNERS TO BE FREE OF BURRS
(ALLE ECKEN UND KANTEN ENTGRATEN)
2. PART HAS TO BE TEMPERED TO HRC 53...60
(TEIL HAERTEN, HAERTE HRC 53...60)
3. COSMETIC REQUIREMENTS PER A-5951-1514-1 (741.100F) CAT.III-C
(KOSMETISCHE ANFORDERUNGEN NACH SPEC A-5951-1514-1 (741.100F) CAT.III-C)

ATGE_MACHINE_A3_REV_2