

# Parallel algorithms

Overhead, time, speedup

Paolo Bientinesi

Umeå Universitet  
pauldj@cs.umu.se

AQTIVATE workshop  
28–29 November 2023



High Performance and  
Automatic Computing



UMEÅ UNIVERSITY



HPC2N

# Sequential (serial) algorithms – 1/2

# Sequential (serial) algorithms – 1/2

## Resources



# Sequential (serial) algorithms – 1/2

**Resources**



**Task**



# Sequential (serial) algorithms – 1/2

**Resources**



**Task**



**Cost function:** Money (or time)

## Sequential (serial) algorithms – 2/2

- ▶ **Resources:**       $p = 1$  processor    (1 worker)

## Sequential (serial) algorithms – 2/2

- ▶ **Resources:**  $p = 1$  processor (1 worker)
- ▶ **Task:** Compute/solve/simulate XYZ

## Sequential (serial) algorithms – 2/2

- ▶ **Resources:**  $p = 1$  processor (1 worker)
- ▶ **Task:** Compute/solve/simulate XYZ
- ▶ **Objective:** Minimize the cost



## Sequential (serial) algorithms – 2/2

- ▶ **Resources:**  $p = 1$  processor (1 worker)
- ▶ **Task:** Compute/solve/simulate XYZ
- ▶ **Objective:** Minimize the cost
- ▶ **Cost:** # FLOPS (floating point operations), # of swaps, # bytes (amount of data) moved, ..., execution time
- ▶ **Cost as a function of the input**
  - ▶ “size of the problem”, “size of the input”  
length of array ( $n$ ), number of vertices and edges ( $V, E$ ), ...
  - ▶ Matrix-matrix multiplication:  $O(n^3), \dots, O(n^{2.37286})$   
Shortest path:  $O(V^2), O((E + V) \log V), O(E + V \log V)$

# Parallel algorithms – 1/2

**Resources**



**Task**



**Cost function**

Money (or time)

# Parallel algorithms – 1/2

## Resources



## Task



### Problems

1. how to split the work?
2. how to coordinate the workers?

## Parallel algorithms – 2/2

- ▶ **Resources:**  $p > 1$  processors  
 *$p$  workers; naturally, we want to exploit all of them*
- ▶ **Task:** Compute/solve/simulate XYZ
- ▶ **Objective:** Minimize the cost

## Parallel algorithms – 2/2

- ▶ **Resources:**  $p > 1$  processors  
 *$p$  workers; naturally, we want to exploit all of them*
- ▶ **Task:** Compute/solve/simulate XYZ
- ▶ **Objective:** Minimize the cost
- ▶ **Computational model:** PRAM, EREW  
*how the workers “operate” and “communicate”*

# Parallel algorithms – 2/2

- ▶ **Resources:**  $p > 1$  processors  
 $p$  workers; *naturally, we want to exploit all of them*
- ▶ **Task:** Compute/solve/simulate XYZ
- ▶ **Objective:** Minimize the cost
- ▶ **Computational model:** PRAM, EREW  
*how the workers “operate” and “communicate”*
- ▶ **Cost:** # FLOPS (floating point operations), # of swaps, # bytes (amount of data) moved, . . . , “execution time”  
*definition for “parallel execution time” needed; more later*
- ▶ **Cost as a function of the input**
  - ▶ Shortest path:  $O(V)$  processors,  $O(E + V)$   
 $O(\log(V))$  processors,  $O(\bar{E}k(N))$

# General pattern for parallel algorithms

1. Decomposition of the problem into sub-problems
2. Parallel solution of the sub-problems
3. Composition of the sub-solutions

## Example: sequential program

**Data:**  $n$  tests, each consisting of  $t$  exercises

**Task:** Grade all exercises of all tests

**Resources:** 1 grader (= sequential program)



## Example: sequential program

**Data:**  $n$  tests, each consisting of  $t$  exercises

**Task:** Grade all exercises of all tests

**Resources:** 1 grader (= sequential program)

- ▶ The grader does everything, in whatever order the program dictates.

## Example: data vs. task parallelism<sup>\*</sup>

<sup>\*</sup>: definitions might differ

**Data:**  $n$  tests, each consisting of  $t$  exercises

**Task:** Grade all exercises of all tests

**Resources:**  $p$  graders

## Example: data vs. task parallelism<sup>\*</sup>

<sup>\*</sup>: definitions might differ

**Data:**  $n$  tests, each consisting of  $t$  exercises

**Task:** Grade all exercises of all tests

**Resources:**  $p$  graders

▶ Each grader works on  $n/p$  tests, all exercises  $\Rightarrow$  **Data parallelism**

Implicit assumption: All exercises can be graded independently

# Example: data vs. task parallelism<sup>\*</sup>

<sup>\*</sup>: definitions might differ

**Data:**  $n$  tests, each consisting of  $t$  exercises

**Task:** Grade all exercises of all tests

**Resources:**  $p$  graders

- ▶ Each grader works on  $n/p$  tests, all exercises  $\Rightarrow$  **Data parallelism**
- ▶ Are all graders equally fast? **Load balancing**

Implicit assumption: All exercises can be graded independently

# Example: data vs. task parallelism<sup>\*</sup>

<sup>\*</sup>: definitions might differ

**Data:**  $n$  tests, each consisting of  $t$  exercises

**Task:** Grade all exercises of all tests

**Resources:**  $p$  graders

- ▶ Each grader works on  $n/p$  tests, all exercises  $\Rightarrow$  **Data parallelism**
  - ▶ Are all graders equally fast? Load balancing
  - ▶ Are all graders competent in all exercises? Specialization

Implicit assumption: All exercises can be graded independently

# Example: data vs. task parallelism<sup>\*</sup>

<sup>\*</sup>: definitions might differ

**Data:**  $n$  tests, each consisting of  $t$  exercises

**Task:** Grade all exercises of all tests

**Resources:**  $p$  graders

- ▶ Each grader works on  $n/p$  tests, all exercises  $\Rightarrow$  **Data parallelism**
  - ▶ Are all graders equally fast? Load balancing
  - ▶ Are all graders competent in all exercises? Specialization
- ▶ Each grader works on  $t/p$  exercises, all tests  $\Rightarrow$  **Task parallelism**

Implicit assumption: All exercises can be graded independently

# Example: data vs. task parallelism<sup>\*</sup>

<sup>\*</sup>: definitions might differ

**Data:**  $n$  tests, each consisting of  $t$  exercises

**Task:** Grade all exercises of all tests

**Resources:**  $p$  graders

- ▶ Each grader works on  $n/p$  tests, all exercises  $\Rightarrow$  **Data parallelism**
  - ▶ Are all graders equally fast? Load balancing
  - ▶ Are all graders competent in all exercises? Specialization
- ▶ Each grader works on  $t/p$  exercises, all tests  $\Rightarrow$  **Task parallelism**
  - ▶ Are all graders equally fast? Load balancing

Implicit assumption: All exercises can be graded independently

# Example: data vs. task parallelism\*

☆: definitions might differ

**Data:**  $n$  tests, each consisting of  $t$  exercises

**Task:** Grade all exercises of all tests

**Resources:**  $p$  graders

- ▶ Each grader works on  $n/p$  tests, all exercises  $\Rightarrow$  **Data parallelism**
  - ▶ Are all graders equally fast? Load balancing
  - ▶ Are all graders competent in all exercises? Specialization
  
- ▶ Each grader works on  $t/p$  exercises, all tests  $\Rightarrow$  **Task parallelism**
  - ▶ Are all graders equally fast? Load balancing
  - ▶ Are all exercises equally time consuming? " "

Implicit assumption: All exercises can be graded independently



# Example: data vs. task parallelism\*

☆: definitions might differ

**Data:**  $n$  tests, each consisting of  $t$  exercises

**Task:** Grade all exercises of all tests

**Resources:**  $p$  graders

- ▶ Each grader works on  $n/p$  tests, all exercises  $\Rightarrow$  **Data parallelism**
  - ▶ Are all graders equally fast? Load balancing
  - ▶ Are all graders competent in all exercises? Specialization
  
- ▶ Each grader works on  $t/p$  exercises, all tests  $\Rightarrow$  **Task parallelism**
  - ▶ Are all graders equally fast? Load balancing
  - ▶ Are all exercises equally time consuming? " "

Implicit assumption: All exercises can be graded independently

# Example: data vs. task parallelism\*

☆: definitions might differ

**Data:**  $n$  tests, each consisting of  $t$  exercises

**Task:** Grade all exercises of all tests

**Resources:**  $p$  graders

- ▶ Each grader works on  $n/p$  tests, all exercises  $\Rightarrow$  **Data parallelism**
  - ▶ Are all graders equally fast? Load balancing
  - ▶ Are all graders competent in all exercises? Specialization
  
- ▶ Each grader works on  $t/p$  exercises, all tests  $\Rightarrow$  **Task parallelism**
  - ▶ Are all graders equally fast? Load balancing
  - ▶ Are all exercises equally time consuming? " "

Implicit assumption: All exercises can be graded independently

What if this is not the case? **Dependencies** — more later

## Demo: Deck sorting

# Demo: Deck sorting

- ▶ 1 Paolo vs. 3 students
- ▶ 1 Paolo vs. 4 students
  
- ▶ Shared memory vs. distributed memory

# General pattern for parallel algorithms

1. Decomposition of the problem into sub-problems

Examples:

- ▶ Data distribution
- ▶ Task decomposition
- ▶ Domain decomposition

2. Parallel solution of the sub-problems

3. Composition of the sub-solutions

All these steps might require

- ▶ Extra computation
  - ▶ Synchronization
  - ▶ Data transfer
- } OVERHEAD

# Time

# Time

- ▶ **Wall time** or “wall-clock time” :  
real time between the beginning and the end of a computation

# Time

- ▶ **Wall time** or “wall-clock time” :  
real time between the beginning and the end of a computation

$T_p(n) :=$  Wall time to solve a problem of size  $n$  using  $p$  procs.

$$T_p(n) = t_1 - t_0$$

$t_0$  : earliest time when one of the procs. starts its execution,

$t_1$  : latest time when one of the procs. completes its execution



# Time

- ▶ **Wall time** or “wall-clock time” :  
real time between the beginning and the end of a computation

$T_p(n) :=$  Wall time to solve a problem of size  $n$  using  $p$  procs.

$$T_p(n) = t_1 - t_0$$

$t_0$  : earliest time when one of the procs. starts its execution,

$t_1$  : latest time when one of the procs. completes its execution

- ▶ **CPU-time** or “core time” :  
cumulative time spent by all processors in a computation

# Time

- ▶ **Wall time** or “wall-clock time” :  
real time between the beginning and the end of a computation

$T_p(n) :=$  Wall time to solve a problem of size  $n$  using  $p$  procs.

$$T_p(n) = t_1 - t_0$$

$t_0$  : earliest time when one of the procs. starts its execution,

$t_1$  : latest time when one of the procs. completes its execution

- ▶ **CPU-time** or “core time” :  
cumulative time spent by all processors in a computation  
Cumulative cost for all workers

# Questions

- ▶ In the analogy of the house, what does wall time measure?

# Questions

- ▶ In the analogy of the house, what does wall time measure?
- ▶ In the analogy of the house, what does CPU-time measure?


# Questions

- ▶ In the analogy of the house, what does wall time measure?
- ▶ In the analogy of the house, what does CPU-time measure?
- ▶ Two programs with same wall time and different CPU-time?

# Questions

- ▶ In the analogy of the house, what does wall time measure?
- ▶ In the analogy of the house, what does CPU-time measure?
- ▶ Two programs with same wall time and different CPU-time?
- ▶ Two programs with same CPU-time and different wall time?

# Concurrency and parallelism\*




Tim Mattson

Example of programs with same CPU-time but different wall time

\*: definitions differ

# Concurrency and parallelism\*



Tim Mattson

Example of programs with same CPU-time but different wall time

Did you spot the mistake?

\*: definitions differ



$$T_p(n)$$

- ▶  $T_p(n) :=$  Wall time to solve a problem of size  $n$  using  $p$  processors

$$T_p(n)$$

►  $T_p(n) :=$  Wall time to solve a problem of size  $n$  using  $p$  processors

►  $n > m \quad \Rightarrow \quad T_p(n) \geq T_p(m)$  Typical evolution with size

$$T_p(n)$$

- ▶  $T_p(n) :=$  Wall time to solve a problem of size  $n$  using  $p$  processors
- ▶  $n > m \Rightarrow T_p(n) \geq T_p(m)$  Typical evolution with size

**Example:** Eigensolver

Time complexity:  $8n^3$

$$T_p(\bar{n}) = t_0$$

$$T_p(1.5\bar{n}) = ?$$

$$T_p(n)$$

- ▶  $T_p(n) :=$  Wall time to solve a problem of size  $n$  using  $p$  processors
- ▶  $n > m \Rightarrow T_p(n) \geq T_p(m)$  Typical evolution with size

**Example:** Eigensolver

Time complexity:  $8n^3$                        $T_p(\bar{n}) = t_0$                        $T_p(1.5\bar{n}) = ?$

$\text{Cost}(1.5\bar{n}) \approx 8(1.5\bar{n})^3 = 8 \times 3.375\bar{n}^3 = 3.375t_0$

$$T_p(n)$$

►  $T_p(n) :=$  Wall time to solve a problem of size  $n$  using  $p$  processors

►  $n > m \Rightarrow T_p(n) \geq T_p(m)$  Typical evolution with size

**Example:** Eigensolver

Time complexity:  $8n^3$   $T_p(\bar{n}) = t_0$   $T_p(1.5\bar{n}) = ?$

$\text{Cost}(1.5\bar{n}) \approx 8(1.5\bar{n})^3 = 8 \times 3.375\bar{n}^3 = 3.375t_0$

►  $p > q \Rightarrow T_p(n) < T_q(n)$  Expected evolution with #procs

# $T_p(n)$

- ▶  $T_p(n) :=$  Wall time to solve a problem of size  $n$  using  $p$  processors

- ▶  $n > m \Rightarrow T_p(n) \geq T_p(m)$  Typical evolution with size

## **Example: Eigensolver**

Time complexity:  $8n^3$   $T_p(\bar{n}) = t_0$   $T_p(1.5\bar{n}) = ?$

$$\text{Cost}(1.5\bar{n}) \approx 8(1.5\bar{n})^3 = 8 \times 3.375\bar{n}^3 = 3.375t_0$$

- ▶  $p > q \Rightarrow T_p(n) < T_q(n)$  Expected evolution with #procs

Ideally:  $T_{2p}(n) \approx \frac{1}{2}T_p(n)$ ,  $T_{4p}(n) \approx \frac{1}{4}T_p(n)$ , ...

# $T_p(n)$

- ▶  $T_p(n) :=$  Wall time to solve a problem of size  $n$  using  $p$  processors

- ▶  $n > m \Rightarrow T_p(n) \geq T_p(m)$  Typical evolution with size

## **Example: Eigensolver**

Time complexity:  $8n^3$   $T_p(\bar{n}) = t_0$   $T_p(1.5\bar{n}) = ?$

$$\text{Cost}(1.5\bar{n}) \approx 8(1.5\bar{n})^3 = 8 \times 3.375\bar{n}^3 = 3.375t_0$$

- ▶  $p > q \Rightarrow T_p(n) < T_q(n)$  Expected evolution with #procs

Ideally:  $T_{2p}(n) \approx \frac{1}{2}T_p(n)$ ,  $T_{4p}(n) \approx \frac{1}{4}T_p(n)$ , ...

In practice, ... OVERHEAD!

# Parallel Speedup

► **Speedup:**  $S_p(n) := \frac{T_1(n)}{T_p(n)}$



# Parallel Speedup

- ▶ **Speedup:**  $S_p(n) := \frac{T_1(n)}{T_p(n)}$ 
  - ▶ typically:  $0 \leq S_p(n) \leq p$
  - ▶ if  $S_p(n) > p$ : “superlinear speedup”  $\leftarrow$  rare, but possible

# Parallel Speedup

- ▶ **Speedup:**  $S_p(n) := \frac{T_1(n)}{T_p(n)}$ 
  - ▶ typically:  $0 \leq S_p(n) \leq p$
  - ▶ if  $S_p(n) > p$ : “superlinear speedup”  $\leftarrow$  rare, but possible
- ▶ **What is  $T_1(n)$ ?**

# Parallel Speedup

- ▶ **Speedup:**  $S_p(n) := \frac{T_1(n)}{T_p(n)}$ 
  - ▶ typically:  $0 \leq S_p(n) \leq p$
  - ▶ if  $S_p(n) > p$ : “superlinear speedup”  $\leftarrow$  rare, but possible
- ▶ **What is  $T_1(n)$ ?**
  - ▶ Time of the best sequential code.
  - ▶ NOT the time for the parallel code run with  $p = 1$ !!

# Parallel Speedup

- ▶ **Speedup:**  $S_p(n) := \frac{T_1(n)}{T_p(n)}$ 
  - ▶ typically:  $0 \leq S_p(n) \leq p$
  - ▶ if  $S_p(n) > p$ : “superlinear speedup” ← rare, but possible
- ▶ **What is  $T_1(n)$ ?**
  - ▶ Time of the best sequential code.
  - ▶ NOT the time for the parallel code run with  $p = 1$ !!

**Note:** The sequential code could possibly implement a different algorithm than the parallel one.

**Example:** Eigenvalues of symmetric tridiagonal matrix

- ▶ Alg.1: dqds      cost:  $O(n^2)$ , BUT inherently sequential
- ▶ Alg.2: BX      cost:  $O(n^3)$ , BUT perfectly parallelizable

# Speedup, Efficiency

- ▶ **What if  $p$  is large?** Then probably  $T_1(n)$  is not obtainable, either because  $n$  is too large a problem to be solved sequentially, or because it would take too long to complete.

In this case,  $S_p(n) := \frac{T_{p_0}(n)}{T_p(n)}$ , and  $0 \leq S_p(n) \leq \frac{p}{p_0}$ .

$T_{p_0}(n)$  is used as a reference, possibly from a different code.

**Note:** Excellent speedup (by itself) does not imply excellent algorithm.

# Speedup, Efficiency

- ▶ **What if  $p$  is large?** Then probably  $T_1(n)$  is not obtainable, either because  $n$  is too large a problem to be solved sequentially, or because it would take too long to complete.

In this case,  $S_p(n) := \frac{T_{p_0}(n)}{T_p(n)}$ , and  $0 \leq S_p(n) \leq \frac{p}{p_0}$ .

$T_{p_0}(n)$  is used as a reference, possibly from a different code.

**Note:** Excellent speedup (by itself) does not imply excellent algorithm.

- ▶ **Parallel efficiency:**

$$E_p(n) := \frac{S_p(n)}{p} \quad \left( \text{or } E_p(n) := \frac{S_p(n)}{p/p_0} \right) \quad 0 \leq E_p(n) \leq 1$$

**Note:** Excellent efficiency (by itself) does not imply excellent algorithm.

# Performance

- ▶ **Performance:** Number of floating point operations per second performed while solving a given problem.

# Performance

- ▶ **Performance:** Number of floating point operations per second performed while solving a given problem.
- ▶ **Theoretical Peak Performance (TPP):** In ideal conditions, the highest number of floating point operations that a processor can perform in one second.



# Performance

- ▶ **Performance:** Number of floating point operations per second performed while solving a given problem.
- ▶ **Theoretical Peak Performance (TPP):** In ideal conditions, the highest number of floating point operations that a processor can perform in one second.
- ▶ **Peak Performance** (“Practical peak performance”): The performance attained by highly tuned matrix-matrix multiplication kernels (DGEMM). For instance, MKL and OpenBLAS.

# Performance

- ▶ **Performance:** Number of floating point operations per second performed while solving a given problem.
- ▶ **Theoretical Peak Performance (TPP):** In ideal conditions, the highest number of floating point operations that a processor can perform in one second.
- ▶ **Peak Performance** (“Practical peak performance”): The performance attained by highly tuned matrix-matrix multiplication kernels (DGEMM). For instance, MKL and OpenBLAS.
- ▶ **Efficiency:** The ratio between the performance attained while solving a given problem and the TPP (or the PPP).

# Speedup & Efficiency in real life

- ▶ `time0.c`  
Cholesky factorization.  
No timings. Only correctness.
- ▶ `time1.c`  
Timings through `clock()`.  
Multithreading (via LAPACK/BLAS). CPU-time.
- ▶ `time2a.c`  
Cycle accurate timer.  
Cycles, frequency. Wall time vs. CPU-time.
- ▶ `time2b.c`  
Performance (#ops/sec), efficiency.
- ▶ Ex. 6 from Report #1

# Scalability – 1/2

- 1) Scalability with respect to resources (# of processors).

Question: *How does the execution time change as the amount of resources increases?*

# Scalability – 1/2

## 1) Scalability with respect to resources (# of processors).

Question: *How does the execution time change as the amount of resources increases?*

**Strong Scalability:** Behaviour of  $T_p(n)$ , as  $p$  increases.  
*Fixed problem size, increasing number of processes.*

# Scalability – 1/2

## 1) Scalability with respect to resources (# of processors).

Question: *How does the execution time change as the amount of resources increases?*

**Strong Scalability:** Behaviour of  $T_p(n)$ , as  $p$  increases.  
*Fixed problem size, increasing number of processes.*

**Example:**  $n = \bar{n}$ ;  $p = 2^i$ , with  $i \in [10, \dots, 14]$

$\Rightarrow T_{1024}(n), T_{2048}(n), T_{4096}(n), T_{8192}(n), T_{16384}(n)$

# Scalability – 1/2

## 1) Scalability with respect to resources (# of processors).

Question: *How does the execution time change as the amount of resources increases?*

**Strong Scalability:** Behaviour of  $T_p(n)$ , as  $p$  increases.  
*Fixed problem size, increasing number of processes.*

**Example:**  $n = \bar{n}$ ;  $p = 2^i$ , with  $i \in [10, \dots, 14]$

$\Rightarrow T_{1024}(n), T_{2048}(n), T_{4096}(n), T_{8192}(n), T_{16384}(n)$

## 2) Scalability with respect to data (problem size).

Question: *How does the execution time change as the problem size increases?*

# Scalability – 1/2

## 1) Scalability with respect to resources (# of processors).

Question: *How does the execution time change as the amount of resources increases?*

**Strong Scalability:** Behaviour of  $T_p(n)$ , as  $p$  increases.  
*Fixed problem size, increasing number of processes.*

**Example:**  $n = \bar{n}$ ;  $p = 2^i$ , with  $i \in [10, \dots, 14]$

$\Rightarrow T_{1024}(n), T_{2048}(n), T_{4096}(n), T_{8192}(n), T_{16384}(n)$

## 2) Scalability with respect to data (problem size).

Question: *How does the execution time change as the problem size increases?*

**Example:**  $p = \bar{p}$ ;  $n = 2^i \bar{n}$ , with  $i \in [0, \dots, 4]$

$\Rightarrow T_p(n), T_p(2n), T_p(4n), T_p(8n), T_p(16n)$



## Scalability – 2/2

- ▶ **Weak Scalability:** Behaviour of  $T_k(n)$ , as  $n$  and  $k$  increase to keep the memory usage per process constant.

*Memory load per processor is fixed, problem size and number of processes increase.*

## Scalability – 2/2

- ▶ **Weak Scalability:** Behaviour of  $T_k(n)$ , as  $n$  and  $k$  increase to keep the memory usage per process constant.

*Memory load per processor is fixed, problem size and number of processes increase.*

**Example:** Algorithm  $\mathcal{A}$ ; input:  $n \in \mathbb{N}$

Time complexity:  $O(n^3)$  (info not needed)

Space complexity:  $O(n^2)$

Reference:  $\bar{n} = 100, \bar{p} = 16$

## Scalability – 2/2

- ▶ **Weak Scalability:** Behaviour of  $T_k(n)$ , as  $n$  and  $k$  increase to keep the memory usage per process constant.

*Memory load per processor is fixed, problem size and number of processes increase.*

**Example:** Algorithm  $\mathcal{A}$ ; input:  $n \in \mathbb{N}$

Time complexity:  $O(n^3)$  (info not needed)

Space complexity:  $O(n^2)$

Reference:  $\bar{n} = 100, \bar{p} = 16$

$\Rightarrow T_{16}(100), T_{64}(200), T_{256}(400), T_{1024}(800)$

## Scalability – 2/2

- ▶ **Weak Scalability:** Behaviour of  $T_k(n)$ , as  $n$  and  $k$  increase to keep the memory usage per process constant.

*Memory load per processor is fixed, problem size and number of processes increase.*

**Example:** Algorithm  $\mathcal{A}$ ; input:  $n \in \mathbb{N}$

Time complexity:  $O(n^3)$  (info not needed)

Space complexity:  $O(n^2)$

Reference:  $\bar{n} = 100, \bar{p} = 16$

$\Rightarrow T_{16}(100), T_{64}(200), T_{256}(400), T_{1024}(800)$

**Question:** Why two definitions of scalability (strong, weak)?  
What are they useful for?

# Weak Scalability – Example #1

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ) =  $O(n^2)$     Space( $\mathcal{B}(n)$ ) =  $3n$     Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{\bar{p}}(2\bar{n})$                       – from problem size to number of processors

# Weak Scalability – Example #1

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

$\text{Time}(\mathcal{B}(n)) = O(n^2)$      $\text{Space}(\mathcal{B}(n)) = 3n$     Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{\bar{p}}(2\bar{n})$                       – from problem size to number of processors  
     $\text{Space}(\bar{n}) = 3\bar{n} \Rightarrow \text{Mem/proc: } 3\bar{n}/\bar{p} =: \text{const}$

# Weak Scalability – Example #1

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ) =  $O(n^2)$     Space( $\mathcal{B}(n)$ ) =  $3n$     Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{\bar{p}}(2\bar{n})$                       – from problem size to number of processors

Space( $\bar{n}$ ) =  $3\bar{n} \Rightarrow$  Mem/proc:  $3\bar{n}/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $6\bar{n} \Rightarrow 6\bar{n}/\bar{p} = \text{const} \Rightarrow$

# Weak Scalability – Example #1

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ) =  $O(n^2)$     Space( $\mathcal{B}(n)$ ) =  $3n$     Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$                       – from problem size to number of processors

Space( $\bar{n}$ ) =  $3\bar{n} \Rightarrow$  Mem/proc:  $3\bar{n}/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $6\bar{n} \Rightarrow 6\bar{n}/?? = \text{const} \Rightarrow ?? = 2\bar{p}$



# Weak Scalability – Example #1

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ) =  $O(n^2)$     Space( $\mathcal{B}(n)$ ) =  $3n$     Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$                       – from problem size to number of processors  
Space( $\bar{n}$ ) =  $3\bar{n} \Rightarrow$  Mem/proc:  $3\bar{n}/\bar{p} =: \text{const}$   
Space( $2\bar{n}$ ) =  $6\bar{n} \Rightarrow 6\bar{n}/?? = \text{const} \Rightarrow ?? = 2\bar{p}$
- ▶  $T_{2\bar{p}}(2\bar{n}) = t_1$              $t_0 > / = / < t_1?$

# Weak Scalability – Example #1

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbf{N}$

Time( $\mathcal{B}(n)$ ) =  $O(n^2)$     Space( $\mathcal{B}(n)$ ) =  $3n$     Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$                       – from problem size to number of processors

Space( $\bar{n}$ ) =  $3\bar{n} \Rightarrow$  Mem/proc:  $3\bar{n}/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $6\bar{n} \Rightarrow 6\bar{n}/?? = \text{const} \Rightarrow ?? = 2\bar{p}$

- ▶  $T_{2\bar{p}}(2\bar{n}) = t_1$              $t_0 > / = / < t_1?$

Assumption: perfect scalability wrt size, strong scalability

$$t_1 = T_{2\bar{p}}(2\bar{n}) \approx 4T_{2\bar{p}}(\bar{n}) \approx 4T_{\bar{p}}(\bar{n})/2 = 2t_0$$

# Weak Scalability – Example #1

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ) =  $O(n^2)$     Space( $\mathcal{B}(n)$ ) =  $3n$     Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$                       – from problem size to number of processors

Space( $\bar{n}$ ) =  $3\bar{n} \Rightarrow$  Mem/proc:  $3\bar{n}/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $6\bar{n} \Rightarrow 6\bar{n}/?? = \text{const} \Rightarrow ?? = 2\bar{p}$

- ▶  $T_{2\bar{p}}(2\bar{n}) = t_1$              $t_0 > / = / < t_1?$

Assumption: perfect scalability wrt size, strong scalability

$t_1 = T_{2\bar{p}}(2\bar{n}) \approx 4T_{2\bar{p}}(\bar{n}) \approx 4T_{\bar{p}}(\bar{n})/2 = 2t_0$

- ▶  $T_{2\bar{p}}(??)$                       – from number of processors to problem size

# Weak Scalability – Example #1

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ) =  $O(n^2)$     Space( $\mathcal{B}(n)$ ) =  $3n$     Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$                       – from problem size to number of processors

Space( $\bar{n}$ ) =  $3\bar{n} \Rightarrow$  Mem/proc:  $3\bar{n}/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $6\bar{n} \Rightarrow 6\bar{n}/?? = \text{const} \Rightarrow ?? = 2\bar{p}$

- ▶  $T_{2\bar{p}}(2\bar{n}) = t_1$              $t_0 > / = / < t_1?$

Assumption: perfect scalability wrt size, strong scalability

$t_1 = T_{2\bar{p}}(2\bar{n}) \approx 4T_{2\bar{p}}(\bar{n}) \approx 4T_{\bar{p}}(\bar{n})/2 = 2t_0$

- ▶  $T_{2\bar{p}}(??)$                       – from number of processors to problem size

Space( $\bar{n}$ ) =  $3\bar{n} \Rightarrow$  Mem/proc:  $3\bar{n}/\bar{p} =: \text{const}$

# Weak Scalability – Example #1

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ) =  $O(n^2)$     Space( $\mathcal{B}(n)$ ) =  $3n$     Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$                       – from problem size to number of processors

Space( $\bar{n}$ ) =  $3\bar{n} \Rightarrow$  Mem/proc:  $3\bar{n}/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $6\bar{n} \Rightarrow 6\bar{n}/?? = \text{const} \Rightarrow ?? = 2\bar{p}$

- ▶  $T_{2\bar{p}}(2\bar{n}) = t_1$              $t_0 > / = / < t_1?$

Assumption: perfect scalability wrt size, strong scalability

$t_1 = T_{2\bar{p}}(2\bar{n}) \approx 4T_{2\bar{p}}(\bar{n}) \approx 4T_{\bar{p}}(\bar{n})/2 = 2t_0$

- ▶  $T_{2\bar{p}}(??)$                       – from number of processors to problem size

Space( $\bar{n}$ ) =  $3\bar{n} \Rightarrow$  Mem/proc:  $3\bar{n}/\bar{p} =: \text{const}$

Space( $??$ ) =  $3 ?? \Rightarrow$  Mem/proc:  $3 ??/2\bar{p} = \text{const} \Rightarrow$

# Weak Scalability – Example #1

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ) =  $O(n^2)$     Space( $\mathcal{B}(n)$ ) =  $3n$     Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$                       – from problem size to number of processors

Space( $\bar{n}$ ) =  $3\bar{n} \Rightarrow$  Mem/proc:  $3\bar{n}/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $6\bar{n} \Rightarrow 6\bar{n}/?? = \text{const} \Rightarrow ?? = 2\bar{p}$

- ▶  $T_{2\bar{p}}(2\bar{n}) = t_1$              $t_0 > / = / < t_1?$

Assumption: perfect scalability wrt size, strong scalability

$t_1 = T_{2\bar{p}}(2\bar{n}) \approx 4T_{2\bar{p}}(\bar{n}) \approx 4T_{\bar{p}}(\bar{n})/2 = 2t_0$

- ▶  $T_{2\bar{p}}(??)$                       – from number of processors to problem size

Space( $\bar{n}$ ) =  $3\bar{n} \Rightarrow$  Mem/proc:  $3\bar{n}/\bar{p} =: \text{const}$

Space( $??$ ) =  $3 ?? \Rightarrow$  Mem/proc:  $3 ??/2\bar{p} = \text{const} \Rightarrow ?? = 2\bar{n}$

## Weak Scalability – Example #2

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ):  $O(n^2)$       Space( $\mathcal{B}(n)$ ):  $n^2$       Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$       – from problem size to number of processors

## Weak Scalability – Example #2

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ):  $O(n^2)$       Space( $\mathcal{B}(n)$ ):  $n^2$       Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{\bar{p}}(2\bar{n})$       – from problem size to number of processors

Space( $\bar{n}$ ) =  $\bar{n}^2 \Rightarrow$  Mem/proc:  $\bar{n}^2/\bar{p} =: \text{const}$



## Weak Scalability – Example #2

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ):  $O(n^2)$       Space( $\mathcal{B}(n)$ ):  $n^2$       Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{\bar{p}}(2\bar{n})$       – from problem size to number of processors

Space( $\bar{n}$ ) =  $\bar{n}^2 \Rightarrow$  Mem/proc:  $\bar{n}^2/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $4\bar{n}^2 \Rightarrow 4\bar{n}^2/?? = \text{const} \Rightarrow$

## Weak Scalability – Example #2

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ):  $O(n^2)$       Space( $\mathcal{B}(n)$ ):  $n^2$       Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$       – from problem size to number of processors

Space( $\bar{n}$ ) =  $\bar{n}^2 \Rightarrow$  Mem/proc:  $\bar{n}^2/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $4\bar{n}^2 \Rightarrow 4\bar{n}^2/?? = \text{const} \Rightarrow ?? = 4\bar{p}$

## Weak Scalability – Example #2

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ):  $O(n^2)$       Space( $\mathcal{B}(n)$ ):  $n^2$       Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$       – from problem size to number of processors

Space( $\bar{n}$ ) =  $\bar{n}^2 \Rightarrow$  Mem/proc:  $\bar{n}^2/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $4\bar{n}^2 \Rightarrow 4\bar{n}^2/?? = \text{const} \Rightarrow ?? = 4\bar{p}$

- ▶  $T_{4\bar{p}}(2\bar{n}) = t_1$        $t_0 > / = / < t_1?$

## Weak Scalability – Example #2

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ):  $O(n^2)$       Space( $\mathcal{B}(n)$ ):  $n^2$       Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$       – from problem size to number of processors

Space( $\bar{n}$ ) =  $\bar{n}^2 \Rightarrow$  Mem/proc:  $\bar{n}^2/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $4\bar{n}^2 \Rightarrow 4\bar{n}^2/?? = \text{const} \Rightarrow ?? = 4\bar{p}$

- ▶  $T_{4\bar{p}}(2\bar{n}) = t_1$        $t_0 > / = / < t_1?$

Assumption: perfect scalability

$t_1 = T_{4\bar{p}}(2\bar{n}) \approx 4T_{4\bar{p}}(\bar{n}) \approx 4T_{\bar{p}}(\bar{n})/4 = t_0$

## Weak Scalability – Example #2

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ):  $O(n^2)$       Space( $\mathcal{B}(n)$ ):  $n^2$       Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$       – from problem size to number of processors

Space( $\bar{n}$ ) =  $\bar{n}^2 \Rightarrow$  Mem/proc:  $\bar{n}^2/\bar{p} =: \text{const}$

Space( $2\bar{n}$ ) =  $4\bar{n}^2 \Rightarrow 4\bar{n}^2/?? = \text{const} \Rightarrow ?? = 4\bar{p}$

- ▶  $T_{4\bar{p}}(2\bar{n}) = t_1$        $t_0 > / = / < t_1?$

Assumption: perfect scalability

$t_1 = T_{4\bar{p}}(2\bar{n}) \approx 4T_{4\bar{p}}(\bar{n}) \approx 4T_{\bar{p}}(\bar{n})/4 = t_0$

- ▶  $T_{2\bar{p}}(??)$       – from number of processors to problem size

## Weak Scalability – Example #2

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ):  $O(n^2)$       Space( $\mathcal{B}(n)$ ):  $n^2$       Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$       – from problem size to number of processors

$$\text{Space}(\bar{n}) = \bar{n}^2 \Rightarrow \text{Mem/proc: } \bar{n}^2 / \bar{p} =: \text{const}$$

$$\text{Space}(2\bar{n}) = 4\bar{n}^2 \Rightarrow 4\bar{n}^2 / ?? = \text{const} \Rightarrow ?? = 4\bar{p}$$

- ▶  $T_{4\bar{p}}(2\bar{n}) = t_1$        $t_0 > / = / < t_1?$

Assumption: perfect scalability

$$t_1 = T_{4\bar{p}}(2\bar{n}) \approx 4T_{4\bar{p}}(\bar{n}) \approx 4T_{\bar{p}}(\bar{n})/4 = t_0$$

- ▶  $T_{2\bar{p}}(??)$       – from number of processors to problem size

$$\text{Space}(\bar{n}) = \bar{n}^2 \Rightarrow \text{Mem/proc: } \bar{n}^2 / \bar{p} =: \text{const}$$

## Weak Scalability – Example #2

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ):  $O(n^2)$       Space( $\mathcal{B}(n)$ ):  $n^2$       Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$       – from problem size to number of processors

$$\text{Space}(\bar{n}) = \bar{n}^2 \Rightarrow \text{Mem/proc: } \bar{n}^2/\bar{p} =: \text{const}$$

$$\text{Space}(2\bar{n}) = 4\bar{n}^2 \Rightarrow 4\bar{n}^2/?? = \text{const} \Rightarrow ?? = 4\bar{p}$$

- ▶  $T_{4\bar{p}}(2\bar{n}) = t_1$        $t_0 > / = / < t_1?$

Assumption: perfect scalability

$$t_1 = T_{4\bar{p}}(2\bar{n}) \approx 4T_{4\bar{p}}(\bar{n}) \approx 4T_{\bar{p}}(\bar{n})/4 = t_0$$

- ▶  $T_{2\bar{p}}(??)$       – from number of processors to problem size

$$\text{Space}(\bar{n}) = \bar{n}^2 \Rightarrow \text{Mem/proc: } \bar{n}^2/\bar{p} =: \text{const}$$

$$\begin{aligned} \text{Space}(??) = ??^2 \Rightarrow \text{Mem/proc: } ??^2/2\bar{p} = \text{const} \Rightarrow ??^2 &= 2\bar{p}\bar{n}^2/\bar{p} \\ \Rightarrow \end{aligned}$$

## Weak Scalability – Example #2

- ▶ Algorithm  $\mathcal{B}(n)$ ; input:  $n \in \mathbb{N}$

Time( $\mathcal{B}(n)$ ):  $O(n^2)$       Space( $\mathcal{B}(n)$ ):  $n^2$       Reference:  $T_{\bar{p}}(\bar{n}) = t_0$

- ▶  $T_{??}(2\bar{n})$       – from problem size to number of processors

$$\text{Space}(\bar{n}) = \bar{n}^2 \Rightarrow \text{Mem/proc: } \bar{n}^2 / \bar{p} =: \text{const}$$

$$\text{Space}(2\bar{n}) = 4\bar{n}^2 \Rightarrow 4\bar{n}^2 / ?? = \text{const} \Rightarrow ?? = 4\bar{p}$$

- ▶  $T_{4\bar{p}}(2\bar{n}) = t_1$        $t_0 > / = / < t_1$ ?

Assumption: perfect scalability

$$t_1 = T_{4\bar{p}}(2\bar{n}) \approx 4T_{4\bar{p}}(\bar{n}) \approx 4T_{\bar{p}}(\bar{n})/4 = t_0$$

- ▶  $T_{2\bar{p}}(??)$       – from number of processors to problem size

$$\text{Space}(\bar{n}) = \bar{n}^2 \Rightarrow \text{Mem/proc: } \bar{n}^2 / \bar{p} =: \text{const}$$

$$\begin{aligned} \text{Space}(??) = ??^2 &\Rightarrow \text{Mem/proc: } ??^2 / 2\bar{p} = \text{const} \Rightarrow ??^2 = 2\bar{p}\bar{n}^2 / \bar{p} \\ &\Rightarrow ?? = \bar{n}\sqrt{2} \end{aligned}$$



# Weak Scalability in real life

“A Parallel Eigensolver for Dense Symmetric Matrices Based on Multiple Relatively Robust Representations”

<https://hpac.cs.umu.se/~pauldj/pubs/PMR3.pdf>

Best possible parallel efficiency?

# Best possible parallel efficiency?

1. #flops/p

no dependencies

# Best possible parallel efficiency?

1. #flops/p

no dependencies

2. Amdahl's law

seq. vs. parallel portions

# Best possible parallel efficiency?

- |                                |                            |
|--------------------------------|----------------------------|
| 1. #flops/p                    | no dependencies            |
| 2. Amdahl's law                | seq. vs. parallel portions |
| 3. Length of the critical path | sequence of deps           |

# Amdahl's law

Maximum possible speedup when only a portion of the code scales

- ▶  $T_{\text{seq}}$  portion of the algorithm (in secs) which is strictly sequential

# Amdahl's law

Maximum possible speedup when only a portion of the code scales

- ▶  $T_{\text{seq}}$  portion of the algorithm (in secs) which is strictly sequential
- ▶  $T_{\text{par}}$  portion of the algorithm (in secs) that can be parallelized

# Amdahl's law

Maximum possible speedup when only a portion of the code scales

- ▶  $T_{\text{seq}}$  portion of the algorithm (in secs) which is strictly sequential
- ▶  $T_{\text{par}}$  portion of the algorithm (in secs) that can be parallelized
- ▶  $\beta := \frac{T_{\text{seq}}}{T_{\text{seq}} + T_{\text{par}}}$  fraction of the algorithm that is strictly sequential



# Amdahl's law

Maximum possible speedup when only a portion of the code scales

- ▶  $T_{\text{seq}}$  portion of the algorithm (in secs) which is strictly sequential
- ▶  $T_{\text{par}}$  portion of the algorithm (in secs) that can be parallelized
- ▶  $\beta := \frac{T_{\text{seq}}}{T_{\text{seq}} + T_{\text{par}}}$  fraction of the algorithm that is strictly sequential
- ▶  $T_1(n) := T_{\text{seq}} + T_{\text{par}}$  by definition

# Amdahl's law

Maximum possible speedup when only a portion of the code scales

- ▶  $T_{\text{seq}}$  portion of the algorithm (in secs) which is strictly sequential
- ▶  $T_{\text{par}}$  portion of the algorithm (in secs) that can be parallelized
- ▶  $\beta := \frac{T_{\text{seq}}}{T_{\text{seq}} + T_{\text{par}}}$  fraction of the algorithm that is strictly sequential
- ▶  $T_1(n) := T_{\text{seq}} + T_{\text{par}}$  by definition
- ▶  $T_p(n) := T_{\text{seq}} + T_{\text{par}}/p$  ideal parallelisation

# Amdahl's law

Maximum possible speedup when only a portion of the code scales

- ▶  $T_{\text{seq}}$  portion of the algorithm (in secs) which is strictly sequential
- ▶  $T_{\text{par}}$  portion of the algorithm (in secs) that can be parallelized
- ▶  $\beta := \frac{T_{\text{seq}}}{T_{\text{seq}} + T_{\text{par}}}$  fraction of the algorithm that is strictly sequential
- ▶  $T_1(n) := T_{\text{seq}} + T_{\text{par}}$  by definition
- ▶  $T_p(n) := T_{\text{seq}} + T_{\text{par}}/p$  ideal parallelisation
- ▶ Speedup:  $S_p(n) := \frac{T_1(n)}{T_p(n)} = \frac{T_{\text{seq}} + T_{\text{par}}}{T_{\text{seq}} + T_{\text{par}}/p}$
- ▶ Ideal Speedup:  $\lim_{p \rightarrow \infty} S_p(n) = \frac{1}{\beta}$

# Amdahl's law

Maximum possible speedup when only a portion of the code scales

- ▶  $T_{\text{seq}}$  portion of the algorithm (in secs) which is strictly sequential
- ▶  $T_{\text{par}}$  portion of the algorithm (in secs) that can be parallelized
- ▶  $\beta := \frac{T_{\text{seq}}}{T_{\text{seq}} + T_{\text{par}}}$  fraction of the algorithm that is strictly sequential
- ▶  $T_1(n) := T_{\text{seq}} + T_{\text{par}}$  by definition
- ▶  $T_p(n) := T_{\text{seq}} + T_{\text{par}}/p$  ideal parallelisation
- ▶ Speedup:  $S_p(n) := \frac{T_1(n)}{T_p(n)} = \frac{T_{\text{seq}} + T_{\text{par}}}{T_{\text{seq}} + T_{\text{par}}/p}$
- ▶ Ideal Speedup:  $\lim_{p \rightarrow \infty} S_p(n) = \frac{1}{\beta}$

**Note:** Counterpart of Amdahl's law for weak scalability: Gustafson's law.

# Amdahl's law in real life

- ▶ `time3.c`  
Timings breakdown: Malloc, init, compute, test.  
Scalability. Serial vs. parallel code. Amdahl's law.
- ▶ “A Scalable, Linear-Time Dynamic Cutoff Algorithm for MD”  
<https://arxiv.org/pdf/1701.05242.pdf>
- ▶ Ex. 3 from Report #1

# Critical path

Longest sequence of dependent tasks

⇒ Dependencies

# On dependencies and parallel execution

- ▶ Two independent instructions can be executed  
“concurrently” = “in parallel” (by different resources)

# On dependencies and parallel execution

- ▶ Two independent instructions can be executed  
“concurrently” = “in parallel” (by different resources)

- ▶ Parallel execution: **NO** time ordering!  
When two instructions are executed in parallel,  
**NO** assumptions about start, duration, end.



# On dependencies and parallel execution

- ▶ Two independent instructions can be executed  
“concurrently” = “in parallel” (by different resources)

Parallel execution: **NO** time ordering!

- ▶ When two instructions are executed in parallel,  
**NO** assumptions about start, duration, end.
- ▶ Dependencies  $\Rightarrow$  ordering  
The “right” ordering is dictated by the semantics of the program

# On dependencies and parallel execution

- ▶ Two independent instructions can be executed  
“concurrently” = “in parallel” (by different resources)

Parallel execution: **NO** time ordering!

- ▶ When two instructions are executed in parallel,  
**NO** assumptions about start, duration, end.
- ▶ Dependencies  $\Rightarrow$  ordering  
The “right” ordering is dictated by the semantics of the program
- ▶ Some dependencies can be removed by duplicating data

# True / Flow dependency

$\{x = 1, y = 2, a = 3\}$

...

$y := a * x + y$

$w := 3 * y$

...

$\{y = 5, w = 15\}$

## True / Flow dependency

$\{x = 1, y = 2, a = 3\}$

...

$y := a * x + y$

$w := 3 * y$

...

$\{y = 5, w = 15\}$

- ▶ The value of  $w$  depends on the updated value of  $y$

# True / Flow dependency

{x = 1, y = 2, a = 3}	
...	...
y := a * x + y	w := 3 * y
w := 3 * y	y := a * x + y
...	...
{y = 5, w = 15}	{y = 5, w = 6}

- ▶ The value of  $w$  depends on the updated value of  $y$
- ▶ The semantics of the program depends on the **order** of the statements

# Anti dependency

$\{x = 1, y = 2, a = 3\}$

...

$w := 3 * y$

$y := a * x + y$

...

$\{y = 5, w = 6\}$

- ▶ The value of  $w$  depends on the initial value of  $y$

# Anti dependency

{x = 1, y = 2, a = 3}	
...	...
w := 3 * y	y := a * x + y
y := a * x + y	w := 3 * y
...	...
{y = 5, w = 6}	{y = 5, w = 15}

- ▶ The value of  $w$  depends on the initial value of  $y$
- ▶ The semantics of the program depends on the **order** of the statements

# Output dependency

$\{x = 1, y = 2, a = 3\}$

...

$w := 3 * y$

$w := a * x$

...

$\{w = 3\}$

- ▶ The value of  $w$  depends on the order of the statements



# Output dependency

$\{x = 1, y = 2, a = 3\}$	
...	...
$w := 3 * y$	$w := a * x$
$w := a * x$	$w := 3 * y$
...	...
$\{w = 3\}$	$\{w = 6\}$

- ▶ The value of  $w$  depends on the order of the statements
- ▶ The semantics of the program depends on the **order** of the statements