

## Lab - Using Wireshark to Examine HTTP and HTTPS Traffic

### Objectives

Part 1: Capture and view HTTP traffic

Part 2: Capture and view HTTPS traffic

### Background / Scenario

HyperText Transfer Protocol (HTTP) is an application layer protocol that presents data via a web browser. With HTTP, there is no safeguard for the exchanged data between two communicating devices.

With HTTPS, encryption is used via a mathematical algorithm. This algorithm hides the true meaning of the data that is being exchanged. This is done through the use of certificates that can be viewed later in this lab.

Regardless of HTTP or HTTPS, it is only recommended to exchange data with websites that you trust. Just because a site uses HTTPS does not mean it is a trustworthy site. Threat actors commonly use HTTPS to hide their activities.

In this lab, you will explore and capture HTTP and HTTPS traffic using Wireshark.

### Required Resources

- CyberOps Workstation VM
- Internet connection

### Instructions

#### Part 1: Capture and View HTTP Traffic

In this part, you will use **tcpdump** to capture the content of HTTP traffic. You will use command options to save the traffic to a packet capture (pcap) file. These records can then be analyzed using different applications that read pcap files, including Wireshark.

##### Step 1: Start the virtual machine and log in.

Start the CyberOps Workstation VM. Use the following user credentials:

Username: **analyst**

Password: **cyberops**

##### Step 2: Open a terminal and start tcpdump.

- Open a terminal application and enter the command **ip address**.

```
[analyst@secOps ~]$ ip address
```

- List the interfaces and their IP addresses displayed in the **ip address** output.

```
lo - 127.0.0.1/8 ens32 - 192.168.179.128/24
```

- While in the terminal application, enter the command **sudo tcpdump -i enp0s3 -s 0 -w httpdump.pcap**. Enter the password **cyberops** for the user analyst when prompted.

```
[analyst@secOps ~]$ sudo tcpdump -i enp0s3 -s 0 -w httpdump.pcap
[sudo] password for analyst:
```

```
tcpdump: listening on enp0s3, link-type EN10MB (Ethernet), capture size 262144 bytes
```

This command starts tcpdump and records network traffic on the **enp0s3** interface.

The **-i** command option allows you to specify the interface. If not specified, the tcpdump will capture all traffic on all interfaces.

The **-s** command option specifies the length of the snapshot for each packet. You should limit snaplen to the smallest number that will capture the protocol information in which you are interested. Setting snaplen to 0 sets it to the default of 262144, for backwards compatibility with recent older versions of tcpdump.

The **-w** command option is used to write the result of the tcpdump command to a file. Adding the extension .pcap ensures that operating systems and applications will be able to read to file. All recorded traffic will be printed to the file httpdump.pcap in the home directory of the user analyst.

Use the man pages for tcpdump to determine the usage of the -s and -w command options.

- d. Open a web browser from the launch bar within the CyberOps Workstation VM. Navigate to <http://www.altoromutual.com/login.jsp>


Because this website uses HTTP, the traffic is not encrypted. Click the Password field to see the warning pop up.

- e. Enter a username of **Admin** with a password of **Admin** and click **Login**.
- f. Close the web browser.
- g. Return to the terminal window where tcpdump is running. Enter **CTRL+C** to stop the packet capture.

### Step 3: View the HTTP capture.


The tcpdump, executed in the previous step, printed the output to a file named httpdump.pcap. This file is located in the home directory for the user **analyst**.

- a. Click the File Manager icon on the desktop and browse to the home folder for the user **analyst**. Double-click the **httpdump.pcap** file, in the Open With dialog box scroll down to Wireshark and then click **Open**.




## Lab - Using Wireshark to Examine HTTP and HTTPS Traffic

- b. In the Wireshark application, filter for **http** and click **Apply**.




- c. Browse through the different HTTP messages and select the **POST** message.



No.	Time	Source	Destination	Protocol	Length	Info
44	7.806931	10.0.2.15	65.61.137.117	HTTP	399	GET /bank/login.jsp HTTP/1.1
46	7.879473	65.61.137.117	10.0.2.15	HTTP	256	HTTP/1.1 302 Found
48	7.987694	10.0.2.15	65.61.137.117	HTTP	447	GET /login.jsp HTTP/1.1
54	8.062632	65.61.137.117	10.0.2.15	HTTP	3228	HTTP/1.1 200 OK (text/html)
81	8.276625	10.0.2.15	65.61.137.117	HTTP	409	GET /style.css HTTP/1.1
89	8.349119	65.61.137.117	10.0.2.15	HTTP	1532	HTTP/1.1 200 OK (text/css)
150	20.856396	10.0.2.15	65.61.137.117	HTTP	637	POST /doLogin HTTP/1.1 (application/x-www-form-urlencoded)
154	20.936367	65.61.137.117	10.0.2.15	HTTP	303	HTTP/1.1 302 Found
156	20.942993	10.0.2.15	65.61.137.117	HTTP	594	GET /bank/main.jsp HTTP/1.1
162	21.027105	65.61.137.117	10.0.2.15	HTTP	2326	HTTP/1.1 200 OK (text/html)

- d. In the lower window, the message is displayed. Expand the **HTML Form URL Encoded: application/x-www-form-urlencoded** section.



What two pieces of information are displayed? [login info ie username pass](#)

- e. Close the Wireshark application.

## Part 2: Capture and View HTTPS Traffic

You will now use tcpdump from the command line of a Linux workstation to capture HTTPS traffic. After starting tcpdump, you will generate HTTPS traffic while tcpdump records the contents of the network traffic. These records will again be analyzed using Wireshark.

### Step 1: Start tcpdump within a terminal.

- a. While in the terminal application, enter the command **sudo tcpdump -i enp0s3 -s 0 -w httpsdump.pcap**. Enter the password **cyberops** for the user analyst when prompted.

```
[analyst@secOps ~]$ sudo tcpdump -i enp0s3 -s 0 -w httpsdump.pcap
[sudo] password for analyst:
tcpdump: listening on enp0s3, link-type EN10MB (Ethernet), capture size 262144 bytes
```

This command will start tcpdump and record network traffic on the **enp0s3** interface of the Linux workstation. If your interface is different than enp0s3, please modify it when using the above command.

All recorded traffic will be printed to the file **httpsdump.pcap** in the home directory of the user analyst.

## Lab - Using Wireshark to Examine HTTP and HTTPS Traffic


- b. Open a web browser from the launch bar within the CyberOps Workstation VM. Navigate to [www.netacad.com](https://www.netacad.com).

**Note:** If you receive a “Secure Connection Failed” webpage it probably means the date and time are incorrect. Update the day and time with the following command, changing to the current day and time:


```
[analyst@secOps ~]$ sudo date -s "12 MAY 2020 21:38:20"
```

What do you notice about the website URL?

- c. Click **Log in**.



- d. Enter in your NetAcad username and password. Click **Next**.




- e. Close the web browser in the VM.
- f. Return to the terminal window where tcpdump is running. Enter **CTRL+C** to stop the packet capture.

### Step 2: View the HTTPS capture.


The tcpdump executed in Step 1 printed the output to a file named `httpsdump.pcap`. This file is located in the home directory for the user **analyst**.

- a. Click the Filesystem icon on the desktop and browse to the home folder for the user **analyst**. Open the **httpsdump.pcap** file.




- b. In the Wireshark application, expand the capture window vertically and then filter by HTTPS traffic via port 443.

Enter **tcp.port==443** as a filter, and click **Apply**.




- c. Browse through the different HTTPS messages and select an **Application Data** message.



- d. In the lower window, the message is displayed.

What has replaced the HTTP section that was in the previous capture file? [TLS transport layer security](#)

- e. Completely expand the **Secure Sockets Layer** section.



```
▶ Frame 1: 110 bytes on wire (880 bits), 110 bytes captured (880 bits)
▶ Ethernet II, Src: PcsCompu_82:75:df (08:00:27:82:75:df), Dst: RealtekU_12:35:02 (52:54:00:12:35:02)
▶ Internet Protocol Version 4, Src: 10.0.2.15, Dst: 104.16.248.249
▶ Transmission Control Protocol, Src Port: 52556, Dst Port: 443, Seq: 1, Ack: 1, Len: 56
▼ Transport Layer Security
  ▼ TLSv1.2 Record Layer: Application Data Protocol: http-over-tls
    Content Type: Application Data (23)
    Version: TLS 1.2 (0x0303)
    Length: 51
    Encrypted Application Data: 7fa9037731c6e38e6213aacc15a0a7281f94046fdb237be9...
```

- f. Click the **Encrypted Application Data**.

Is the application data in a plaintext or readable format? [not readable](#)

- g. Close all windows and shut down the virtual machine.

## Reflection Questions

1. What are the advantages of using HTTPS instead of HTTP?

[security](#)

2. Are all websites that use HTTPS considered trustworthy?

[no because a website can be using self signed certificates for https, also secure connection doesnt mean that the website is safe ie it could be a phishing site or something](#)