

APPENDIX D

EXPENDABLE AND DURABLE ITEMS LIST

SECTION I INTRODUCTION

D-1 SCOPE.

D-1.1 General.

This appendix lists expendable supplies and materials needed to operate and maintain the helicopter.

D-1.2 Description.

WARNING

Observe all cautions and warnings on the containers when using consumable materials. When applicable, wear necessary protective gear during handling and use. If a consumable is flammable or explosive, make certain consumable and its vapors are kept away from heat, spark, and flame. Make certain helicopter is properly grounded and fire fighting equipment is readily available prior to use. For additional information on toxicity, flashpoint, and flammability of chemicals, consult the manufacturer of the consumable.

CAUTION

Some contemporary products contain ingredients that may damage sealants, bushings, and protective coatings. To avoid this hazard it is recommended that only those consumable materials indicated in this appendix be used on the helicopter.

This Appendix is a complete list of consumable materials required for maintenance of the helicopter. Many of these materials are listed by their appropriate United States military or federal specifications. These specifications are generally known throughout the world and products meeting their requirements are usually readily available. In most cases, the specifications listed are identified by only the basic number without reference to any revision letter. Unless otherwise stated, only the latest revision applies, and it is the operator's responsibility to obtain and use only materials meeting the latest revision of each specification. When a specific revision letter is listed for a specification, it is because materials conforming to that particular revision best meet the requirements for the specified use of the consumable; a later or future revision may not meet the needed properties as well, and should not be used until qualified by Sikorsky Aircraft.

In many cases, suitable products by other manufacturers are available and have the properties required by the specification. The commercial products listed for each specification are those that were used by Sikorsky Aircraft in the production of the helicopter at the time the list was prepared. Unless otherwise stated, use of these commercial products is discretionary with the operator, but any other product that is chosen must be qualified to the specification that is listed. The operator may also find that some consumable materials in this list conform to military specifications, but that these military specifications are not called out for them. In such cases it may be assumed that only the products specified in the maintenance instructions are approved and

recommended by Sikorsky Aircraft as having the necessary properties and performance. The consumable materials in this list may also be purchased from Sikorsky Aircraft.

D-1.3 Warnings Applicable to Consumable Materials.

Consult your local safety and health staff concerning any questions regarding hazardous materials, Material Safety Data Sheet(s) (MSDS), personal protective equipment requirements, appropriate handling and emergency procedures, and disposal guidance.

WARNING

Acetic acid, Item 24, is combustible. Keep away from ignition sources (heat, flame). Oxidizer - may increase the flammability of nearby combustibles (wood, paper). When mixing with water, always add acid to water not water to acid. Keep glacial acetic acid off skin, eyes, and clothes. Contact with concentrated solution may cause severe burns. May cause allergic skin reactions in sensitive individuals. Do not breathe vapors. Inhalation may cause serious damage to the lining of the nose, throat, and lungs. Long-term overexposure may cause chronic inflammation of the respiratory tract. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, full-body impervious clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Acetone, Item 25, is flammable and toxic to eyes, skin, and respiratory tract. Avoid repeated or prolonged contact. Use only in well-ventilated areas (or use approved respirator as determined by local safety/industrial hygiene personnel). Keep away from open flames, sparks, hot surfaces, or other sources of ignition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: protective goggles or face shield, protective gloves.

WARNING

Adhesion promoter, Item 25A, is extremely flammable. Do not use near open flames, near welding areas, or on hot surfaces. Do not smoke when using it, and do not use it where others are smoking. Bond/ground metal containers to prevent ignition of product vapors by static discharge. Dispose of liquid soaked rags in approved metal container. Avoid contact. Prolonged or repeated contact may irritate the eyes and skin. Inhaling product vapors may cause headache, drowsiness, dizziness, nausea, and respiratory irritation. Long-term overexposure without use of protective equipment may cause damage to nervous system and lungs. **FIRST AID:** If product contacts the eyes, flush them immediately with water for at least 10 minutes; seek medical attention. In case of skin contact, wash affected area(s) with soap and water. Remove and launder contaminated clothing before reuse. If overcome by product vapor seek fresh air and possible medical attention. **CONTAINS:** Isopropyl, Toluene, Polyamide Resin. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses/goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 30, is flammable and irritating to the eyes and skin. Keep container closed; keep sparks, flames, and heat away. Use with proper ventilation. Breathing vapors may cause headaches, dizziness, and nausea. If skin or eye contact occurs, wash immediately with water. If ingested, do not induce vomiting. Seek immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves.

WARNING

Adhesive, Item 31, may be moderately irritating to the skin and eyes. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information, and local Occupational Safety and Health (OSH) regulations for appropriate safety precautions. Protection: goggles, gloves.

WARNING

Adhesive, Item 32, may irritate the eyes and skin. Keep adhesive off skin, eyes, and clothes. Prolonged or repeated contact may cause sensitization or allergic skin reaction. Avoid contact with mineral acids. Avoid mixing resin and curing agent in batches greater than one pound; toxic gases may be released by heat build-up. Dispose of resin waste in accordance with local, state, or federal regulations. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, protective gloves, forced ventilation, NIOSH/MSHA-approved respirator, if curing vapors or dust from sanding, milling, or drilling cured product exceeds established exposure limits.

WARNING

Adhesive, Item 33A, may irritate the eyes and skin. Keep adhesive off skin, eyes, and clothes. Prolonged or repeated contact may cause sensitization - allergic skin reaction. Avoid contact with mineral acids. Do not mix resin and curing agent in batches greater than one pound or in batches that will not be used within 20 minutes; toxic gases may be released by heat build-up. Dispose of resin waste in accordance with local, state, or federal regulations. Sanding cured dust may create silica dust, which could damage lung tissue. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, appropriate protective gloves, NIOSH/MSHA-approved respirator, if curing vapors or dust from sanding, milling, or drilling cured product exceeds established exposure limits.

WARNING

Adhesive, Item 34, may irritate the eyes. Prolonged or repeated contact may trigger sensitization which will result in allergic reactions. Contains asbestos, which has been found to cause cancer. Exposure to asbestos should not occur during mixture and use of adhesive, since the asbestos is bound to the adhesive. However, if the cured product is sanded without proper local exhaust ventilation and NIOSH/MSHA-approved toxic particle respirators, exposure by inhalation is probable. Mix resin and curing agent in batches to be used immediately. Stored mixture may exotherm if not used soon after preparation. Do not heat mixed adhesive above 75°F (24°C) unless curing surfaces to be bonded; toxic gases from excessive heat build-up may be released. Keep resin off skin, eyes, and clothes. Avoid breathing vapors. If dry sanding, machining, or drilling is required after curing, NIOSH/MSHA-approved respirator shall be worn. Dispose of resin waste in accordance with local, state, or federal regulations. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, impervious plastic or rubber gloves, good ventilation.

WARNING

Adhesive, Item 35, Part A - May irritate the skin. Prolonged or repeated contact may trigger sensitization which will result in allergic reactions. Part B - Corrosive - May severely burn the eyes and skin on contact. Breathing vapor may cause chest discomfort and respiratory irritation. Contact may trigger skin sensitization followed by allergic reaction. Mixture Parts A and B - Mix resin and curing agent in batches to be used immediately. Stored mixture may exotherm if not used soon after preparation. Do not heat mixed adhesive above 75°F (24°C) unless curing surfaces to be bonded; toxic gases from excessive heat build-up may be released. Avoid contact of epoxy resin with skin, eyes, and clothes. In case of contact with epoxy resin, flush skin or eyes with water and seek medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, impervious plastic or rubber gloves, good ventilation.

WARNING

Adhesive, Item 36, may be moderately irritating to the skin and eyes. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information, and local Occupational Safety and Health (OSH) regulations for appropriate safety precautions. Protection: goggles, gloves.

WARNING

Adhesive, Item 37, is extremely flammable. Do not use near open flames, welding areas, or on hot surfaces. Bond/ground metal containers to prevent ignition through static discharge. Keep containers securely closed when not in use. Product applicators, such as brushes or rags, must be properly disposed or cleaned. Do not smoke when using or use where others are smoking. Avoid contact. Liquid and vapor may cause moderate to severe irritation of the eyes and skin, depending on the duration of exposure. If eye contact occurs, flush eyes with plenty of water for at least 10 minutes; in case of skin contact, wash affected area with soap and water. Prolonged inhalation of vapors is dangerous. Breathing vapor may cause headache, dizziness, nausea, and respiratory irritation. If such symptoms persist, seek fresh air and medical attention. Repeated or extreme overexposure to product vapor may cause nervous system damage. Use product in well-ventilated spaces (explosion-proof ventilation) with proper personal protective equipment. If swallowed, do not induce vomiting; consequent aspiration of product into the lungs may injure lung tissue. CONTAINS: Petroleum Distillate, Methyl Ethyl Ketone, Magnesium Resinate, Polychloroprene, Toluene. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles, approved gloves, protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 38, is a two component system, Part A and Part B. The precautions for each component should be observed when separate or mixed. Use with proper ventilation. Avoid breathing vapors released during heat curing. Curing equipment should be properly vented. Avoid breathing dust from cutting, grinding, or sanding operations. Avoid eye and skin contact. Direct eye contact may cause severe irritation. Contact with the skin may cause moderate irritation, and allergic rash in sensitized individuals. If eye contact occurs, flush immediately with water for at least 10 minutes. If skin contact occurs, wash affected area thoroughly with soap and water. Wash contaminated clothing before reuse. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, protective clothing to prevent skin contact, NIOSH/MSHA-approved respirator, if curing vapors or dust from sanding, milling, or drilling cured product exceed established exposure limits.

WARNING

Adhesive, Item 39, is flammable. Keep container closed; keep sparks, flames, and heat away; keep adhesive off skin, eyes, and clothes. May irritate the eyes and skin. If eye contact occurs, flush with water for 15 minutes and seek medical attention. Do not breathe vapors. Breathing vapor may cause headache, dizziness, and nausea. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, impermeable gloves; good ventilation and/or NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 40, is composed of resins and hardness or curing agents that may contain hazardous ingredients. Keep adhesive away from strong oxidizing agents and heat. Avoid eye and skin contact. Avoid, inhalation of vapors created during the cure cycle, and dust created by cutting, sanding or grinding. If contact with eyes occur immediately flush eyes with large amounts of water and get immediate medical attention. If it contacts skin, wash skin with soap and large amounts of water. If swallowed do not induce vomiting. Drink two glasses of water and call a physician. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: vented safety glasses with side shields, appropriate gloves, NIOSH/MSHA-approved respirator, if vapor exceeds established exposure limits.

WARNING

Adhesive, Item 41, is composed of resins and hardness or curing agents that may contain hazardous ingredients. Dusts from grinding, sanding, and cutting operations on cured material may irritate the eyes, skin, and respiratory tract. If adhesive contacts eyes, flush immediately with large quantities of water and seek medical attention. If it contacts skin, wash thoroughly with soap and water. Prolonged or repeated contact may cause allergic reaction in susceptible persons. Do not inhale vapors during curing. Use only with adequate ventilation. Wash hands thoroughly after handling. If spilled on clothing, wash contaminated clothing before reuse. If spilled, completely clean up area of spillage. Incinerate properly in accordance with local regulations. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: approved protective safety glasses, protective gloves.

WARNING

Adhesive, Item 42, contains organic solvent and is extremely flammable - do not use near open flames, welding areas, or on hot surfaces. Bond/ground containers during transfer. Do not smoke when using or use where others are smoking. May severely irritate the eyes. Avoid skin contact. May irritate the skin on prolonged or repeated contact. Prolonged breathing of vapors is dangerous. Breathing vapor may cause headache, dizziness, nausea, and respiratory irritation. Long-term overexposure may cause heart, liver, kidney, and blood damage. If swallowed, do not induce vomiting. Use in well-ventilated spaces. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles, impervious gloves, good ventilation and NIOSH/MSHA-approved respirator, particularly in confined areas.

WARNING

Adhesive, Item 44, is a fast curing adhesive and may cause instant skin-to-skin bonding. If skin bonding occurs, soak surfaces in warm, soapy water. Never attempt to separate surfaces by pulling apart. Seek medical attention. Adhesive in eyes will loosen in several hours. If eyelid bonding occurs, wash thoroughly with warm, soapy water and apply gauze pad. Eyelids will open on their own within 1 to 4 days. Do not attempt to force eyelids open. Skin contact may irritate skin. Vapors may irritate eyes and respiratory tract, and may cause asthma-like allergic reactions in some individuals. Keep container closed; keep spark, flames and heat away. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, protective gloves, good ventilation.

WARNING

Adhesive, Item 44A, is combustible. Keep container closed and store in a cool, dry place. Use only in well-ventilated areas. Keep clear of all sources of ignition or sparks during application. Breathing vapors may cause headaches, dizziness, and nausea; avoid prolonged inhalation of vapors. May cause skin and eye irritation. If skin or eye contact occurs, wash immediately with water for at least 15 minutes. If ingested, do not induce vomiting. Seek immediate medical attention. Wash hands thoroughly with soap and water after use. Wash contaminated clothing before reuse. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 46, is flammable. Keep container closed; keep sparks, flames, and heat away; keep adhesive off skin, eyes, and clothes. May irritate the eyes and skin. If eye contact occurs, flush with water for 15 minutes and seek medical attention. Do not breathe vapors. Breathing vapor may cause headache, dizziness, and nausea. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, impermeable gloves, good ventilation and/or NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 47, is extremely flammable. Vapors may ignite explosively. Keep container closed and store in a cool, dry place. Bond and ground containers of product to prevent ignition through static discharge. Use only in well-ventilated areas. Keep clear of all sources of ignition or sparks during application and curing. Avoid inhaling vapors. Breathing vapors may cause headaches, dizziness, and nausea. Liquid and vapor may irritate the eyes. Prolonged or repeated contact may irritate the skin. May be absorbed through the skin in levels that may affect inner organ systems. If skin or eye contact occurs, wash immediately with water. If ingested, do not induce vomiting. Seek immediate medical attention. Protection: safety glasses or goggles, approved gloves, good ventilation, protective clothing to prevent contact, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits, particularly in confined areas.

WARNING

Adhesive, Item 48, may irritate the eyes. Prolonged or repeated contact may trigger sensitization which will result in allergic reactions. Contains asbestos, which has been found to cause cancer. Exposure to asbestos should not occur during mixture and use of adhesive, since the asbestos is bound to the adhesive. However, if the cured product is sanded without proper local exhaust ventilation and NIOSH/MSHA-approved toxic particle respirators, exposure by inhalation is probable. Mix resin and curing agent in batches to be used immediately. Stored mixture may exotherm if not used soon after preparation. Do not heat mixed adhesive above 75°F (24°C) unless curing surfaces to be bonded; toxic gases from excessive heat build-up may be released. Keep resin off skin, eyes, and clothes. Avoid breathing vapors. If dry sanding, machining, or drilling is required after curing, NIOSH/MSHA-approved respirator shall be worn. Dispose of resin waste in accordance with local, state, or federal regulations. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, impervious plastic or rubber gloves, good ventilation.

WARNING

Adhesive, Item 49, is flammable. Keep container closed. Keep sparks, flames, and heat away. Keep adhesive off skin, eyes, and clothes. May irritate the eyes and skin. Do not breathe vapors. Breathing vapor may cause headache, dizziness, nausea. Long-term overexposure may damage the liver, kidneys, lungs, and nervous system. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, protective gloves, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 52, as an uncured product may irritate the eyes, skin, nose, and throat. Product releases toxic, irritating acetic acid during application and curing; mechanical ventilation should be used to keep acetic acid mist well below established exposure limits. Keep sealant off skin, eyes, and clothes. Keep sparks, flames, and heat away. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 53, as an uncured product may irritate the eyes and skin. Avoid contact with the eyes and skin. Uncured product may irritate the eyes and skin. Avoid breathing vapors. Use only in a well-ventilated area. Uncured product may cause respiratory irritation. Product releases irritating acetic acid during application and curing; acetic acid vapor is combustible; do not apply near ignition sources (heat, flame); mechanical ventilation should be used to maintain vapor levels well below established limits. Repeated or prolonged inhalation may result in chronic bronchitis. Do not handle contact lenses until sealant has been cleaned from fingernails and tips; residual silicone may cause severe eye irritation. If vapor irritates eyes or skin, flush affected area immediately with water. For respiratory irritation, seek fresh air and possible medical attention. Do not eat, drink, or smoke in work area. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, rubber gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 54, as an uncured product may irritate the eyes, skin, nose, and throat. Product releases toxic, irritating acetic acid during application and curing; mechanical ventilation should be used to keep acetic acid mist well below established exposure limits. Keep sparks, flames, and heat away. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 55, is combustible. Keep sparks, flames, and heat away; keep adhesive off skin, eyes, and clothes. Do not breathe vapors. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, impervious gloves, good ventilation.

WARNING

Adhesive, Item 56, as an uncured product can irritate eyes. If contact with eyes occurs, flush immediately with water for 15 minutes and seek medical attention. May cause mild skin irritation. If skin contact occurs, wipe with dry cloth then wash with soap and water. Individuals who wear contact lenses should thoroughly wash hands prior to handling lenses. Residual silicone may transfer from fingertips to lenses, causing severe eye irritation. Adhesive/sealant may irritate the stomach if swallowed. CAUTION: Product releases toxic, flammable methanol during application and curing; mechanical ventilation designed for flammable vapor should be used to maintain methanol vapor levels well below established exposure limits. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, protective gloves, NIOSH/MSHA-approved respirator, if curing vapors or dust from hot work applications on cured product exceed established exposure limits.

WARNING

Adhesive, Item 57, is combustible. Keep container closed; keep sparks, flames, and heat away. CAUTION: Reacts with water and acids, liberating flammable methyl alcohol. Wash hands thoroughly after use. Keep sealant off eyes, skin, and clothes. Uncured adhesive/sealant can irritate eyes. If contact with eyes occurs, flush immediately with water for 15 minutes and seek medical attention. Prolonged or repeated contact may irritate the skin; should contact with the skin occur, wipe off and flush with water. Do not wear contact lenses when handling. Residual adhesive/sealant may remain on fingers, nails, or cuticles for several days and transfer to lenses, causing severe eye irritation. Do not breathe vapors; inhalation may cause drowsiness and upper respiratory irritation. If irritation persists, seek fresh air and possible medical attention. Long-term overexposure without protective equipment may cause nervous system damage. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, protective gloves, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 59, is irritating to skin, eyes, nose, and throat. Do not breathe vapors. Do not eat, drink, or smoke in work area. Clean contaminated clothing thoroughly before reuse. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles and/or face shield, rubber gloves, good ventilation or NIOSH/MSHA-approved acid vapor respirator.

WARNING

Adhesive, Item 60, is flammable. Keep container closed and store in a cool, dry place. Use only in well-ventilated areas. Bond and ground metal containers during use and transfer to prevent ignition through static discharge. Keep clear of all sources of ignition or sparks during application and curing. Breathing vapors may cause headaches, dizziness, confusion, and respiratory irritation. Long-term overexposure without protective equipment may cause liver and kidney damage, and may trigger "asthmatic-type" respiratory responses and allergic skin reactions. May cause skin and eye irritation. If skin or eye contact occurs, wash immediately with water for at least 15 minutes. If ingested, do not induce vomiting. Seek immediate medical attention. Wash hands thoroughly with soap and water after use. Launder contaminated clothing before reuse. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 64, is flammable. Keep product away from potential sources of ignition, such as heat, spark, and flame. Product may cause eye, skin and respiratory tract irritation. Long-term exposure may cause headache, nausea, and dermatitis. If eye contact occurs, flush eyes immediately with large amounts of water. If product contacts the skin, wash affected areas with soap and water and remove contaminated clothing. Seek fresh air, if breathing is difficult, and provide oxygen. If swallowed, do not induce vomiting. Give one or two glasses of milk and call for medical assistance. Protection: appropriate gloves safety glasses or goggles. Wash hands thoroughly after use. Accelerator is combustible. Keep away from heat, sparks and open flame. Keep containers tightly closed. WARNING: Product contains benzoyl peroxide. If solvents evaporate, dried residue may ignite with heat or friction. Eye and skin contact may cause irritation. Inhaling of product may irritate the respiratory system, causing dryness of the throat, tightness of the chest and shortness of breath. In addition, overexposure to this product may cause nervous system damage, causing headache, dizziness and staggering. If product contacts the skin, wash affected areas with soap and water and remove contaminated clothing. If breathing is difficult, seek fresh air, provide oxygen. If swallowed, do not induce vomiting. Give one or two glasses of milk and call for medical assistance. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, rubber gloves. Wash hands thoroughly after each use.

WARNING

Adhesive, Item 66, is flammable. Keep away from sparks, heat, flame, and other ignition sources. Bond and ground metal containers during transfer to prevent ignition through static discharge. Keep containers closed when not in use. Avoid contact. May irritate the eyes and skin. May be absorbed through the skin in potentially dangerous levels that may affect inner organs. Avoid breathing vapor. Inhalation may cause headache, dizziness, nausea, and respiratory irritation. Long-term overexposure may cause liver, heart, and kidney damage. No eating, drinking, or smoking is allowed where paints are being mixed, handled, or cleaned-up. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive, Item 66E, is irritating to skin, eyes, nose, and throat. Do not breathe vapors. Avoid exposure to air or moisture until ready to use, acetic acid vapors form during curing. Do not eat, drink, or smoke in work area. Clean contaminated clothing thoroughly before reuse. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles and/or face shield, rubber gloves, good ventilation or NIOSH/MSHA-approved acid vapor respirator.

WARNING

Adhesive primer, Item 67, Parts A and B, are flammable. Part A and may irritate the eyes and skin. May cause allergic skin reaction in certain individuals. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Long-term overexposure may affect the heart, liver, kidney, and blood. Part B - May irritate the eyes and skin. May cause allergic skin reaction. May be absorbed through the skin in potentially dangerous amounts that may affect inner organ systems. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Long-term overexposure may affect the liver, kidney, and blood. Chronic overexposure to the component 2-ethoxyethyl acetate may cause birth defects and male reproductive system changes. Chronic overexposure to component chromates has been found to cause cancer. Mixture Part A & B - Flammable - Keep away from ignition sources (heat, flame). Bond/ground metal containers during transfer to prevent ignition through static discharge. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, impervious gloves, full-body protective clothing, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Adhesive primer, Item 68, is extremely flammable. Keep container closed; keep sparks, flames, and heat away. Bond and ground metal containers during transfer to prevent ignition through static discharge. Keep adhesive primer off skin, eyes, and clothes. Direct contact may irritate the eyes. Upon eye contact, flush immediately with water for 15 minutes. Prolonged or repeated contact may irritate the skin, leading potentially to dermatitis. If adhesive primer contacts the skin, wash with soap and water; remove and launder contaminated clothing. Avoid breathing vapor; inhalation may cause headache, dizziness, nausea, and upper respiratory irritation. If these symptoms persist, seek fresh air and possible medical attention. If swallowed, do not try to vomit; chemical may enter lungs, causing damage. CAUTION: Contains strontium chromate. Inhalation of mists from spray painting or dusts from grinding primed parts may cause cancer. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, gloves, good ventilation, full-body protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Denatured alcohol, Item 70, is flammable and toxic to eyes, skin, and respiratory tract. Avoid repeated or prolonged contact. Use only in well-ventilated areas. Keep away from open flames, sparks, or other sources of ignition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, protective gloves, good ventilation or use approved respirator as determined by local safety/industrial hygiene personnel.

WARNING

Isopropyl alcohol, Item 72, is flammable and toxic to eyes, skin, and respiratory tract. Avoid repeated or prolonged contact. Use only in well-ventilated areas. Keep away from open flames, sparks, or other sources of ignition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, protective gloves, good ventilation or use approved respirator as determined by local safety/industrial hygiene personnel.

WARNING

Alodine, Item 73, is a strong oxidizing agent that may ignite combustible material such as sawdust, rags, and paper or organic substances. Keep container closed; keep sparks, flames, and heat away. Keep alodine off skin, eyes, and clothes. May severely burn the eyes and skin on contact. Do not breathe vapors. Breathing dusts or mists may irritate the respiratory tract. Long-term overexposure by breathing mists or absorption through the skin may cause cancer, kidney and liver damage, and ulceration of the nasal septum. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, neoprene or polyvinyl gloves, apron, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Antiseize compound, Item 74, is flammable. Do not use near open flames, near welding areas, or on hot surfaces. Do not smoke when using it and do not use it where others are smoking. Metal container must be grounded to maintain electrical continuity. Dispose of liquid-soaked rags in approved metal safety container. Contact with the liquid can cause severe skin and eye irritation. After any prolonged skin contact, wash contacted area with soap and water. If liquid contacts eyes, flush eyes thoroughly with water for 15 minutes. If vapors cause drowsiness, move to fresh air. Get medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: If repeated or prolonged application of aerosol with spray can or brush is likely, wear NIOSH/MSHA-approved respirator, gloves, and goggles.

WARNING

Antiseize compound, Item 75, is combustible. Do not use near open flames, near welding areas, or on hot surfaces. Do not smoke when using it and do not use it where others are smoking. Prolonged or repeated contact may irritate the eyes and skin. After any prolonged skin contact, wash contacted area with soap and water. If liquid contacts eyes, flush eyes thoroughly with water. Dispose of liquid-soaked rag in approved metal safety container. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, approved gloves.

WARNING

Antiseize compound, Item 76, may irritate the eyes and skin. Avoid prolonged or repeated contact. Vapors from heated product or mists from spray applications may irritate the respiratory tract; as a paste, the product poses minimal inhalation hazard. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, approved gloves.

WARNING

Assembly fluid, Item 79, may irritate the skin and eyes on contact. If assembly fluid contacts the eyes, flush immediately for 15 minutes. Prolonged or repeated use without hand protection may cause dermatitis. At normal temperatures, assembly fluid poses minimal health hazard by inhalation. If the product is heated or applied as a mist, use of a NIOSH/MSHA-approved respirator may be necessary. Wash hands with soap and water after use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles or safety glasses, oil-resistant gloves, skin-protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Technical chromium trioxide, Item 91, is highly reactive. Do not mix with organic materials or materials that oxidize such as paper and wood. When mixing solutions, add acid to water, not water to acid. Avoid contact with the eyes and skin; contact may cause severe burns and skin ulcers. If any liquid or powder contacts skin, flush affected area with water, and immediately change contaminated clothing. Contaminated clothing must not be laundered at home. If skin ulcers appear, get medical attention. Breathing vapors, mists, or powder may cause severe respiratory irritation. Long-term overexposure by inhalation or absorption through the skin may cause cancer and liver, kidney, and respiratory system damage. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles, approved gloves, apron, long sleeves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Cleaning compound, Item 92, is combustible - Keep cleaning compound away from potential sources of ignition, including heat, spark, and flame. CAUTION: Combustion of product or heat of flame may produce irritating and poisonous gases. Avoid contact. Direct contact may irritate the eyes and skin. In case of contact, flush affected area immediately with plenty of water. Avoid breathing mists or vapors. Inhalation may cause headache, dizziness, nausea, and respiratory irritation. In case of contact, flush affected area immediately with plenty of water. Seek medical attention if irritation persists. Products meeting this specification may have varying component ingredients. Product hazards vary with respect to unique chemical composition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Cleaning compound, Item 94, may irritate the eyes and skin. Avoid contact. May be absorbed through the skin in levels that may affect inner organs. Should eye or skin contact occur, flush the affected area immediately with water for about 15 minutes. Seek medical attention if irritation persists. Avoid inhaling vapors, particularly if product is applied to hot surfaces. Breathing vapors may cause headache, dizziness, nausea, and respiratory irritation. NOTE: Severity of exposure symptoms varies with specific product composition and duration of use. Products meeting this specification may have varying component ingredients. Product hazards vary with respect to unique chemical composition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, full-body protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Solvent cleaning compound, Item 99, VAPOR IS HAZARDOUS AND CAN CAUSE DEATH BY ASPHYXIATION IF TOO MUCH IS INHALED. Vapor from one pint of liquid evaporated in a small room is nearly odorless, but immediately dangerous to life or health. In case of spill, warn others and leave the area immediately. When used indoors, do not rely upon oxygen deficiency monitor to warn of dangerous concentrations of Trichlorotrifluoroethane. Have at least two people present at all times with one as observer. Have emergency escape breathing devices available for immediate use. Repeated or prolonged contact with liquid can cause skin and eye irritation. Breathing vapor may cause drowsiness, dizziness, headache, confusion and heart damage. After prolonged skin contact, wash contacted area with soap and water. Remove contaminated clothing. If vapors cause irritation, go to fresh air; get medical attention. Do not enter places where Trichlorotrifluoroethane is stored until ventilated, and air sample verifies that levels of Freon are well below established limits and oxygen concentration is between 19.5% and 22%. Dispose of liquid-soaked rags in approved metal container. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Solvent cleaning compound, Item 99A, is combustible and toxic to eyes, skin, and respiratory tract. Avoid repeated or prolonged contact. Use only in well-ventilated areas. Keep away from open flames, sparks, or other sources of ignition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, protective gloves, good ventilation, approved organic vapor respirator, with dust and mist filter, if exposed to vapor mist.

WARNING

Solvent cleaning compound, Item 99B, is combustible and toxic to eyes, skin, and respiratory tract. Avoid repeated or prolonged contact. Use only in well-ventilated areas. Keep away from open flames, sparks, or other sources of ignition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, protective gloves, good ventilation, approved organic vapor respirator, with dust and mist filter, if exposed to vapor mist.

WARNING

Solvent cleaning compound, Item 99C, may cause slight eye and skin irritation. If eyes become red or have a burning sensation, flush with cool water for 15 minutes. Then seek medical attention. If dermatitis occurs on skin, flush skin with water use good quality hand cream. If irritation persists, consult a physician. If ingested, drink 2 large glasses of water, do not induce vomiting. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, approved gloves.

WARNING

Solvent cleaning compound, Item 100, is combustible - Keep away from potential sources of ignition, including heat, spark, and flame. CAUTION: Combustion of product or heat of flame may produce irritating and poisonous gases. Avoid contact. Direct contact may irritate the eyes and skin. Certain components maybe absorbed through the skin in potentially dangerous levels that may affect inner organs. In case of contact, flush affected area immediately with plenty of water. Avoid breathing mists or vapors. Inhalation may cause headache, dizziness, nausea, and respiratory irritation. In case of contact, flush affected area immediately with plenty of water. Seek medical attention if irritation persists. Products meeting this specification may have varying component ingredients. Product hazards vary with respect to unique chemical composition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or chemical splashproof goggles, approved gloves, full-body protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Solvent cleaning compound, Item 100A, is combustible and toxic to eyes, skin, and respiratory tract. Avoid repeated or prolonged contact. Use only in well-ventilated areas. Keep away from open flames or other sources of ignition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, protective gloves, good ventilation or use approved respirator as determined by local safety/ industrial hygiene personnel.

WARNING

Coating compound, Item 106, is flammable. Keep product away from potential sources of ignition, such as heat, spark, and flame. Bond/ground metal containers. Keep containers securely closed when not in use. Product applicators, such as brushes and rags must be properly disposed or cleaned. Avoid contact. Direct contact may cause moderate eye irritation. Product may moderately irritate skin. Inhaling product vapors may cause headache, dizziness, nausea, and respiratory irritation. Long-term overexposure to product may cause dermatitis and central nervous system affects. If eye contact occurs immediately flush eyes in a continuous stream for at least 15 minutes. Seek medical attention. In case of skin contact wash thoroughly with soap and water. Seek medical attention if irritation persists. If overcome by product vapors go to fresh air and seek medical assistance. If ingested do not induce vomiting if available drink a glass of milk and seek medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggle or face shield, heavy duty neoprene/polyethylene gloves, protective clothes to prevent skin contact, good ventilation, NIOSH/MSHA-approved respiratory protection, if vapors exceed established exposure limits.

WARNING

Corrosion compound, Item 108, is corrosive. It may burn exposed body tissues on contact. Avoid contact with skin and eyes; do not breathe mists. May contain chemicals that may be absorbed through the skin in dangerous amounts that can affect inner organ systems. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, approved gloves, protective clothing as required. Wash hands thoroughly after handling.

WARNING

Corrosion preventive compound, Item 108A, may irritate the eyes. Avoid contact with product. Prolonged or repeated contact may irritate the skin. Long-term use without proper hand protection may cause dermatitis. If splashed on clothing or eyes, remove clothing immediately and flush the eyes and skin with water for 15 minutes. Avoid breathing vapor. Keep containers closed when not in use; use in a well-ventilated area. Inhalation may cause headache, dizziness, nausea, and respiratory irritation. If swallowed, do not try to vomit; chemical may enter the lungs, causing damage; seek immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Corrosion preventive compound, Item 108B, may irritate the eyes. Avoid contact with product. Prolonged or repeated contact may irritate the skin. Long-term use without proper hand protection may cause dermatitis. If splashed on clothing or eyes, remove clothing immediately and flush the eyes and skin with water for 15 minutes. Avoid breathing vapor. Keep containers closed when not in use; use in a well-ventilated area. Inhalation may cause headache, dizziness, nausea, and respiratory irritation. If swallowed, do not try to vomit; chemical may enter the lungs, causing damage; seek immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Corrosion preventive compound, Item 108C, is reactive - strong oxidizer; may enhance the flammability of nearby combustibles. Keep container closed. Keep sparks, flames, and heat away. Keep away from alkaline materials. Corrosive - Burns the eyes and skin on contact. Should skin or eye contact occur, immediately flush with water for 15 minutes. Seek medical attention. Contaminated clothing must be removed immediately and laundered before reuse. Avoid breathing mists. Inhalation may cause severe respiratory irritation, marked by coughing and labored breathing. If these symptoms occur, seek fresh air and medical attention. Long-term overexposure without protective equipment may cause ulceration of the skin and nasal passages and dermatitis. CAUTION: May contain chemicals that may be absorbed through the skin in potentially dangerous levels that may affect inner organs. May contain Chromic Acid - found to cause cancer. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles or face shield, protective gloves and boots, full-body chemical-resistant clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Corrosion preventive compound, Item 109, Item 110, Item 111, and Item 112, is combustible. Keep it away from heat, sparks, and open flames. Do not smoke when using it. Use in a well-ventilated area. Direct contact may severely irritate the eyes. Prolonged or repeated contact may irritate the skin. If splashed on clothing or in eyes, remove clothing immediately and flush skin/eyes with clear water for 15 minutes. Breathing vapor may cause headache, dizziness, nausea, and respiratory irritation. If vapors cause light-headedness, go to fresh air. If liquid is swallowed, do not induce vomiting, aspiration may damage the lungs. Get prompt medical attention. Keep away from spillage. Use absorbent to soak up spilled solution. Dispose of absorbent in accordance with local, state, and federal regulations. Keep solution away from oxygen and strong oxidants. Store in approved metal safety container. Keep containers closed when not in use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles or face shield, rubber, neoprene, or nitrile gloves, protective neoprene apron.

WARNING

Corrosion preventive compound, Item 113, may irritate the eyes. Avoid contact with corrosion preventive compound. Prolonged or repeated contact may irritate the skin. Long-term use without proper hand protection may cause dermatitis. May be absorbed through the skin in levels that could affect certain "target" organs. If splashed on clothing or eyes, remove clothing immediately and flush the eyes and skin with water for 15 minutes. Avoid breathing vapor. Keep containers closed when not in use; use in a well-ventilated area. Inhalation may cause headache, dizziness, nausea, and respiratory irritation; acute overexposures may cause heart irregularities. If these symptoms occur, seek fresh air and possible medical attention. If swallowed, do not try to vomit; chemical may enter the lungs, causing damage; seek immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, full-body protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Corrosion preventive compound, Item 114 and Item 115, is combustible. Keep it away from heat, sparks, and open flames. Do not smoke when using it. Use in a well-ventilated area. Inhalation of vapors is harmful. If splashed on clothing or in eyes, remove clothing immediately and flush skin/eyes with clear water for 15 minutes. If vapors cause light-headedness, move to fresh air. If liquid is swallowed, do not induce vomiting. Get prompt medical attention. Use absorbent to soak up spilled solution. Dispose of absorbent in accordance with local, state, and federal regulations. Keep solution away from oxygen and strong oxidants. Store in approved metal safety container. Keep containers closed when not in use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles or face shield, oil-impervious gloves, protective apron.

WARNING

Corrosion preventive compound, Item 115A, may irritate the eyes; flush immediately with large amounts of water. Prolonged or repeated contact may cause mild skin irritation; wash contacted area with soap and water. Remove and launder contaminated clothing. Breathing vapors, generated at high temperature, or mists may cause headache, dizziness, and respiratory irritation. If swallowed, do not try to vomit; fluid may be aspirated into lungs, causing damage. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, long sleeves/pant legs, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Corrosion compound, Item 116, is corrosive. It may burn exposed body tissues on contact. Avoid contact with skin and eyes; do not breathe mists. May contain chemicals that may be absorbed through the skin in dangerous amounts that can affect inner organ systems. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, approved gloves, protective clothing as required. Wash hands thoroughly after handling.

WARNING

Corrosion resistant coating, Item 117, Item 118, and Item 118A, is a strong oxidizing agent that may ignite combustible material such as sawdust, rags, and paper or organic substances. Keep container closed; keep sparks, flames, and heat away. Keep alodine off skin, eyes, and clothes. May severely burn the eyes and skin on contact. Do not breathe vapors. Breathing dusts or mists may irritate the respiratory tract. Long-term overexposure by breathing mists or absorption through the skin may cause cancer, kidney and liver damage, and ulceration of the nasal septum. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, neoprene or polyvinyl gloves, apron, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Damping fluid, Item 121, may mildly irritate the eyes and skin. Minimize contact with damping fluid. In case of eye contact, flush eyes immediately with water. Should prolonged contact with the skin occur, wipe off excess product and flush the skin with water. Remove and launder saturated clothing. Wash hands at shift end and prior to eating, drinking, or smoking. CAUTION: Traces of formaldehyde found to cause cancer and other hazardous decomposition products may be generated at high temperatures. Such high temperature operations may require the use of increased ventilation and/or use of a NIOSH/MSHA-approved respirator. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, approved gloves.

WARNING

Solvent cleaning compound, Item 124, is combustible and toxic to eyes, skin, and respiratory tract. Avoid repeated or prolonged contact. Use only in well-ventilated areas. Keep away from open flames or other sources of ignition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, protective gloves, good ventilation or use approved respirator as determined by local safety/industrial hygiene personnel.

WARNING

Dry ice, Item 125, will cause severe frostbite on exposed skin. Avoid contact. Avoid breathing vapor. Prolonged inhalation may cause shortness of breath, nose/throat irritation, watery eyes and headache. Prolonged overexposure may cause coma and death. If solid carbon dioxide contacts skin, immediately flush area with lukewarm water. Do not rub affected area. Seek medical attention. If other symptoms of overexposure appear, seek fresh air and possible medical attention. CAUTION: Do not place solid carbon dioxide in sealed containers; heat will sublime ice to form gas, increasing pressure and resulting in explosion. Do not put head or limbs into dry ice containers. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or face shield, heavy approved gloves, thick full-body protective clothing.

WARNING

Epoxy coating, Item 126A, is flammable. Keep container closed; keep sparks, flames, and heat away. Bond/ground metal containers during transfer to prevent ignition through static discharge. Keep coating off skin, eyes, and clothes. May irritate the eyes and skin. May contain chemicals that may be absorbed through the skin in dangerous amounts that can affect inner organ systems or that may, upon long-term exposure, damage inner "target" organs. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, gloves, forced ventilation or NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Epoxy patch kit, Item 134, is a two component product consisting of an epoxy resin Part A and hardener, Part B. The precautions for each should be observed when separate or mixed. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Epoxy Resin, AA0151, Part A: Direct contact with eyes may cause moderate irritation. Skin contact may cause moderate irritation. Inhalation should not be a hazard due to low volatility. Ingestion should not be a hazard due to low order of toxicity. In case of eye contact, flush with water for 15 minutes holding eyes open, obtain medical attention; in case of skin contact, wash with soap and water and obtain medical attention if irritation persists. In case of inhalation remove to fresh air and obtain medical attention; In case of ingestion, do not induce vomiting and obtain medical advice. Protection: safety goggles, approved gloves, good ventilation. Hardener, AB0151, Part B: Product severely irritates the eyes and skin. Permanent impairment of vision or blindness may occur. Ingestion may cause burns to the mouth and upper gastrointestinal tract. Inhaling vapors will cause irritation and sensitization responses in susceptible individuals such as respiratory distress. In case of eye contact, flush with water for 30 minutes while holding lids open and obtain immediate medical attention. In case of skin contact, flush the area with water, remove contaminated clothing and obtain medical attention. In case of inhalation, remove to fresh air and obtain medical attention if symptoms persist. In case of ingestion, do not induce vomiting, give large quantities of water if conscious and obtain immediate medical attention. Protection: safety goggles, approved gloves, good ventilation.

WARNING

Epoxy primer, Item 135, is flammable. Do not use near open flames, welding areas, or on hot surfaces. Do not eat, drink, or smoke where primers are being mixed, handled, or cleaned up. Prolonged breathing of vapors or spray mist should be avoided. Avoid prolonged skin contact. Contains chromates; follow approved toxic waste disposal procedures. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: respiratory protection.

WARNING

Etching Solution, Item 136, is flammable. Do not use near open flames, welding areas, or hot surfaces. Bond and ground metal containers during transfer to prevent ignition through static discharge. Keep containers closed when not in use. Dispose of liquid-soaked rags in approved metal container. Avoid contact; contact will cause severe burns to exposed tissue. May be absorbed through the skin in potentially dangerous levels that may affect inner organs. If liquid contacts the eyes or skin, immediately flush the affected area thoroughly with water, and get medical attention. Change contaminated clothing immediately. Avoid breathing vapor. Inhalation may cause fatigue, headache, dizziness, nausea, and upper respiratory irritation. If symptoms appear, seek fresh air and possible medical attention. CAUTION: Reacts with water to form caustic soda. May form explosive peroxide if stored for over six months. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles or face shield, neoprene gloves, full-body protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Ethylene Glycol, Item 137, may cause slight eye and skin irritation upon prolonged or repeated contact. Keep container closed; keep sparks, flames, and heat away. Keep ethylene glycol off skin, eyes, and clothes. Breathing vapors or mists of heated or agitated ethylene glycol may cause dizziness and upper respiratory irritation. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles or safety glasses, chemical-resistant gloves, other protective clothing as needed, good ventilation.

WARNING

Grease, Item 143, may cause moderate irritation to eyes. In case of eye contact, immediately flush eyes with water. Wash hands at shift end and prior to eating. CAUTION: Traces of polytetrafluoroethylene found to cause polymer fever and other hazardous decomposition products may be generated at high temperatures. Such high temperatures may require the use of increased ventilation and/or use of a NIOSH/MSHA-approved respirator. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses.

WARNING

Grease, Item 144, is combustible. Keep away from heat, sparks, and flames. Do not apply to hot surfaces; toxic gases may be released. Keep grease off skin, eyes, clothes. Prolonged or repeated contact may irritate the eyes and skin. Long-term use without hand protection may cause dermatitis. Wash hands thoroughly before eating, drinking, and smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed.

WARNING

Grease, Item 145, is combustible. Keep away from heat, sparks, and flames. Do not apply to hot surfaces; toxic gases may be released. Do not breathe vapors. Keep grease off skin, eyes, and clothes. Prolonged or repeated contact may irritate the eyes and skin. Long-term use without hand protection may cause dermatitis. Wash hands thoroughly before eating, drinking, and smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed, good ventilation.

WARNING

Grease, Item 146, is combustible. Keep away from heat, sparks, and flames. Do not apply to hot surfaces; toxic gases may be released. Keep grease off skin, eyes, clothes. Prolonged or repeated contact may irritate the eyes and skin. Long-term use without hand protection may cause dermatitis. Wash hands thoroughly before eating, drinking, and smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed.

WARNING

Grease, Item 147, is a skin and eye irritant. Minimize contact with grease. Prolonged or repeated contact may irritate the eyes and skin. Long-term use without hand protection may cause dermatitis. Product used under normal conditions poses minimal hazard by inhalation. However, vapors produced during high temperature operations may cause headache, dizziness, and upper respiratory irritation. Wash hands thoroughly before eating, drinking, and smoking. Refer to the Material Safety Data Sheet (MSDS) for additional health and safety information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed, good ventilation.

WARNING

Grease, Item 148, may irritate the eyes and skin. Minimize contact with grease. Long-term use without hand protection may cause dermatitis. Product used under normal conditions poses minimal hazard by inhalation. Wash hands thoroughly before eating, drinking, and smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed.

WARNING

Grease, Item 149, is combustible. Keep away from heat, sparks, and flames. Do not apply to hot surfaces; toxic gases may be released. Keep grease off skin, eyes, and clothes. Prolonged or repeated contact may irritate the eyes and skin. Long-term use without hand protection may cause dermatitis. Wash hands thoroughly before eating, drinking, and smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, oil-resistant gloves, other protective clothing as needed.

WARNING

Grease, Item 150, is a skin and eye irritant. Avoid any skin contact with grease/lubricant material. Prolonged or repeated contact may irritate the eyes and skin. Breathing vapor may irritate the upper respiratory tract. If swallowed, do not induce vomiting; aspiration may damage the lungs. Wash hands thoroughly prior to eating, drinking, or smoking. Do not apply to hot surfaces; toxic gases may be released. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Grease, Item 151, may cause moderate eye irritation. Prolonged or repeated skin contact may cause skin irritation. May cause dermatitis after prolonged contact. Keep grease away from ignition sources (heat, sparks, flame) and strong oxidizers. Store out of direct sunlight in a cool, dry, well-ventilated areas. In case of eye contact flush with water for at least 15 minutes and obtain medical attention. In case of skin contact wash area thoroughly with soap and water. If irritation persists seek medical attention. If inhaled, remove to fresh air, administer oxygen if required, and obtain immediate medical attention. If ingested, obtain immediate medical attention. Do not induce vomiting. Wash with soap and water after handling product. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles or face shields, approved gloves, good ventilation.

WARNING

Grease, Item 151A, is a skin and eye irritant. Avoid any skin contact with grease/lubricant material. Prolonged or repeated contact may irritate the skin; direct contact may irritate the eyes. Inhaling high concentrations of mists or vapors from heated product may cause headache, dizziness, and respiratory irritation. Keep containers closed when not in use. Do not use near heat, sparks, or hot surfaces; toxic gases may be released. Wash hands thoroughly prior to eating, drinking, or smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves.

WARNING

Hydraulic fluid, Item 154, is combustible. Do not use or store near flames, sparks, or hot surfaces. Use only in a well-ventilated area. If hydraulic fluid is decomposed by heat, toxic gases are released. Prolonged contact with liquid or mist can cause dermatitis and severe skin irritation. If there is any prolonged contact with skin, wash contacted area with soap and water. Remove contaminated clothing and launder before reuse. If liquid contacts eyes, flush eyes with water immediately. If fluid is swallowed, do not try to vomit; fluid may enter the lungs and cause severe injury. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: rubber gloves, impervious protective clothing, NIOSH/MSHA-approved respirator, if prolonged contact with mist is likely.

WARNING

Hydraulic fluid, Item 155, if decomposed by heat, will release toxic gases. Inhalation of vapors should be avoided. Prolonged contact with liquid or mist can cause dermatitis and irritation. If there is any prolonged contact with skin, wash contacted area with soap and water. If liquid contacts eyes, flush eyes with water immediately for 15 minutes. Remove saturated clothing. If fluid is swallowed, do not induce vomiting. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: rubber gloves.

WARNING

Insulating compound, Item 157, is flammable. Keep it away from ignition sources (heat, flame). Bond/ground metal containers during mixing or transfer to prevent ignition from static discharge. Keep compound off skin, eyes, and clothes. Direct contact may severely irritate the eyes. May irritate the skin. May cause allergic skin rash in sensitized individuals. Breathing vapor may cause headaches, dizziness, nausea, and respiratory irritation (marked by sore throat, chest discomfort, and difficulty in breathing). Certain individuals may develop "isocyanate sensitization", which will cause them to experience an "asthmatic-type" reaction at levels well below established limits. Long-term overexposure may cause permanent damage to brain, nervous system, kidneys, and lungs. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, neoprene gloves, forced ventilation, NIOSH/MSHA-approved respirator, if vapor exceeds established exposure limits.

WARNING

Insulating compound, Item 158, as an uncured product may irritate the eyes, skin, nose, and throat. Product releases toxic, irritating acetic acid during application and curing; mechanical ventilation should be used to keep acetic acid mist well below established exposure limits. Keep sealant off skin, eyes, and clothes. Keep sparks, flames, and heat away. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Lacquer, Item 182B, is flammable. Keep away from ignition sources such as heat, spark, and flames. Bond/ground metallic containers during use or transfer. Avoid contact; product may cause moderate to severe eye and skin irritation. In case of eye contact, flush eyes immediately with water for 15 minutes. If product contacts the skin, wash affected areas thoroughly with soap and water. Remove contaminated clothing immediately and launder before reuse. Avoid breathing vapors; inhalation may cause headache, dizziness, nausea, and respiratory irritation. Seek fresh air and possible medical attention if such symptoms persists. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Lacquer, Item 182C, is flammable. Keep away from potential sources of ignition, including heat, spark, and flame. Bond and ground metal containers to prevent ignition through static electrical discharge. Keep containers tightly closed, in a cool, dry area when not in use. Avoid contact. Direct contact may irritate the eyes and skin, particularly when prolonged or repeated. Avoid breathing vapors and mists. Inhalation may cause headache, dizziness, nausea, and respiratory irritation. In case of contact, flush affected areas immediately with water. Seek medical attention if irritation persists. NOTE: Covers a series of acrylic-nitrocellulose camouflage lacquers, ranging in color specification. May contain components that may, upon long-term use without proper protective equipment, cause nervous system damage, cancer, and reproductive effects. Certain components may be absorbed through the skin in levels that may affect inner organs. Products meeting this specification may have varying component ingredients. Product hazards vary with respect to unique chemical composition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles; approved gloves; full-body protective clothing; NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Lacquer, Item 183, Item 184, and Item 185, is flammable. Keep away from potential sources of ignition, including heat, spark, and flame. Bond and ground metal containers to prevent ignition through static electrical discharge. Keep containers tightly closed, in a cool, dry area when not in use. Avoid contact. Direct contact may irritate the eyes and skin, particularly when prolonged or repeated. Avoid breathing vapors and mists. Inhalation may cause headache, dizziness, nausea, and respiratory irritation. In case of contact, flush affected areas immediately with water. Seek medical attention if irritation persists. NOTE: Covers a series of acrylic-nitrocellulose camouflage lacquers, ranging in color specification. May contain components that may, upon long-term use without proper protective equipment, cause nervous system damage, cancer, and reproductive effects. Certain components may be absorbed through the skin in levels that may affect inner organs. Products meeting this specification may have varying component ingredients. Product hazards vary with respect to unique chemical composition. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles; approved gloves, full-body protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Lacquer, Item 186, Item 187, and Item 188, is flammable. Keep away from ignition sources such as heat, spark, and flames. Bond/ground metallic containers during use or transfer. Avoid contact; product may cause moderate to severe eye and skin irritation. In case of eye contact, flush eyes immediately with water for 15 minutes. If product contacts the skin, wash affected areas thoroughly with soap and water. Remove contaminated clothing immediately and launder before reuse. Avoid breathing vapors; inhalation may cause headache, dizziness, nausea, and respiratory irritation. Seek fresh air and possible medical attention if such symptoms persists. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Leak detection fluid, Item 189, is a mild skin and eye irritant. If eye contact occurs, flush with water. If eye irritation persists, seek medical attention. Wash hands with soap and water after use. If ingested, induce vomiting and seek medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, approved gloves.

WARNING

Lubricant, Item 200, if applied to hot surfaces, will release toxic gases. Avoid contact with lubricant material. Direct eye contact and prolonged or repeated skin contact may cause mild irritation. Heavy mists or vapors generated by high temperatures may cause headache, dizziness, and respiratory irritation. Wash hands thoroughly prior to eating, drinking, or smoking. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Solid film lubricant, Item 201, is flammable. At high temperatures, it can decompose into a toxic substance. Keep container closed; keep sparks, flames, and heat away. Keep solid film lubricant off skin, eyes, and clothes. May irritate the eyes and skin. Do not breathe vapors. Breathing mists may cause headache, dizziness, nausea, respiratory irritation. Methylene chloride, a major component, has been found to cause cancer. May contain chemicals found to cause target organ and reproductive effects upon chronic overexposure. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, neoprene gloves, impervious clothing, forced ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Lubricating oil, Item 202, is combustible. Keep away from potential sources of ignition, such as heat, spark, and flame. Keep containers securely closed when not in use. Prolonged or repeated contact may irritate the skin. Liquid or vapor may irritate the eyes. Inhaling product vapors may cause headache, dizziness, nausea, and respiratory irritation. Product contains components that may be absorbed through the skin, thus contributing to the overall effects of overexposure to the product. Prolonged overexposure to product without proper personal protective equipment may cause cancer. Flush eyes thoroughly with water for at least 15 minutes. If ingested, provide water and seek medical attention. Wipe excess product from skin, then wash thoroughly with soap and water. Seek medical attention if irritation persists. If overcome by product vapor or mist, seek fresh air and possible medical assistance. Launder soiled clothing after use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, full-body protective clothing, NIOSH/MSHA-approved respiratory protection, if vapors exceed established exposure limits.

WARNING

Lubricating oil, Item 203, may irritate the eyes and skin if prolonged or repeated contact occurs. If contact with skin is prolonged, wash area with soap and water. If product contacts eyes, flush eyes with water immediately. Remove and launder saturated clothing. Caution: Traces of benzene, found to cause cancer, may be generated at high temperatures. Such high temperature operations may require the use of increased ventilation and/or use of a NIOSH/MSHA-approved respirator. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses, approved gloves.

WARNING

Lubricating oil, Item 204A, may irritate skin if prolonged or repeated contact occurs. Liquid or mist may irritate the eyes. If liquid contacts eyes flush eyes with water immediately. Long-term exposure without proper hand protection may cause dermatitis. If there is any prolonged contact with skin, wash contacted area with soap and water. Remove saturated clothing. Breathing vapors generated at high temperatures or mists may cause headache, dizziness, and respiratory irritation. If fluid is swallowed, do not try to vomit; fluid may be aspirated into lungs, causing damage. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Lubricating oil, Item 205, may irritate the eyes and skin if prolonged or repeated contact occurs. Long-term use without hand protection may cause dermatitis. Breathing mists may cause respiratory irritation. If there is any prolonged contact with skin, wash area with soap and water. Remove saturated clothing. If solution contacts eyes, flush eyes with water immediately. If oil is swallowed, do not try to vomit; aspiration may damage lungs. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Lubricating oil, Item 205A, may irritate the eyes and skin if prolonged or repeated contact occurs. Long-term use without hand protection may cause dermatitis. Breathing mists may cause respiratory irritation. If there is any prolonged contact with skin, wash area with soap and water. Remove saturated clothing. If solution contacts eyes, flush eyes with water immediately. If oil is swallowed, do not try to vomit; aspiration may damage lungs. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Lubricating oil, Item 206, may irritate the eyes and skin if prolonged or repeated contact occurs. If there is any prolonged contact with skin, wash area with soap and water. If solution contacts eyes, flush eyes with water immediately. Remove saturated clothing. Breathing vapor may irritate the upper respiratory tract. If oil is swallowed, do not try to vomit, aspiration may damage the lungs. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Lubricating oil, Item 207, may irritate the eyes and skin if prolonged or repeated contact occurs. Long-term use without hand protection may cause dermatitis. Breathing mists may cause respiratory irritation. If there is any prolonged contact with skin, wash area with soap and water. Remove saturated clothing. If solution contacts eyes, flush eyes with water immediately. If oil is swallowed, do not try to vomit; aspiration may damage lungs. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Lubricating oil, Item 208, may irritate the eyes and skin if prolonged or repeated contact occurs. Long-term use without hand protection may cause dermatitis. Breathing mists may cause respiratory irritation. If there is any prolonged contact with skin, wash area with soap and water. Remove saturated clothing. If solution contacts eyes, flush eyes with water immediately. If oil is swallowed, do not try to vomit; aspiration may damage lungs. Get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Lubricating oil, Item 209, is combustible. Keep away from ignition sources (heat, flame). Keep container closed. Keep lubricating oil off skin, eyes, and clothes. Direct contact may severely irritate the eyes. Prolonged or repeated contact may irritate the skin. Do not breathe vapors. Breathing mists may cause headache, dizziness, nausea, and respiratory irritation. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, neoprene or polyvinyl gloves, impervious clothing, good ventilation, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Methyl ethyl ketone, Item 217, is flammable. Do not use near open flames, near welding areas, or on hot surfaces. Do not smoke when using it, and do not use it where others are smoking. Contact with liquid or vapor can cause skin and eye irritation, dermatitis, and drowsiness. If there is any prolonged skin contact, wash contacted area with soap and water. Remove solvent-saturated clothing. If vapors cause drowsiness, move to fresh air. If irritation persists, get medical attention. Dispose of liquid-soaked rags in approved metal container. When storing, metal containers of solution must be grounded to maintain electrical continuity. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: when handling liquid at air-exhausted workbench, wear approved goggles and gloves; when handling liquid or liquid-soaked cloth in open unexhausted area, wear chemical splashproof goggles and approved gloves.

WARNING

Methyl isobutyl ketone, Item 218, is flammable, and irritating to eyes, skin, nose, and throat. Keep container closed; keep sparks, flames, and heat away. Keep methyl isobutyl ketone off skin, eyes, and clothes. Wash contacted skin with soap and water. If solvent contacts eyes, flush them with clean water and get immediate medical help. Do not breathe vapors. Breathing vapor or mists may cause headache, dizziness, and nausea. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, impervious gloves and clothing, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Molybdenum disulfide, Item 219, may irritate the eyes and skin if prolonged or repeated contact occurs. Avoid any skin contact with grease material. Breathing vapor may irritate the upper respiratory tract. If swallowed, do not induce vomiting, aspiration may damage the lungs. Wash hands thoroughly prior to eating, drinking, or smoking. Do not apply to hot surfaces; toxic gases may be released. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Nitric acid, Item 220, is reactive. Keep away from organic or combustible materials (wood, paper). May react with metals to form flammable hydrogen gas. When mixing with water, always add acid to water not water to acid. Keep off eyes, skin, and clothes. It is corrosive. May severely irritate or burn the eyes and skin. Do not breathe mists. Inhalation may cause headache and nausea and severe respiratory irritation marked by coughing and labored breathing. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, full-body impervious clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Nitrogen, Item 221, is a non-toxic inert gas that may displace the air used for breathing and cause asphyxiation. Use nitrogen in a well-ventilated area. Symptoms of oxygen deficiency may include dizziness, weakened speech, and loss of coordination. However, asphyxiation can occur without warning signs. A positive pressure air line with mask or self-contained breathing apparatus should be available for emergency use. Compressed gas cylinder must be stored upright and firmly secured. Valve protection caps must be used to protect stored cylinders. Empty and full cylinders must be segregated. Do not heat compressed gas cylinders to increase the discharge rate. Caution: Nitrogen in a liquid state can cause skin burns and frostbite. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: face shield, cryogenic gloves, full-body protective clothing, safety shoes.

WARNING

Heat resistant aluminum paint, Item 221A, is flammable. Keep product away from heat, sparks, and open flame. Keep containers tightly closed when not in use. Long-term contact may cause drying, cracking and irritation of the skin. May react with skin and cause rash, scaling or blistering. Overexposure to product without use of proper personal protective equipment may cause nervous system damage. If overcome by vapors remove to fresh air, and obtain medical attention. If skin contact occurs, flush with water. If eye contact occurs, flush immediately with large amounts of water and seek medical attention, if ingested, do not induce vomiting, keep person warm and get medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, protective gloves, NIOSH/OSHA-approved respiratory protection.

WARNING

Polyurethane paint, Item 222, Item 222A, Item 223, Item 224, Item 225, Item 226, Item 227, and Item 227A, is flammable. Keep container closed; keep away from ignition sources (sparks, flames, heat). Bond and ground metal containers during transfer to prevent ignition through static discharge. Keep off eyes, skin, and clothes. May irritate the eyes and skin. May cause allergic skin reactions in sensitive individuals. Avoid breathing vapor. Inhalation may cause headache, dizziness, and respiratory irritation. Prolonged exposure may cause "asthmatic-type" reactions. Certain individuals may develop "sensitization", causing them to react adversely to vapor levels well below established exposure limits. Long-term overexposure to some solvents has been linked to brain and nervous system damage. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, long sleeve and long leg clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Polyurethane paint, Item 228, is flammable. Do not use near open flames, welding areas, or on hot surfaces. Bond/ground metal containers during mixing or transfer to prevent ignition through static discharge. Do not eat, drink, or smoke where paints are being mixed, handled, or cleaned up. Contains isocyanate compounds. Certain individuals may develop isocyanate sensitization, which will cause them to experience an asthmatic-type reaction at levels well below established limits. Avoid prolonged skin contact. After use, wash hands before eating or smoking. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Long-term overexposure may cause allergic skin response, and delayed effects involving the blood, gastrointestinal, nervous and reproductive systems. May contain chromates, which have been found to cause cancer. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, long sleeve and long leg clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Paint remover, Item 230, may severely irritate or burn the eyes and skin. Keep paint remover off skin, eyes, and clothes. May be absorbed through the skin in potentially dangerous levels that may affect inner organs. Avoid breathing vapor. Inhalation may cause headache, dizziness, and nausea. Long-term overexposure may injure the lungs, pancreas, liver, and kidney. Contains components found to cause cancer. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, neoprene gloves, full-body protective clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits. Gloves should be changed frequently.

WARNING

Paint remover, Item 231, is combustible. Use paint remover only with adequate ventilation. Do not use it near welding area, near open flame, or on hot surfaces. Corrosive: Contact may cause severe burns on exposed tissue. If spilled on clothing, change immediately; wash clothes before wearing again. Do not breathe vapors. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Frequent replacement of gloves during stripping operations may be necessary. May contain chemicals that may be absorbed through the skin in potentially dangerous amounts that could affect inner organ systems. Chronic overexposure to certain chemicals may cause liver and kidney damage, and cancer. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles and face shield to protect the skin from contact, approved neoprene or polyvinyl gloves, apron, boots, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Parting compound, Item 233, is extremely flammable. Do not use near open flames, near welding areas, or on hot surfaces. Do not smoke when using it and do not use it where others are smoking. Bond/ground metal containers to prevent ignition of product vapors through static discharge. Dispose of liquid soaked rags in approved metal safety container. Avoid contact. Direct contact may severely irritate or burn the eyes. May irritate the skin, particularly upon prolonged or repeated contact. Inhaling product vapors may cause headache, dizziness, nausea, and irregular heart beat. Long-term overexposure without proper protective equipment may cause liver, kidney, and nervous system damage, and blood defects. FIRST AID: If product contacts eyes, flush eyes thoroughly with lukewarm water for 15 minutes; seek immediate medical attention. CONTAINS: Methylene Chloride (found to cause cancer), Propane, Isobutane. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles or face shield, approved gloves, protective clothing, NIOSH/MSHA-approved respiratory protection (air-supplied), if product vapor levels exceed established exposure limits.

WARNING

Petrolatum, Item 234, may irritate the eyes and skin if prolonged or repeated contact occurs. Use in a well-ventilated area. Avoid eye and skin contact. Do not breathe vapors. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, full-body protective clothing, NIOSH/MSHA-approved respirator, if oil mists exceed established exposure limits.

WARNING

Polyurethane coating, Item 240, is flammable. Keep container closed; keep away from ignition sources (sparks, flames, heat). Bond and ground metal containers during transfer to prevent ignition through static discharge. Keep off eyes, skin, and clothes. May irritate the eyes and skin. May cause allergic skin reactions in sensitive individuals. Avoid breathing vapor. Inhalation may cause headache, dizziness, and respiratory irritation. Prolonged exposure may cause "asthmatic-type" reactions. Certain individuals may develop "sensitization", causing them to react adversely to vapor levels well below established exposure limits. Long-term overexposure to some solvents has been linked to brain and nervous system damage. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, long sleeve and long leg clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Polyurethane coating, Item 240A, is flammable. Keep polyurethane coating away from potential sources of ignition, including heat, spark, and open flame. Store containers in a cool, dry area when not in use. Bond and ground metal containers to prevent ignition through static electrical discharge. Avoid eye and skin contact. Direct contact may cause moderate to severe irritation, particularly with prolonged or repeated use. Certain components may be absorbed through the skin in potentially dangerous levels that may affect inner organs. May cause skin sensitization, whereby exposure to minimal amounts of product result in allergic skin reactions. Avoid breathing vapors or mists. Inhalation may cause headache, dizziness, nausea and respiratory irritation. May trigger immediate or delayed "asthmatic-type" reactions. In case of contact, flush affected area immediately with plenty of water. Seek medical attention if irritation persists. Seek fresh air and medical attention if allergic reactions occur. Product may contain chemicals that may damage internal "target" organs upon long-term overexposure without proper personal protective equipment. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: approved gloves; safety goggles, full-body protective clothing; NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Polyurethane coating, Item 241, is flammable. Do not use near open flames, welding areas, or on hot surfaces. Bond/ground metal containers during mixing or transfer to prevent ignition through static discharge. Do not eat, drink, or smoke where paints are being mixed, handled, or cleaned up. Contains isocyanate compounds. Certain individuals may develop isocyanate sensitization, which will cause them to experience an asthmatic-type reaction at levels well below established limits. Avoid prolonged skin contact. After use, wash hands before eating or smoking. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Long-term overexposure may cause allergic skin response, and delayed effects involving the blood, gastrointestinal, nervous and reproductive systems. May contain chromates, which have been found to cause cancer. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved protective gloves, long sleeve and long leg clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Primer, Item 254, is flammable. Keep container closed and store in a cool, dry place. Use only in well-ventilated areas. Bond and ground metal containers during use and transfer to prevent ignition through static discharge. Keep clear of all sources of ignition or sparks during application and curing. Breathing vapors may cause headaches, dizziness, confusion, and respiratory irritation. Long-term overexposure without protective equipment may cause liver and kidney damage, and may trigger "asthmatic-type" respiratory responses and allergic skin reactions. May cause skin and eye irritation. If skin or eye contact occurs, wash immediately with water for at least 15 minutes. If ingested, do not induce vomiting. Seek immediate medical attention. Wash hands thoroughly with soap and water after use. Launder contaminated clothing before reuse. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves, and good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Primer, Item 257 and Item 258, is flammable. Do not use near open flames, near welding areas, or on hot surfaces. Do not eat or smoke when using it, and do not use it where others are smoking. Contact with liquid or vapor can cause skin or eye irritation, dizziness, and headache. Prolonged overexposure can result in kidney and liver damage. After prolonged skin contact, wash contacted area with soap and water. Flush eyes for 15 minutes, seek medical attention. If vapors cause dizziness, go to fresh air. If irritation persists, get medical attention. Dispose of liquid-soaked rags in approved metal container. Contains zinc chromates which are listed as carcinogens under OSHA. Follow approved toxic waste disposal procedures. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: when handling small quantities (less than 1 gallon), wear eye protection, approved gloves, and apron; when handling large quantities of liquid, (greater than a gallon), at unexhausted workbench, wear approved goggles, gloves, apron, long sleeves, respirator.

WARNING

Primer coating, Item 259, is flammable - Keep away from ignition sources (heat, sparks, flame) and strong oxidizers. Store out of direct sunlight in cool, dry, well-ventilated non-confined areas; ventilation systems must be explosion-proof and grounded. Do not store above 120°F (49°C). Closed containers may explode when exposed to extreme heat. If cans rupture, extinguish all ignition sources and ventilate. May cause severe irritation to eyes. Prolonged contact without proper skin protection may cause pain, numbness and burns. Prolonged inhalation may cause respiratory irritation, temporary nervous system impairment. Overexposure may cause headache, dizziness, giddiness, and irritability. Ingestion may cause lung damage/death. Digestive system irritation with nausea, vomiting, nervous system impairment. In case of eye contact flush with large volumes of water for at least 15 minutes, obtain medical attention. In case of skin contact flush area thoroughly with soap and water. If irritation persists seek medical attention. If inhaled, remove to fresh air, obtain medical attention. If ingested, do not induce vomiting, obtain immediate medical attention. Wash with soap and water after handling product. Launder soiled clothing and rags after use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles/face shields, full-body protective clothing, approved gloves, good ventilation, NIOSH/MSHA-approved respirator, if airborne levels exceed established exposure limits.

WARNING

Sealing compound, Item 272, may irritate skin or produce allergic skin reactions and "asthmatic-type" respiratory responses in susceptible individuals if prolonged or repeated contact occurs; effects may be delayed. May be absorbed through the skin in levels that may affect inner organ systems. Direct eye contact may cause severe irritation. In case of skin contact, wash area thoroughly with soap and water; if eye contact occurs, flush immediately with water for at least 15 minutes. Seek immediate medical attention. Use with proper ventilation. Vapors may irritate the nose and throat. Long-term use without protective equipment may cause liver and kidney damage, blood changes, and reproductive disorders. Keep container closed in a cool, dry place. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, protective clothing to prevent skin contact, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Sealing compound, Item 273 and Item 274, is combustible. Keep container closed and store in a cool, dry place. Use only in well-ventilated areas. Keep clear of all sources of ignition or sparks during application. Breathing vapors may cause headaches, dizziness, and nausea; avoid prolonged inhalation of vapors. May cause skin and eye irritation. If skin or eye contact occurs, wash immediately with water for at least 15 minutes. If ingested, do not induce vomiting. Seek immediate medical attention. Wash hands thoroughly with soap and water after use. Launder contaminated clothing before reuse. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Sealing compound, Item 275, may irritate the eyes and skin. Keep container closed; keep sparks, flames, and heat away. Keep sealing compound off skin, eyes, and clothes. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles or safety glasses, impervious gloves, good ventilation.

WARNING

Sealing compound, Item 276, Item 277, Item 278, Item 279, Item 280, Item 281, Item 282, and Item 283, is combustible - do not use near open flames, near welding areas, or on hot surfaces. Keep containers closed when not in use. Avoid contact with eyes and skin. Liquid may be irritating to eyes. Repeated or prolonged contact with skin may result in dermatitis. Inhalation of product vapors may cause headache, dizziness, nausea, and respiratory irritation. Vapor may be irritating to eyes. If ingested, do not induce vomiting; seek medical attention. If eye contact occurs, flush them in a continuous stream of water for at least fifteen minutes. Seek medical attention. In case of skin contact, wipe affected areas with water and wash with soap and water. If irritation persists, seek medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles, approved gloves.

WARNING

Sealing compound, Item 284, is flammable. Do not use near open flames, welding areas, or on hot surfaces. Do not smoke when using or where others are smoking. Avoid skin contact. May irritate the eyes and skin. Breathing vapor may cause headache, dizziness, and nausea. Use respirator in confined areas. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles or safety glasses, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Sealing compound, Item 285 and Item 286, may irritate the eyes and skin if prolonged or repeated contact occurs. Avoid skin and eye contact with thread locking sealant. If any liquid contacts skin or eyes, immediately flush affected area thoroughly with water. Wash hands thoroughly after handling. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, protective rubber or plastic gloves.

WARNING

Sealing compound, Item 287 and Item 288, can irritate skin and cause burns. Avoid contact with skin, eyes, and clothing. In case of contact, immediately flush skin or eyes with water for at least 15 minutes. Get medical attention for eyes. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information.

WARNING

Sealing compound, Item 290 and Item 291, is a two part sealing compound mixture consisting of a base compound and an accelerant. The following warning summarizes health and physical hazards of the product as a mixture. Minimize contact. Prolonged or repeated contact may irritate the eyes and skin. Liquid or vapor may irritate the eyes. Inhaling product vapors may cause headache, dizziness, nausea, and narcosis. Product contains components that may be absorbed through the skin, thus contributing to the overall effects of overexposure to the product. Prolonged overexposure to product without proper personal protective equipment may cause muscular weakness, insomnia, and nervous system damage. Flush eyes thoroughly with water for at least 15 minutes. Wipe excess product from skin, then wash thoroughly with soap and water. Seek medical attention if irritation persists. If overcome by product vapor or mist, seek fresh air and possible medical assistance. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves.

WARNING

Sealing compound, Item 292, can irritate skin and cause burns. Avoid contact with skin, eyes, and clothing. In case of contact, immediately flush skin or eyes with water for at least 15 minutes. Get medical attention for eyes. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information.

WARNING

Sealing compound, Item 293A, may irritate the eyes and skin if prolonged or repeated contact occurs. Avoid skin and eye contact with thread locking sealant. If any liquid contacts skin or eyes, immediately flush affected area thoroughly with water. Wash hands thoroughly after handling. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, protective rubber or plastic gloves.

WARNING

Sealing compound, Item 295, is combustible. Keep sealing compound away from potential sources of ignition, such as heat, spark, and flame. Keep containers securely closed when not in use. Prolonged or repeated contact may irritate the skin. Liquid or vapor may irritate the eyes. Inhaling product vapors may cause headache, dizziness, nausea, and respiratory irritation. Product contains components that may be absorbed through the skin, thus contributing to the overall effects of overexposure to the product. Prolonged overexposure to dust of cured product without proper personal protective equipment may cause cancer. Flush eyes thoroughly with water for at least 15 minutes. If ingested, provide water and seek medical attention. Wipe excess product from skin, then wash thoroughly with soap and water. Seek medical attention if irritation persists. If overcome by product vapor or mist, seek fresh air and possible medical assistance. Launder soiled clothing after use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, full-body protective clothing, NIOSH/MSHA-approved respiratory protection, if airborne levels exceed established exposure limits.

WARNING

Sealing compound, Item 295A, Parts A and B, are flammable. Part A - May irritate the eyes and skin. May cause allergic skin reaction in certain individuals. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Long-term overexposure may affect the heart, liver, kidney, and blood. Part B - May irritate the eyes and skin. May cause allergic skin reaction. May be absorbed through the skin in potentially dangerous amounts that may affect inner organ systems. Breathing vapor may cause headache, dizziness, nausea, respiratory irritation. Long-term overexposure may affect the liver and kidney. Mixture Part A & B - Flammable - Keep away from ignition sources (heat, flame). Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, impervious gloves, full-body protective clothing, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Sealing compound, Item 296 and Item 296A, is a skin and eye irritant. Adequate ventilation required during curing. Prolonged or repeated exposure may irritate the eyes and skin. If skin or eye contact occurs, wash immediately with water for at least 15 minutes. If ingested, seek immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety glasses or goggles, approved gloves.

WARNING

Sealing compound, Item 297, is flammable. Keep product away from potential ignition sources such as heat, spark, and flame. Bond/ground metal containers. Keep container closed. Direct contact may cause mild skin irritation and moderate to severe eye irritation. Inhalation of product vapor may cause headache, dizziness, and impaired motor coordination. Long-term overexposure without proper protective equipment may damage the liver. CAUTION: Product safety and health hazards may vary according to manufacturer and manufacturer product code, since different compositions can conform to the specification. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: splashproof goggles or safety glasses, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Sealing compound, Item 301A, is extremely flammable. Keep away from ignition sources (heat, sparks, flame) and strong oxidizers. Keep all containers closed in a cool, dry place when not in use. Use only in well-ventilated non-confined areas; ventilation systems must be explosion-proof and grounded. May irritate the eyes and skin. Prolonged contact without proper skin protection can cause dermatitis. Prolonged inhalation may cause headaches, dizziness, respiratory irritation, drowsiness and nausea. In case of eye contact, flush with water for at least 15 minutes and obtain medical attention. In case of skin contact, flush area thoroughly with soap and water. If irritation persists seek medical attention. If inhaled, remove to fresh air, obtain immediate medical attention. If ingested, obtain immediate medical attention. Wash with soap and water after handling product. Launder soiled clothing and rags after use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles/face-shields, approved gloves, full-body protective clothing, good ventilation, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Sealing compound, Item 302A, is a two component product consisting of an epoxy resin, Part A and hardener, Part B. The precautions for each should be observed when separate or mixed. Do not mix batches greater than 1 pound to prevent excessive heat build-up with the release of toxic gases. Part A - Contact: Direct contact with eyes causes irritation. Skin contact may cause irritation and allergic skin reaction. Harmful if inhaled. Harmful if swallowed. In case of eye contact, flush with water; obtain medical attention if irritation persists. In case of skin contact, wash with soap and water and obtain medical attention if irritation persists. If swallowed, dilute by giving two glasses of water, obtain medical attention. If inhaled, remove from area to fresh air get immediate medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, protective clothing, good ventilation, NIOSH/MSHA-approved respirator. Part B - Product causes severe eye and skin burns. Contact: In case of eye contact, flush with water for 15 minutes while holding lids open and obtain medical attention. In case of skin contact, wash area with soap and water, remove contaminated clothing and obtain medical attention. If swallowed, dilute by giving two glasses of water, obtain medical attention. In case of inhalation, remove to fresh air and obtain medical attention. Wash with soap and water after handling product. Launder soiled clothing and rags after use. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: safety goggles, approved gloves, protective clothing, good ventilation, NIOSH/MSHA-approved respirator.

WARNING

Sealing compound, Item 305, and Item 306, is combustible - do not use near open flames, near welding areas, or on hot surfaces. Keep containers closed when not in use. Avoid contact with eyes and skin. Liquid may be irritating to eyes. Repeated or prolonged contact with skin may result in dermatitis. Inhalation of product vapors may cause headache, dizziness, nausea, and respiratory irritation. Vapor may be irritating to eyes. If ingested, do not induce vomiting; seek medical attention. If eye contact occurs, flush them in a continuous stream of water for at least fifteen minutes. Seek medical attention. In case of skin contact, wipe affected areas with water and wash with soap and water. If irritation persists, seek medical attention. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles, approved gloves.

WARNING

Silicone compound, Item 309, may irritate the eyes, skin, nose, and throat if prolonged or repeated contact occurs. Keep sparks, flames, and heat away. Keep grease off skin, eyes, and clothes. Do not breathe vapors. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles or safety glasses, protective gloves, other protective clothing as needed, good ventilation.

WARNING

Toluene, Item 339, is flammable. Do not use solution near welding areas, near open flames, or on hot surfaces. Do not smoke, and do not use it where others are smoking. Dispose of liquid-soaked rags in approved metal container. Store solvent in approved and grounded metal safety container. Bond/ground metal containers during transfer to prevent ignition from static discharge. May severely irritate the eyes on contact. May irritate the skin. Repeated exposure can cause dermatitis, and temporary tingling sensation in fingers. If any liquid contacts skin, flush affected area thoroughly with water. Immediately remove solvent-saturated clothing. Breathing vapor may cause headache, dizziness, nausea. If these symptoms occur, seek fresh air. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical goggles, approved (PVA) polyvinyl alcohol gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Trichloroethane, Item 341, may irritate the eyes and skin if prolonged or repeated contact occurs. Avoid contact. Skin irritation is heightened by liquid trapped against the skin from contaminated clothing. May be absorbed through the skin in levels that may affect inner organs. Long-term exposure without proper hand protection may result in dermatitis. After prolonged skin contact, wash affected area with soap and water. Remove contaminated clothing. Get medical attention. Avoid inhaling vapor. Breathing vapor may cause narcotic effects (headache, dizziness, and nausea); severe acute exposure may cause heart damage. If vapors cause irritation, go to fresh air. Dispose of liquid-soaked rags in approved metal container. No smoking in area. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: chemical splashproof goggles, approved gloves, full-body impervious clothing, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

WARNING

Trichloroethane, Item 342, may irritate the eyes and skin if prolonged or repeated contact occurs and may be heightened by liquid trapped against the skin from contaminated clothing. After prolonged skin contact, wash contacted area with soap and water. Remove contaminated clothing. Get medical attention for severe skin and eye irritation. May be absorbed through the skin in levels that may affect inner organ systems. Breathing vapor may cause narcotic effects (headache, dizziness, and nausea) heart damage (following severe acute exposure). If these symptoms occur, seek fresh air. Dispose of liquid-soaked rags in approved metal container. No eating, drinking, or smoking in area. Refer to the product Material Safety Data Sheet (MSDS) for specific component and associated health hazard information. Protection: goggles, approved gloves, NIOSH/MSHA-approved respirator, if vapors exceed established exposure limits.

D-1.4 Explanation of Columns.

- a. Column (1) - Item Number.

NOTE

Expendable supplies and materials with no National Stock Number (NSN) listed may be purchased from the manufacturer indicated by the five-digit code.

- b. Column (2) - National Stock Number. This is the NSN assigned to the item; use it to request or requisition the item.
- c. Column (3) - Description. Indicates the Federal item name and, if required, a description to identify the item. The second line for each item indicates the part number. The last line for each item indicates the Commercial and Government Entity (CAGE) in parentheses, if applicable.
- d. Column (4) - Unit of Measure (U/M) / Unit of Issue (U/I). Indicates the measure used in performing the actual maintenance function. This measure is expressed by a two- or three-character alphabetical abbreviation (e.g., ea, lb, pr, cyl, lbs). If the unit of measure differs from the unit of issue, requisition the lowest unit of issue that will satisfy your requirements.

SECTION II EXPENDABLE AND DURABLE ITEMS LIST

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
1	9320-01-247-7735	Abrasion Resistant Tape SS9538-002 (CAGE 78286)	rl
1A	5350-00-246-0331	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 40- Grit (CAGE 80204)	sh
2	5350-00-192-5047	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 80- Grit (CAGE 80204)	sh
3	5350-00-161-9066	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 100- Grit (CAGE 80204)	sh
4	5350-00-192-5050	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 150- Grit (CAGE 80204)	sh
5	5350-00-192-9316	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 220- Grit (CAGE 80204)	sh
6	5350-00-161-9715	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 240- Grit (CAGE 80204)	sh
7	5350-00-229-3081	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 280- Grit (CAGE 80204)	sh
8	5350-00-246-0330	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 320- Grit (CAGE 80204)	sh
9	5350-00-271-5950	Abrasive Cloth ANSI B74.18, 30-, 40-, 60-, 80-, 100-, 120-Grit (Assorted Pack) (CAGE 80204)	sh

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
9A	5350-00-856-5700	Abrasive Cloth ANSI B74.18, Type 1, Class 1, 400- Grit (CAGE 80204)	sh
10	5350-00-221-0872	Abrasive Cloth ANSI B74.18, No. 320 (CAGE 80204)	sh
11	5350-00-584-4660	Abrasive Cloth ANSI B74.18, No. 80 (CAGE 80204)	ea
12	5350-00-584-4653	Abrasive Cloth ANSI B74.18, No. 180 (CAGE 80204)	ea
13	5350-00-584-4654	Abrasive Cloth ANSI B74.18, No. 220 (CAGE 80204)	ea
14	5350-00-967-5089	Abrasive Mat A-A-58054, 280 - 400-Grit (CAGE 58536)	sh
14A	3460-01-289-1062	Abrasive Pad Scotch-Brite 7448 (CAGE 27293)	sh
15	5350-00-721-8115	Abrasive Paper ANSI B74.18, 120-Grit (CAGE 80204)	sh
16	5350-00-721-8116	Abrasive Paper ANSI B74.18, 150-Grit (CAGE 80204)	sh
17	5350-00-224-7209	Abrasive Paper ANSI B74.18, 220-Grit (CAGE 80204)	sh
17A	5350-00-224-7207	Abrasive Paper ANSI B74.18, 240-Grit (CAGE 80204)	sh
18	5350-00-224-7202	Abrasive Paper ANSI B74.18, 360-Grit (CAGE 80204)	sh
19	5350-00-221-0882	Abrasive Paper ANSI B74.18, 120-Grit (CAGE 80204)	sh

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
20	5350-00-186-8819	Abrasive Paper ANSI B74.18, 220-Grit (CAGE 80204)	sh
21		Deleted (Refer to Item 1)	
22	5345-01-193-6709	Abrasive Wheel ST-90-ALO-382 (CAGE 08659)	ea
23		Deleted (Refer to Item 25A)	
*24	6810-00-275-1215	Acetic Acid A-A-55829 (CAGE 58536)	bt
*25	6810-00-184-4796	Acetone ASTM D 329 (CAGE 81346)	5 gal
*25A	6850-01-326-1607	Adhesion Promoter No. 86A (CAGE 52152)	pt
26		Deleted (Refer to Item 182B)	
27		Deleted (Refer to Item 182C)	
28		Deleted (Refer to Item 30)	
29		Deleted (Refer to Item 66H)	
*30	8040-01-419-8062	Adhesive Dapcotac 3300 (CAGE 58093)	kt
*31	8040-00-839-4919	Adhesive EC1099 (CAGE 76381)	qt
*32	8040-01-163-3481	Adhesive EA9309.3NA (CAGE 04347)	kt
33		Deleted (Refer to Item 32)	
*33A	8040-01-446-7381	Adhesive EA9359.3 (CAGE 05972)	kt
*34	8040-00-016-8662	Adhesive EA 934NA (CAGE 33564)	kt

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*35	8040-00-463-7042	Adhesive EA 956 (CAGE 33564)	kt
*36	8040-00-858-9799	Adhesive EC1099 (CAGE 76381)	kt
*37	8040-00-273-8717 8040-00-165-8614	Adhesive 1300L (CAGE 1A9T3)	pt qt
*38	8040-00-181-7548 8040-00-123-6954 8040-00-959-1854	Adhesive EC1751 A/B (CAGE 52152)	2 oz pt qt
*39	8040-00-152-0063	Adhesive EC2126 (CAGE 94960)	2 oz
*40	8040-00-180-6161	Adhesive EC2214 (CAGE 04963)	5 gal
*41	8040-00-145-0432	Adhesive EC2216 (CAGE 04963)	kt
*42	8040-00-390-7959	Adhesive EC847 (CAGE 04963)	qt
42A	8040-00-185-5631	Adhesive FM37 (CAGE 07542)	bx
42B		Adhesive KS0004 (KE4238/HD3475) (CAGE 04347)	kt
43	8040-00-849-5196	Adhesive MIL-A-81236 (CAGE 81349)	qt
43A	8040-00-530-4820	Adhesive 7526F (CAGE 65313)	pt
*44	8040-01-284-3984	Adhesive 380 (CAGE 05972)	oz

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*44A	8030-00-180-6222	Adhesive 60931 (CAGE 05972)	bt
44B	8040-01-090-9320	Adhesive 42061 (Loctite 420) (CAGE 05972)	pt
45	8040-01-339-6818	Adhesive Loctite Primer 704 (CAGE 05972)	gal
*46	8040-00-515-2250	Adhesive MMM-A-1617 (CAGE 81348)	qt
*47	8040-00-714-8223	Adhesive MMM-A-121 (CAGE 81348)	tu
*48	8040-00-152-0017 8040-00-152-0028	Adhesive MMM-A-132, Type 1, Class 3 (CAGE 81348)	2.5 oz 6 oz
*49	8040-00-266-7429	Adhesive Pliobond, No. 20 (CAGE 34897)	pt
50		Deleted (Refer to Item 105A)	
51	8040-00-526-1910	Adhesive PS18 (CAGE 95696)	kt
*52	8030-00-225-4548	Adhesive RTV102 (CAGE 01139)	ca
*53	8040-00-902-3871	Adhesive RTV106 (CAGE 01139)	kt
*54	8040-00-522-3429	Adhesive RTV118 (CAGE 01139)	kt
*55	8040-01-481-1516	Adhesive RTV133 (CAGE 01139)	ca

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*56	8040-00-118-2695	Adhesive RTV162 (CAGE 01139)	kt
*57	8040-00-144-9774 8040-00-145-0020	Adhesive RTV3145 (CAGE 71984)	10.3 oz 3 oz
57A		Deleted (Refer to Item 66E)	
58	8040-01-146-2656	Adhesive SL-5 (CAGE 15674)	200 yd
*59	8040-01-203-1443	Adhesive A-A-3097, Type 1, Class 2 (CAGE 58536)	oz
*60	8040-01-160-9551	Adhesive Versilok 204/Accelerator 4 (CAGE 30676)	3 oz
61		Deleted (Refer to Item 37)	
62		Deleted (Refer to Item 271A)	
63	8040-01-180-4988	Adhesive 416 (CAGE 05972)	bt
*64	8040-01-170-3599	Adhesive Versilok 506/Accelerator 4 (CAGE 30676)	3 oz
65	8040-01-129-2559	Adhesive 82C18 (CAGE 56221)	pt
*66	8040-01-355-6366	Adhesive EA 9203 (CAGE 33564)	gal
66A	8040-00-148-9849	Adhesive Epocast 50A (CAGE 99384)	kt
66B	8040-00-843-7873	Adhesive Epon 815 (CAGE 86961)	kt
66C	8040-01-046-2944	Adhesive 1210A/B (CAGE 99384)	kt

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
66D	8030-00-086-1505 8040-00-822-6430	Adhesive Epon 828 (CAGE 54527)	pt qt
*66E	8040-01-010-8758 8040-00-843-0802	Adhesive, Clear RTV732 (CAGE 71984)	10.3 oz 3 oz
66F		Adhesive Magnobond 6380 (CAGE 22121)	kt
66G	8040-00-084-4338	Adhesive Hardener 9615A (CAGE 02684)	kt
66H	8040-01-151-4258	Adhesive Primer Chemlok 7701 (CAGE 30676)	gal
*67	8040-00-065-6578	Adhesive Primer EC 1945 A/B (CAGE 04963)	qt
*68	8040-01-192-2491	Adhesive Primer EC-3917 (CAGE 04963)	qt
69	7930-00-267-5588	Aircraft Wax MIL-W-18723 (CAGE 81349)	gal
*70	6810-00-577-4889	Alcohol, Denatured 27 CFR 21.35 (CAGE 0MUS3)	qt
71	6810-00-264-5906	Alcohol, Ethyl A-A-59282 (CAGE 58536)	pt
*72	6810-00-983-8551 6810-00-286-5435	Alcohol, Isopropyl TT-I-735 (CAGE 81348)	32 oz gal
*73	8030-00-779-4699	Alodine, Chemical MIL-C-5541, Kit-120 (CAGE 84063)	kt
73A	5920-01-520-6122	Aluminum Mesh Screen SS9615 (CAGE 78286)	sh

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*74	8030-00-597-5367	Antiseize Compound MIL-A-907 (CAGE 81439)	2.5 lbs
*75	8030-01-044-5034	Antiseize Compound AMS 2518 (CAGE 81343)	lb
*76	8030-00-087-8630	Antiseize Compound MIL-PRF-83483 (CAGE 81349)	lb
77	8030-00-889-5285	Antiseize Compound 8001 (CAGE 78976)	tu
78	6515-00-303-8250	Applicator GG-A-616 (CAGE 81348)	pkg
*79	9150-00-159-5012	Assembly Fluid Assembly Fluid 1 (CAGE 56385)	tu
80	8135-00-282-0565	Barrier Material MIL-PRF-131 (CAGE 81349)	rl
80A	1680-01-337-2890	Breather Material Airweave N-10 (CAGE 53912)	rl
81	8315-01-244-7225	Braid, Textile S8999-7 (CAGE 59364)	ea
82	5977-01-101-9857	Brush 287511 (CAGE 99932)	ea
83	7920-00-205-2401	Brush MIL-B-43871 (CAGE 81349)	ea
84	7920-00-514-2417	Brush, Acid A-A-289 (CAGE 58536)	ea
85	8070-00-224-8022	Brush, Artist H-B-118 (CAGE 81348)	ea

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
86	8020-00-263-3866	Brush, Paint H-B-420 (CAGE 81348)	6 ea
87	8530-00-290-2920	Brush, Tooth A-A-123 (CAGE 58536)	bx
87A	5999-00-280-3499	Cap, Electrical MS25274-2 (CAGE 96906)	10 ea
88		Deleted (Refer to Item 160C)	
89		Deleted (Refer to Item 64)	
90	8305-00-267-3015	Cheesecloth CCC-C-440 (CAGE 81348)	yd
*91	6810-00-264-6517	Chromium Trioxide, Technical A-A-55827 (CAGE 58536)	5 lb cn
*92	6850-00-181-7280	Cleaning Compound Actusol T776 (CAGE 72008)	55 gal
93	6850-00-527-2426	Cleaning Compound AMS 1640 (CAGE 81343)	5 gal
*94	6850-01-390-7811	Cleaning Compound MIL-PRF-87937 (CAGE 81349)	5 gal
95	6850-00-209-7947	Cleaning Compound O-C-1889 (CAGE 81348)	gal
96	6850-01-215-4776	Cleaning Compound Spray "Clean" (CAGE 65290)	gal
97	6850-00-181-7115	Cleaning Compound T-WD 602 (CAGE 88559)	5 gal
97A	7930-01-306-8369	Cleaning Compound 13005 (CAGE 1Z575)	bt

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
98	6850-00-224-6663	Cleaning Compound, Solvent MIL-PRF-372 (CAGE 81349)	gal
*99	6850-00-105-3084	Cleaning Compound, Solvent CRC 2016 (CAGE Z2542)	cn
*99A	6850-01-371-8048 6850-01-375-5554 6850-01-375-5553 6850-01-375-5555	Cleaning Compound, Solvent Electron (CAGE 0WU71)	15 oz cn gal 6 gal 55 gal
*99B	6850-01-411-8815 6850-01-412-0026 6850-01-412-0028	Cleaning Compound, Solvent Positron (CAGE 0WU71)	gal 6 gal 55 gal
*99C	6850-01-443-9519	Cleaning Compound, Solvent Shopmaster RC (CAGE 0YG51)	qt
*100	6850-01-248-9828	Cleaning Compound, Solvent MIL-PRF-85570 (CAGE 81349)	cn
*100A	6850-00-264-9038	Cleaning Compound, Solvent MIL-PRF-680 (CAGE 81348)	5 gal
101		Deleted (Refer to Item 97A)	
102	7920-00-044-9281	Cloth, Cleaning A-A-59323 (CAGE 58536)	bx
102A	7920-00-165-7195	Cloth, Cleaning A-A-59323 (CAGE 58536)	bx
102B	8305-01-100-9061	Cloth, Coated Fluorpeel No. 3 (CAGE 07512)	rl
103	8305-00-641-5603	Cloth, Coated MIL-C-8068 (CAGE 81349)	yd
104	8305-01-102-7912	Cloth, Nylon MIL-C-20696, Type 1, Class 3 (CAGE 81349)	yd

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
105	8305-00-082-6135	Cloth, Satin MIL-C-9084 (CAGE 81349)	yd
105A	8030-00-575-5985	Coating Compound PR-420 (CAGE 83574)	pt
*106	8030-00-082-2425	Coating Compound MIL-C-8514 (CAGE 81349)	kt
106A	6850-00-616-9019	Coating Compound, Black Oxide MIL-C-13924 (CAGE 81349)	50 lbs
106B	8010-01-054-7229	Coating Kit, Rain Erosion Resisting M331/M201 (CAGE 30676)	kt
107		Deleted (Refer to Item 209A)	
*108	6850-00-656-1292	Corrosion Compound MIL-C-10578 (CAGE 81349)	5 gal
*108A	8030-01-386-3877	Corrosion Preventive Compound Fluid Film Liquid A (CAGE 0RA06)	gal
*108B	8030-01-381-7311	Corrosion Preventive Compound Fluid Film Liquid AR (CAGE 0RA06)	gal
*108C	8030-01-512-2416	Corrosion Preventive Compound AMS-M-3171, Type VI (CAGE 81343)	kt
*109	8030-00-244-1297	Corrosion Preventive Compound MIL-C-16173, Class 1, Grade 2 (CAGE 81349)	gal
*110	8030-00-062-6950 8030-00-231-2345 8030-00-244-1299	Corrosion Preventive Compound MIL-C-16173, Class 1, Grade 1 (CAGE 81349)	qt gal 5 gal
*111	8030-00-837-6557 8030-00-244-1296	Corrosion Preventive Compound MIL-C-16173, Class 1, Grade 3 (CAGE 81349)	pt gal

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*112	8030-00-062-5866 8030-00-526-1605	Corrosion Preventive Compound MIL-C-16173, Class 1, Grade 4 (CAGE 81349)	gal 5 gal
*113	8030-01-041-1596	Corrosion Preventive Compound MIL-C-85054, Type 1 (CAGE 81349)	pt
113A	8030-01-347-0979	Corrosion Preventive Compound MIL-DTL-85054, Type 1, Class 134A (CAGE 81349)	cn
*114	8030-00-938-1947	Corrosion Preventive Compound MIL-C-81309, Type 2, Class 2 (CAGE 81349)	16 oz
*115	8030-00-546-8637	Corrosion Preventive Compound MIL-C-81309, Type 3, Class 2 (CAGE 81349)	16 oz
*115A	8030-00-285-1570	Corrosion Preventive Compound MIL-C-11796, Class 3 (CAGE 81349)	35 lbs
*116	6850-00-926-5298	Corrosion Removing Compound MIL-C-10578 (CAGE 81349)	15 gal
116A	6850-00-550-5565	Corrosion Removing Compound A-A-59260 (CAGE 58536)	500 lbs
*117	8030-00-065-0957	Corrosion Resistant Coating MIL-C-5541, Class 3, Alodine 600 (CAGE 81439)	qt
*118	8030-00-142-9272 8030-00-811-3723 8030-00-823-8039	Corrosion Resistant Coating MIL-C-5541, Class 1A, Alodine 1200S (CAGE 81349)	pt bt gal
*118A	8030-01-018-2838	Corrosion Resistant Coating MIL-C-5541 (CAGE 81349)	bt
119	8320-01-362-5829	Cotton Swabs 6003-0019 (CAGE 17794)	pkg
120	8030-00-839-1442	Curing Agent (CAGE 17794)	cn

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*121	9150-00-269-8246	Damping Fluid DC200-100SCTK (CAGE 71984)	cn
121A	6810-00-995-4804	Diethylenetriamine A-A-59162 (CAGE 58536)	pt
121B		Deleted (Refer to Item 99C)	
122	7930-00-764-5066	Dishwashing Compound P-D-410 (CAGE 81348)	qt
123	6810-00-682-6867	Distilled Water ASTM D 1193 (CAGE 81346)	gal
123A	9150-01-528-5624	Dry Lubricant MS-122AD (CAGE 18598)	16 oz
*124	6850-00-274-5421 6850-00-285-8012	Dry-Cleaning Solvent MIL-PRF-680, Type 2 (CAGE 81348)	5 gal 55 gal
*125	6830-01-011-7848	Dry Ice BB-C-104 (CAGE 81348)	10 lb
125A	8010-01-030-7250	Epoxy Coating 17564-4B2 (CAGE 17564)	kt
126		Deleted (Refer to Item 221B)	
*126A	8010-01-419-1142	Epoxy Coating Kit MIL-PRF-22750 (CAGE 81349)	kt
126B	8010-01-314-2526	Epoxy Coating Kit MIL-PRF-23377 (CAGE 81349)	kt
127		Deleted (Refer to Item 302A)	
128		Deleted (Refer to Item 182A)	
129		Deleted (Refer to Item 66A)	
130		Deleted (Refer to Item 66B)	
131		Deleted (Refer to Item 302B)	

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
132		Deleted (Refer to Item 66C)	
133		Deleted (Refer to Item 66G)	
133A		Deleted (Refer to Item 66D)	
*134	8040-00-061-8303	Epoxy Patch Kit EPK 0151 (CAGE 04347)	kt
*135	8010-00-082-2450	Epoxy Primer Coating Kit MIL-PRF-23377 (CAGE 81349)	kt
135A	8010-00-264-8866	Epoxy Primer Coating Kit MIL-P-53030 (CAGE 81349)	kt
*136	6850-00-431-8662	Etching Solution Tetra-Etch (CAGE 17217)	cn
*137	6810-00-006-4205	Ethylene Glycol ASTM E 1119 (CAGE 81346)	gal
137A	8315-00-006-9835	Fastener Tape, Hook A-A-55126 (CAGE 58536)	yd
137B	8315-00-006-9836	Fastener Tape, Pile A-A-55126 (CAGE 58536)	yd
137C	8315-00-935-0505	Fastener Tape, Pile A-A-55126 (CAGE 58536)	yd
138	1615-01-126-9445	Fiberglass Repair Kit 70072-15001-011 (CAGE 78286)	ea
138A		Fiberglass Ski Repair Kit L20500-200 (CAGE 17564)	kt
139	4020-00-240-2142	Fibrous Cord A-A-55622 (CAGE 58536)	1200 ft rl
139A	8030-00-195-4831	Filler, Metal Surface Dent 01125 (CAGE 10054)	ea

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
139B		Deleted (Refer to Item 141A)	
140	8305-00-641-5606	Flannel Cloth CCC-C-458 (CAGE 81348)	yd
141	8010-00-958-8147	Fluorescent Paint A-A-713, Color: No. 38905 (CAGE 81348)	pt
141A	4210-01-056-8343 4210-01-139-4972	Foam Liquid, Fire Extinguishing MIL-F-24385 (CAGE 81349)	5 gal
141B	1560-01-305-7909	Fuel Tank Parts Kit 052M001-501 (CAGE 59297)	kt
142	1560-01-305-7912	Fuel Tank Parts Kit 052M004-501 (CAGE 59297)	kt
*143	9150-01-040-1423	Grease FS-3451 (CAGE 71984)	3 oz tu
*144	9150-00-754-2595	Grease MIL-G-21164 (CAGE 81349)	1.75 lbs
*145	9150-00-985-7246 9150-00-985-7247 9150-00-985-7248	Grease MIL-PRF-23827 (CAGE 81349)	1.75 lbs 6.5 lbs 35 lbs
*146	9150-00-141-6770	Grease MIL-G-25013 (CAGE 81349)	1.75 lbs
*147	9150-00-616-9020	Grease MIL-G-25537 (CAGE 81349)	1.75 lbs
*148	9150-01-584-4299	Grease A-A-59173 (CAGE 58536)	oz
*149	9150-00-944-8953 9150-00-145-0268	Grease MIL-PRF-81322 (CAGE 81349)	1.75 lb cn 5 lb cn

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*150	9150-00-408-9635	Grease MIL-G-81827 (CAGE 81349)	1.75 lb cn
*151	9150-01-018-8960	Grease MIL-G-4343 (CAGE 81349)	ca
*151A	9150-00-663-1770	Grease 630AA (CAGE 73219)	6 lbs
151B	9150-01-444-2469	Grease AA-100 (CAGE 64856)	ca
152	5325-00-074-3301	Grommet, Nonmetallic MS21266-2N (CAGE 96906)	ea
152A	5325-00-926-1394	Grommet, Nonmetallic MS21266-3N (CAGE 96906)	ea
153	8520-00-527-9942	Hand Cleaner P-H-31, Type 1, Class 1 (CAGE 81348)	pt
*154	9150-00-252-6383 9150-00-223-4134	Hydraulic Fluid MIL-PRF-5606 (CAGE 81349)	qt gal
*155	9150-00-149-7432	Hydraulic Fluid MIL-PRF-83282 (CAGE 81349)	gal
155A	9150-00-698-2382	Hydraulic Fluid, Automatic Transmission Dexron II (CAGE 24617)	qt
156	7690-01-368-2663	Identification Marker HM200-300 (CAGE 94858)	pkg
*157	5970-01-029-7961	Insulating Compound MIL-I-46058 (CAGE 81349)	cn
*158	5970-01-100-4464	Insulating Compound RTV102 (CAGE 01139)	2.8 oz

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
159	5970-01-363-8394	Insulating Compound RTV-3140 (CAGE 71984)	qt
160	5970-00-900-9372	Insulating Varnish 1201 (CAGE 08000)	cn
160A	5970-01-356-5954	Insulation Sleeving MIL-I-631 (CAGE 81349)	36 in
160B	5970-01-072-0014	Insulation Sleeving, Boot MS3117-11AC (CAGE 96906)	ea
160C	5970-00-484-2821	Insulation Sleeving, Electrical M23053/8-009-C (CAGE 81349)	ea
160D	5970-00-729-2966	Insulation Sleeving PVC105-11 (CAGE 81349)	in
161	5970-00-899-6651	Insulation Sleeving, Heat-Shrinkable M22129-02-N (CAGE 81349)	ft
162	5970-00-812-2969	Insulation Sleeving, Heat-Shrinkable M23053/5-104-0 (CAGE 81349)	ft
163	5957-01-088-0413	Insulation Sleeving, Heat-Shrinkable M23053/1-202-0 (CAGE 81349)	ft
164	5970-00-740-2971	Insulation Sleeving, Heat-Shrinkable M23053/5-107-9 (CAGE 81349)	ft
165	5970-00-983-7970	Insulation Sleeving, Heat-Shrinkable M23053/5-105-5 (CAGE 81349)	ft
166		Insulation Sleeving, Heat-Shrinkable M23053/16-75-5 (CAGE 81349)	ft
167	5970-00-787-2310	Insulation Sleeving, Heat-Shrinkable M23053/5-101-0 (CAGE 81349)	ft

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
168		Deleted (Refer to Item 162)	
169	5970-00-812-2967	Insulation Sleeving, Heat-Shrinkable M23053/5-108-0 (CAGE 81349)	ft
170		Deleted (Refer to Item 160A)	
171	5970-00-221-5316	Insulation Sleeving, Heat-Shrinkable MIL-I-631 (CAGE 81349)	ft
172	5970-00-899-6660	Insulation Sleeving, Heat-Shrinkable M22129-20-N (CAGE 81349)	ft
173		Deleted (Refer to Item 219A)	
174		Deleted (Refer to Item 160B)	
175	5970-00-146-1122	Insulation Sleeving, Heat-Shrinkable SS7072G0125W010 (CAGE 78286)	ft
176		Deleted (Refer to Item 180)	
177	5970-00-812-2974	Insulation Sleeving, Heat-Shrinkable M23053/5-103-0 (CAGE 81349)	ft
178	5970-00-781-6832	Insulation Sleeving, Heat-Shrinkable M23053/5-114-0 (CAGE 81349)	ft
179	5970-01-158-3818	Insulation Sleeving, Heat-Shrinkable M23053/11-130-C (CAGE 81349)	ft
180	5970-01-028-6789	Insulation Sleeving, Heat-Shrinkable MS3109-11AC (CAGE 96906)	ft
181	5970-00-832-4298	Insulation Tape A-A-59474 (CAGE 58536)	rl
182	5970-00-881-3657	Insulation Tape MIL-I-15126 (CAGE 81349)	rl
182A	5970-00-226-9577	Insulating Compound, Electrical Epocast 4-H-A/946 (CAGE 99384)	kt

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*182B	8010-01-042-4196	Lacquer MIL-L-46159 (CAGE 81349)	cn
*182C	8010-00-066-9430	Lacquer MIL-PRF-81352 (CAGE 81349)	gal
*183	8010-00-082-2479	Lacquer MIL-L-19538 Color: Black (CAGE 81349)	qt
*184	8010-00-527-2888	Lacquer MIL-L-19538 Color: Olive Drab (CAGE 81349)	gal
*185	8010-00-083-6588	Lacquer MIL-L-19538, Class 1, X34089 (CAGE 81349)	5 gal
*186	8010-00-083-6588	Lacquer MIL-L-46159 (CAGE 81349)	16 oz
*187	8010-01-016-1488	Lacquer MIL-L-46159, Type 1 Color: Olive Drab (CAGE 81349)	pt
*188	8010-01-042-4196	Lacquer MIL-L-46159, Type 2 Color: Olive Drab (CAGE 81349)	16 oz
*189	6850-00-935-4068	Leak Detection Fluid 372 (CAGE 03530)	4 oz
190	6640-00-290-0146	Litmus Paper MS36253-2 (CAGE 96906)	vial
191	6640-00-290-0147	Litmus Paper MS36253-1 (CAGE 96906)	vial
192		Deleted (Refer to Item 285 or Item 286)	

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
193	9525-00-221-2650	Lockwire MS20995C20 (CAGE 96906)	1 lb sp
194	9505-01-054-2676	Lockwire MS20995C32 (CAGE 96906)	1 lb sp
194A	9505-01-499-6879	Lockwire MS20995C47 (CAGE 96906)	1 lb sp
195	9525-01-047-6455	Lockwire MS20995CY20 (CAGE 96906)	1 lb sp
196	9525-00-618-0257	Lockwire MS20995NC20 (CAGE 96906)	1 lb sp
197	9525-00-803-3044	Lockwire MS20995NC32 (CAGE 96906)	5 lb sp
198	9525-00-990-7799	Lockwire MS20995NC40 (CAGE 96906)	1 lb sp
199	9525-00-409-1866	Lockwire MS20995NC47 (CAGE 96906)	1 lb sp
199A		Deleted	
199B		Deleted (Refer to Item 123A)	
199C	9150-01-106-7078	Lubricant Molykote III (CAGE 94499)	cn
*200	2640-00-476-3144	Lubricant, Inner Tube MIL-C-5024 (CAGE 81349)	gal
200A	6850-01-441-2633	Lubricant, Seal L-001 (CAGE 04171)	tu
200B		Lubricant, Solid Film MIL-L-8937, Type II (CAGE 81349)	gal

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*201	9150-01-260-2534	Lubricant, Solid Film MIL-L-23398 (CAGE 81349)	16 oz
201A		Deleted (Refer to Item 200A)	
201B	6850-01-260-8055	Lubricant, Water Displacing MIL-L-87177, Type I (CAGE 81349)	cn
*202	9150-00-263-3490	Lubricating Oil MIL-PRF-7870 (CAGE 81349)	cn
*203	9150-00-543-7220	Lubricating Oil DOD-L-25681 (CAGE 81349)	lb
204	9150-00-292-9687	Lubricating Oil MIL-PRF-14107 (CAGE 81349)	5 gal
*204A	9150-00-753-4937	Lubricating Oil SAE J 1899 (CAGE 81343)	55 gal
*205	9150-00-985-7099	Lubricating Oil MIL-PRF-23699 (See Note) (CAGE 81349)	qt
*205A	9150-01-311-5640	Lubricating Oil MIL-PRF-6085 (CAGE 81349)	qt
*206	9150-01-209-2684	Lubricating Oil DOD-L-85734 (CAGE 81349)	qt
*207	9150-00-273-2388	Lubricating Oil MIL-PRF-6081 (CAGE 81349)	qt
*208	9150-00-782-2627	Lubricating Oil MIL-PRF-7808 (CAGE 81349)	qt
*209	9150-00-231-6689	Lubricating Oil MIL-PRF-32033 (CAGE 81349)	qt

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
209A	9150-00-664-4449	Lubricating Oil, Refrigerant Compressor ED45263-106 (CAGE 64959)	gal
210		Deleted (Refer to Item 151A)	
211	7920-00-260-1279	Machinery Towel DDD-T-541 (CAGE 81348)	50 ea bx
211A	1560-00-450-3622	Maintenance Kit, Window A-A-52686 (CAGE 81349)	kt
211B		Deleted (Refer to Item 66F)	
211C	7520-00-043-3408	Marking Pen A-A-2778 (CAGE 58536)	ea
212	7510-00-266-6712	Masking Tape, 1-inch A-A-883 (CAGE 58536)	rl
213	7510-00-266-6709	Masking Tape, 1 1/2-inches A-A-883 (CAGE 58536)	rl
214	7510-00-266-6710	Masking Tape, 2-inches A-A-883 (CAGE 58536)	rl
215	7510-00-266-6707	Masking Tape, 3-inches A-A-883 (CAGE 58536)	rl
216	9340-01-177-8572	Mat, Reinforcing, Fibrous 1659 (CAGE 95746)	50 yd rl
*217	6810-00-281-2785 6810-00-281-2762 6810-00-281-2763	Methyl Ethyl Ketone ASTM D 740 (CAGE 81346)	gal 5 gal 55 gal
*218	6810-00-180-5976 6810-00-281-2761	Methyl Isobutyl Ketone ASTM D 1153 (CAGE 81346)	5 gal 55 gal
*219	6810-00-264-6715	Molybdenum Disulfide AMS-M-7866 (CAGE 81343)	1 lb

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
219A	2925-00-497-4957	Neoprene Sleeve 10-30233 (CAGE 77820)	ft
*220	6810-00-222-9655 6810-00-237-2918	Nitric Acid A-A-59105 (CAGE 58536)	500 ml 80 oz
*221	6830-00-782-2641 6830-01-028-9402	Nitrogen A-A-59503 (CAGE 58536)	187 cu ft cyl 226 cu ft cyl
*221A	8010-00-664-7468	Paint, Heat Resistant Aluminum TT-P-28 (CAGE 81348)	qt
221B	8010-01-357-4155	Paint, Heat Resisting GES-69AR (CAGE 58913)	kt
*222	8010-01-131-6254	Paint, Polyurethane MIL-DTL-53039, Type 2 Color: No. 37030, Black (CAGE 81349)	kt
*222A	8010-01-131-6255	Paint, Polyurethane MIL-DTL-53039, Type 2 Color: No. 34031, Dark Green (CAGE 81349)	kt
*223	8010-01-146-2646	Paint, Polyurethane MIL-DTL-53039, Type 2 Color: No. 37038, Black (CAGE 81349)	kt
*224	8010-01-146-2649	Paint, Polyurethane MIL-DTL-53039, Type 2 Color: No. 36231, Dark Gull Gray (CAGE 81349)	kt
*225	8010-01-144-9872	Paint, Polyurethane MIL-DTL-53039, Type 2 Color: No. 37875, Insignia White (CAGE 81349)	kt
*226	8010-01-144-9873	Paint, Polyurethane MIL-DTL-53039, Type 2 Color: No. 31136, Insignia Red (CAGE 81349)	kt

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*227	8010-01-055-2319	Paint, Polyurethane MIL-DTL-53039, Type 2 Color: No. 34088, Olive Drab (CAGE 81349)	kt
*227A	8010-01-235-8059	Paint, Polyurethane MIL-DTL-53039, Type 2 Color: No. 33538, Orange Yellow (CAGE 81349)	kt
*228	8010-01-042-1004	Paint, Polyurethane MIL-C-83286 (CAGE 81349)	kt
229	8010-00-815-2970	Paint Remover MIL-R-25134 (CAGE 81349)	1 gal
*230	8010-00-142-9273 8010-00-926-1488 8010-00-926-1489	Paint Remover MIL-R-81294 (CAGE 81349)	pt 5 gal 55 gal
*231	8010-00-515-2258	Paint Remover TT-R-248 (CAGE 81348)	5 gal
232	8010-00-558-7026	Paint Thinner A-A-2904 (CAGE 58536)	5 gal
*233	3680-00-237-3457	Parting Compound 225 (CAGE 22401)	cn
233A	9150-00-223-4119	Penetrating Oil VV-P-216 (CAGE 81348)	ea
*234	9150-00-250-0926	Petrolatum VV-P-236 (CAGE 81348)	1.75 lbs
234A	9330-01-196-5436	Plastic Sheet A4000 (CAGE 53912)	rl
235	9330-00-260-3800	Plastic Sheet M24768/16-S-14 (CAGE 81349)	sh

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
235A	9330-01-473-7822	Plastic Sheet 51789/52006 (CAGE 0NMM3)	sh
236		Deleted (Refer to Item 237B)	
236A	9330-01-182-2750 9330-01-341-7812 9339-01-358-7526	Plastic Sheet CADCO 0731 (CAGE 12626) KGOC20543S (CAGE 7Z980) A-A-2848 (CAGE 58536)	rl rl sh
237	9330-00-169-6407	Plastic Strip 8561 (CAGE 52152)	rl
237A	9330-01-208-1025	Plastic Strip Artus -.015 Pink-5x20 (CAGE 96013)	ea
237B	9330-00-982-5707	Plastic, Polyvinyl Sheet MIL-P-78 (CAGE 81349)	sh
238		Deleted (Refer to Item 211A)	
239		Deleted (Refer to Item 258A)	
*240	8010-01-131-6255	Polyurethane Coating MIL-C-46168 (CAGE 81349)	kt
*240A	8010-01-265-9127	Polyurethane Coating MIL-PRF-85285 (CAGE 81349)	kt
240B	8010-01-057-3599	Polyurethane Coating 23-T3-103 (CAGE OKXA5)	kt
*241	8010-00-181-8281	Polyurethane Coating MIL-C-83286 (CAGE 81349)	kt
241A	9320-01-247-7735	Polyurethane Tape, Abrasion Resistant SS9538-002 (CAGE 78286)	rl

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
241B		Polyurethane Tape, Abrasion Resistant SS9538-007 (CAGE 78286)	rl
241C	9330-01-202-8903	Polyurethane Tape WX-1206 (CAGE 61748)	rl
241D	8010-01-131-9195	Polyurethane Coating MIL-C-83286 (CAGE 81349)	kt
242	7510-01-326-1568	Pressure Sensitive Adhesive Tape 8663-SS-1-4 (CAGE 52152)	rl
243	9330-01-326-1821	Pressure Sensitive Adhesive Tape 8663-SS-1-8 (CAGE 52152)	rl
243A	9330-01-338-9994	Pressure Sensitive Adhesive Tape 8681HS (CAGE 52152)	rl
244	7510-01-326-1567	Pressure Sensitive Adhesive Tape 8663-2 (CAGE 52152)	rl
244A		Deleted (Refer to Item 241C)	
244B	7510-01-408-9946	Pressure Sensitive Adhesive Tape Flashbreaker 2 (CAGE 53912)	rl
244C	7510-00-079-7604	Pressure Sensitive Adhesive Tape 4516 (CAGE 52152)	rl
245	7510-00-551-9826	Pressure Sensitive Adhesive Tape A-A-113 (CAGE 58536)	rl
246		Deleted (Refer to Item 251B)	
247	7510-00-290-2026	Pressure Sensitive Adhesive Tape A-A-883 (CAGE 58536)	rl
248	7510-01-032-4082	Pressure Sensitive Adhesive Tape 4508 (CAGE 52152)	rl

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
249	7510-00-663-0195 7510-00-663-0196	Pressure Sensitive Adhesive Tape PPP-T-60 (CAGE 81348)	yd yd
250	7510-01-158-6603	Pressure Sensitive Adhesive Tape 218 (CAGE 52152)	rl
250A	7510-00-079-7604	Pressure Sensitive Adhesive Tape 4516 (CAGE 52152)	rl
250B	5330-01-514-8772	Pressure Sensitive Adhesive Tape HT3000-100 (CAGE 1NPE1)	rl
250C	5330-01-513-0861	Pressure Sensitive Adhesive Tape HT3000-150 (CAGE 1NPE1)	rl
250D	5330-01-513-0876	Pressure Sensitive Adhesive Tape HT3000-200 (CAGE 1NPE1)	rl
250E	5970-01-623-9080	Pressure Sensitive Adhesive Tape 8663MB (CAGE 76381)	rl
251	7510-01-248-7514	Pressure Sensitive Adhesive Tape 5423 (CAGE 52152)	in.
251A		Pressure Sensitive Tape 5430 (CAGE 52152)	rl
251B	7510-01-200-0832	Pressure Sensitive Tape K1245 (CAGE 04963)	rl
252	4920-01-307-3169	Pressure Test Kit TO26A179-401 (CAGE 59297)	kt
253		Deleted (Refer to Item 106B)	
*254	8040-01-181-2355	Primer Accelerator No. 4 (CAGE 30676)	8 oz

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
255	8040-01-205-6819	Primer METLBOND 6726 (CAGE 04622)	gal
256		Deleted (Refer to Item 135A)	
*257	8010-00-582-5318	Primer TT-P-1757 (CAGE 81348)	cn
*258	8010-00-899-0931	Primer TT-P-1757 (CAGE 81348)	pt
258A	8010-01-371-1952	Primer Coating Aeroglaze 9924 (CAGE 30676)	3 oz
*259	8010-01-040-0947	Primer Coating No. 81 (CAGE 52152)	15 oz
259A		Deleted (Refer to Item 25A)	
260		Deleted (Refer to Item 115A)	
261	6830-01-137-7971	Refrigerant A-A-58060 (CAGE 58536)	50 lb cyl
262	6830-01-370-8756	Refrigerant HFC-134A (CAGE 2S827)	125 lb cyl
263		Refrigerant SUVA 9000, R-407C (CAGE 82348)	gal
263A	9150-01-443-9390	Refrigerant Oil Icematic SW 32 (CAGE 2R128)	gal
264	1560-01-305-7910	Repair Plug Kit 052M002-501 (CAGE 59297)	kt
264A		Deleted (Refer to Item 302C)	
264B	1560-01-305-7911	Repair Plug Kit 052M003-501 (CAGE 59297)	kt

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
265	8415-00-266-8677	Rubber Gloves MIL-DTL-32066 (CAGE 81349)	pr
266		Deleted (Refer to Item 264B)	
267	9320-01-154-2225	Rubber Sheet MIL-C-3133, Grade SCE 3L (CAGE 81349)	sh
267A	9320-00-580-6756	Rubber Sheet, 0.063-inch thick MIL-C-3133, Grade SBE 11L (CAGE 81349)	sh
267B		Rubber Sheet, 0.050-inch thick MIL-R-6855, Class 2, Grade 60 (CAGE 81349)	sh
268	9320-01-157-9070	Rubber Sheet, 0.062-inch thick MIL-R-6855, Class 2, Grade 60 (CAGE 81349)	sh
269	9320-00-241-9764	Rubber Sheet, 0.188-inch thick MIL-R-6855, Class 2, Grade 60 (CAGE 81349)	sh
269A	8305-01-163-1882	Satin Cloth 7781 (CAGE 95746)	yd
270	7920-00-934-3469	Scouring Pad LP50 (CAGE 81348)	bx
270A	7510-00-736-6407	Seal, Moisture CMC-3750 Tape B-540 (CAGE 85480)	rl
271		Deleted (Refer to Item 302A)	
271A	8030-01-014-5869	Sealing Compound 24231 (CAGE 05972)	bt
*272	8030-00-180-5931	Sealing Compound Epocast 169A-1/9615 (CAGE 99384)	kt
272A	8030-01-132-9624 8030-01-475-2444	Sealing Compound 243 (CAGE 05927)	bt

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*273	8030-00-891-8358	Sealing Compound MIL-R-46082, Type 1 (CAGE 81349)	bt
*274	8030-00-181-7529	Sealing Compound MIL-R-46082, Type 2 (CAGE 81349)	bt
*275	8030-00-433-4145	Sealing Compound MIL-S-11030, Type 3 (CAGE 81349)	ro
*276	8030-00-964-7537	Sealing Compound ASTM D 5363, Grade C (CAGE 81346)	bt
*277	8030-00-081-2340	Sealing Compound ASTM D 5363, Grade AA (CAGE 81346)	bt
*278	8030-00-081-2329	Sealing Compound ASTM D 5363, Grade E (CAGE 81346)	bx
*279	8030-00-081-2336	Sealing Compound ASTM D 5363, Grade AV (CAGE 81346)	bt
*280	8030-00-081-2335	Sealing Compound ASTM D 5363, Grade B (CAGE 81346)	bt
*281	8030-00-081-2326	Sealing Compound ASTM D 5363, Grade H (CAGE 81346)	bt
*282	8030-00-082-2508	Sealing Compound ASTM D 5363, Grade T (CAGE 81346)	bt
*283	8030-00-081-2339	Sealing Compound ASTM D 5363, Grade A (CAGE 81346)	bt
*284	8030-00-664-4019	Sealing Compound MIL-S-4383 (CAGE 81349)	pt
*285	8030-00-111-2762	Sealing Compound MIL-S-46163, Type III, Grade R (CAGE 81349)	bt

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*286	8030-00-111-2763	Sealing Compound MIL-S-46163, Type III, Grade R (CAGE 81349)	bx
286A	8030-01-069-3046	Sealing Compound MIL-S-46163, Type II, Grade M (CAGE 81349)	bt
*287	8030-01-192-2807	Sealing Compound MIL-PRF-81733 (CAGE 81349)	kt
*288	8030-00-008-7204	Sealing Compound MIL-S-81733, Type 3-1 (CAGE 81349)	kt
289	8030-00-174-2597	Sealing Compound MIL-S-8516 (CAGE 81349)	kt
*290	8030-00-152-0021	Sealing Compound MIL-S-8784 (CAGE 81349)	ca
*291	8030-00-680-2041	Sealing Compound MIL-S-8784 (CAGE 81349)	kt
*292	8030-00-723-2746	Sealing Compound MIL-S-8802 (CAGE 81349)	kt
293	8030-01-044-5527	Sealing Compound 07331 (CAGE 05972)	bt
*293A	8030-01-158-6070	Sealing Compound 27131 (CAGE 05972)	bt
294	8030-00-714-3013	Sealing Compound 590 (CAGE 77464)	gal
*295	8030-01-234-2186	Sealing Compound PR1436GB-2 (CAGE 83574)	pt
*295A	8030-01-370-2161	Sealing Compound PR-1775, B-2 (CAGE 85374)	6 oz

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*296	8030-00-753-5006	Sealing Compound PR-1440, B-2 (CAGE 83574)	kt
*296A	8030-00-753-4597	Sealing Compound PR-1440, B-1/2 (CAGE 83574)	kt
*297	8030-00-209-8005	Sealing Compound TT-S-1732 (CAGE 81348)	0.5 pt
298	8030-00-599-7753	Sealing Compound 1372W (CAGE 77247)	tu
299	8030-00-148-9833	Sealing Compound 27121 (CAGE 05972)	bt
300	8030-01-393-5471	Sealing Compound CHO-Shield 2002 (CAGE 18565)	gal
301	8010-14-360-0749	Sealing Compound (MASTINOX 6856KD (1913/3601)) (CAGE F1419)	tu
*301A	8030-01-450-0381	Sealing Compound CA 1000 (CAGE 83574)	tu
302	8030-00-339-0310	Sealing Compound 69-31 (CAGE 05972)	bt
*302A	8030-00-142-9718	Sealing Compound Epocast 1652 A/B (CAGE 99384)	kt
302B	8030-00-142-9738	Sealing Compound Epocast 1310A/9226 (CAGE 99384)	kt
302C	8030-01-387-2007	Sealing Compound 68060 (CAGE 05972)	bt
302D	8030-01-494-9651	Sealing Compound TG8498-50 (CAGE 1NPE1)	ca

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
303		Deleted (Refer to Item 301A)	
304		Deleted (Refer to Item 305)	
*305	8030-00-181-8372	Sealing Primer MIL-S-22473 (CAGE 81349)	bt
*306	8030-00-900-2373	Sealing Primer ASTM D 5363, Grade N (CAGE 81346)	bt
307		Deleted (Refer to Item 282)	
307A		Deleted (Refer to Item 237A)	
308		Deleted (Refer to Item 309)	
*309	6850-00-177-5094 6850-00-880-7616	Silicone Compound MIL-S-8660 (CAGE 81349)	2 oz 8 oz
310		Deleted (Refer to Item 121)	
311	5970-00-284-8468	Sleeving, Insulation MIL-I-7444 (CAGE 81349)	ft
312		Deleted (Refer to Item 313)	
313	3439-00-269-9610	Solder QQ-S-571 (CAGE 81348)	sp
313A		Deleted (Refer to Item 99B)	
314	9330-00-753-5372	Spiral Wrap R23100-1 (CAGE 50599)	ea
315	9330-00-688-7856	Spiral Wrap R23100-3 (CAGE 50599)	ft
315A	9330-00-688-7857	Spiral Wrap R23100-4 (CAGE 50599)	ft
315B	9330-00-074-0963	Spiral Wrap R23100-5 (CAGE 50599)	ft

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
315C	7340-00-753-5565	Stirring Stick, Beverage A-A-1081 (CAGE 58536)	ea
316		Deleted (Refer to Item 231)	
316A	8030-00-889-3535	Tape, Antiseize A-A-58092 (CAGE 58536)	ea
317		Deleted (Refer to Item 282)	4 oz
317A	8510-00-170-5469	Talcum Powder U-T-30 (CAGE 81348)	16 oz
317B	4020-00-900-0986	Tape A-A-52080 (CAGE 58536)	rl
317C	4020-01-179-1949	Tape SS7057-2 (CAGE 78286)	ft
318		Deleted (Refer to Item 319B)	
318A	9320-01-247-7735	Tape, Anti-Chafe 8671 (CAGE 52152)	rl
318B	5640-00-103-2254	Tape, Duct A-A-2231 (CAGE 58536)	rl
319	5970-00-723-5413	Tape, Insulation HM 350 (CAGE 71643)	rl
319A		Tape, Insulation 1300891 (CAGE 04813)	lb
319B	5970-00-883-1161	Tape, Insulation A2005 (CAGE 71643)	rl
320	5970-00-186-6627	Tape, Insulation 7001 (CAGE 88301)	rl
320A	5970-00-955-9976	Tape, Insulation, Electrical MS70T09-S (CAGE 07099)	rl

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
321		Deleted (Refer to Item 317B)	
321A		Deleted (Refer to Item 317C)	
322	9390-01-334-4357	Tape, Reflective 7610 (CAGE 52170)	rl
322A		Teflon Urethane Coating 23-73-90 (CAGE 17564)	kt
323	6685-01-177-2764	Temp Indicator Card 4B-225 (CAGE 82682)	pkg
324	6810-00-819-1128	Tetrachloroethylene ASTM D 4376 (CAGE 81346)	5 gal
324A	8010-01-097-5253	Thinner 9958 (CAGE 30676)	1 gal
324B	8010-00-165-6760	Thinner, Acrylic MIL-T-81722, Type III (CAGE 81349)	1 gal
325	8310-00-204-3749	Thread V-T-295, Type 1, Class A (CAGE 81348)	tu
326	8310-00-530-1182	Thread A-A-52094 (CAGE 58536)	yd
327	8310-01-341-2715	Thread, Break-A-Way MIL-T-43624 Jewel Red 16/4 (CAGE 81349)	rl
328	5975-00-984-6582	Tiedown Strap MS3367-1-0 (CAGE 81343)	100 pkg
329	5975-00-074-2072	Tiedown Strap MS3367-1-9 (CAGE 81343)	100 pkg
330	5975-00-899-4606	Tiedown Strap MS3367-2-0 (CAGE 81343)	100 pkg

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
331	5975-00-156-3253	Tiedown Strap MS3367-2-9 (CAGE 81343)	100 pkg
332	5975-00-985-6630	Tiedown Strap MS3367-3-0 (CAGE 81343)	100 pkg
333	5975-00-451-5001	Tiedown Strap MS3367-3-9 (CAGE 81343)	100 pkg
334	5975-00-903-2284	Tiedown Strap MS3367-4-0 (CAGE 81343)	100 pkg
334A	5975-00-727-5153	Tiedown Strap MS3367-4-9 (CAGE 81343)	100 pkg
335	5975-00-111-3208	Tiedown Strap MS3367-5-9 (CAGE 81343)	100 pkg
336	5975-01-048-2922	Tiedown Strap MS3367-6-0 (CAGE 81343)	100 pkg
337	5975-00-133-8696	Tiedown Strap MS3367-6-9 (CAGE 81343)	100 pkg
338	5975-00-570-9598	Tiedown Strap MS3367-7-9 (CAGE 81343)	100 pkg
*339	6810-00-579-8431 6810-00-281-2002	Toluene A-A-59107 (CAGE 58536)	qt gal
340		Deleted (Refer to Item 155A)	
340A	6810-00-141-6078	Tribasic Sodium Phosphate O-S-642 (CAGE 81348)	1 lb
*341	6810-00-476-5612	Trichloroethane 1,1,1 MIL-T-81533 (CAGE 81349)	cn

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

(1) ITEM NO.	(2) NATIONAL STOCK NUMBER	(3) DESCRIPTION	(4) (U/M)/(U/I)
*342	6810-00-930-6311	Trichloroethane 1,1,1 ASTM D 4126 (CAGE 81346)	12 oz
343	6810-00-678-4418	Trichloroethylene, Technical ASTM D 4080 (CAGE 81346)	55 gal
344	4720-01-145-6685	Tubing, Nonmetallic Tygothane 3/8-inch ID (CAGE 34384)	ft
345		Deleted (Refer to Item 141B)	
345A		Vacuum Bagging Film SL800 (CAGE 53912)	rl
346		Deleted (Refer to Item 137A)	
347		Deleted (Refer to Item 137B)	
347A		Deleted (Refer to Item 137C)	
347B	8315-01-331-4506	Velcro Strap SJ3401-200/3.00 (CAGE 52152)	yd
348	8030-00-267-1583	Walkway Compound A-A-59166 (CAGE 58536)	gal
349		Deleted (Refer to Item 315C)	
NOTE: When using lubricating oil for servicing engine only, refer to General Electric SEI-671 manual for approved oils.			

* Read the associated hazardous material warning for this item. Warnings are called out in Paragraph D-1.3 of this Appendix.

