

# 3 Regular Expressions, Regular Languages

[Linz, Ch. 3]

## Regular Expressions over $\Sigma$

Let  $\Sigma$  be a finite alphabet.

A **regular expression** over  $\Sigma$  (or  $\Sigma$ -regular expression) is a string built up from the  $\Sigma$ -symbols,  $\lambda$  and  $\emptyset$ , and the operators  $+$ ,  $\cdot$ ,  $*$  and  $(,)$ .

**$RegExp(\Sigma)$**  is the set of  $\Sigma$ -regular expressions.

## Recursive Definition of $RegExp(\Sigma)$

[Cf. p. 1-14 for recursive definition of  $\Sigma^*$ ]

**Basis:**

- $a \in \Sigma \implies a \in RegExp(\Sigma)$
- $\lambda \in RegExp(\Sigma)$
- $\emptyset \in RegExp(\Sigma)$

### Recursive Steps:

- $r_1, r_2 \in \text{RegExp}(\Sigma) \implies r_1 + r_2 \in \text{RegExp}(\Sigma)$
- $r_1, r_2 \in \text{RegExp}(\Sigma) \implies r_1 \cdot r_2 \in \text{RegExp}(\Sigma)$
- $r \in \text{RegExp}(\Sigma) \implies r^* \in \text{RegExp}(\Sigma)$
- $r \in \text{RegExp}(\Sigma) \implies (r) \in \text{RegExp}(\Sigma)$

Alternatively, use **modified BNF** to define  $\text{RegExp}(\Sigma)$ :

Given  $\Sigma$ , with elements  $a, \dots$ ,

define  $\text{RegExp}(\Sigma)$ , with elements  $r, r_1, r', \dots$ :

$$r ::= a \mid \lambda \mid \emptyset \mid (r_1 + r_2) \mid (r_1 \cdot r_2) \mid r^* \mid (r)$$

### Note:

(1) Can **drop** “.” for concatenation

(2) Can **drop parentheses**

- Use **Rules of Precedence**

\*

.

+

A  $\Sigma$ -regular expression  $r$  defines a  $\Sigma$ -language  $L(r) \subseteq \Sigma^*$ .

**Definition:** We define  $L(r) \subseteq \Sigma^*$  by **structural recursion** on  $r \in \text{RegExp}(\Sigma)$ .

(Cf. definition of  $\text{RegExp}(\Sigma)$  by **structural recursion** on p. 3-1.)

**Base cases:**

$$L(a) = \{a\}$$

$$L(\lambda) = \{\lambda\}$$

$$L(\emptyset) = \emptyset$$

**Recursive Steps:**

$$L(r_1 + r_2) = L(r_1) \cup L(r_2)$$

$$L(r_1 \cdot r_2) = L(r_1) \cdot L(r_2) \quad L(r^*) = L(r)^*$$

$$L((r)) = L(r)$$

**Note:**

Alternatively, this definition is by (CV) recursion on  $\text{compl}(r)$  or  $|r|$ .

**Exercises:**

- (a) Given a regular expression, describe what **language** it defines.
- (b) Given a set  $A \subseteq \Sigma$ , find a regular expression,  $r$ , which defines  $A$ , i.e. s.t.  $L(r) = A$ .

Linz, section 3.1 has **many examples** of these.

**Examples:** [Assume  $\Sigma = \{a, b\}$  unless otherwise stated.]

- (1) Find  $r$  s.t.  $L(r) = \{a^m b^n \mid m, n \geq 0, m \text{ even}, n \text{ odd}\}$
- (2) Find  $r$  s.t.  $L(r) = \Sigma^*$  if  $\Sigma = \{a_1, \dots, a_k\}$
- (3) Find  $r : L(r) = \text{set of all } \Sigma\text{-strings with no consec. } a\text{'s or } b\text{'s.}$

**Definition: Equivalence of Regular Expressions**

$$r_1 \equiv r_2 \iff L(r_1) = L(r_2)$$

**Examples:** Are the following pairs of regular expressions equivalent? (assume  $\Sigma = \{a, b\}$ )

$$(1) \quad r_1 + r_2 \stackrel{?}{=} r_2 + r_1$$

$$(2) \quad r_1 r_2 \stackrel{?}{=} r_2 r_1$$

$$(3) \quad (r^*)^* \stackrel{?}{=} r^*$$

$$(4) \quad r_1(r_2 + r_3) \stackrel{?}{=} r_1 r_2 + r_1 r_3$$

**Examples:** Try some of the following:

L6, §3.1 Exs p. 78-79:

Questions: 7, 8, 9.ab, 10, 15, 16, 18, 19.ab, 20.abc, 21.b


L5, §3.1 Exs p. 75-77:

Questions: 4, 5, 6.ab, 7, 11, 13, 15, 16.ab, 17.abc, 18.b

**Note:**

(1) We saw earlier (p. 2-16) that changing the definition of **nfa's** to allow more than one state would not make a significant difference, since any **nfa** with more than one start state can be replaced by an **equivalent nfa** with one start state.

(2) Similarly, we can assume without loss of generality (w.l.o.g. for future reference) that any **nfa** that we are using does not have more than one final state. Why? Consider:



Assume, given an alphabet,  $\Sigma$ .

**Definition:** A  $\Sigma$ -language,  $L \subseteq \Sigma^*$ , is **regular** if it is defined by a **regular expression**, r. i.e. if

$$L = L(r)$$

**Note:**

This is **not** Linz's definition of a regular language (Def. 2.3, p. 46 in L6), but it turns out to be equivalent.