

ALGORITHMS & COMPLEXITY

Winter 2018

George Karakostas, Rm. ITB/218, karakos@mcmaster.ca

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Other kinds of analysis: **average case analysis**,

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Other kinds of analysis: **average case analysis, amortized analysis,**

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Other kinds of analysis: **average case analysis, amortized analysis, best case analysis...**

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Input size N : Typically the number of "atomic" objects handled by the algorithm.

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Input size N : Typically the number of "atomic" objects handled by the algorithm. For example:

- For searching/sorting an array: $N = \#$ of keys n

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Input size N : Typically the number of "atomic" objects handled by the algorithm. For example:

- For searching/sorting an array: $N = \#$ of keys n
- For DFS: $N = [\# \text{ of nodes } n] + [\# \text{ of edges } m]$ (*adj. list*)

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Input size N : Typically the number of "atomic" objects handled by the algorithm. For example:

- For searching/sorting an array: $N = \#$ of keys n
- For DFS: $N = [\# \text{ of nodes } n] + [\# \text{ of edges } m]$ (*adj. list*)
OR $N = n^2$ (*adj. matrix*)

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Input size N : Typically the number of "atomic" objects handled by the algorithm. For example:

- For searching/sorting an array: $N = \#$ of keys n
- For DFS: $N = [\# \text{ of nodes } n] + [\# \text{ of edges } m]$ (*adj. list*)
OR $N = n^2$ (*adj. matrix*)
- For integer multiplication alg: $N = \#$ of bits

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Input size N : Typically the number of "atomic" objects handled by the algorithm. For example:

- For searching/sorting an array: $N = \#$ of keys n
- For DFS: $N = [\# \text{ of nodes } n] + [\# \text{ of edges } m]$ (*adj. list*)
OR $N = n^2$ (*adj. matrix*)
- For integer multiplication alg: $N = \#$ of bits
- etc...

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Recall the **tilde** approximation $T(N) \sim g(N)$ from CS 2C03:

$$\lim_{N \rightarrow \infty} \frac{T(N)}{g(N)} = 1$$

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Recall the **tilde** approximation $T(N) \sim g(N)$ from CS 2C03:

$$\lim_{N \rightarrow \infty} \frac{T(N)}{g(N)} = 1$$

What does this tell us? That $T(N)$ is actually of the form:

$$T(N) = g(N) + \text{lower order terms...}$$

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

Recall the **tilde** approximation $T(N) \sim g(N)$ from CS 2C03:

$$\lim_{N \rightarrow \infty} \frac{T(N)}{g(N)} = 1$$

What does this tell us? That $T(N)$ is actually of the form:

$$T(N) = g(N) + \text{lower order terms...}$$

so that we will have

$$\begin{aligned} \lim_{N \rightarrow \infty} \frac{T(N)}{g(N)} &= \lim_{N \rightarrow \infty} \frac{g(N) + \text{lower order terms...}}{g(N)} \\ &= 1 + \lim_{N \rightarrow \infty} \frac{\text{lower order terms...}}{g(N)} = 1 + 0 = 1 \end{aligned}$$

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

...i.e., we may not know $T(N)$ exactly, but we need to guess exactly its highest order component $g(N)$.

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

...i.e., we may not know $T(N)$ exactly, but we need to guess exactly its highest order component $g(N)$. For example, if

$$T(N) = 3N^2 + 20\sqrt{N} - 40N \log N,$$

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

*...i.e., we may not know $T(N)$ exactly, but we need to guess **exactly** its highest order component $g(N)$. For example, if*

$$T(N) = 3N^2 + 20\sqrt{N} - 40N \log N,$$

we need to guess

$$g(N) = 3N^2.$$

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

*...i.e., we may not know $T(N)$ exactly, but we need to guess **exactly** its highest order component $g(N)$. For example, if*

$$T(N) = 3N^2 + 20\sqrt{N} - 40N \log N,$$

we need to guess

$$g(N) = 3N^2.$$

*A guess $g(N) = cN^2$, with some constant $c \neq 3$ **won't do!***

Analysis of algorithms

Worst case analysis We try to *estimate* the **largest** possible running time $T(N)$ of the algorithm over *all* inputs of size N .

*...i.e., we may not know $T(N)$ exactly, but we need to guess **exactly** its highest order component $g(N)$. For example, if*

$$T(N) = 3N^2 + 20\sqrt{N} - 40N \log N,$$

we need to guess

$$g(N) = 3N^2.$$

*A guess $g(N) = cN^2$, with some constant $c \neq 3$ **won't do!***

BIG problem: What if we can guess N^2 , but **not** the exact c ?

Analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Tight bounds. $T(n)$ is $\Theta(f(n))$ if it is **both** $O(f(n))$ and $\Omega(f(n))$.

Analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Tight bounds. $T(n)$ is $\Theta(f(n))$ if it is **both** $O(f(n))$ and $\Omega(f(n))$.

- We write $T(n) = O(f(n))$, $T(n) = \Omega(f(n))$, $T(n) = \Theta(f(n))$ (abuse of notation!).

Analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Tight bounds. $T(n)$ is $\Theta(f(n))$ if it is **both** $O(f(n))$ and $\Omega(f(n))$.

- We write $T(n) = O(f(n))$, $T(n) = \Omega(f(n))$, $T(n) = \Theta(f(n))$ (abuse of notation!).
- Our analysis is still **asymptotic**, since it holds for **large enough** n (at least as big as n_0).

Analysis of algorithms




Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Tight bounds. $T(n)$ is $\Theta(f(n))$ if it is **both** $O(f(n))$ and $\Omega(f(n))$.

- We write $T(n) = O(f(n))$, $T(n) = \Omega(f(n))$, $T(n) = \Theta(f(n))$ (abuse of notation!).
- Our analysis is still **asymptotic**, since it holds for **large enough** n (at least as big as n_0).
- For input sizes $0 \leq n < n_0$ we guarantee **nothing!**

Asymptotic growth of functions



Asymptotic analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Tight bounds. $T(n)$ is $\Theta(f(n))$ if it is **both** $O(f(n))$ and $\Omega(f(n))$.

Asymptotic analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Tight bounds. $T(n)$ is $\Theta(f(n))$ if it is **both** $O(f(n))$ and $\Omega(f(n))$.

Ex: $T(n) = 32n^2 + 17n + 32$.

Asymptotic analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Tight bounds. $T(n)$ is $\Theta(f(n))$ if it is **both** $O(f(n))$ and $\Omega(f(n))$.

Ex: $T(n) = 32n^2 + 17n + 32$.

- $T(n)$ is $O(n^2)$, $O(n^3)$, $\Omega(n^2)$, $\Omega(n)$, and $\Theta(n^2)$.

Asymptotic analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Tight bounds. $T(n)$ is $\Theta(f(n))$ if it is **both** $O(f(n))$ and $\Omega(f(n))$.

Ex: $T(n) = 32n^2 + 17n + 32$.

- $T(n)$ is $O(n^2)$, $O(n^3)$, $\Omega(n^2)$, $\Omega(n)$, and $\Theta(n^2)$.
- $T(n)$ is not $O(n)$, $\Omega(n^3)$, $\Theta(n)$, or $\Theta(n^3)$.

Asymptotic analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Tight bounds. $T(n)$ is $\Theta(f(n))$ if it is **both** $O(f(n))$ and $\Omega(f(n))$.

Ex: $T(n) = 32n^2 + 17n + 32$.

- $T(n)$ is $O(n^2)$, $O(n^3)$, $\Omega(n^2)$, $\Omega(n)$, and $\Theta(n^2)$.
- $T(n)$ is not $O(n)$, $\Omega(n^3)$, $\Theta(n)$, or $\Theta(n^3)$.
- $T(n) = O(1)$ means $T(n) = \text{constant}$.

Asymptotic analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Tight bounds. $T(n)$ is $\Theta(f(n))$ if it is **both** $O(f(n))$ and $\Omega(f(n))$.

Ex: $T(n) = 32n^2 + 17n + 32$.

- $T(n)$ is $O(n^2)$, $O(n^3)$, $\Omega(n^2)$, $\Omega(n)$, and $\Theta(n^2)$.
- $T(n)$ is not $O(n)$, $\Omega(n^3)$, $\Theta(n)$, or $\Theta(n^3)$.
- $T(n) = O(1)$ means $T(n) = \text{constant}$.
- **Common meaningless statement:** "Any comparison-based sorting algorithm **requires at least** $O(n \log n)$ comparisons!"

Asymptotic analysis of algorithms

Upper bounds. $T(n)$ is $O(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \leq c \cdot f(n)$.

Lower bounds. $T(n)$ is $\Omega(f(n))$ if there exist **constants** $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$ we have $T(n) \geq c \cdot f(n)$.

Tight bounds. $T(n)$ is $\Theta(f(n))$ if it is **both** $O(f(n))$ and $\Omega(f(n))$.

Ex: $T(n) = 32n^2 + 17n + 32$.

- $T(n)$ is $O(n^2)$, $O(n^3)$, $\Omega(n^2)$, $\Omega(n)$, and $\Theta(n^2)$.
- $T(n)$ is not $O(n)$, $\Omega(n^3)$, $\Theta(n)$, or $\Theta(n^3)$.
- $T(n) = O(1)$ means $T(n) = \text{constant}$.
- **Common meaningful statement:** "Any comparison-based sorting algorithm **requires** $\Omega(n \log n)$ comparisons!"

Transitivity.

- If $f = O(g)$ and $g = O(h)$ then $f = O(h)$.
- If $f = \Omega(g)$ and $g = \Omega(h)$ then $f = \Omega(h)$.
- If $f = \Theta(g)$ and $g = \Theta(h)$ then $f = \Theta(h)$.

Properties

Transitivity.

- If $f = O(g)$ and $g = O(h)$ then $f = O(h)$.
- If $f = \Omega(g)$ and $g = \Omega(h)$ then $f = \Omega(h)$.
- If $f = \Theta(g)$ and $g = \Theta(h)$ then $f = \Theta(h)$.

Additivity.

- If $f = O(h)$ and $g = O(h)$ then $f + g = O(h)$.
- If $f = \Omega(h)$ and $g = \Omega(h)$ then $f + g = \Omega(h)$.
- If $f = \Theta(h)$ and $g = O(h)$ then $f + g = \Theta(h)$.

Properties

Transitivity.

- If $f = O(g)$ and $g = O(h)$ then $f = O(h)$.
- If $f = \Omega(g)$ and $g = \Omega(h)$ then $f = \Omega(h)$.
- If $f = \Theta(g)$ and $g = \Theta(h)$ then $f = \Theta(h)$.

Additivity.

- If $f = O(h)$ and $g = O(h)$ then $f + g = O(h)$.
- If $f = \Omega(h)$ and $g = \Omega(h)$ then $f + g = \Omega(h)$.
- If $f = \Theta(h)$ and $g = O(h)$ then $f + g = \Theta(h)$.

Other.

- If $f = O(c \cdot h)$ for some constant c then $f = O(h)$.
Same for Ω, Θ .

Asymptotic analysis of algorithms

Comparison between O , Ω , Θ estimates and $\tilde{}$ estimates:

Asymptotic analysis of algorithms

Comparison between O, Ω, Θ estimates and **tilde** estimates:

- Both are **asymptotic**.

Asymptotic analysis of algorithms

Comparison between O, Ω, Θ estimates and **tilde** estimates:

- Both are **asymptotic**.
- O, Ω, Θ estimates are **weaker** than tilde estimates:

Asymptotic analysis of algorithms

Comparison between O, Ω, Θ estimates and **tilde** estimates:

- Both are **asymptotic**.
- O, Ω, Θ estimates are **weaker** than tilde estimates:

Theorem

(2.1) Suppose that for two functions $f(n)$ and $g(n)$ we have:

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = c$$

for some **constant** c . Then $f(n) = \Theta(cg(n)) = \Theta(g(n))$.

Asymptotic analysis of algorithms

Comparison between O, Ω, Θ estimates and **tilde** estimates:

- Both are **asymptotic**.
- O, Ω, Θ estimates are **weaker** than tilde estimates:

Theorem

(2.1) Suppose that for two functions $f(n)$ and $g(n)$ we have:

$$\lim_{n \rightarrow \infty} \frac{f(n)}{g(n)} = c$$

for some **constant** c . Then $f(n) = \Theta(cg(n)) = \Theta(g(n))$.

Proof: By the definition of lim.



Asymptotic Bounds for Some Common Functions

Polynomials. $a_0 + a_1n + \dots + a_dn^d = \Theta(n^d)$ if $a_d > 0$.

Logarithms. $O(\log_a n) = O(\log_b n)$ for any constants $a, b > 0$.

Logarithms. For every $x > 0$, $\log n = O(n^x)$.

Exponentials. For every $r > 1$ and every $d > 0$, $n^d = O(r^n)$.

Examples: Constant time $O(1)$

- **INSERT**(x, A) in an *unsorted* array A .
- **FINDMIN**(H) in a heap H .
- **FIND**(x, S) in a quick-find Union-Find structure S .

Examples: Logarithmic time $O(\log n)$

- **Binary search** in a *sorted* array.
- **SEARCH(x,T)** in a red-black tree T.
- **UNION, FIND** in a weighted quick-find Union-Find structure.

Examples: Linear time $O(n)$

- **FINDMAX(A)** in an *unsorted* array A.
- **Search** in a hash table with chaining.
- **BFS, DFS** run in time $O(N) = O(n + m)$

Examples: Linearithmic time $O(n \log n)$

- **Sorting.** MERGESORT and HEAPSORT make $O(n \log n)$ comparisons. We have shown that no comparison-based sorting alg makes fewer than $1/2(n \log n)$, hence MERGESORT and HEAPSORT make $\Theta(n \log n)$ comparisons.
- **MST** takes $O(m \log n)$ time by Kruskal's or Prim's alg.
- **DIJSTRA** runs in $O(m + n \log n)$ time.

Examples: Quadratic time $O(n^2)$

- Multiplication of $1 \times N$ vector with $N \times N$ matrix takes $O(N^2)$ arithmetic ops.
- QUICKSORT makes $O(n^2)$ comparisons in the worst case. It also requires $\Omega(n \log n)$ comparisons (notice the gap).

Examples: Cubic time $O(n^3)$

- **BELLMAN-FORD** is $O(n^3)$.
- **(Naive) multiplication of two $N \times N$ matrices** takes $O(N^3)$ arithmetic ops.

Examples: Cubic time $O(n^3)$

- **BELLMAN-FORD** is $O(n^3)$.
- **(Naive) multiplication of two $N \times N$ matrices** takes $O(N^3)$ arithmetic ops.

...but can do it with $O(N^{\log_2 7})$ ops with Strassen's alg **!!!**

Pseudo-polynomial time

Definition

pseudo /'sōdô/ *adj.* not genuine; sham.

Pseudo-polynomial time

Definition

pseudo /'sōdô/ *adj.* not genuine; sham.

Example:

INPUT: Integer n

OUTPUT: 'Yes' if n is prime

Pseudo-polynomial time

Definition

pseudo /'sōdô/ *adj.* not genuine; sham.

Example:

INPUT: Integer n

OUTPUT: 'Yes' if n is prime

Q: Algorithm: Divide n by $2, 3, \dots, \sqrt{n}$; if non evenly, then 'Yes'.
Is it polynomial?

Pseudo-polynomial time

Definition

pseudo /'sōdô/ *adj.* not genuine; sham.

Example:

INPUT: Integer n

OUTPUT: 'Yes' if n is prime

Q: Algorithm: Divide n by $2, 3, \dots, \sqrt{n}$; if non evenly, then 'Yes'.
Is it polynomial?

A: NO! The input size is $\log_2 n$

Pseudo-polynomial time

Definition

pseudo /'sōdô/ *adj.* not genuine; sham.

Example:

INPUT: Integer n

OUTPUT: 'Yes' if n is prime

Q: Algorithm: Divide n by $2, 3, \dots, \sqrt{n}$; if non evenly, then 'Yes'.
Is it polynomial?

A: NO! The input size is $\log_2 n$...and $n = 2^{\log_2 n}$ is **exponential** on the size of the input.

Pseudo-polynomial time

Definition

pseudo /'sōdô/ *adj.* not genuine; sham.

Example:

INPUT: Integer n

OUTPUT: 'Yes' if n is prime

Q: Algorithm: Divide n by $2, 3, \dots, \sqrt{n}$; if non evenly, then 'Yes'.
Is it polynomial?

A: NO! The input size is $\log_2 n$...and $n = 2^{\log_2 n}$ is **exponential** on the size of the input.

Bottom line: Always consider the input size! (stay tuned for flow algorithms, new appreciation for Dijkstra, Kruskal, Prim...)

Examples: Exponential time

Find a clique of size k in an undirected graph.

INPUT: Graph $G = (V, E)$, an integer k

OUTPUT: 'Yes' if there is a clique with k nodes

Examples: Exponential time

Find a clique of size k in an undirected graph.

INPUT: Graph $G = (V, E)$, an integer k

OUTPUT: 'Yes' if there is a clique with k nodes

Brute force: Try all $\binom{n}{k}$ subsets of V ; if clique found, output 'Yes'

Examples: Exponential time

Find a clique of size k in an undirected graph.

INPUT: Graph $G = (V, E)$, an integer k

OUTPUT: 'Yes' if there is a clique with k nodes

Brute force: Try all $\binom{n}{k}$ subsets of V ; if clique found, output 'Yes'

Running time: About $O(\binom{n}{k}) = O(k^2 \cdot n^k / k!) = O(n^k)$.

Examples: Exponential time

Find a clique of size k in an undirected graph.

INPUT: Graph $G = (V, E)$, an integer k

OUTPUT: 'Yes' if there is a clique with k nodes

Brute force: Try all $\binom{n}{k}$ subsets of V ; if clique found, output 'Yes'

Running time: About $O(\binom{n}{k}) = O(k^2 \cdot n^k / k!) = O(n^k)$.

In general, our algorithms search a huge (e.g., exponential on the size of the input) space for a solution; therefore, brute force searching takes exponential time (worst case).

Examples: Exponential time

Find a clique of size k in an undirected graph.

INPUT: Graph $G = (V, E)$, an integer k

OUTPUT: 'Yes' if there is a clique with k nodes

Brute force: Try all $\binom{n}{k}$ subsets of V ; if clique found, output 'Yes'

Running time: About $O(\binom{n}{k}) = O(k^2 \cdot n^k / k!) = O(n^k)$.

In general, our algorithms search a huge (e.g., exponential on the size of the input) space for a solution; therefore, brute force searching takes exponential time (worst case).

Big complexity problem: For many problems, our currently best is brute force. *Can we do better?*

The complexity class P

Efficient algorithms: Algorithms that run in polynomial time $O(n^d)$ are much better than brute force, and the only practical(?) ones (especially when the degree d is small, usually smaller than 3).

The complexity class P

Efficient algorithms: Algorithms that run in polynomial time $O(n^d)$ are much better than brute force, and the only practical(?) ones (especially when the degree d is small, usually smaller than 3).

Definition

A **complexity class** is a set of problems.

The complexity class P

Efficient algorithms: Algorithms that run in polynomial time $O(n^d)$ are much better than brute force, and the only practical(?) ones (especially when the degree d is small, usually smaller than 3).

Definition

A **complexity class** is a set of problems.

Example: All problems that can be solved by an algorithm belong to the class of **Decidable** problems. The HALTING problem doesn't belong to this class.

The complexity class P

Efficient algorithms: Algorithms that run in polynomial time $O(n^d)$ are much better than brute force, and the only practical(?) ones (especially when the degree d is small, usually smaller than 3).

Definition

A **complexity class** is a set of problems.

Example: All problems that can be solved by an algorithm belong to the class of **Decidable** problems. The HALTING problem doesn't belong to this class.

Definition

P is the class of all problems that can be solved by a polynomial algorithm.

The complexity class P

Efficient algorithms: Algorithms that run in polynomial time $O(n^d)$ are much better than brute force, and the only practical(?) ones (especially when the degree d is small, usually smaller than 3).

Definition

A **complexity class** is a set of problems.

Example: All problems that can be solved by an algorithm belong to the class of **Decidable** problems. The HALTING problem doesn't belong to this class.

Definition

P is the class of all problems that can be solved by a polynomial algorithm.

Example: Essentially all the problems we studied in CS 2C03 belong in **P**.

The complexity class P

Efficient algorithms: Algorithms that run in polynomial time $O(n^d)$ are much better than brute force, and the only practical(?) ones (especially when the degree d is small, usually smaller than 3).

Definition

A **complexity class** is a set of problems.

Example: All problems that can be solved by an algorithm belong to the class of **Decidable** problems. The HALTING problem doesn't belong to this class.

Definition

P is the class of all problems that can be solved by a polynomial algorithm.

Example: Essentially all the problems we studied in CS 2C03 belong in **P**. This is no coincidence: **P** is the set of problems that can be solved **efficiently**.

Why it matters

Table 2.1 The running times (rounded up) of different algorithms on inputs of increasing size, for a processor performing a million high-level instructions per second. In cases where the running time exceeds 10^{25} years, we simply record the algorithm as taking a very long time.

	n	$n \log_2 n$	n^2	n^3	1.5^n	2^n	$n!$
$n = 10$	< 1 sec	< 1 sec	< 1 sec	< 1 sec	< 1 sec	< 1 sec	4 sec
$n = 30$	< 1 sec	< 1 sec	< 1 sec	< 1 sec	< 1 sec	18 min	10^{25} years
$n = 50$	< 1 sec	< 1 sec	< 1 sec	< 1 sec	11 min	36 years	very long
$n = 100$	< 1 sec	< 1 sec	< 1 sec	1 sec	12,892 years	10^{17} years	very long
$n = 1,000$	< 1 sec	< 1 sec	1 sec	18 min	very long	very long	very long
$n = 10,000$	< 1 sec	< 1 sec	2 min	12 days	very long	very long	very long
$n = 100,000$	< 1 sec	2 sec	3 hours	32 years	very long	very long	very long
$n = 1,000,000$	1 sec	20 sec	12 days	31,710 years	very long	very long	very long

How to analyze algorithms

A typical algorithm:

How to analyze algorithms

A typical algorithm:

- 1 Algorithm makes some decision(s)

How to analyze algorithms

A typical algorithm:

- ① Algorithm makes some decision(s)
- ② Problem is broken into k subproblems (n_1, \dots, n_k)

How to analyze algorithms

A typical algorithm:

- ① Algorithm makes some decision(s)
- ② Problem is broken into k subproblems (n_1, \dots, n_k)
- ③ Solve k subproblems recursively

How to analyze algorithms

A typical algorithm:

- ① Algorithm makes some decision(s)
- ② Problem is broken into k subproblems (n_1, \dots, n_k)
- ③ Solve k subproblems recursively
- ④ Algorithm combines decision(s) from (1) with solutions from (3), to output solution

How to analyze algorithms

A typical algorithm:

- ① Algorithm makes some decision(s)
- ② Problem is broken into k subproblems (n_1, \dots, n_k)
- ③ Solve k subproblems recursively
- ④ Algorithm combines decision(s) from (1) with solutions from (3), to output solution

Recurrence: $T(n) = [\text{work done in (1),(2),(4)}] + \sum_{i=1}^k T(n_i)$

Divide-and-conquer algorithms

A typical D&C algorithm:

- ① Algorithm makes some decision(s)
- ② Divide: Problem is broken into k subproblems (n_1, \dots, n_k)
- ③ Conquer: Solve k subproblems recursively
- ④ Algorithm combines solutions from (3), to output solution

Divide-and-conquer algorithms

A typical D&C algorithm:

- ① Algorithm makes some decision(s)
- ② Divide: Problem is broken into k subproblems (n_1, \dots, n_k)
- ③ Conquer: Solve k subproblems recursively
- ④ Algorithm combines solutions from (3), to output solution

Recurrence: $T(n) = [\text{work done in (2),(4)}] + \sum_{i=1}^k T(n_i)$

Divide-and-conquer algorithms

Example of D&C: MERGESORT

- 1 Algorithm makes some decision(s)
- 2 MERGESORT($A[1..n/2]$), MERGESORT($A[n/2..n]$)
- 3 MERGE($A[1..n/2]$, $A[n/2..n]$)

Divide-and-conquer algorithms

Example of D&C: MERGESORT

- 1 Algorithm makes some decision(s)
- 2 MERGESORT($A[1..n/2]$), MERGESORT($A[n/2..n]$)
- 3 MERGE($A[1..n/2]$, $A[n/2..n]$)

Recurrence: $T(n) \leq cn + 2T(n/2)$, $T(1) = 0$

Solving recurrences

First method: unrolling the recurrence

Try to find the recurrence pattern by *unrolling* it:

$$T(n) \leq cn + 2T(n/2) \quad (\text{level 1})$$

$$\leq cn + (2c(n/2) + 4T(n/4)) = 2cn + 4T(n/4) \quad (\text{level 2})$$

$$\leq 2cn + (4c(n/4) + 8T(n/8)) = 3cn + 8T(n/8) \quad (\text{level 3})$$

...

$$\leq kcn + 2^k T(n/2^k) \quad (\text{level } k)$$

...

$$\leq (\log n)cn + 2^{\log n} T(n/2^{\log n}) = cn \log n \quad (\text{level } \log n)$$

Solving recurrences

First method: unrolling the recurrence

Try to find the recurrence pattern by *unrolling* it:

$$T(n) \leq cn + 2T(n/2) \quad (\text{level 1})$$

$$\leq cn + (2c(n/2) + 4T(n/4)) = 2cn + 4T(n/4) \quad (\text{level 2})$$

$$\leq 2cn + (4c(n/4) + 8T(n/8)) = 3cn + 8T(n/8) \quad (\text{level 3})$$

...

$$\leq kcn + 2^k T(n/2^k) \quad (\text{level } k)$$

...

$$\leq (\log n)cn + 2^{\log n} T(n/2^{\log n}) = cn \log n \quad (\text{level } \log n)$$

Theorem

$$T(n) = O(n \log n)$$

Solving recurrences

Second method: substitution

- 1 Try to guess the recurrence solution
- 2 Prove that substituting your guess for the recurrence verifies the guess

Solving recurrences

Second method: substitution

- 1 Try to guess the recurrence solution
- 2 Prove that substituting your guess for the recurrence verifies the guess

Example: $T(n) \leq cn + 2T(n/2)$, $T(1) = 0$

Solving recurrences

Second method: substitution

- 1 Try to guess the recurrence solution
- 2 Prove that substituting your guess for the recurrence verifies the guess

Example: $T(n) \leq cn + 2T(n/2)$, $T(1) = 0$

- 1 We guess that $T(n) = O(n \log n)$, i.e., $T(n) \leq kn \log n$ for some constant $k=?$

Solving recurrences

Second method: substitution

- 1 Try to guess the recurrence solution
- 2 Prove that substituting your guess for the recurrence verifies the guess

Example: $T(n) \leq cn + 2T(n/2)$, $T(1) = 0$

- 1 We guess that $T(n) = O(n \log n)$, i.e., $T(n) \leq kn \log n$ for some constant k (?)
- 2

$$\begin{aligned} T(n) &\leq cn + 2T(n/2) \\ &\leq cn + 2k(n/2) \log(n/2) \\ &= cn + kn(\log n - 1) \\ &= kn \log n + cn - kn \\ &\leq kn \log n \end{aligned}$$

...provided we pick a $k > c$.

Theorem (Master Theorem)

Let $a \geq 1, b > 1$ be constants, and

$$T(n) = aT(n/b) + f(n)$$

- ① $f(n) = O(n^{\log_b a - \epsilon})$ for constant $\epsilon > 0 \Rightarrow T(n) = \Theta(n^{\log_b a})$
- ② $f(n) = \Theta(n^{\log_b a}) \Rightarrow T(n) = \Theta(n^{\log_b a} \log n)$
- ③ $f(n) = \Omega(n^{\log_b a + \epsilon})$ for constant $\epsilon > 0$ and $af(n/b) \leq cf(n)$ for some constant $c < 1 \Rightarrow T(n) = \Theta(f(n))$

Theorem (Master Theorem)

Let $a \geq 1$, $b > 1$ be constants, and

$$T(n) = aT(n/b) + f(n)$$

- ① $f(n) = O(n^{\log_b a - \epsilon})$ for constant $\epsilon > 0 \Rightarrow T(n) = \Theta(n^{\log_b a})$
- ② $f(n) = \Theta(n^{\log_b a}) \Rightarrow T(n) = \Theta(n^{\log_b a} \log n)$
- ③ $f(n) = \Omega(n^{\log_b a + \epsilon})$ for constant $\epsilon > 0$ and $af(n/b) \leq cf(n)$ for some constant $c < 1 \Rightarrow T(n) = \Theta(f(n))$

Examples

- $T(n) = 2T(n/2) + \Theta(n)$

Theorem (Master Theorem)

Let $a \geq 1, b > 1$ be constants, and

$$T(n) = aT(n/b) + f(n)$$

- ① $f(n) = O(n^{\log_b a - \epsilon})$ for constant $\epsilon > 0 \Rightarrow T(n) = \Theta(n^{\log_b a})$
- ② $f(n) = \Theta(n^{\log_b a}) \Rightarrow T(n) = \Theta(n^{\log_b a} \log n)$
- ③ $f(n) = \Omega(n^{\log_b a + \epsilon})$ for constant $\epsilon > 0$ and $af(n/b) \leq cf(n)$ for some constant $c < 1 \Rightarrow T(n) = \Theta(f(n))$

Examples

- $T(n) = 2T(n/2) + \Theta(n)$
 $a = 2, b = 2, f(n) = \Theta(n) = \Theta(n^{\log_2 2})$
 $\Rightarrow T(n) = \Theta(n^{\log_2 2} \log n) = \Theta(n \log n)$ (Case 2)

Theorem (Master Theorem)

Let $a \geq 1, b > 1$ be constants, and

$$T(n) = aT(n/b) + f(n)$$

- ① $f(n) = O(n^{\log_b a - \epsilon})$ for constant $\epsilon > 0 \Rightarrow T(n) = \Theta(n^{\log_b a})$
- ② $f(n) = \Theta(n^{\log_b a}) \Rightarrow T(n) = \Theta(n^{\log_b a} \log n)$
- ③ $f(n) = \Omega(n^{\log_b a + \epsilon})$ for constant $\epsilon > 0$ and $af(n/b) \leq cf(n)$ for some constant $c < 1 \Rightarrow T(n) = \Theta(f(n))$

Examples

- $T(n) = T(2n/3) + \Theta(1)$

Theorem (Master Theorem)

Let $a \geq 1, b > 1$ be constants, and

$$T(n) = aT(n/b) + f(n)$$

- ① $f(n) = O(n^{\log_b a - \epsilon})$ for constant $\epsilon > 0 \Rightarrow T(n) = \Theta(n^{\log_b a})$
- ② $f(n) = \Theta(n^{\log_b a}) \Rightarrow T(n) = \Theta(n^{\log_b a} \log n)$
- ③ $f(n) = \Omega(n^{\log_b a + \epsilon})$ for constant $\epsilon > 0$ and $af(n/b) \leq cf(n)$ for some constant $c < 1 \Rightarrow T(n) = \Theta(f(n))$

Examples

- $T(n) = T(2n/3) + \Theta(1)$
 $a = 1, b = 3/2, f(n) = \Theta(1) = \Theta(n^{\log_{3/2} 1})$
 $\Rightarrow T(n) = \Theta(n^{\log_{3/2} 1} \log n) = \Theta(\log n)$ (Case 2)

Theorem (Master Theorem)

Let $a \geq 1, b > 1$ be constants, and

$$T(n) = aT(n/b) + f(n)$$

- ① $f(n) = O(n^{\log_b a - \epsilon})$ for constant $\epsilon > 0 \Rightarrow T(n) = \Theta(n^{\log_b a})$
- ② $f(n) = \Theta(n^{\log_b a}) \Rightarrow T(n) = \Theta(n^{\log_b a} \log n)$
- ③ $f(n) = \Omega(n^{\log_b a + \epsilon})$ for constant $\epsilon > 0$ and $af(n/b) \leq cf(n)$ for some constant $c < 1 \Rightarrow T(n) = \Theta(f(n))$

Examples

- $T(n) = 3T(n/4) + \Theta(n \log n)$

Theorem (Master Theorem)

Let $a \geq 1, b > 1$ be constants, and

$$T(n) = aT(n/b) + f(n)$$

- ① $f(n) = O(n^{\log_b a - \epsilon})$ for constant $\epsilon > 0 \Rightarrow T(n) = \Theta(n^{\log_b a})$
- ② $f(n) = \Theta(n^{\log_b a}) \Rightarrow T(n) = \Theta(n^{\log_b a} \log n)$
- ③ $f(n) = \Omega(n^{\log_b a + \epsilon})$ for constant $\epsilon > 0$ and $af(n/b) \leq cf(n)$ for some constant $c < 1 \Rightarrow T(n) = \Theta(f(n))$

Examples

- $T(n) = 3T(n/4) + \Theta(n \log n)$ $a = 3, b = 4, f(n) = n \log n = \Omega(n^{\log_4 3 + 0.2}), af(n/b) = 3(n/4) \log(n/4) \leq n \log n = 1 \cdot f(n)$

Theorem (Master Theorem)

Let $a \geq 1, b > 1$ be constants, and

$$T(n) = aT(n/b) + f(n)$$

- ① $f(n) = O(n^{\log_b a - \epsilon})$ for constant $\epsilon > 0 \Rightarrow T(n) = \Theta(n^{\log_b a})$
- ② $f(n) = \Theta(n^{\log_b a}) \Rightarrow T(n) = \Theta(n^{\log_b a} \log n)$
- ③ $f(n) = \Omega(n^{\log_b a + \epsilon})$ for constant $\epsilon > 0$ and $af(n/b) \leq cf(n)$ for some constant $c < 1 \Rightarrow T(n) = \Theta(f(n))$

Examples

- $T(n) = 3T(n/4) + \Theta(n \log n)$ $a = 3, b = 4, f(n) = n \log n = \Omega(n^{\log_4 3 + 0.2}), af(n/b) = 3(n/4) \log(n/4) \leq n \log n = 1 \cdot f(n) \Rightarrow T(n) = \Theta(n \log n)$ (Case 3)

Divide-and-conquer algorithms

A typical D&C algorithm:

- ① Algorithm makes some decision(s)
- ② Divide: Problem is broken into k subproblems (n_1, \dots, n_k)
- ③ Conquer: Solve k subproblems recursively
- ④ Algorithm combines solutions from (3), to output solution

Divide-and-conquer algorithms

A typical D&C algorithm:

- ① Algorithm makes some decision(s)
- ② Divide: Problem is broken into k subproblems (n_1, \dots, n_k)
- ③ Conquer: Solve k subproblems recursively
- ④ Algorithm combines solutions from (3), to output solution

Other examples of D&C: [QUICKSORT](#), [counting inversions](#), [integer multiplication](#), [closest points](#), ...