

EasySave 3.0 - Technical Support Information

Installation and runtime

- Client: EasySaveWpf.exe (.NET 10, Windows). Requires EasyLog.dll and CryptoSoft.dll beside the exe.
- Central log server: EasySaveLogServer (.NET 8) or Docker image from docker-compose.yml.
- Minimum: Windows 10+, read/write access to source and target paths and %AppData%.

Default file locations (%AppData%\EasySave\)

- settings.json - all user settings (language, formats, LogMode, server host:port, priorities, etc.).
- backup_jobs.json - list of backup jobs.
- state.json or state.xml - real-time status of all jobs (updated during backup).
- Logs\yyyy-MM-dd.json|.xml - local daily logs (EasyLog), when LogMode is Local or Both.

Centralized logging

- Server listens on TCP port 5132 (override: env EASYSAVE_LOG_PORT in Docker).
- Client setting DockerLogServerUrl: host:port (e.g. 192.168.1.10:5132). Protocol: length-prefixed JSON over TCP (not HTTP).
- Server writes one daily file per format: Logs/yyyy-MM-dd.json and/or .xml (machineName, userName, SenderIP on server).
- Docker: docker compose up - build; volume easysave_central_logs maps to /app/Logs in container.

Troubleshooting

- No central logs: verify server is running, firewall allows port 5132, LogMode is Centralized or Both.
- Access denied on copy: run as administrator or choose non-system source folders.
- Business software block: check process names in settings (e.g. Calculator for demo).