


Computer Science III
2024-III
WorkShop No. 1 — The Old Times

Eng. Carlos Andrés Sierra, M.Sc.
Computer Engineering
Universidad Distrital Francisco José de Caldas


1. For each of the following **languages**, define the corresponding **finite-state machine**:
 - (i) $\Sigma = \{0, 1, 2\}$. $L = (01^*2 \cup 2102)^*101(01 \cup 12 \cup 20)^*$.
 - (ii) $\Sigma = \{a, b, c\}$. $L = (abc \cup bca \cup cab)(abc \cup bca \cup cab)^*$.
 - (iii) $\Sigma = \{a, b, c\}$. $L = (abc \cup bca \cup cab)^*(abc \cup bca \cup cab)$.
 - (iv) $\Sigma = \{0, 1, 2\}$. $L = (01^*2 \cup 10^*2 \cup 21^*0)^*(01 \cup 12 \cup 20)^*101$.
2. For each one of the following **finite-state machines**, define the corresponding **regular expression** and a **generative grammar**:
 - (i) $\Sigma = \{0, 1\}$.



- (ii) $\Sigma = \{a, b, c\}$.

Carlos Andrés Sierra, Computer Engineer, M.Sc. on Computer Engineering, Titular Professor at Universidad Distrital Francisco José de Caldas.

Any comment or concern related to this document could be send to Carlos A. Sierra at e-mail: *cavir-guezs@udistrital.edu.co*



3. For each of the following **regular expressions**, define the corresponding **generative grammar** (all over the alphabet $\Sigma = \{a, b, c, d\}$):

- (i) $\{a^i b^j c^j d^i : i, j \geq 1\}$.
- (ii) $\{a^i b^i c^j d^j : i, j \geq 1\}$.
- (iii) $\{a^i b^j c^j d^i : i, j \geq 1\} \cup \{a^i b^i c^j d^j : i, j \geq 1\}$.
- (iv) $\{a^i b^j c^{i+j} : i \geq 0, j \geq 1\}$.

4. Be G a **context-free grammar** with the following productions:

$$G = \begin{cases} S \rightarrow ABC \mid BaC \mid aB \\ A \rightarrow Aa \mid a \\ B \rightarrow BAB \mid bab \\ C \rightarrow cC \mid \lambda \end{cases}$$

Found derivation trees for the following strings:

- (i) $w_1 = abab$.
 - (ii) $w_2 = babacc$.
 - (iii) $w_3 = ababababc$.
5. As follows there is a **context-free grammar** to generate **real numbers** without sign, the alphabet is $\Sigma = \{0, 1, 2, 3, 4, 5, 6, 7, 8, 9, ., +, -, E\}$:

$$\begin{aligned}
 \langle real \rangle &\rightarrow \langle digits \rangle \langle decimal \rangle \langle exp \rangle \\
 \langle digits \rangle &\rightarrow \langle digits \rangle \langle digits \rangle \mid 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9 \\
 \langle decimal \rangle &\rightarrow \langle digits \rangle \mid \lambda \\
 \langle exp \rangle &\rightarrow E \langle digits \rangle \mid E+ \langle digits \rangle \mid E- \langle digits \rangle \mid \lambda
 \end{aligned}$$

Define the derivation tree for the following strings:

- (i) $w_1 = 47.236$
- (ii) $w_2 = 321.25E + 35$

$$(iii) \ w_3 = 0.8E9$$

$$(iv) \ w_4 = 0.8E + 9$$

6. As follows there is a **context-free grammar** to generate **identifiers**, identifiers are strings of letters and digits, starting with a letter:

$$\begin{aligned} \langle identifier \rangle &\rightarrow \langle letter \rangle \langle lds \rangle \\ \langle lds \rangle &\rightarrow \langle letter \rangle \langle lds \rangle | \langle digit \rangle \langle lds \rangle | \lambda \\ \langle letter \rangle &\rightarrow a | b | c | \dots | x | y | z | A | B | C | \dots | X | Y | Z \\ \langle digit \rangle &\rightarrow 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 \end{aligned}$$

Define the derivation tree for the following names:

$$(i) \ w_1 = MyVariable$$

$$(ii) \ w_2 = temp2$$

$$(iii) \ w_3 = string2int$$

$$(iv) \ w_4 = 2NotAVariable$$

Deadline: Saturday, 5th of October, 2024, 18:00 (local time).