

# BACKEND & DATA LAYER

## Software Design Foundations

Author: Eng. Carlos Andrés Sierra, M.Sc.  
cavirguezs@udistrital.edu.co

Computer Engineer  
Lecturer  
Universidad Distrital Francisco José de Caldas

2024-III



UNIVERSIDAD DISTRITAL  
FRANCISCO JOSÉ DE CALDAS

# Outline

- 1 Data Layer
- 2 Backend Layer
- 3 Deployment



# Outline

- 1 Data Layer
- 2 Backend Layer
- 3 Deployment



# Data System Concepts

## Key Points of Data Systems:

- **Data modeling** is the process of designing the **structure** and organization of data.
- Data storage is the process of storing data in a structured or unstructured format.
- Data retrieval is the process of accessing and retrieving data from a storage system.
- Data manipulation is the process of modifying and **transforming** data.
- Data security is the process of protecting data from unauthorized access and ensuring its **integrity** and **confidentiality**.



# Data System Concepts

## Key Points of Data Systems:

- **Data modeling** is the process of designing the **structure** and organization of data.
- **Data storage** is the process of storing data in a structured or unstructured format.
- **Data retrieval** is the process of accessing and retrieving data from a storage system.
- **Data manipulation** is the process of modifying and **transforming** data.
- **Data security** is the process of protecting data from unauthorized access and ensuring its **integrity** and **confidentiality**.



# Data System Concepts

## Key Points of Data Systems:

- **Data modeling** is the process of designing the **structure** and organization of data.
- **Data storage** is the process of storing data in a structured or unstructured format.
- **Data retrieval** is the process of accessing and retrieving data from a storage system.
- **Data manipulation** is the process of modifying and **transforming** data.
- **Data security** is the process of protecting data from unauthorized access and ensuring its **integrity** and **confidentiality**.



# Data System Concepts

## Key Points of Data Systems:

- **Data modeling** is the process of designing the **structure** and organization of data.
- **Data storage** is the process of storing data in a structured or unstructured format.
- **Data retrieval** is the process of accessing and retrieving data from a storage system.
- **Data manipulation** is the process of modifying and **transforming** data.
- **Data security** is the process of protecting data from unauthorized access and ensuring its **integrity** and **confidentiality**.



# Data System Concepts

## Key Points of Data Systems:

- **Data modeling** is the process of designing the **structure** and organization of data.
- **Data storage** is the process of storing data in a structured or unstructured format.
- **Data retrieval** is the process of accessing and retrieving data from a storage system.
- **Data manipulation** is the process of modifying and **transforming** data.
- **Data security** is the process of protecting data from unauthorized access and ensuring its **integrity** and **confidentiality**.





# Relational Databases

- A **database management system** (DBMS) is a software system that uses a standard method to **store** and **retrieve** data.
- A **relational database management system** (RDBMS) is a type of database management system that stores data in a **structured format**, using rows and columns.
- An **entity-relationship diagram** (ERD) is a data modeling technique that graphically represents an **information** system's entities and the relationships between them.
- SQL is a **domain-specific language** used in programming and designed for managing data held in a **relational database management system**.



# Relational Databases

- A **database management system** (DBMS) is a software system that uses a standard method to **store** and **retrieve** data.
- A **relational database management system** (RDBMS) is a type of database management system that stores data in a **structured format**, using rows and columns.
- An **entity-relationship diagram** (ERD) is a data modeling technique that graphically represents an **information** system's entities and the relationships between them.
- SQL is a **domain-specific language** used in programming and designed for managing data held in a **relational database** management system.



# Relational Databases

- A **database management system** (DBMS) is a software system that uses a standard method to **store** and **retrieve** data.
- A **relational database management system** (RDBMS) is a type of database management system that stores data in a **structured format**, using rows and columns.
- An **entity-relationship diagram** (ERD) is a data modeling technique that graphically represents an **information** system's entities and the relationships between them.
- SQL is a **domain-specific language** used in programming and designed for managing data held in a **relational database management system**.



# Relational Databases

- A **database management system** (DBMS) is a software system that uses a standard method to **store** and **retrieve** data.
- A **relational database management system** (RDBMS) is a type of database management system that stores data in a **structured format**, using rows and columns.
- An **entity-relationship diagram** (ERD) is a data modeling technique that graphically represents an **information** system's entities and the relationships between them.
- SQL is a **domain-specific language** used in programming and designed for managing data held in a **relational database** management system.



# ER Diagrams

- An **entity-relationship diagram** (ERD) is a data modeling technique that graphically represents an **information** system's entities and the relationships between them.
- An **entity** is a real-world object or concept that has a **unique identity**, such as a person, place, or thing.
- An **attribute** is a **property** or characteristic of an entity, such as a person's name or age.
- A **relationship** is a **connection** between two or more **entities**, such as a person's relationship to a company or a product's relationship to a customer.
- A **cardinality** is a constraint that specifies the number of **instances** of one entity that can be associated with the number of instances of another entity.



# ER Diagrams

- An **entity-relationship diagram** (ERD) is a data modeling technique that graphically represents an **information** system's entities and the relationships between them.
- An **entity** is a real-world object or concept that has a **unique identity**, such as a person, place, or thing.
- An **attribute** is a **property** or characteristic of an entity, such as a person's name or age.
- A **relationship** is a **connection** between two or more **entities**, such as a person's relationship to a company or a product's relationship to a customer.
- A **cardinality** is a constraint that specifies the number of **instances** of one entity that can be associated with the number of instances of another entity.



# ER Diagrams

- An **entity-relationship diagram** (ERD) is a data modeling technique that graphically represents an **information** system's entities and the relationships between them.
- An **entity** is a real-world object or concept that has a **unique identity**, such as a person, place, or thing.
- An **attribute** is a **property** or characteristic of an entity, such as a person's name or age.
- A **relationship** is a **connection** between two or more **entities**, such as a person's relationship to a company or a product's relationship to a customer.
- A **cardinality** is a constraint that specifies the number of **instances** of one entity that can be associated with the number of instances of another entity.



# ER Diagrams

- An **entity-relationship diagram** (ERD) is a data modeling technique that graphically represents an **information** system's entities and the relationships between them.
- An **entity** is a real-world object or concept that has a **unique identity**, such as a person, place, or thing.
- An **attribute** is a **property** or characteristic of an entity, such as a person's name or age.
- A **relationship** is a **connection** between two or more **entities**, such as a person's relationship to a company or a product's relationship to a customer.
- A **cardinality** is a constraint that specifies the number of **instances** of one entity that can be associated with the number of instances of another entity.





# ER Diagrams

- An **entity-relationship diagram** (ERD) is a data modeling technique that graphically represents an **information** system's entities and the relationships between them.
- An **entity** is a real-world object or concept that has a **unique identity**, such as a person, place, or thing.
- An **attribute** is a **property** or characteristic of an entity, such as a person's name or age.
- A **relationship** is a **connection** between two or more **entities**, such as a person's relationship to a company or a product's relationship to a customer.
- A **cardinality** is a constraint that specifies the number of **instances** of one entity that can be associated with the number of instances of another entity.



# Study Case: ER Diagram for an Academic System



# Data Access Objects and Data Transfer Objects

**Data Access Objects** (DAOs) and **Data Transfer Objects** (DTOs) are design patterns used to separate the data access logic from the business logic in an application.

- A **Data Access Object** (DAO) is an object that provides **an abstract interface** to some type of database or other persistence mechanism.
- A **Data Transfer Object** (DTO) is an object that **carries data** between processes in an application.
- The **DAO pattern** is used to **separate the** data access logic from the business logic in an application.
- The **DTO pattern** is used to **transfer data** between processes in an application.



# Data Access Objects and Data Transfer Objects

**Data Access Objects** (DAOs) and **Data Transfer Objects** (DTOs) are design patterns used to separate the data access logic from the business logic in an application.

- A **Data Access Object** (DAO) is an object that provides **an abstract interface** to some type of database or other persistence mechanism.
- A **Data Transfer Object** (DTO) is an object that **carries data** between processes in an application.
- The **DAO pattern** is used to **separate the data access logic** from the business logic in an application.
- The **DTO pattern** is used to **transfer data** between processes in an application.



# Data Access Objects and Data Transfer Objects

**Data Access Objects** (DAOs) and **Data Transfer Objects** (DTOs) are design patterns used to separate the data access logic from the business logic in an application.

- A **Data Access Object** (DAO) is an object that provides **an abstract interface** to some type of database or other persistence mechanism.
- A **Data Transfer Object** (DTO) is an object that **carries data** between processes in an application.
- The **DAO pattern** is used to **separate the** data access logic from the business logic in an application.
- The **DTO pattern** is used to **transfer data** between processes in an application.



# Object-Relational Mapping

- **Object-Relational Mapping** (ORM) is a programming technique that **converts data** between incompatible type systems using object-oriented programming languages.
- An ORM framework is a tool that **automates** the process of **mapping** objects to relational databases.
- ORM frameworks include features such as **data validation**, **data retrieval**, and **data manipulation**.
- ORM frameworks lets you work with data in an **object-oriented way**, rather than in a relational way.



# Object-Relational Mapping

- **Object-Relational Mapping** (ORM) is a programming technique that **converts data** between incompatible type systems using object-oriented programming languages.
- An ORM framework is a tool that **automates** the process of **mapping** objects to relational databases.
- ORM frameworks include features such as **data validation**, **data retrieval**, and **data manipulation**.
- ORM frameworks lets you work with data in an **object-oriented way**, rather than in a relational way.



# PostgreSQL and SQLAlchemy

- **PostgreSQL** is a powerful, **open-source object-relational database** system.
- **SQLAlchemy** is an **open-source SQL toolkit** and Object-Relational Mapping (ORM) library for Python.
- **SQLAlchemy** provides a full suite of well-known **enterprise-level** persistence patterns, designed for efficient and high-performing database access.





# PostgreSQL and SQLAlchemy

- [PostgreSQL](#) is a powerful, **open-source object-relational database** system.
- [SQLAlchemy](#) is an **open-source SQL toolkit** and Object-Relational Mapping (ORM) library for Python.
- [SQLAlchemy](#) provides a full suite of well-known **enterprise-level** persistence patterns, designed for efficient and high-performing database access.



# Outline

- 1 Data Layer
- 2 Backend Layer
- 3 Deployment



# Backend Concepts

## Key Points of Backend Systems:

- A **backend system** is a software system that provides the **logic** and functionality to support the front-end of an application.
- A **backend system** typically consists of a **server**, a **database**, and an **application server**.
- A **server** is a computer that provides **services** to other computers over a network.
- An **application server** is a software framework that provides an environment for **running web applications**.
- A **database** is a collection of data that is **organized and stored** in a defined format.



# Backend Concepts

## Key Points of Backend Systems:

- A **backend system** is a software system that provides the **logic** and functionality to support the front-end of an application.
- A **backend system** typically consists of a server, a database, and an application server.
- A **server** is a computer that provides **services** to other computers over a network.
- An **application server** is a software framework that provides an environment for **running web applications**.
- A **database** is a collection of data that is **organized and stored** in a defined format.



# Backend Concepts

## Key Points of Backend Systems:

- A **backend system** is a software system that provides the **logic** and functionality to support the front-end of an application.
- A **backend system** typically consists of a server, a database, and an application server.
- A **server** is a computer that provides **services** to other computers over a network.
- An **application server** is a software framework that provides an environment for **running web applications**.
- A **database** is a collection of data that is **organized and stored** in a defined format.



# Backend Concepts

## Key Points of Backend Systems:

- A **backend system** is a software system that provides the **logic** and functionality to support the front-end of an application.
- A **backend system** typically consists of a server, a database, and an application server.
- A **server** is a computer that provides **services** to other computers over a network.
- An **application server** is a software framework that provides an environment for **running web applications**.
- A **database** is a collection of data that is **organized and stored** in a defined format.



# Backend Concepts

## Key Points of Backend Systems:

- A **backend system** is a software system that provides the **logic** and functionality to support the front-end of an application.
- A **backend system** typically consists of a server, a database, and an application server.
- A **server** is a computer that provides **services** to other computers over a network.
- An **application server** is a software framework that provides an environment for **running web applications**.
- A **database** is a collection of data that is **organized and stored** in a defined format.



# Connection with Data Layer

- The **backend layer** is responsible for managing the **data layer** and providing the logic and functionality to support the front-end of an application.
- The **connection** between the backend and data layers is typically managed through an **application programming interface (API)**.
- An **API** is a set of **rules** and protocols that allows different software applications to **communicate** with each other.
- The **API provides** a way for the front-end of an application to interact with the backend and access the data stored in the database.
- **ORM frameworks** such as SQLAlchemy are often used to manage the **connection** between the backend and data layers.





# Connection with Data Layer

- The **backend layer** is responsible for managing the **data layer** and providing the logic and functionality to support the front-end of an application.
- The **connection** between the backend and data layers is typically managed through an **application programming interface** (API).
- An **API** is a set of **rules** and protocols that allows different software applications to **communicate** with each other.
- The **API provides** a way for the front-end of an application to interact with the backend and access the data stored in the database.
- **ORM frameworks** such as SQLAlchemy are often used to manage the **connection** between the backend and data layers.



# Connection with Data Layer

- The **backend layer** is responsible for managing the **data layer** and providing the logic and functionality to support the front-end of an application.
- The **connection** between the backend and data layers is typically managed through an **application programming interface** (API).
- An **API** is a set of **rules** and protocols that allows different software applications to **communicate** with each other.
- The **API provides** a way for the front-end of an application to interact with the backend and access the data stored in the database.
- **ORM frameworks** such as SQLAlchemy are often used to manage the **connection** between the backend and data layers.



# Connection with Data Layer

- The **backend layer** is responsible for managing the **data layer** and providing the logic and functionality to support the front-end of an application.
- The **connection** between the backend and data layers is typically managed through an **application programming interface** (API).
- An **API** is a set of **rules** and protocols that allows different software applications to **communicate** with each other.
- The **API provides** a way for the front-end of an application to interact with the backend and access the data stored in the database.
- **ORM frameworks** such as SQLAlchemy are often used to manage the **connection** between the backend and data layers.



# Connection with Data Layer

- The **backend layer** is responsible for managing the **data layer** and providing the logic and functionality to support the front-end of an application.
- The **connection** between the backend and data layers is typically managed through an **application programming interface** (API).
- An **API** is a set of **rules** and protocols that allows different software applications to **communicate** with each other.
- The **API provides** a way for the front-end of an application to interact with the backend and access the data stored in the database.
- **ORM frameworks** such as SQLAlchemy are often used to manage the **connection** between the backend and data layers.



# Domain-Driven Design

- **Domain-Driven Design** (DDD) is an approach to software development that focuses on the **core domain** and domain logic of an application.
- The **core domain** is the main focus of the application and represents the **key concepts** and entities that the application is designed to manage.
- **DDD domain layer** is divided into **domain objects**, which represent the core concepts and entities of the application.
- **DDD application layer** is divided into **services**, which are responsible for coordinating the domain objects and implementing the application logic.
- **DDD infrastructure layer** is responsible for managing the **connection** between the application and the external systems, such as the database or data repositories.



# Domain-Driven Design

- **Domain-Driven Design** (DDD) is an approach to software development that focuses on the **core domain** and domain logic of an application.
- The **core domain** is the main focus of the application and represents the **key concepts** and entities that the application is designed to manage.
- DDD domain layer is divided into **domain objects**, which represent the core concepts and entities of the application.
- DDD application layer is divided into **services**, which are responsible for coordinating the domain objects and implementing the application logic.
- DDD infrastructure layer is responsible for managing the **connection** between the application and the external systems, such as the database or data repositories.



# Domain-Driven Design

- **Domain-Driven Design** (DDD) is an approach to software development that focuses on the **core domain** and domain logic of an application.
- The **core domain** is the main focus of the application and represents the **key concepts** and entities that the application is designed to manage.
- **DDD domain layer** is divided into **domain objects**, which represent the core concepts and entities of the application.
- **DDD application layer** is divided into **services**, which are responsible for coordinating the domain objects and implementing the application logic.
- **DDD infrastructure layer** is responsible for managing the **connection** between the application and the external systems, such as the database or data repositories.



# Domain-Driven Design

- **Domain-Driven Design** (DDD) is an approach to software development that focuses on the **core domain** and domain logic of an application.
- The **core domain** is the main focus of the application and represents the **key concepts** and entities that the application is designed to manage.
- **DDD domain layer** is divided into **domain objects**, which represent the core concepts and entities of the application.
- **DDD application layer** is divided into **services**, which are responsible for coordinating the domain objects and implementing the application logic.
- **DDD infrastructure layer** is responsible for managing the **connection** between the application and the external systems, such as the database or data repositories.





# Domain-Driven Design

- **Domain-Driven Design** (DDD) is an approach to software development that focuses on the **core domain** and domain logic of an application.
- The **core domain** is the main focus of the application and represents the **key concepts** and entities that the application is designed to manage.
- **DDD domain layer** is divided into **domain objects**, which represent the core concepts and entities of the application.
- **DDD application layer** is divided into **services**, which are responsible for coordinating the domain objects and implementing the application logic.
- **DDD infrastructure layer** is responsible for managing the **connection** between the application and the external systems, such as the database or data repositories.



# Sockets

- A **socket** is an **endpoint** for communication between two machines over a network.
- A **socket** is a **software** structure that allows two machines to **exchange data** over a network.
- A **socket** is identified by an **IP address** and a **port number**.



# RESTful APIs

- A **Representational State Transfer** (REST) is an **architectural style** that defines a set of constraints for creating web services.
- A **RESTful API** is an API that follows the principles of REST and uses **HTTP methods** to perform operations on resources.
- **RESTful APIs** use standard **HTTP headers**, such as Content-Type, Accept, and Authorization, to provide additional information about a request or response.
- **RESTful APIs** are typically used to build **web services** that can be accessed by other applications over the internet.



# RESTful APIs

- A **Representational State Transfer** (REST) is an **architectural style** that defines a set of constraints for creating web services.
- A **RESTful API** is an API that follows the principles of REST and uses **HTTP methods** to perform operations on resources.
- **RESTful APIs** use standard **HTTP headers**, such as Content-Type, Accept, and Authorization, to provide additional information about a request or response.
- **RESTful APIs** are typically used to build **web services** that can be accessed by other applications over the internet.



# RESTful APIs

- A **Representational State Transfer** (REST) is an **architectural style** that defines a set of constraints for creating web services.
- A **RESTful API** is an API that follows the principles of REST and uses **HTTP methods** to perform operations on resources.
- **RESTful APIs** use standard **HTTP headers**, such as Content-Type, Accept, and Authorization, to provide additional information about a request or response.
- **RESTful APIs** are typically used to build **web services** that can be accessed by other applications over the internet.



# RESTful APIs

- A **Representational State Transfer** (REST) is an **architectural style** that defines a set of constraints for creating web services.
- A **RESTful API** is an API that follows the principles of REST and uses **HTTP methods** to perform operations on resources.
- **RESTful APIs** use standard **HTTP headers**, such as Content-Type, Accept, and Authorization, to provide additional information about a request or response.
- **RESTful APIs** are typically used to build **web services** that can be accessed by other applications over the internet.



# HTTP Methods

- The **Hypertext Transfer Protocol** (HTTP) is a protocol that defines how data is transmitted over the **internet**.
- **HTTP methods** are used to perform operations on resources, such as retrieving, creating, updating, or deleting data (**CRUD**).
- The most common **HTTP methods** are GET, POST, PUT, PATCH, and DELETE.
  - GET is used to retrieve data from a server.
  - POST is used to create new data on a server.
  - PUT is used to update existing data on a server.
  - PATCH is used to partially update existing data on a server.
  - DELETE is used to delete data from a server.



# HTTP Methods

- The **Hypertext Transfer Protocol** (HTTP) is a protocol that defines how data is transmitted over the **internet**.
- **HTTP methods** are used to perform operations on resources, such as retrieving, creating, updating, or deleting data (**CRUD**).
- The most common **HTTP methods** are GET, POST, PUT, PATCH, and DELETE.
  - **GET** is used to **retrieve** data from a server.
  - **POST** is used to **create** new data on a server.
  - **PUT** is used to **update** existing data on a server.
  - **PATCH** is used to **partially update** existing data on a server.
  - **DELETE** is used to **delete** data from a server.





# HTTP Codes

- **HTTP status codes** are standard response codes given by **web servers** on the internet.
- The status codes are divided into five categories:
  - 1xx Informational — Request received, continuing process.
  - 2xx Success — The action was successfully received, understood, and accepted.
  - 3xx Redirection — Further action must be taken to complete the request.
  - 4xx Client Error — The request contained invalid data or cannot be fulfilled.
  - 5xx Server Error — The server failed to fulfil an apparently valid request.



# HTTP Codes

- **HTTP status codes** are standard response codes given by **web servers** on the internet.
- The status codes are divided into five categories:
  - **1xx: Informational** — Request received, continuing process.
  - **2xx: Success** — The action was successfully received, understood, and accepted.
  - **3xx: Redirection** — Further action must be taken to complete the request.
  - **4xx: Client Error** — The request contains bad syntax or cannot be fulfilled.
  - **5xx: Server Error** — The server failed to fulfill an apparently valid request.



# HTTP Codes

- **HTTP status codes** are standard response codes given by **web servers** on the internet.
- The status codes are divided into five categories:
  - **1xx: Informational** — Request received, continuing process.
  - **2xx: Success** — The action was successfully received, understood, and accepted.
  - **3xx: Redirection** — Further action must be taken to complete the request.
  - **4xx: Client Error** — The request contains bad syntax or cannot be fulfilled.
  - **5xx: Server Error** — The server failed to fulfill an apparently valid request.



# HTTP Codes

- **HTTP status codes** are standard response codes given by **web servers** on the internet.
- The status codes are divided into five categories:
  - **1xx: Informational** — Request received, continuing process.
  - **2xx: Success** — The action was successfully received, understood, and accepted.
  - **3xx: Redirection** — Further action must be taken to complete the request.
  - **4xx: Client Error** — The request contains bad syntax or cannot be fulfilled.
  - **5xx: Server Error** — The server failed to fulfill an apparently valid request.



# HTTP Codes

- **HTTP status codes** are standard response codes given by **web servers** on the internet.
- The status codes are divided into five categories:
  - **1xx: Informational** — Request received, continuing process.
  - **2xx: Success** — The action was successfully received, understood, and accepted.
  - **3xx: Redirection** — Further action must be taken to complete the request.
  - **4xx: Client Error** — The request contains bad syntax or cannot be fulfilled.
  - **5xx: Server Error** — The server failed to fulfill an apparently valid request.



# HTTP Codes

- **HTTP status codes** are standard response codes given by **web servers** on the internet.
- The status codes are divided into five categories:
  - **1xx: Informational** — Request received, continuing process.
  - **2xx: Success** — The action was successfully received, understood, and accepted.
  - **3xx: Redirection** — Further action must be taken to complete the request.
  - **4xx: Client Error** — The request contains bad syntax or cannot be fulfilled.
  - **5xx: Server Error** — The server failed to fulfill an apparently valid request.



# FastAPI

- **FastAPI** is a modern, fast (high-performance), **web framework** for building APIs with Python 3.6+.
- **FastAPI** is based on standard Python **type hints**, which makes it easy to use and understand.
- **FastAPI** is designed to be easy to use and understand, with a focus on **performance and scalability**.
- **FastAPI** is built on top of Starlette for the web parts and Pydantic for the data parts.
- **FastAPI** could use RPC (Remote Procedure Call) to improve the performance of the API.



# FastAPI

- **FastAPI** is a modern, fast (high-performance), **web framework** for building APIs with Python 3.6+.
- **FastAPI** is based on standard Python **type hints**, which makes it easy to use and understand.
- **FastAPI** is designed to be easy to use and understand, with a focus on **performance and scalability**.
- **FastAPI** is built on top of Starlette for the web parts and Pydantic for the data parts.
- **FastAPI** could use RPC (Remote Procedure Call) to improve the performance of the API.





# FastAPI

- **FastAPI** is a modern, fast (high-performance), **web framework** for building APIs with Python 3.6+.
- **FastAPI** is based on standard Python **type hints**, which makes it easy to use and understand.
- **FastAPI** is designed to be easy to use and understand, with a focus on **performance and scalability**.
- **FastAPI** is built on top of Starlette for the web parts and Pydantic for the data parts.
- **FastAPI** could use RPC (Remote Procedure Call) to improve the performance of the API.



# FastAPI

- **FastAPI** is a modern, fast (high-performance), **web framework** for building APIs with Python 3.6+.
- **FastAPI** is based on standard Python **type hints**, which makes it easy to use and understand.
- **FastAPI** is designed to be easy to use and understand, with a focus on **performance and scalability**.
- **FastAPI** is built on top of Starlette for the web parts and Pydantic for the data parts.
- **FastAPI** could use RPC (Remote Procedure Call) to improve the performance of the API.



# FastAPI

- **FastAPI** is a modern, fast (high-performance), **web framework** for building APIs with Python 3.6+.
- **FastAPI** is based on standard Python **type hints**, which makes it easy to use and understand.
- **FastAPI** is designed to be easy to use and understand, with a focus on **performance and scalability**.
- **FastAPI** is built on top of Starlette for the web parts and Pydantic for the data parts.
- **FastAPI** could use RPC (Remote Procedure Call) to improve the performance of the API.



# Postman

- **Postman** is a collaboration **platform** for API development that allows you to design, build, and test APIs.
- **Postman** provides a user-friendly interface for creating and managing API **requests**.
- **Postman** allows you to create **collections** of API requests, which can be shared with other team members.
- **Postman** provides a powerful **testing environment** for running automated tests on your APIs.
- **Postman** provides a variety of tools for **debugging** and troubleshooting API requests.



# Postman

- **Postman** is a collaboration **platform** for API development that allows you to design, build, and test APIs.
- **Postman** provides a user-friendly interface for creating and managing **API requests**.
- **Postman** allows you to create **collections** of API requests, which can be shared with other team members.
- **Postman** provides a powerful **testing environment** for running automated tests on your APIs.
- **Postman** provides a variety of tools for **debugging** and troubleshooting API requests.



# Postman

- **Postman** is a collaboration **platform** for API development that allows you to design, build, and test APIs.
- **Postman** provides a user-friendly interface for creating and managing **API requests**.
- **Postman** allows you to create **collections** of API requests, which can be shared with other team members.
- **Postman** provides a powerful **testing environment** for running automated tests on your APIs.
- **Postman** provides a variety of tools for **debugging** and troubleshooting API requests.



# Postman

- **Postman** is a collaboration **platform** for API development that allows you to design, build, and test APIs.
- **Postman** provides a user-friendly interface for creating and managing API **requests**.
- **Postman** allows you to create **collections** of API requests, which can be shared with other team members.
- **Postman** provides a powerful **testing environment** for running automated tests on your APIs.
- **Postman** provides a variety of tools for **debugging** and troubleshooting API requests.



# Postman

- **Postman** is a collaboration **platform** for API development that allows you to design, build, and test APIs.
- **Postman** provides a user-friendly interface for creating and managing API **requests**.
- **Postman** allows you to create **collections** of API requests, which can be shared with other team members.
- **Postman** provides a powerful **testing environment** for running automated tests on your APIs.
- **Postman** provides a variety of tools for **debugging** and troubleshooting API requests.





# Outline

- 1 Data Layer
- 2 Backend Layer
- 3 Deployment



# Containers & Docker

- A **Container** is a standard unit of software that **packages up code** and all its dependencies so the application runs quickly and reliably from one computing environment to another.
- A **Docker** is a platform for developing, shipping, and running **applications in containers**.
- A **Dockerfile** is a text document that contains all the commands a user could call on the command line to **assemble a docker image**.
- A **Docker image** is a file that contains all the necessary **files and dependencies** to run a container.



# Containers & Docker

- A **Container** is a standard unit of software that **packages up code** and all its dependencies so the application runs quickly and reliably from one computing environment to another.
- A **Docker** is a platform for developing, shipping, and running **applications in containers**.
- A **Dockerfile** is a text document that contains all the commands a user could call on the command line to **assemble a docker image**.
- A **Docker image** is a file that contains all the necessary **files and dependencies** to run a container.



# Containers & Docker

- A **Container** is a standard unit of software that **packages up code** and all its dependencies so the application runs quickly and reliably from one computing environment to another.
- A **Docker** is a platform for developing, shipping, and running **applications in containers**.
- A **Dockerfile** is a text document that contains all the commands a user could call on the command line to **assemble a docker image**.
- A **Docker image** is a file that contains all the necessary **files and dependencies** to run a container.



# Containers & Docker

- A **Container** is a standard unit of software that **packages up code** and all its dependencies so the application runs quickly and reliably from one computing environment to another.
- A **Docker** is a platform for developing, shipping, and running **applications in containers**.
- A **Dockerfile** is a text document that contains all the commands a user could call on the command line to **assemble a docker image**.
- A **Docker image** is a file that contains all the necessary **files and dependencies** to run a container.



# Docker Compose

- **Docker Compose** is a tool for defining and running **multi-container Docker applications**.
- With **Docker Compose**, you use a **YAML** file to configure your application's services.
- Then, with a **single command**, you create and start **all the services** from your configuration.



# Docker Compose

- **Docker Compose** is a tool for defining and running **multi-container Docker applications**.
- With **Docker Compose**, you use a YAML file to configure your application's services.
- Then, with a **single command**, you create and start **all the services** from your configuration.



# Docker Compose

- **Docker Compose** is a tool for defining and running **multi-container Docker applications**.
- With **Docker Compose**, you use a YAML file to configure your application's services.
- Then, with a **single command**, you create and start **all the services** from your configuration.





# Outline

- 1 Data Layer
- 2 Backend Layer
- 3 Deployment



# Thanks!

## Questions?



Repo: <https://github.com/EngAndres/ud-public/tree/main/courses/software-modeling>

