

NAVIGATING THE PLATFORM

TABLE OF CONTENTS

Introduction.....	2
Logging In	2
Navigating the End-User Interface	3
Dojos & Challenges	3
Challenge Desktop	5
Challenge Workspace.....	5
Navigating the Admin Panel	6
Users	6
Config	7
Desktops	8
Adding a Challenge	8
Navigating the Containers	9
Docker Commands.....	9
Root Container	10
Nested Containers.....	10

INTRODUCTION

PwnIoT is a Capture the Flag (CTF) web-based platform based on pwncollege¹, which itself is based on the CTFd platform². The purpose of the platform is to allow users access to specific operating systems directly on the website, in order to complete coding or administrative challenges on those systems. PwnIoT in particular focuses its challenges on Internet of Things (IoT) devices.

LOGGING IN

The default username and password after installation will be “admin” and “admin”, respectively.

¹ <https://pwn.college>

² <https://ctfd.io>

NAVIGATING THE END-USER INTERFACE


The live version can be accessed here: <http://pwniot.cacti.academy>

After local installation (see “Installing PwnIoT Locally” documentation), navigating to <http://localhost> will show the local version.

DOJOS & CHALLENGES




Dojos can be accessed by clicking the “Dojos” link at in the top menu bar.



A dojo is a collection of challenge modules. Clicking on any dojo will show its modules.




Likewise, each module is a collection of challenges. Clicking on any module will list its challenges.



Clicking each challenge will display some options:


- **Start:** initiate the challenge, which will also start the challenge container. The user will have access to the container as an unprivileged user.
- **Practice:** this is the same as "Start", but the user will instead have privileged access to the container. This will allow them to run administrative commands that they otherwise would not be able to.
- **Flag:** when a challenge is completed successfully, the user is presented with a flag. Submitting the flag in this textbox will mark the challenge as complete.

CHALLENGE DESKTOP



When a challenge is started, the user may navigate to the “Desktop” link in the top menu bar. This will display the user’s current working container. It is here that the user can complete the challenge using a desktop environment. Note that the home directory of the user is shared across all challenges.


CHALLENGE WORKSPACE



In addition to the desktop, clicking the “Workspace” link in the top menu bar will show the user an embedded VSCode instance that is connected to the challenge container, including via the terminal. This allows the user to complete the challenge without using the desktop environment.

NAVIGATING THE ADMIN PANEL

Log in as an administrator (see [Logging In](#)) by clicking “Login” in the top menu bar.



After logging in, click the “Admin Panel” link that is now available in the top menu bar. This will take you to the home page of the admin panel. The primary sections useful for development will be within the “Users”, “Config”, and “Desktop” pages.

USERS

Users +

Name Search for matching users

<input type="checkbox"/>	ID	User	Email	Country	Admin	Verified	Hidden	Banned
<input type="checkbox"/>	1	admin	admin@example.com		admin	verified	hidden	

Clicking “Users” in the top bar will list all the users that are registered.

Create User

User Name

Email

Password

Website Optional

Affiliation Optional

Country Optional

User ▼ ☐ Verified ☐ Hidden ☐ Banned

[Submit](#)

Clicking the “+” icon will show the user-creation form. Creating new users can be important for testing. As well, the user may have their role set between “User” and “Admin”; an admin may add new challenges, which can be useful for additional testing.

CONFIG

Configuration

[Appearance](#)
Theme
Accounts
Custom Fields
MajorLeagueCyber
Settings
Security
Email
Time
Legal
Backup
User Mode
Reset


Competition Name
Competition name displayed instead of a logo

CTF Description
Description for the CTF

[Update](#)

Clicking on “Config” in the top menu bar will display all the site-wide settings for the whole platform.

DESKTOPS



Clicking on "Desktops" in the top menu bar will list all of the active challenge containers. Clicking on any one of them will log you into that container.

ADDING A CHALLENGE



As an administrator, viewing the "Dojos" page from the end-user panel (not the "Dojos" page within the admin panel) will show a "+" icon that will allow you to add a new challenge.

A screenshot of a "Create Dojo" form. It has a dark background with green text. The form includes a "GitHub Repository" field with a URL, a "Deploy Key" field with a long alphanumeric string, and a "Create" button at the bottom right.

Note: The default suggested input of "pwncollege/example-dojo" will fail to install, as the codebase for PwnIoT has diverged from the original pwncollege codebase. A working example can be installed with "mjkrooz/example-dojo".

NAVIGATING THE CONTAINERS

DOCKER COMMANDS

The following Docker commands will be useful in navigating the containers.

- List the containers that are currently running:

```
docker container ls
```

- List the images that were created that the containers are based off of:

```
docker images
```

- Start and stop the root container, named "pwniot.academy":

```
docker container start pwniot.academy  
docker container stop pwniot.academy
```

- Enter a bash shell based on the name of the container:

```
docker container exec -it <container_name> bash
```

e.g.

```
docker container exec -it pwniot.academy bash
```

- Remove a container based on its name:

```
docker container rm <container_name>
```

- Remove an image based on its name. This may fail if stopped containers are being used by it, but it will list those containers which can then be removed by the previous command:

```
docker rmi <image_name>
```

ROOT CONTAINER

```
pwniot@pwniot2:~$ docker container ls
CONTAINER ID   IMAGE          COMMAND                  CREATED        STATUS        PORTS                               NAMES
6c10b9280ddf   pwniot.academy "dojo start"            3 weeks ago   Up 4 days    0.0.0.0:22->22/tcp, :::22->22/tcp, 0.0.0.0:80->80/tcp, :::80->80/tcp, 0.0.0.0:443->443/tcp, :::443->443/tcp   pwniot.academy
pwniot@pwniot2:~$
```

After installing locally, open a terminal. Use the `docker` command to list the containers to see that there will be a single docker container instance running.

```
pwniot@pwniot2:~$ docker container exec -it pwniot.academy bash
root@6c10b9280ddf:/opt/pwn.college#
```

A shell into the root container can be created and entered using the `exec` argument.

NESTED CONTAINERS

```
root@6c10b9280ddf:/opt/pwn.college# docker container ls
CONTAINER ID   IMAGE          COMMAND                  CREATED        STATUS        PORTS                               NAMES
f4a1bb1a8c06   pwncollege-challenge "/bin/sleep 6h"         52 minutes ago Up 52 minutes                               user_1
3ce44ec3350a   pwncollege-ctfd   "/bin/sh -c '[' \"dev... 4 days ago    Up 4 days (healthy)   8000/tcp              ctfd
c49b1a1d6330   nginxproxy/acme-companion "/bin/bash /app/entr... 2 months ago   Up 4 days                               nginx_certs
3f82185b3b18   mariadb:10.4.12   "docker-entrypoint.s..." 2 months ago   Up 4 days                               db
dalfad1dd3bc   redis:4           "docker-entrypoint.s..." 2 months ago   Up 4 days                               cache
5a75105328f3   nginxproxy/nginx-proxy "/app/docker-entryp... 2 months ago   Up 4 days             0.0.0.0:80->80/tcp, 0.0.0.0:443->443/tcp   nginx
root@6c10b9280ddf:/opt/pwn.college#
```

Within the root container are a set of additional containers that each serve a particular purpose:

- **ctfd**: this is the primary web server for the web interface. It includes the admin panel source code as well.
- **db**: the MySQL server that acts as the database for the web server.
- **cache**: a caching server running Redis.
- **nginx**: a reverse proxy based off of `nginx-proxy`³ that serves as the primary entry-point to the web server.
- **nginx_certs**: an instance of Acme Companion⁴ that accompanies `nginx-proxy`, and is used for SSL certificate generation.
- **"user_#"**: a currently-running challenge container for a particular user.

Each can be entered using their name. For example, entering the "db" container is done as follows:

```
docker exec -it db bash
```

³ <https://github.com/nginx-proxy/nginx-proxy>

⁴ <https://hub.docker.com/r/nginxproxy/acme-companion>