Canting calculation: changes

The governing equations and material parameters are unchanged.

- Mesh: create each `Gmsh` mesh once, then use custom `radial mesh motion` with fixed connectivity. This removes repeated remeshing and the resulting jumps in computed gradients.

- Field solves: recover continuous gradients using `L2 projection`; interpolate boundary pressure using a `periodic cubic spline`. Use `LU factorization` for the linear systems and reuse the FEM setup.

- Resolution: increase contact-line nodes from 20 to 80, use cubic FEM fields, and decrease mesh size from 0.60 to 0.30 mm. Keep `BDF` time integration, with tolerances $(\mathrm{rtol}, \mathrm{atol}) = (10^{-6}, 10^{-8})$; enforce left/right symmetry.

- Curvature: use `centered finite differences` along the contact line $\mathbf{r}(s,t)$, avoiding second time derivatives of trajectory splines:

$$D_s f_i = \frac{f_{i+1} - f_{i-1}}{2\Delta s}, \qquad \mathbf{T} = D_s \mathbf{r}, \qquad \mathbf{v} = \sigma(\theta)\mathbf{n},$$
$$\alpha = K_\alpha \kappa, \qquad \kappa = \frac{\mathbf{T} \times D_s \mathbf{v}}{|\mathbf{T}|^2 \, |\sigma(\theta)|}.$$

  Here $\times$ denotes the scalar two-dimensional cross product. Exclude nearly stationary samples, where curvature is unreliable.

- Averaging: use a `Gaussian kernel` and the `trapezoidal rule` for a spatial mean, replacing the time-sample-weighted robust average. For mirror-paired samples $(+,-)$, with α in radians and x in mm,

$$g_k = \frac{180}{\pi} \frac{\alpha_{k,+} - \alpha_{k,-}}{x_{k,+} - x_{k,-}}, \qquad g = \frac{\sum_k W_k g_k}{\sum_k W_k},$$
$$W_k = \exp\left[-\frac{|\mathbf{r}_k - \mathbf{r}_0|^2}{2\ell^2}\right] |\sigma_k| \, |\mathbf{T}_k| \, \omega_k, \qquad \ell = 0.30\,\mathrm{mm}.$$

  Here ω_k is the trapezoidal time weight; the constant material-node spacing cancels. The evaluation point remains $\mathbf{r}_0 = (1.35,\, 2.7\cos(\pi/6))\,\mathrm{mm}$. Post-processing-only error bars are $\Delta g = (\max g_{\mathrm{variants}} - \min g_{\mathrm{variants}})/2$, varying kernel width, stationary-speed cutoff, and saved-sample spacing.

- More runs: increase from 9 to 24 independently simulated heights, concentrated around the bend. Use `process parallelism` with six workers and one numerical-library thread per worker. Reuse matching completed runs, resume checkpoints, and skip completed cases. The black curve is a separate `nonlinear least squares` fit; no smoothing across heights is applied to the simulation points.