Results Compendium

AIM-2 food intake detection, ETS dataset. Caelan Dunlea, 4 November 2026.

Every result for the paper in one place, with the run it comes from and its caveats. Reference material for writing, not paper text. Section 10 lists what must be recomputed or confirmed before submission.

Conventions used throughout

- Leave-one-subject-out (LOSO): 43 folds, each holding out one participant with all of their sessions; 5 of the remaining participants choose early stopping and the threshold.
- Pooled metrics are computed over all held-out windows together; participant metrics are computed per participant, then summarized.
- Windows are 8 s. Training uses a 4 s hop; every score uses non-overlapping windows set up per session.
- “Final configuration” is the frozen setup with 5 validation participants, run with 3 seeds. “Reference configuration” is the earlier 2-validation-participant setup; numbers from it are marked.

1. Dataset

Table 1. Dataset summary.

Item	Value
Participants	43
Sessions	61: breakfast 8, lunch 18, dinner 12, snack 23
Sessions with eating	60 (AIM125068 snack has no window labeled eating)
Annotated recording	24.2 h, of which 9.6 h eating
Annotated span per session	2 to 55 min
Eating share per session	0% to 86%
Full recordings (sensor data)	0.09 to 12.5 h per session
Training windows (8 s, 4 s hop)	18,227 (7,014 eating, 38.5%)
Scored windows (8 s, non-overlapping)	9,133
Annotation	Video, 10 Hz: chewing bouts, bites, individual chews
Label	Eating = bout or bite; window eating if more than half of its annotated samples are eating
Excluded windows	Under half annotated, or over half of sensor samples missing
Inter-annotator agreement	F1 0.912 on 8 s windows, one snack session (C. Dunlea and K. Nguyen)

Source: ets_cache\ets_windows_w8_h4.npz; process_database.py --list; literature review model description.

2. Model and training




Figure 1. Model architecture (from the literature review). The chew-count head is trained jointly; its rate output is not used (Section 8).

Table 2. Layers and parameters.

Layer	Configuration	Output	Parameters
Input	Acc X, Y, Z, optical	1024 × 4	–
Conv block 1	32 filters, kernel 9, stride 2, BN, max-pool 2	256 × 32	1,312
Conv block 2	64 filters, kernel 9, stride 2, BN, max-pool 2	64 × 64	18,752
Conv block 3	64 filters, kernel 5, BN	64 × 64	20,800
Channel attention	Squeeze-excite, 64 → 16 → 64	64 × 64	2,128
Attention pooling	1 × 1 conv, softmax over time	64	65
Dense	64, ReLU, dropout 0.3	64	4,160
Eating head	1, sigmoid	1	65
Total at inference			47,282
Chew-count head	32 → 1, softplus (trained jointly)	1	2,113

Table 3. Training settings.

Setting	Value
Preprocessing	Per window and channel: mean removed, z-score over valid samples, gaps set to 0. No band-pass filter.
Optimizer	Adam, learning rate 0.0003, batch 64, class-balanced sample weights
Stopping	Up to 80 epochs; early stopping on validation ROC AUC, patience 12, best weights restored; learning rate halved on plateau
Chew target	Annotated chews per window divided by its 99th percentile; loss weight 0.2
Threshold	Chosen per fold on the 5 validation participants to maximize F1
Seeds	3 (9, 10, 11)

3. Window-level results (LOSO)

Table 4. Final configuration, 43 participants, 3 seeds.

Metric	Value
F1	0.86 (0.859 to 0.861 across seeds)
Accuracy	0.890
Balanced accuracy	0.886
Precision	0.849
Recall (sensitivity)	0.870
Specificity	0.902 (from balanced accuracy and recall)
Median participant F1	0.862
False alarms per hour of non-eating	43.8 windows
Seed-to-seed variation	about ±0.007 F1
Human agreement (one session)	0.912

Source: results_fixed\time_se_attnpool_chew0.2_w8_128hz_loso_seed9_x3_stopauc_lr0.0003_inner5; docs/presentation/final_metrics_table.pptx.




Figure 2. F1 per held-out participant, final configuration, with the pooled F1 dashed. Participant IDs must become P1 to P43 in the paper.

Table 5. Lowest participants and causes (F1 read from Figure 2).

Participant	F1	Cause
AIM132097	~0.50	Chews about 4 s, pauses about 3 s to talk, repeats: bouts shorter than a window; errors at edges
AIM126487	~0.62	Not investigated; the lunch is the weak session (re-annotation planned)
AIM147560	~0.63	Soft food (oatmeal) barely moves the jaw sensor; 6 min session, 46 windows
AIM122571	~0.65	Short eating bouts
AIM119072	~0.70	Not investigated
AIM107903	~0.73	Weak at both meals
AIM127703	~0.73	Long high-probability stretches between annotated bouts; possible unannotated eating (check video at 1.8–3, 11.3–12.3, 15.5–16.3 min)

AIM112400 was 0.48 with 2 validation participants (threshold too strict) and is about 0.80 in the final configuration.

4. Episode-level results

Table 6. Final configuration. An episode is a run of consecutive eating windows.

Measure	Value
Eating episodes detected	91.9%
Episodes of 64 s or longer detected	100%
Episodes of 8 s detected	82%
Median delay to first detection	0 s
False episodes per hour (away from meals)	9.9
Episode precision	87.8%
Sessions with eating that had a detection	60 of 60

Source: episode_metrics.py on the final run; docs/presentation/episode_table_final.pptx. Confirm the merge gap used (0 or 32 s) before reporting.




Figure 3. Held-out example, AIM146271 lunch (final model): annotated eating above, model probability below with the 0.75 threshold dashed. F1 0.886, precision 0.925, recall 0.849.

5. Where errors occur

Table 7. Error location (reference configuration, one seed; recompute on the final configuration).

Measure	Value
Errors at bout edges	62% of all errors
False-alarm windows at edges	75%
Missed windows at edges	49%
F1 with edge windows forgiven	0.944
Isolated false alarms	19% of false alarms
False episodes per hour	8.9
Fold thresholds	0.06 to 0.93 (with 2 validation participants)

Source: results_fixed\time_se_attnpool_chew0.2_w8_128hz_loso_seed9_stopauc_lr0.0003 (2 validation participants); error_breakdown.py.

6. Design comparisons

Table 8. Same LOSO folds; differences in F1 from the reference unless stated.

Change	Result
Frequency (FFT) input instead of time domain	F1 0.854 → 0.791; false alarms 41 → 84 per hour; 5 of 43 participants better
5 validation participants instead of 2	+0.008 [0.001, 0.016], 30 better / 12 worse, p = 0.004
8 validation participants instead of 5	+0.001 (no difference)
Recurrent model over 2 min of windows	−0.003 (no difference)
Soft labels	+0.001 (no difference)
32 Hz / 16 Hz instead of 128 Hz	−0.013 / −0.020
16 s windows instead of 8 s	−0.014 [−0.030, +0.002]
Within seed variation	Average pooling, no channel attention, chew weight 0 or 1, transformer layer, 3-model ensemble, augmentation, 4 s windows, 64 Hz
Excluding the 3 participants below 0.55	0.854 → 0.864, inside the 95% CI

Source: compare_runs.py on results_fixed\ (paired bootstrap over participants, Wilcoxon).




Figure 4. Recall against false alarms per hour, time-domain vs FFT input, same network. Dots: operating points chosen on validation participants.

7. Meal type

Table 9. Final configuration, LOSO.

Meal	Sessions	F1 (pooled)	Recall	Median bout
Breakfast	8	0.882	0.909	16 s
Dinner	12	0.884	0.931	24 s
Lunch	18	0.829 (precision 0.841)	0.819	16 s
Snack	23 (22 with eating)	0.877	0.891	20 s

- Per-session median F1: lunch 0.815 vs 0.890 for other meals, Mann-Whitney p = 0.009.
- Participants with a lunch and another session (9): 7 lower at lunch, median difference −0.081, Wilcoxon p = 0.098.
- Some lunches were eaten alone: this is a meal-type result, not a group-eating result.

Source: session_type_analysis.py and plot_meal_types.py on results_fixed\time_se_attnpool_chew0.2_w8_128hz_loso_seed9_x3_stopauc_lr0.0003_inner5.




Figure 5. Left: every session's F1 by meal type, medians marked. Right: the 9 participants with a lunch and another session.

8. Final model, inference and chewing

Table 10. The shipped model.

Item	Value
Training participants	38
Validation participants	AIM146271, AIM128555, AIM109345, AIM147560, AIM116725 (early stopping and threshold only)
Threshold	0.750
Best epoch	3 of 15
Whole database	61 recordings, 370 eating episodes; about 1 s per recording (4 s for 12.5 h)
Median F1, 8 held-out sessions	0.854 (LOSO median participant F1: 0.862)
Median F1, 53 trained-on sessions	0.889 (optimistic: the model trained on them)

Table 11. Held-out sessions (final model).

Participant	Meal	F1
AIM109345	Lunch	0.792
AIM109345	Snack	0.864
AIM116725	Lunch	0.823
AIM116725	Snack	0.865
AIM128555	Breakfast	0.844
AIM128555	Snack	0.915
AIM146271	Lunch	0.886
AIM147560	Breakfast	0.667
Median		0.854

Source: train_final_model.py; process_database.py --overwrite, 4 November 2026.

Table 12. Chews and chewing rate per meal against the annotations.

Estimate	Windows	Meals	r	Median error
Chew count, model output	Detected	8 held out / 53 trained	0.92 / 0.97	14% / 10%
Chewing rate, model output	Detected	8 / 52	−0.23 / 0.42	20% / 12%
Chewing rate, optical peak count	Annotated	59	0.72	7%
Chewing rate, optical spectral peak	Annotated	59	0.67	15% (16% high)
Chewing rate, optical peak count	Detected	8 / 52	0.39 / 0.75	7% / 7%
Same rate for every meal (baseline)	–	60	–	10%

- The chew-count output is right mainly because eating time is right: it predicts about the same chews per window for everyone, so its rate is nearly constant.
- Optical peak count: optical signal band-passed to 0.94–2.17 Hz (Po et al. 2011), peaks at least 0.46 s apart counted. No training; settings fixed from the literature and not tuned on these meals. It needs no held-out split; the r of 0.39 is on 8 meals only.
- Annotated rate: chews in annotated eating windows per minute of those windows (61 to 112 chews/min, mean 85).

Source: plot_meals.py and chew_rate_check.py, 4 November 2026.




Figure 6. Chews per meal and chewing rate from the model's chew output (earlier two-panel version). Replace with figures\chew_check.png from the lab machine, which adds the optical rate, and add figures\chew_rate_check.png.

9. Prior work for comparison

Table 13. Not directly comparable: data, epochs and protocols differ.

Study	Data and method	Result
Doulah et al. 2021 (AIM-2)	30 participants, 10 s epochs, hand-crafted features, SVM, LOSO	F1 81.8 ± 10.1% (mean over participants); episode detection accuracy 82.7%
Ghosh and Sazonov 2022	AIM-2 time series, five deep architectures	Best (ResNet) balanced accuracy 93.47%
Ghosh et al. 2024	AIM-2 images plus accelerometer, free living	F1 80.77% combined (sensitivity 94.59%, precision 70.47%)
Kyritsis et al. 2021	Smartwatch inertial data, CNN plus LSTM, LOSO	Bite F1 0.923; meal start/end Jaccard 0.820
This work	43 participants, 8 s windows, compact CNN, LOSO	F1 0.86 pooled; median participant 0.862; 91.9% of episodes

To compare with Doulah et al., also report this work's mean ± standard deviation of per-participant F1 (not yet computed for the final configuration).

10. To recompute or confirm before submission

- Error location (Section 5) and the fold threshold range on the final configuration.
- Mean ± SD of per-participant F1, final configuration.
- Episode metrics: which merge gap the reported table used.
- AIM125068 snack: why no window is labeled eating (near-empty snack or missing annotation).
- Sensor type: the ETS database calls the channel optical; Doulah 2021 describes a flex sensor. Confirm which AIM-2 version ETS used.
- Whether Doulah 2021 or Ghosh 2022 compared against inter-annotator agreement.
- Inter-annotator agreement on more than one session (re-annotation of the weakest participants planned).
- Relabel participants P1 to P43 in figures.
- With Dr. Sazonov: author list and order, funding and grant number, whether ETS data can be published, SoutheastCon deadline, AI-use disclosure wording.