

# Rockchip Solutions DDR SDRAM Support List

**Ver 2.03**

**2013-10-7**

## ◆ Revision History

Revision No.	History	Date
2.00	ORG.	2012.12.24
2.01	Add some supporting messages	2013.01.28
2.02	Add some supporting messages	2013.5.17
2.03	Add some supporting messages	2013.10.07

## ◆ Symbol

Symbol	Description
√	Fully Tested and Mass production
T/A	Fully Tested and Applicable
N/A	Not Applicable

## ◆The Latest Reference Circuits Version

Chip	DRAM Support Type	RK Reference Circuit Version
RK281x	DDR2	RK2818_REF_V1.3
RK2906	DDR2/DDR3	RK2906_PMIC_REF_V20_0418
RK2918	DDR2/DDR3	RK2918_REF_V13_20110517
RK2926/RK3026	DDR3	2926_86v_v1.2_20121109
RK2928/RK3028/RK3028A	DDR3	RK2928-DDR3P208SD4-V10-20120712LX.pcb
RK3066	DDR2/DDR3/LPDDR2	RK3066_REF_TPS659102_V12_20121024_1CELL
RK3168/RK3188	DDR2/DDR3/LPDDR2	RK3188-DDR3P416SS4-V10-20130607WF.pcb

Application Note:

[1] Following SOC's not support the 512Mx8 DDR3 because of the package without Address Input pin A15:  
RK2906-6, RK2906-8, RK3066.

[2] The DRAM Part Number is usually consists of two parts divided by '-', which the first part contains memory type, density, organization, package, and the second part usually means data rate.

[3] RockChip platform can support all the chips that match the first part of Part Number which marks '√' or 'T/A', and do not need to care the second part. If you want your system running more effective, you may need to find out the exact data rate in DRAM datasheet and config in kernel menuconfig.

[4] Since DDR is high speed device. Please directly copy our PCB DRAM Part Template and follow our PCB product guide.

Contact information: fae@rock-chips.com

Manufacturer	Part Number	Density	Organization	Type	RK281x	RK290x RK2918	RK2928 RK3028A	RK2926 RK3026	RK3066/RK3066A RK3168/RK3188	与RK兼容情况
Elpida	E1116AEBG-8E-F	1G bit	64M×16	DDR2	√	√				除个别老款颗粒如： EDJ2108BDBG对pcb要求 偏高外总体兼容情况 良好
	EDJ1108DJBG	1G bit	128M x 8	DDR3		√				
	EDJ1116DJBG	1G bit	64M×16	DDR3						
	EDJ2116DEBG	2G bit	128M×16	DDR3		√				
	EDJ2116EEBG	2G bit	128M×16	DDR3L		T/A				
	EDJ2108DEBG	2G bit	256M×8	DDR3		√	T/A	T/A	√	
	EDJ2108BDBG	2G bit	256M×8	DDR3		√	T/A	N/A	√	
	EDJ2108EEBG	2G bit	256M×8	DDR3L						
	EDJ4216BASE	4G bit	256M×16	DDR3		√				
	EDJ4216BBBG	4G bit	256M×16	DDR3		√			√	
	EDJ4216EBBG	4G bit	256M×16	DDR3L		T/A			T/A	
	EDJ2108EDBG	2G bit	256M×8	DDR3L					T/A	
	EDJ4216EFBG	4G bit	256M×16	DDR3L		T/A	T/A	T/A	T/A	
	EDJ4208BBBG	4G bit	512M×8	DDR3			T/A	T/A	T/A <sup>[1]</sup>	
	EDJ4208EFBG	4G bit	512M×8	DDR3L			T/A	T/A	T/A <sup>[1]</sup>	
	EDJ4208EBBG	4G bit	512M×8	DDR3L			T/A	N/A	T/A <sup>[1]</sup>	
	EDB4032B2MA	4Gb/2CS	64M×32×2pcs	LPDDR2					T/A	
	EDB8132B3MA	8Gb/2CS	128M×32×2pcs	LPDDR2					T/A	
	EDB8132B3MC	8Gb/2CS	128M×32×2pcs	LPDDR2						
Micron	MT47H64M16HR-25	1G bit	64M×16	DDR2	√	√				兼容性好
	MT41J128M8JP-15E:G	1G bit	128M x 8	DDR3		√				
	MT41J128M16HA-15E:D	2G bit	128M×16	DDR3		√				
	MT41J256M8HX-15E:D	2G bit	256M×8	DDR3		√	T/A	T/A	T/A	
	MT41K128M16HA-15E:D	2G bit	128M×16	DDR3L		√				
	MT41K256M16RE-15E:D	4G bit	256M×16	DDR3L		√				
	MT41K512M8RA-15E:D	4G bit	512M×8	DDR3L						
	MT41K256M8DA-125:K	2G bit	256M×8	DDR3L		√	T/A	T/A	T/A	
	MT41K128M16JT-125:K	2G bit	128M×16	DDR3L		√			T/A	
	MT41K512M8RH-125:E	4G bit	512M×8	DDR3L			T/A	T/A	T/A <sup>[1]</sup>	
	MT41K256M16HA-125:E	4G bit	256M×16	DDR3L		√	T/A	T/A	N/A	
	MT41K256M8DA-125:M	2G bit	256M×8	DDR3L		T/A	T/A	T/A	T/A	
	MT41K256M16HA-125M:E	4G bit	256Mx16	DDR3L						

Manufacturer	Part Number	Density	Organization	Type	RK281x	RK290x RK2918	RK2928 RK3028A	RK2926 RK3026	RK3066/RK3066A RK3168/RK3188	与RK兼容情况
Hynix	H5PS1G63CFP	1G bit	64M×16	DDR2	√	√				兼容性好
	H5PS1G63EFR	1G bit	64M×16	DDR2	√	√				
	H5TQ1G83DFR	1G bit	128M×8	DDR3		√			T/A	
	H5TQ2G63BFR	2G bit	128M×16	DDR3		√				
	H5TQ2G83CFR	2G bit	256M×8	DDR3		√	√	√	√	
	H5TQ2G83BFR	2G bit	256M×8	DDR3		T/A	T/A	T/A	√	
	H5TQ1G83TFR	1G bit	128M×8	DDR3		√				
	H5TQ4G63MFR	4G bit	256M×16	DDR3		√	T/A	T/A	T/A	
	H5TQ2G63DFR	2G bit	128M×16	DDR3		√			T/A	
	H5TQ2G83EFR	2G bit	256M×8	DDR3		T/A	T/A	T/A	T/A	
	H5TQ4G83AFR	4G bit	512M×8	DDR3			T/A	T/A	T/A <sup>[1]</sup>	
	H5TC4G83AFR	4G bit	512M×8	DDR3L					T/A <sup>[1]</sup>	
	H5TQ4G63AFR	4G bit	256M×16	DDR3		T/A	T/A	T/A	T/A	
	H5TC4G63AFR	4G bit	256M×16	DDR3L					T/A	
	H5TQ1G63DFR	1G bit	64M×16	DDR3						
	H5TQ4G83MFR	4G bit	512M×8	DDR3			T/A	T/A	T/A <sup>[1]</sup>	
	H9TCNNN4JDMMPR	4Gb/2CS	128M×32	LPDDR2						
	H9TP33A8LDMCMR	8Gb/2CS	256M×32	LPDDR2+eNAND						
Nanya	NT5TU32M16CG-3C	512M bit	32M×16	DDR2	√	√				兼容性好
	NT5TU64M16GG	1G bit	64M×16	DDR2	√					
	NT5CB128M8DN	1G bit	128M×8	DDR3		√				
	NT5CB128M16BP	2G bit	128M×16	DDR3		√	T/A	T/A	T/A	
	NT5CB128M16HP	2G bit	128M×16	DDR3		T/A			T/A	
	NT5CC128M8DN	1G bit	128M×8	DDR3L		√			T/A	
	NT5CC128M16BP	2G bit	128M×16	DDR3L		√				
	NT5CB256M8GN	2G bit	256M×8	DDR3		√	T/A	T/A	T/A	
	NT5CB256M8BN	2G bit	256M×8	DDR3		√	T/A	T/A	T/A	
	NT5CB256M16BP	4G bit	256M×16	DDR3		√	T/A	T/A	T/A	
	NT5CB256M8FN	2G bit	256M×8	DDR3		√	T/A	T/A	T/A	
	NT5CB128M16FP	4G bit	128M×16	DDR3		√				
	NT5CB512M8BN	4G bit	512M×8	DDR3			T/A	T/A	T/A <sup>[1]</sup>	
	NT5CC256M16CP	4G bit	256M×16	DDR3		T/A	T/A	T/A	T/A	
	NT5CC512M8CN	4G bit	512M×8	DDR3L			T/A	T/A	T/A <sup>[1]</sup>	
	NT6TL256F32AI	8G bit	256M×32	LPDDR2					T/A	
	NT6TL256T32AI	8G bit	256M×32	LPDDR2					T/A	

Manufacturer	Part Number	Density	Organization	Type	RK281x	RK290x RK2918	RK2928 RK3028A	RK2926 RK3026	RK3066/RK3066A RK3168/RK3188	与RK兼容情况
Samsung	K4T1G164QE	1G bit	64M×16	DDR2	√	√				兼容性好
	K4B2G1646C	2G bit	128M×16	DDR3		√				
	K4B1G0846G	1G bit	128M×8	DDR3		√			T/A	
	K4B2G0846C	2G bit	256M×8	DDR3		√				
	K4B2G1646E	2G bit	128M×16	DDR3		T/A			T/A	
	K4B2G1646Q	2G bit	128M×16	DDR3		T/A			T/A	
	K4B4G1646B	4G bit	256M×16	DDR3		√	T/A	T/A	T/A	
	KMKJS000VM	8Gb/2CS	256M×32	LPDDR2+eMMC						
SPECTEK	PE918-15E (PRN256M8V79DG8GQF-15E)	2G bit	256M×8	DDR3		T/A	T/A	T/A	T/A	MICRON子品牌， 兼容性良好
	PE936-15E (PRN256M8V89CG8GQF-15E)	2G bit	256M×8	DDR3		T/A	T/A	T/A	N/A	
	PE947-15E (PRN256M8V80AG8RHF-15E)	2G bit	256M×8	DDR3						
	PEB08-15E (PRN512M8V80AG8RHF-15E)	4G bit	512M×8	DDR3			T/A	T/A	T/A <sup>[1]</sup>	
	PEB15-15E (PRN256M16V80AG8GPF-15E)	4G bit	256M×16	DDR3		T/A	T/A	T/A	T/A	
	PEB16-15E (PRM256M16V80AG8GPF-15E)	4G bit	256M×16	DDR3						
Elixir	N2TU1G16GG-AC	1G bit	64M×16	DDR2		√				NANYA子品牌， 兼容性良好
	N2CB1G80GN-CG	2G bit	128M×8	DDR3		√				
	N2CB2G80GN	2G bit	256M×8	DDR3		√			√	
	N2CB2G16BP-CG	2G bit	128M×16	DDR3		√				
	N2CB2G16FP-DI	2G bit	128M×16	DDR3			T/A	T/A	T/A	
	N2CB4G08DN-CG	4G bit	512M×8	DDR3			T/A	T/A	T/A <sup>[1]</sup>	
	N2CB4G16BP-DI	4G bit	256M×16	DDR3			T/A	T/A	T/A	
Eorex	EM47DM1688SBA	2G bit	128M×16	DDR3		N/A				台湾颗粒厂商， 兼容性较好
	EM47EM0888SBA-150	2G bit	256M×8	DDR3		T/A	N/A	N/A	T/A	
	EM47EM1688SBA-150	4G bit	256M×16	DDR3		T/A				

Manufacturer	Part Number	Density	Organization	Type	RK281x	RK290x RK2918	RK2928 RK3028A	RK2926 RK3026	RK3066/RK3066A RK3168/RK3188	与RK兼容情况
Etron Tech	EM68B16CWPA-25H	512M bit	32M×16	DDR2	√	√				台湾颗粒厂商，兼容性较好
	EM6GE16EW5B-15H	4G bit	256M×16	DDR3		T/A	T/A	T/A	T/A	
MIRA	P3R1GE4CFF-G8E	1G bit	64M×16	DDR2	√	√				使用Elpida技术兼容性一般。PCB不允许有参考层有割断的现象。
	P3R1GE3FGF-G8E	1G bit	128M×8	DDR2	√	√				
	P3P4GF3BLF-GGN	4G bit	512M×8	DDR3			T/A	N/A	N/A	
	P3P4GF4BLF-GGN	4G bit	256M×16	DDR3			T/A		N/A	
SCSemicon	HXB18T2G160AF-25D	2G bit	128M×16	DDR2	√	√				使用Elpida晶圆兼容性一般。PCB不允许有参考层有割断的现象。
	HXB18T1G160AF-25D	1G bit	64M×16	DDR2	√	√				
	HXB15H2G800BF-15H	2G bit	256M×8	DDR3		N/A	T/A	N/A	T/A	
	HXB15H4G800BF-15H	4G bit	512M×8	DDR3		N/T <sup>[1]</sup>	T/A	N/A	T/A <sup>[1]</sup>	
	HXB15H4G160BF-15H	4G bit	256M×16	DDR3		T/A			N/A	
ADATA	3CCD-1211A EL1250V	2G bit	256M×8	DDR3		N/A	T/A	N/A	T/A	使用Elpida晶圆兼容性一般。PCB不允许有参考层有割断的现象。
	DWND-1211A EL1311V	4G bit	512M×8	DDR3						
	D2ND-1211A EL1345V	4G bit	256M×16	DDR3						
ANOR	AM43Q2G08AFP-150C	2G bit	256M×8	DDR3		N/A	T/A	N/A	T/A	使用Elpida晶圆兼容性一般。PCB不允许有参考层有割断的现象。
	AM43Q4G08AFP-150C	4G bit	512M×8	DDR3			T/A	N/A		
ProMOS	V59C1G01168QBASXJ25	1G bit	64M×16	DDR2	√	√				
	V59C1G02168QB	2G bit	128M×16	DDR2		√				
	V73CAG01808RA JI9	1G bit	128M×8	DDR3		√				
SMART	S4B2G0846C-HYH9	2G bit	256M×8	DDR3					T/A	巴西颗粒，国内用的不多
	S4B2G0846D-HYK0	2G bit	256M×8	DDR3					T/A	
πPM	PME810816BBR-E6DN	1G bit	64M×16	DDR2						
	PMF510816ABR-G8DN	1G bit	64M×16	DDR3		√				
	PMF511816ABR-G8DN	2G bit	128M×16	DDR3		√				
	PMF510808ABR-I9DN	1G bit	128M x 8	DDR3						

[illegible]