

Basic SQL

Dr Paolo Guagliardo

`dbs-lecturer@ed.ac.uk`



THE UNIVERSITY of EDINBURGH
informatics

Fall 2018

The data model of SQL

Data is organised in **tables** (also called **relations**)
which are collections of **tuples** (also called **rows** or **records**)
which are *all of the same length*

Schema

- ▶ Set of **table names**
- ▶ List of *typed* distinct **column names**
(also called **attributes**) for each table
- ▶ **Constraints** within a table or between tables ⇐ *not for now*

Instance

- ▶ Actual data (that is, the rows of the table)
- ▶ Must satisfy typing and constraints

SQL

- ▶ **Structured Query Language**
- ▶ **Declarative** language for relational databases
- ▶ Implemented in all major (free and commercial) RDBMSs
- ▶ International Standard since 1987 (latest rev. Dec 2016)
- ▶ Consists of two sublanguages:
 - DDL** (Data Definition Language)
operations on the schema
 - DML** (Data Manipulation Language)
operations on the instance

Creating tables

Basic syntax

```
CREATE TABLE <table_name> (  
    <column1> <type1>,  
    <column2> <type2>,  
    ...  
    <columnN> <typeN>  
);
```

Example

```
CREATE TABLE Customer (  
    custid varchar(10),  
    name varchar(20),  
    city varchar(30),  
    address varchar(30)  
);
```

Most common SQL data types

Strings

- ▶ **varchar** (n) – variable length, at most n characters

Numbers

- ▶ **smallint**
- ▶ **integer** or **int**
- ▶ **bigint**
- ▶ **numeric** (p, s) – arbitrary precision number
At most p total digits and s digits in the fractional part

Date & Time

- ▶ **date** – e.g., '2016-10-03'
- ▶ **time** – time of the day: e.g., '21:09'
- ▶ **timestamp**

Default values

Syntax

```
CREATE TABLE <table_name> (  
    <column1_name> <column1_type>,  
    <column2_name> <column2_type> DEFAULT <value>,  
    ...  
    <columnN_name> <columnN_type>  
);
```

Example

```
CREATE TABLE Account (  
    accnum varchar(12),  
    branch varchar(30),  
    custid varchar(10),  
    balance numeric(14,2) DEFAULT 0  
);
```

Populating tables

General syntax

```
INSERT INTO <table_name> VALUES (...), ..., (...);
```

Examples

```
INSERT INTO Account VALUES  
('243576', 'Edinburgh', 'cust1', -120);
```

```
INSERT INTO Customer VALUES  
('cust1', 'Renton', 'Edinburgh', '2 Wellington Pl'),  
('cust2', 'Watson', 'London', '221B Baker St'),  
('cust3', 'Holmes', 'London', '221B Baker St');
```

Populating tables with default values

Two possibilities:

1. Use the keyword **DEFAULT** in **INSERT**

Example

```
INSERT INTO Account VALUES  
('250018', 'London', 'cust3', DEFAULT)
```

2. List attributes explicitly (omitted ones will get the default)

Example

```
INSERT INTO Account (accnum, branch, custid) VALUES  
('250018', 'London', 'cust3')
```

Attributes without **DEFAULT** in **CREATE TABLE**
have default value **NULL** ⇐ more on this later

Changing the definition of a table

```
ALTER TABLE <name>
    RENAME TO <new_name>;
RENAME <column> TO <new_column>;
ADD <column> <type>;
DROP <column>;
ALTER <column>
    TYPE <type>;
    SET DEFAULT <value>;
    DROP DEFAULT;
```

Destroying tables

```
TRUNCATE TABLE <name>;
DROP TABLE <name>;
```

Many other changes are possible ...

Basic queries in SQL

Follow the basic pattern:

```
SELECT <list_of_attributes>
FROM   <list_of_tables>
WHERE  <condition>
```

Idea

1. Loop over all rows of the tables listed in **FROM**
2. Take those that satisfy the **WHERE** condition
3. Output the values of the attributes listed in **SELECT**

An extremely simple example

Customer			
ID	Name	City	Address
cust1	Renton	Edinburgh	2 Wellington Pl
cust2	Watson	London	221B Baker St
cust3	Holmes	London	221B Baker St

List all customers

```
SELECT *  
FROM Customer
```

* means “all attributes”

What is the output to this query?

A very simple example

Customer			
ID	Name	City	Address
cust1	Renton	Edinburgh	2 Wellington Pl
cust2	Watson	London	221B Baker St
cust3	Holmes	London	221B Baker St

List name and address of all customers

```
SELECT Name, Address  
FROM Customer
```

Output:

Name	Address
Renton	2 Wellington Pl
Watson	221B Baker St
Holmes	221B Baker St

A simple example

Customer			
ID	Name	City	Address
cust1	Renton	Edinburgh	2 Wellington Pl
cust2	Watson	London	221B Baker St
cust3	Holmes	London	221B Baker St

List name and address of customers living in Edinburgh

```
SELECT Name, Address
FROM Customer
WHERE City='Edinburgh'
```

Output:

Name	Address
Renton	2 Wellington Pl

More than one table in FROM

Table1	
A	B
1	2
3	4

Table2	
C	D
2	1

```
SELECT B, C
FROM Table1, Table2
```

1. Each row of Table1 is **concatenated** with each row of Table2

A	B	C	D
1	2	2	1
3	4	2	1

2. For each resulting row the values for attributes B and C are returned

B	C
2	2
4	2

Joining tables

Customer			Account		
ID	Name	City	AccNum	CustID	Balance
cust1	Renton	Edinburgh	123321	cust3	1330.00
cust2	Watson	London	243576	cust1	-120.00
cust3	Holmes	London			

List customers' names and their accounts' numbers

```
SELECT Name, AccNum
FROM Customer, Account
WHERE ID = CustID
```

Semantics: nested loop over the tables listed in FROM

Output:	Name	AccNum
	Renton	243576
	Holmes	123321

The basic WHERE clause

term :=

- ▶ attribute
- ▶ value

comparison :=

- ▶ term1 op term2, with op $\in \{=, <>, <, >, <=, >=\}$
- ▶ term **IS NULL**
- ▶ term **IS NOT NULL**

condition :=

- ▶ condition1 **AND** condition2
- ▶ condition1 **OR** condition2
- ▶ **NOT** condition

Database modification: Deletion

General form

```
DELETE FROM <table>  
WHERE <condition>
```

All rows in <table> satisfying <condition> are deleted

Example

Remove accounts with zero balance and unknown owner

```
DELETE FROM Account  
WHERE Balance=0 AND CustID IS NULL
```

Database modification: Replacement

General form

```
UPDATE <table>  
SET <assignments>  
WHERE <condition>
```

Replace the values of some attributes (using <assignments>) in each row of <table> that satisfies <condition>

Examples

Set a new balance on account 745622

```
UPDATE Account  
SET balance=1503.82  
WHERE accnum='745622'
```

Accounts in London with positive balance get a 0,2% bonus

```
UPDATE Account  
SET balance = balance + 0.002*balance  
WHERE branch='London' AND balance > 0
```

WHERE conditions in queries

- **filter** data within a table

```
SELECT Name, Address
FROM    Customer
WHERE    City='Edinburgh'
```

- **join** data from different tables

```
SELECT Name, AccNum
FROM    Customer, Account
WHERE    ID = CustID
```

Filtering and join together

```
SELECT Name, Address, AccNum
FROM    Customer, Account
WHERE    ID = CustID AND City='Edinburgh'
```

Explicit join syntax

```
table1 JOIN table2 ON <condition>
...
      JOIN tableN ON <condition>
```

Logically separate join conditions from filters

```
SELECT Name, Balance
FROM    Customer, Account
WHERE    ID = CustID AND Balance < 0
```

```
SELECT Name, Balance
FROM    Customer JOIN Account ON ID=CustID
WHERE    Balance < 0
```

Qualification of attributes

Customer			Account		
CustID	Name	City	AccNum	CustID	Balance
cust1	Renton	Edinburgh	123321	cust3	1330.00
cust2	Watson	London	243576	cust1	-120.00
cust3	Holmes	London			

List the name of customers whose account is overdrawn

```
SELECT Customer.Name, Account.Balance
FROM    Customer, Account
WHERE   Account.CustID = Customer.CustID
AND     Account.Balance < 0
```

We need to specify the relations attributes are coming from

What is the output of this query?

Range variables

Assign new names to tables in FROM

```
SELECT Customer.Name, Account.Balance
FROM    Customer, Account
WHERE   Account.CustID = Customer.CustID
AND     Account.Balance < 0
```

```
SELECT C.Name, A.Balance
FROM    Customer C, Account AS A
WHERE   A.CustID = C.CustID
AND     A.Balance < 0
```

```
SELECT C.Name, A.Balance
FROM    Customer C JOIN Account A ON C.CustID=A.CustID
WHERE   A.Balance < 0
```

Renaming attributes

```
SELECT C.Name CustName, A.Balance AS AccBal
FROM    Customer C, Account A
WHERE   A.CustID = C.CustID
        AND A.Balance < 0
```

This does not work:

```
SELECT C.Name CustName, A.Balance AS AccBal
FROM    Customer C, Account A
WHERE   A.CustID = C.CustID
        AND AccBal < 0
```