# Foundations of Natural Language Processing Lecture 16 Semantic Role Labelling and Argument Structure

Alex Lascarides

(Slides based on those of Schneider, Koehn, Lascarides)

15 March 2019



## Language is Flexible

- Often we want to know who did what to whom (when, where, how and why)
- But the same event and its participants can have different syntactic realizations.


```
Sandy broke the glass. vs. The glass was broken by Sandy. She gave the boy a book. vs. She gave a book to the boy.
```

 Instead of focusing on syntax, consider the semantic roles (also called thematic roles) defined by each event.

## **Argument Structure and Alternations**

- Mary opened the door The door opened
- John slices bread with a knife
   This bread slices easily
   The knife slices cleanly
- Mary loaded the truck with hay
   Mary loaded hay onto the truck
   The truck was loaded with hay (by Mary)
   The hay was loaded onto the truck (by Mary)
- John gave a present to Mary John gave Mary a present

## **Stanford Dependencies**



cf Mary ate the sandwich with Kim!

# **Syntax-Semantics Relationship**

	Add another family member
Relationship Status:	•
Interested in:	Single In a Relationship Engaged Married
Looking for:	It's Complicated In an Open Relationship Widowed
	■ Networking
Political Views:	
Religious Views:	

## **Outline**

- syntax  $\neq$  semantics
- The **semantic roles** played by different participants in the sentence are not trivially inferable from syntactical relations
- . . . though there are patterns!
- The idea of semantic roles can be combined with other aspects of meaning (beyond this course).

# **Commonly used thematic roles**

Role	Example
Agent	The boy kicked his toy
Theme	The boy kicked his toy
Experiencer	The boy felt sad
Result	The girl built a shelf with power tools
Instrument	The girl built a shelf with power tools
Source	She came from home
	•••

• J&M give definitions and additional roles

## Issues with thematic roles

- No universally agreed-upon set of roles
- Items with the "same" role (e.g., Instrument) may not behave quite the same Sandy opened the door with a key The key opened the door Sandy ate the salad with a fork \*The fork ate the salad
- The two main NLP resources for thematic roles avoid these problems by defining very fine-grained roles:
  - Specific to individual verbs only (PropBank)
  - Specific to small groups of verbs (FrameNet)

## Semantic role labelling

- The NLP task of identifying which words/phrases play which roles in an event.
- Supervised classification:
  - Resource data is **PropBank**: Repository of **frame files** for each verb (more shortly) plus annotations on constituents in Penn treebank with their semantic roles (wrt the relevant frame file).
  - Features are mostly related to syntactic structure and the particular words involved (i.e., assumes pipeline architecture)
- Current research focuses on reducing the need for training data (e.g., to work on non-English languages)

## **Example Frame Roles:** *load*

Mary loaded the truck with hay at the depot on Friday

load: load.01 'cause to be burdened'

Arg0-PAG: loader,agent

Frame roles: Arg1-GOL: beast of burden

Arg2-PPT: cargo

Arg3-MNR: instrument

load\_up: load.02 'phrasal cause to be burdened'
 Frame roles are the same as load.01

• *load*: load.03 'fix, set up to cheat'

Arg0-PAG: cheater

**Frame roles:** Arg1-GOL: thing loaded (dice, the deck, etc)

Arg2-PPT: with what

• All sentences can have temporal, spatial adjuncts (AM-TMP, AM-LOC)...

## **PropBank**

Penn treebank annotated with Arg0, Arg1 etc, and verb with its sense; so specific semantic role recoverable.

Mary loaded the truck with hay at the depot on Friday.

Nary loaded hay onto the truck at the depot on Friday.

## **Semantic Role Labelling**

#### Traditional pipeline:

- 1. Either assume or compute syntactic parse and predicate senses
- 2. **Argument identification** (deterministic): select the predicate's argument phrases (by parsing the parse tree)
- 3. **Argument classification:** select a role for each argument (wrt to the frame role for the predicate's sense).
  - Useful feature: predicate-to-argument path in the tree (e.g., NP-S-VP-V).

## **Problems**

• Numbered roles are predicate specific:

load.01.ARG1: beast of burden put.01.ARG1: thing.put put.01.ARG2: beast of burden.

• FrameNet tries to generalise via verb classes; but less treebank data.

# **Paraphrase**

James snapped a photo of me with Sheila. Sheila and I had our picture taken by James


# **Paraphrase**

James snapped a photo of me with Sheila. Sheila and I had our picture taken by James



#### Photo Labelled. . .

photograph vs. take picture vs. snap picture. . .



## **Idealised Stanford Dependencies**

James snapped a photo of me with Sheila nsubj(snap, James)
 dobj(snap, photo)
 prep\_of(photo,me)
 prep\_with(me,Sheila)
 det(photo,a)

Sheila and I had our picture taken with James nsubjpass(taken,Sheila)
 nsubjpass(taken,I)
 conj\_and(Sheila,I)
 aux(taken,had)
 dobj(taken,picture)
 poss(picture,our)
 prep\_with(picture,James)

Here, agent is the complement introduced with by in a passive construction. . .

## FrameNet: Meanings are reletavised to scenes!

- Tries to capture relationships among word and phrase meanings by assigning them the same frame (and so captures paraphrases).
- $\bullet \approx 1000$  frames represent scenarios.
  - Most are associated with lexical units (predicates);
     but some are phrases
- Frames are explained with textual descriptions and linguistic examples.

## **Example:** Create\_physical\_artwork

#### **Definition:**

A Creator creates an artefact that is typically an iconic Representation of an actual or imagined entity or event. The Representation may also be evocative of an idea while not based on resemblance.

Diagrams must be clearly <u>drawn</u> on construction paper.
 I <u>took</u> his picture and told him it came out well.

#### Frame Elements:

Core: creator, representation

**Non-Core** manner, location\_of\_representation . . .

18

## FrameNet Resources

- FrameNets for several languages
- Some (limited!) data annotated with Frame elements from FrameNet
- SEMAFOR is a frame-semantic parser
  - Ongoing research at CMU, Google, Edinburgh. . .

## **Summary**

- Grammatical relations on their own don't determine who did what to whom
- You need to (also) know about word and phrase meanings and how they relate to grammatical roles
- There is flexibility in how a verb realises its participants syntactically (connected with the kind of event that the verb denotes)
- One must exploit those patterns to obtain NL understanding (e.g., predict entailments, paraphrases etc).