BIG DATA · Academic year 2026-2027

Assignment 1

Basic Matrix Multiplication in Python, Java and C

Grado en Ciencia e Ingeniería de Datos
Universidad de Las Palmas de Gran Canaria

Repository: https://github.com/Cafabri/Assigment1

Abstract

This study compares a naive $O(n^3)$ triple-loop matrix multiplication implemented in Python 3.11, Java 21 (JVM with JIT) and C (gcc 16.1.0, `-O0`) across matrix sizes from $n = 10$ to $n = 1000$. Runtime grows cubically in all three languages. Java achieves the lowest execution time, outperforming C compiled without optimisation flags due to JIT compilation. Python is consistently the slowest, reaching approximately 12 minutes at $n = 1000$. Memory usage scales as $O(n^2)$ across all implementations. Results are scoped to the tested hardware, compiler settings and input sizes.

1 Introduction and Objective

Matrix multiplication is a fundamental operation in scientific computing. Its naive implementation requires $O(n^3)$ arithmetic operations for $n \times n$ matrices, making performance differences across languages clearly visible as n grows.

Research question: How does matrix size affect the runtime and memory usage of a naive triple-loop matrix multiplication implemented in Python, Java and C, when each language runs in its standard execution environment?

Hypothesis: Runtime will grow cubically for all three implementations. Languages closer to the hardware (C, Java) are expected to be faster than an interpreted language (Python).

2 Background

The standard triple-loop algorithm computes $C[i][j] = \sum_k A[i][k] \cdot B[k][j]$ for all i, j, performing n^3 multiply-accumulate operations. Its theoretical complexity is $O(n^3)$ in time and $O(n^2)$ in space for the output matrix.

The three languages differ fundamentally in how they execute code:

- **Python (CPython):** interpreted line by line. Each operation involves dynamic type checking and object overhead, making inner loops expensive.
- **Java (JVM):** compiled to bytecode and then JIT-compiled to native machine code at runtime. The JIT identifies hot loops and applies optimisations automatically after warm-up.
- **C (gcc `-O0`):** compiled ahead-of-time to native code without compiler optimisations. Every operation maps directly to machine instructions, but without register allocation, loop scheduling or vectorisation.

3 Methodology

Implementations

Each implementation uses the same `ijk` triple-loop order and 64-bit floating-point arithmetic (`float` in Python, `double` in Java and C). No optimised library calls are used for the multiplication itself. Storage is row-major in all three cases.

Correctness

Before benchmarking, each implementation verifies three test cases: $A \times I = A$ (identity matrix), $A \times \mathbf{0} = \mathbf{0}$ (zero matrix), and a 2×2 product with a known result. All checks passed in all three languages.

Execution environment

Item	Value
CPU	Intel Core i7-13700KF (16 cores, 24 logical processors)
RAM	31.8 GB
OS	Windows 11 Pro
Python	CPython 3.11.9 — interpreter, no JIT
Java	OpenJDK 21.0.12 (Microsoft Build) — JIT enabled (default)
C compiler	gcc 16.1.0 (MSYS2/MinGW64), flags: `-O0`

Table 1: Execution environment.

Measurement protocol

- **Sizes tested:** $n \in \{10, 50, 100, 200, 300, 500, 750, 1000\}$.
- **Repetitions:** 5 measured runs per configuration, preceded by warm-up runs (1 for Python, 3 for Java, 2 for C) to reduce cold-start effects.
- **Timing:** `perf_counter` (Python), `nanoTime` (Java), `QueryPerformanceCounter` (C). All timers measure wall-clock time of the multiplication kernel only; input generation is outside the timed region.

- **Memory:** peak heap via `tracemalloc` (Python); heap delta via `Runtime.totalMemory()` − `freeMemory()` after `gc()` (Java); allocated matrix storage $3n^2 \times 8$ bytes (C — exact, since allocation is explicit).
- **Summary statistic:** median and interquartile range (IQR) over 5 repetitions.
- **Inputs:** matrices generated with fixed seeds (42 for A, 43 for B) using each language's standard PRNG, values in $[0, 10]$. Cross-language PRNGs differ, so matrices are statistically similar but not bit-identical.

4 Results

Runtime

n	C (s)	Java (s)	Python (s)
10	0.000002	0.000022	0.000202
50	0.000229	0.000140	0.028243
100	0.001786	0.000444	0.344134
200	0.014107	0.003165	1.801821
300	0.049343	0.013094	11.699590
500	0.235239	0.085622	58.140186
750	0.943930	0.365947	284.902533
1000	2.125408	0.989217	721.430916

Table 2: Median runtime (seconds) over 5 repetitions. IQR below 2% of the median in all cases.




Figure 1: Median runtime vs matrix size n (log scale). Error bars show IQR.

Memory

n	C (KB)	Java (KB)	Python (KB)
10	2.3	41.6	1.2
100	234.4	86.9	312.5
300	2109.4	747.8	2825.1
500	5859.4	2008.4	7837.7
1000	23437.5	7952.3	31307.1

Table 3: Median memory usage (KB). Metrics differ across languages; see Section 3.




Figure 2: Memory usage vs matrix size n.

5 Discussion

Cubic growth. All three implementations exhibit clear cubic growth. From $n = 100$ to $n = 200$ (factor of 2), runtimes multiply by approximately 8 (2^3), consistent with $O(n^3)$. Slight deviations at larger sizes are expected due to cache pressure as the working set exceeds the L2/L3 cache.

Java faster than C. A notable result is that Java consistently outperforms C. This is explained by the difference in execution model: C is compiled with `-O0`, which disables all compiler optimisations, while Java's JVM applies JIT compilation at runtime after the warm-up phase. The JIT identifies the hot inner loop and generates optimised native code, including efficient register allocation and instruction scheduling. This is not a general claim about the languages: C compiled with `-O2` or `-O3` would be significantly faster than Java. The result reflects the chosen conditions — each language in its standard runtime

environment, with C intentionally unoptimised to isolate the algorithm from compiler transformations. Compiler optimisations will be explored in Assignment 2.

Python overhead. Python is approximately 340× slower than C and 730× slower than Java at $n = 1000$. CPython interprets each bytecode instruction individually, performs dynamic type checks on every operation, and represents numbers as heap-allocated objects. These overheads dominate the inner loop and explain the large constant factor relative to compiled implementations.

Memory. Memory scales as $O(n^2)$ in all three cases, consistent with storing three $n \times n$ matrices. The different measurement methods produce different absolute values: C reports exact allocated storage, while Python and Java include object headers and runtime overhead. These metrics should not be compared as if identical.

Limitations. Cross-language PRNG differences mean input matrices are statistically similar but not bit-identical. The Java memory metric is approximate due to GC activity. Results are specific to the tested hardware, OS and language versions.

6 Conclusions

All three implementations exhibit the expected $O(n^3)$ runtime growth. Under the tested conditions — each language in its standard execution environment — Java achieves the lowest execution time due to JIT compilation, followed by C (`-O0`), then Python. Python's interpreter overhead makes it unsuitable for large-scale naive matrix multiplication without vectorised libraries. Memory usage scales quadratically in all cases, with differences in absolute values explained by the measurement method.

These conclusions apply strictly to the tested implementation, hardware, and settings. Compiler optimisations (addressed in Assignment 2) would substantially change the relative performance of C.

References and Materials

- Source code, raw measurements (CSV), analysis scripts and plots: https://github.com/Cafabri/Assigment1
- Python Software Foundation. *Python 3.11 documentation*. https://docs.python.org/3.11/
- Oracle. *Java SE 21 Documentation*. https://docs.oracle.com/en/java/javase/21/
- Free Software Foundation. *GCC 16 Manual*. https://gcc.gnu.org/onlinedocs/
- Cormen, T.H., Leiserson, C.E., Rivest, R.L., & Stein, C. (2009). *Introduction to Algorithms* (3rd ed.). MIT Press.