```
-------------------------------------------------------------------------------
Address 65: Tire Pressure          Labels: 8J0-907-273.lbl
   Part No SW: 8J0 907 273 A     HW: 8J0 907 273 A
   Component: J502_RDK          H02 0300
   Revision: --H02-D0     Serial number: 1267977137077
   Coding: 0860022
   Shop #: 06435 000
   VCID: 2F381AE0EB1C309F843-807A

 Address 72: Door, Rear Right          Labels: 8P4-959-802.lbl
    Part No SW: 8P4 959 802 E     HW: 8P4 959 802 E
    Component: Tuer-SG           H04 0040
    Coding: 0001176
    Shop #: 000 1012544
    VCID: 42DE4354488EADF77BD-8016
-------------------------------------------------------------------------------
```


Memory Locations
1A 11 22
31 4A 3C
1B 1A 33
1A 11 22 31 4A
33 00 00 00
3C 1B 1A
Data

Assumption Scenario

Requirements Says :

- There should be **no pre-condition** for this service to be used
- ALD , Memory Address, Memory size & Data Record to be mentioned as
  - **ALFD** : 12
  - **Memory Address** : **4B 3A**
  - **Memory Size** : **04**
  - **Data Record** : **02 3D**

Introduction

- The Read Memory By Address service is used to **Read** information present in the ECU at an **internal memory location** specified by the provided **memory address** and **memory size**.
- The data can be identified by memory address and size that may or may not be secured (Security Access (0x27) may or may not be included as prior service)
- This is vehicle manufacturer's choice that the **server conditions** are met when performing this service.

"Purpose : Read data in the server using Memory Address"

Frame Format of **Read Memory by Address**

- **Request Frame:**

Service Id

Address & Length Format Id Data

Memory Address

Memory Size

- **Positive Response Frame:**

Service Id

Data

- **Negative Response Frame:**

Negative Response (7F)

Service Id

NRC Code

Terms !!

Data Record

- This parameter provides the data record associated with the **memory address** that the tester is requesting to write in to the server as **data**.

Address and Length Format Identifier

- The number of bytes used for the **Memory Address** and **Memory Size** parameters is defined by Address and Length Format Identifier (low and high nibble)
- It is also possible to have a **fixed** Address and Length Format Identifier within the Memory Address or Memory Size parameter are padded with the value 00 hex in the higher range address locations.
  - **Bit 7-4 : length of memory size parameter**
  - **Bit 3-0 : length of memory address parameter**

Terms !!

Memory Size

- The parameter memory **Size** in the Write Memory by Address request message specifies the number of bytes to be written starting at the address **specified by memory Address** in the **server's memory**.

Memory Address

- The parameter Memory address is the **starting address** of server memory to which data is to be written.
- Its just an address of **memory location** where the data has to be resides



Request & Response





Request & Response



23 - Service ID

12 -

Bit 7-4 : length of memory size parameter (1)

Bit 3-0 : length of memory address parameter (2)

1C 45 - Memory Address

02 - Memory Size

4D CE - Data

0010 – Higher Nibble **(2)**

0001 – Lower Nibble **(1)**

Reading data bytes into server memory for different bytes are possible, for example : 2-byte, 3-byte, and 4-byte addressing formats



Request & Response
3 Bytes



23 - Service ID

13 -

Bit 7-4 : length of memory size parameter (1)

Bit 3-0 : length of memory address parameter (2)

1C 45 2A - Memory Address

03 - Memory Size

4D CE 11- Data

0011 – Higher Nibble **(3)**

0001 – Lower Nibble **(1)**



Request & Response
4 Bytes



23 - Service ID

14 -

Bit 7-4 : length of memory size parameter (1)

Bit 3-0 : length of memory address parameter (2)

1C 45 2A 54 - Memory Address

04 - Memory Size

4D CE 11 01- Data

0100 – Higher Nibble **(4)**

0001 – Lower Nibble **(1)**

List of NRCs Supported

- 0x13 Incorrect Message Length
- 0x22 Conditions Not Correct
- 0x31 Request Out of Range
- 0x33 Security Access Denied

(NRC Priority *)

End of the Tutorial !!