



# PRELIMINARY WORK ITEM International Standard

**ISO/PWI 93333**

## Digital product passport — Vocabulary

*Passeport numérique de produit — Vocabulaire*

ICS: 35.240.63

ISO/JTC 5

Secretariat: DIN

THIS DOCUMENT IS A DRAFT CIRCULATED FOR COMMENTS AND APPROVAL. IT IS THEREFORE SUBJECT TO CHANGE AND MAY NOT BE REFERRED TO AS AN INTERNATIONAL STANDARD UNTIL PUBLISHED AS SUCH.

IN ADDITION TO THEIR EVALUATION AS BEING ACCEPTABLE FOR INDUSTRIAL, TECHNOLOGICAL, COMMERCIAL AND USER PURPOSES, DRAFT INTERNATIONAL STANDARDS MAY ON OCCASION HAVE TO BE CONSIDERED IN THE LIGHT OF THEIR POTENTIAL TO BECOME STANDARDS TO WHICH REFERENCE MAY BE MADE IN NATIONAL REGULATIONS.

RECIPIENTS OF THIS DRAFT ARE INVITED TO SUBMIT, WITH THEIR COMMENTS, NOTIFICATION OF ANY RELEVANT PATENT RIGHTS OF WHICH THEY ARE AWARE AND TO PROVIDE SUPPORTING DOCUMENTATION.

© ISO 2026

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

|                                                                                          |           |
|------------------------------------------------------------------------------------------|-----------|
| <b>Foreword</b>                                                                          | <b>iv</b> |
| <b>Introduction</b>                                                                      | <b>v</b>  |
| <b>1 Scope</b>                                                                           | <b>1</b>  |
| <b>2 Normative references</b>                                                            | <b>1</b>  |
| <b>3 Terms related to the digital product passport</b>                                   | <b>1</b>  |
| <b>4 Terms related to identity and carriers</b>                                          | <b>1</b>  |
| <b>5 Terms related to actors and issuance</b>                                            | <b>5</b>  |
| <b>6 Terms related to lifecycle and events</b>                                           | <b>8</b>  |
| <b>7 Terms related to trust and verification</b>                                         | <b>10</b> |
| <b>8 Terms related to semantics and profiles</b>                                         | <b>13</b> |
| <b>9 Terms related to measurement and material flow</b>                                  | <b>18</b> |
| <b>10 Terms related to the framework: profiles, lenses and jurisdiction</b>              | <b>18</b> |
| <b>11 Terms related to the framework: projection, composition and service tiers</b>      | <b>19</b> |
| <b>12 Terms related to the framework: provenance, identity lattice and edge segments</b> | <b>20</b> |
| <b>13 Terms related to the framework: stamps and the transformation algebra</b>          | <b>22</b> |
| <b>14 Terms related to the framework: characteristic profiles and orphan objects</b>     | <b>23</b> |
| <b>15 Terms related to the framework: capability classes and digital twins</b>           | <b>24</b> |
| <b>16 Terms related to the framework: passport relationship algebra</b>                  | <b>25</b> |
| <b>17 Terms related to the framework: visibility and enumeration resistance</b>          | <b>27</b> |
| <b>18 Terms related to the framework: trust semantics, degradation and federation</b>    | <b>28</b> |
| <b>Annex A Relationship to other standards</b>                                           | <b>31</b> |
| <b>Bibliography</b>                                                                      | <b>35</b> |

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see [www.iso.org/patents](http://www.iso.org/patents)) or the IEC list of patent declarations received (see <https://patents.iec.ch>).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO and IEC specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see [www.iso.org/iso/foreword.html](http://www.iso.org/iso/foreword.html).

This document was prepared by Joint Technical Committee ISO/IEC JTC 5, *Digital product passport*.

## Introduction

A digital product passport makes product-related information available to economic operators, authorities and other parties over the life of a product. The same designations are used today with different definitions in different instruments. Without a single vocabulary, systems that claim conformance to those instruments do not interoperate on meaning.

This document is that vocabulary. It defines the terms required for digital product passport work in ISO/IEC JTC 5 and for referring documents.

Two classes of entry are distinguished. **Structural terms** name the speech acts, roles and mechanisms of the passport framework — attestation, classification, designation, profile, custody transfer — and are defined globally. **Domain-scoped entries** name concepts whose criteria of application are owned by a community: jurisdictions (placed on the market), sectors (textile product), or cultural and appraisal communities (quality designations). Domain-scoped entries are recorded for navigational completeness; each carries a NOTE to that effect, and nothing in this document harmonizes their criteria across communities. Where correspondence between communities exists, it is expressed as a registered mapping item in a semantic registry maintained under the disciplines of ISO 19135, not by definition. Interoperability in this framework is a matter of shared negotiability — identity, time, attestation form, measurement discipline and trust — rather than of shared meaning.

Clause 3 is organized by subject: the digital product passport itself; identity and carriers; actors; life cycle; trust and verification; semantics and profiles; measurement; and the concepts of projection, provenance, composition, capability and federation used when a passport is operated across jurisdictions and systems. Where a definition is taken from another International Standard, that standard is indicated with the entry.

[Annex A](#) provide the relationship of this document to other standards and publications that define or use terms related to those in Clause 3.



# Digital product passport — Vocabulary

## 1 Scope

This document defines terms for the digital product passport (DPP).

This document is applicable to standards, technical specifications and information systems that specify or use digital product passport concepts.

## 2 Normative references

There are no normative references in this document.

## 3 Terms related to the digital product passport

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

- ISO Online browsing platform: available at <https://www.iso.org/obp>
- IEC Electropedia: available at <https://www.electropedia.org>

### 3.1

#### **digital product passport**

concept or technology which enables sharing of product related information that is essential for product sustainability and circularity, including those specified in regulations, across all relevant economic actors

Note 1 to entry: Example characteristics include environmental sustainability, environmental impact, and recyclability.

[SOURCE: CEN EN 18220:2026, 3.6<sup>[56]</sup>, modified — modified, CEN EN 18223:2026, 3.4, modified, CEN EN 18216:2026, 3.7, modified, CEN EN 18221:2026, 3.2, modified, CEN EN 18222:2026, 3.2, modified, CEN EN 18239:2026, 3.9, modified, CEN EN 18246:2026, 3.2, modified, CEN EN 18219:2026, 3.1.3, modified, ISO/AWI 25534-1:2026, 3.1]

### 3.2

#### **digital product passport id**

unique identifier of an instance of the digital product passport

[SOURCE: CEN EN 18223:2026, 3.5<sup>[59]</sup>]

## 4 Terms related to identity and carriers

### 4.1

#### **unique product identifier**

unique string of characters for the identification of a product that also enables a web link to the digital product passport

[SOURCE: CEN EN 18246:2026, 3.3<sup>[61]</sup>, modified]

### 4.2

#### **unique identifier**

identifier which is guaranteed to be unique among all identifiers used for those objects and for a specific purpose

Note 1 to entry: A unique identifier refers to unique product identifier (*unique product identifier* (4.1)), unique economic operator identifier (*unique economic operator identifier* (4.12)), and unique facility identifier (*unique facility identifier* (4.13)).

Note 2 to entry: For more information, see ISO/IEC 15459-1.

Note 3 to entry: Recorded variance: EN 18219:2026 modification: Note 1 to entry removed and a new Note 1 to entry added. EN 18220:2026 modification: “identifier” replaced by “string of characters”, Note 1 to entry removed and a new Note 1 to entry added.

[SOURCE: ISO 29404:2015, 3.26, modified — CEN EN 18219:2026, 3.1.24, similar, CEN EN 18220:2026, 3.18, similar, CEN CWA 18291:2025, 3.3, ISO/IEC 15459-1]

### **4.3** **digital identifier**

sequence of characters associated with digital, non-digital, or abstract entities, such as books, images, reports, metadata records or events

[SOURCE: ISO 24619:2011, 3.2.1, modified — CEN EN 18216:2026, 3.1]

### **4.4** **identification**

process of recognizing an object in a particular domain as distinct from other objects

[SOURCE: ISO/IEC 24760-1, 3.2.1, modified — CEN EN 18216:2026, 3.3]

### **4.5** **identification scheme**

system for allocating identifiers to objects

[SOURCE: ISO/IEC 6523-1, 3.6, modified — modified, CEN EN 18219:2026, 3.1.6]

### **4.6** **domain**

specified area of knowledge, application, or activity within which a unique identifier is used

[SOURCE: CEN EN 18219:2026, 3.1.4<sup>[55]</sup> ]

### **4.7** **self-issuing system**

decentralized identification scheme

system or mechanism that an organization uses to generate and assign unique identifiers to its objects without the intervention or oversight of an external authority

[SOURCE: CEN EN 18219:2026, 3.1.20<sup>[55]</sup> ]

### **4.8** **persistence**

process to keep a unique identifier associated with an identified object throughout its life cycle

[SOURCE: CEN EN 18219:2026, 3.1.13<sup>[55]</sup> , modified — CEN EN 18220:2026, 3.12]

### **4.9** **preservation**

activity of ensuring that a unique identifier and its denotation remain stable, valid, and retrievable for as long as required

[SOURCE: CEN EN 18219:2026, 3.1.15<sup>[55]</sup> ]



#### 4.10

##### **resolution**

process in which an identifier is translated or mapped to another identifier, associated information or metadata about the object it represents

[SOURCE: CEN EN 18219:2026, 3.1.18<sup>[55]</sup>, modified]

#### 4.11

##### **resolver**

system or service that performs resolution (*resolution* ([4.10](#)))

[SOURCE: CEN EN 18219:2026, 3.1.19<sup>[55]</sup>, modified]

#### 4.12

##### **unique economic operator identifier**

unique string of characters for the identification of an actors involved in a product's value chain

Note 1 to entry: The source prints "an actors"; the definition is reproduced verbatim.

[SOURCE: CEN EN 18219:2026, 3.1.22<sup>[55]</sup>]

#### 4.13

##### **unique facility identifier**

unique string of characters for the identification of location or building involved in a product's value chain or used by actors involved in a product's value chain

[SOURCE: CEN EN 18219:2026, 3.1.23<sup>[55]</sup>]

#### 4.14

##### **unique registration identifier**

identifier returned after uploading the unique identifiers and any other data required to the DPP registry

EXAMPLE Unique identifiers can be unique product identifier, unique facility identifier, unique operator identifier of the economic operator etc.

[SOURCE: CEN EN 18222:2026, 3.6<sup>[58]</sup>]

#### 4.15

##### **data carrier**

device or medium used to store data as a relay mechanism in an automatic identification and data capture system

[SOURCE: CEN EN 18220:2026, 3.5<sup>[56]</sup>]

#### 4.16

##### **additional software**

additional application, program, or tool that a user will install or access separately from the default setup of most smartphones or similar devices to interact with the digital product passport

EXAMPLE Proprietary applications, plugins or extensions, dedicated apps, specialized middleware, or customized software readers.

Note 1 to entry: Standard functionalities, such as web browsers, camera-based QR readers, and universal communication protocols (e.g. DNS, HTTP, HTTPS), are not considered as additional software.

[SOURCE: CEN EN 18220:2026, 3.1<sup>[56]</sup>]

#### 4.17

##### **barcode**

printed data carrier indicating either a reference to a linear or a 2D matrix

Note 1 to entry: It excludes RFID data carriers.

[SOURCE: CEN EN 18220:2026, 3.2<sup>[56]</sup>]

#### 4.18

##### **near field communication**

NFC

subset of HF passive radio-frequency identification with low range

[SOURCE: CEN EN 18220:2026, 3.11<sup>[56]</sup>]

#### 4.19

##### **radio-frequency identification**

identification technology that uses electromagnetic fields to automatically identify and track tags attached to objects

[SOURCE: CEN EN 18220:2026, 3.15<sup>[56]</sup>]

#### 4.20

##### **RAIN RFID**

UHF RFID

passive UHF radio-frequency identification (*radio-frequency identification* ([4.19](#)))

Note 1 to entry: Source entry heading: "RAIN RFID (UHF RFID) per ISO/IEC 18000-63".

[SOURCE: CEN EN 18220:2026, 3.16<sup>[56]</sup>]

#### 4.21

##### **two-dimensional symbol**

code representing data in machine-readable form by a collection of polygonal or circular cells in a regular pattern which are read optically by scanning

[SOURCE: CEN EN 18220:2026, 3.17<sup>[56]</sup>]

#### 4.22

##### **X dimension**

specified width of the narrow in a bar code symbol or the specified width of a single element in a two-dimensional symbol

[SOURCE: ISO/IEC 19762, 3.2.1.10, modified — CEN EN 18220:2026, 3.19]

#### 4.23

##### **batch**

subset of a model (*model* ([4.25](#))) that is grouped by an economic operator based on common characteristics

[SOURCE: CEN EN 18220:2026, 3.3<sup>[56]</sup>, modified — similar, CEN EN 18219:2026, 3.1.1]

#### 4.24

##### **item**

single unit of a model (*model* ([4.25](#)))

[SOURCE: CEN EN 18220:2026, 3.8<sup>[56]</sup>, modified — similar, CEN EN 18219:2026, 3.1.9]

#### 4.25

##### **model**

version of a product of which all units share the same technical characteristics and the same model identifier

[SOURCE: CEN EN 18219:2026, 3.1.11<sup>[55]</sup>, modified — CEN EN 18220:2026, 3.10]

#### 4.26

##### **identifier**

identity information that unambiguously distinguishes one entity from another one in a given domain

Note 1 to entry: There are specific identifiers, e.g. UUID Universal unique identifier, IEC 15418 (GS1).

[SOURCE: Glossar Industrie 4.0[47] ]

## 5 Terms related to actors and issuance

### 5.1

#### **economic operator**

manufacturer, authorized representative, importer, distributor, dealer or fulfilment service provider

[SOURCE: CEN EN 18219:2026, 3.1.5<sup>[55]</sup> , modified — similar, CEN EN 18220:2026, 3.7, similar, CEN EN 18221:2026, 3.1]

### 5.2

#### **digital product passport service provider**

natural or legal person that is an independent third party authorized by the economic operator (*economic operator* (5.1)) that places the product on the market or puts it into service and that processes the digital product passport data for that product for the purpose of making such data available to economic operators and other relevant actors with a right to access those data

[SOURCE: CEN EN 18221:2026, 3.3<sup>[57]</sup> ]

### 5.3

#### **main digital product passport service provider**

digital product passport service provider (*digital product passport service provider* (5.2)) that is hosting the digital product passport (*digital product passport* (3.1)) on behalf of the economic operator (*economic operator* (5.1)) if the economic operator chooses not to host the digital product passport themselves

[SOURCE: CEN EN 18221:2026, 3.3.1<sup>[57]</sup> ]

### 5.4

#### **back-up digital product passport service provider**

digital product passport service provider (*digital product passport service provider* (5.2)) that is hosting the back-up copy of the digital product passport (*digital product passport* (3.1))

[SOURCE: CEN EN 18221:2026, 3.3.2<sup>[57]</sup> ]

### 5.5

#### **issuing agency**

organisation entrusted by a Registration Authority (RA) to manage unique identification schemes

[SOURCE: CEN EN 18219:2026, 3.1.8<sup>[55]</sup> ]

### 5.6

#### **actor**

organization or individual that fulfils a role

[SOURCE: ISO 23234:2021, 3.4, modified — CEN EN 18239:2026, 3.7]

### 5.7

#### **notified actor**

organization or individual entitled by an authorized accrediting body or authority, that fulfils a role in the DPP lifecycle

[SOURCE: CEN EN 18239:2026, 3.8<sup>[60]</sup> ]

**5.8**

**consumer**

individual member of the general public purchasing or using goods, property or services for private purposes

[SOURCE: CEN EN ISO 14025:2010, 3.16<sup>[62]</sup>, modified — CEN EN 18219:2026, 3.1.2, CEN EN 18220:2026, 3.4, CEN CWA 18291:2025, 3.24]

**5.9**

**customer**

organization or person that receives a product

Note 1 to entry: The customer may be the user or a distributor [SOURCE: ISO 9000].

[SOURCE: ISO 9000:2015]

**5.10**

**expert**

expert in charge of performing a study

[SOURCE: CEN CWA 18291:2025, 3.8<sup>[53]</sup>]

**5.11**

**reviewer**

expert in charge of reviewing a study

[SOURCE: CEN CWA 18291:2025, 3.9<sup>[53]</sup>]

**5.12**

**exporter**

name and address of the person who makes, or on whose behalf the “export declaration” is made, and who is the owner of the goods or has similar right of disposal over them at the time when the declaration is accepted

[SOURCE: ISO/TS 24533:2012]

**5.13**

**seller**

company or company function that sells a product

[SOURCE: CEN CWA 18291:2025, 3.11<sup>[53]</sup>]

**5.14**

**subcontractor**

company or company function that performs activities as a sub-contractor (for example cutting/sewing operations but also dyeing)

[SOURCE: CEN CWA 18291:2025, 3.12<sup>[53]</sup>]

**5.15**

**buyer**

individual or entity purchasing goods or services

[SOURCE: ISO 24533-2:2022]

**5.16**

**producer**

company or company function that produces final or non-final fashion products (yarns, fabrics, garments, accessories, footwear, etc.); its industrial process has in input materials and in output components or final fashion goods for the business customers or final customers

[SOURCE: CEN CWA 18291:2025, 3.14<sup>[53]</sup>]

**5.17**

**supplier**

company or company function that produces non final products (accessories, fabrics, yarns...); its industrial process has in input materials and in output components for the business customers

[SOURCE: CEN CWA 18291:2025, 3.15<sup>[53]</sup> ]

**5.18**

**yarn producer**

company or company function that produces yarns from raw material; it has mainly Fabric and Knitwear producers as customers (Apparel Producers sometimes)

Note 1 to entry: Domain-scoped entry — the criteria of application of this concept are owned by the communities (jurisdictional, sectoral or cultural) that govern it; this entry is recorded for navigational completeness and does not harmonize those criteria across communities (see the Introduction).

[SOURCE: CEN CWA 18291:2025, 3.16<sup>[53]</sup> ]

**5.19**

**retailer**

company or company function that sells garments to the Consumer. It is a client of Apparel Producer, Knitwear Producer, and Yarn Producer

[SOURCE: CEN CWA 18291:2025, 3.17<sup>[53]</sup> ]

**5.20**

**apparel producer**

company or company function that organizes manufacturing and material supplying to obtain finished garments from fabrics. It is a client of Fabric Producer and partially of Yarn Producer

Note 1 to entry: Domain-scoped entry — the criteria of application of this concept are owned by the communities (jurisdictional, sectoral or cultural) that govern it; this entry is recorded for navigational completeness and does not harmonize those criteria across communities (see the Introduction).

[SOURCE: CEN CWA 18291:2025, 3.18<sup>[53]</sup> ]

**5.21**

**sorter**

person or a system that categorizes discarded textile materials by their fibre composition, color, and condition to determine their potential for reuse, repair, or recycling

Note 1 to entry: Domain-scoped entry — the criteria of application of this concept are owned by the communities (jurisdictional, sectoral or cultural) that govern it; this entry is recorded for navigational completeness and does not harmonize those criteria across communities (see the Introduction).

[SOURCE: CEN CWA 18291:2025, 3.19<sup>[53]</sup> ]

**5.22**

**textile collector**

actor involved in separate collection of textiles

Note 1 to entry: Domain-scoped entry — the criteria of application of this concept are owned by the communities (jurisdictional, sectoral or cultural) that govern it; this entry is recorded for navigational completeness and does not harmonize those criteria across communities (see the Introduction).

[SOURCE: ISO 5157:2023]

**5.23**

**recycler**

company or company function that performs activities to obtain recovered resources for use in a process or a product, excluding energy recovery

Note 1 to entry: Activities to obtain resources include activities such as recovery, collection, transport, sorting, cleaning, and re-processing.

Note 2 to entry: Recycling does not include reuse.

[SOURCE: ISO 59004:2024]

#### 5.24

##### **eService platform**

platform for eBusiness centralized services

[SOURCE: CEN CWA 18291:2025, 3.5<sup>[53]</sup>]

#### 5.25

##### **traceability platform**

platform dedicated to traceability services

[SOURCE: CEN CWA 18291:2025, 3.6<sup>[53]</sup>]

#### 5.26

##### **sustainability management platform**

platform dedicated to sustainability data collection, management and reporting

[SOURCE: CEN CWA 18291:2025, 3.7<sup>[53]</sup>]

## 6 Terms related to lifecycle and events

### 6.1

#### **life cycle**

consecutive and interlinked stages of a product system, from raw material acquisition or generation from natural resources to final disposal

[SOURCE: ISO 14040:2006, 3.1, modified — ISO/AWI 25534-1:2026, 3.2, CEN EN 18219:2026, 3.1.10, CEN EN 18220:2026, 3.9]

### 6.2

#### **product**

any physical good that is placed on the market (*placed on the market* (6.3)) or put into service (*put into service* (6.4))

[SOURCE: CEN EN 18220:2026, 3.14<sup>[56]</sup>, modified — similar, CEN EN 18219:2026, 3.1.16]

### 6.3

#### **placed on the market**

first making available of a product

Note 1 to entry: Domain-scoped entry — the criteria of application of this concept are owned by the communities (jurisdictional, sectoral or cultural) that govern it; this entry is recorded for navigational completeness and does not harmonize those criteria across communities (see the Introduction).

[SOURCE: CEN EN 18219:2026, 3.1.14<sup>[55]</sup>]

### 6.4

#### **put into service**

first use, for its intended purpose, of a product

Note 1 to entry: Domain-scoped entry — the criteria of application of this concept are owned by the communities (jurisdictional, sectoral or cultural) that govern it; this entry is recorded for navigational completeness and does not harmonize those criteria across communities (see the Introduction).

[SOURCE: CEN EN 18219:2026, 3.1.17<sup>[55]</sup> ]

## 6.5

### **digital product passport lifetime**

period during which the digital product passport (*digital product passport* (3.1)) is required by regulation to be available to any operator or natural or legal person with a right to access its data

[SOURCE: CEN EN 18221:2026, 3.4<sup>[57]</sup> ]

## 6.6

### **end-of-use**

point in time during the life cycle at which a product or resource is transferred by the holder to some other holder

EXAMPLE When an organization (e.g., shop or retailer) in possession of the product considers it to be a waste since it hasn't or can't be sold.

[SOURCE: ISO 59004:2024]

## 6.7

### **end-of-life**

point in time during the life cycle at which a product or resource is taken out of use and is disposed

Note 1 to entry: Disposal could be in the form of incineration, deposit to landfill, or composting.

[SOURCE: ISO 59004:2024]

## 6.8

### **collection**

process of gathering and transporting used textile products or waste materials to a sorting facility for further processing such as reuse, repair, remanufacturing, or recycling

[SOURCE: ISO 5157:2023]

## 6.9

### **closed loop system**

system by which products or resources are used and then recovered and turned into new products or recovered resources, without losing their inherent properties

[SOURCE: ISO 59004:2024]

## 6.10

### **traceability**

ability to trace the history, application or location of an object in a value chain

Note 1 to entry: Lineage: ISO/AWI 25534-1, 3.5 adopts this definition from ISO 9000:2015, modified by the addition of "in a value chain".

[SOURCE: UNECE Recommendation No. 46<sup>[49]</sup> , modified — CEN CWA 18291:2025, 3.29]

## 6.11

### **traceability system**

practical system of processes, procedures and information exchanges that implements traceability

[SOURCE: UNECE Recommendation No. 46<sup>[49]</sup> ]

## 6.12

### **traceable asset**

traceable asset is any product or material (individually, in batches, or in trade units) that needs to be tracked along a value chain

[SOURCE: UNECE Recommendation No. 46<sup>[49]</sup> ]

### 6.13

#### **textile product**

product made mainly of textile fibres, yarns and/or fabrics and intended to be used, as such or in conjunction with other textile or non-textile elements

Note 1 to entry: Domain-scoped entry — the criteria of application of this concept are owned by the communities (jurisdictional, sectoral or cultural) that govern it; this entry is recorded for navigational completeness and does not harmonize those criteria across communities (see the Introduction).

Note 2 to entry: These articles can contain non-textile parts, such as plastics (e.g. buttons and membrane or coatings) or metals.

Note 3 to entry: Source entry heading: “textile product – product”.

[SOURCE: ISO 5157:2023]

### 6.14

#### **circular economy**

products and materials are designed in such a way that they can be reused, remanufactured, recycled or recovered and thus maintained in the economy for as long as possible, along with the resources of which they are made, and the generation of waste, especially hazardous waste, is avoided or minimized and greenhouse gas emissions are prevented or reduced, can contribute significantly to sustainable consumption and production

Note 1 to entry: Domain-scoped entry — the criteria of application of this concept are owned by the communities (jurisdictional, sectoral or cultural) that govern it; this entry is recorded for navigational completeness and does not harmonize those criteria across communities (see the Introduction).

[SOURCE: ISO/AWI 25534-1:2026, 3.3, modified]

### 6.15

#### **product circularity**

refers to repairing, reusing and remanufacturing equipment, and harvesting and recycling metals indefinitely through product design and collection processes

Note 1 to entry: Domain-scoped entry — the criteria of application of this concept are owned by the communities (jurisdictional, sectoral or cultural) that govern it; this entry is recorded for navigational completeness and does not harmonize those criteria across communities (see the Introduction).

[SOURCE: ISO/AWI 25534-1:2026, 3.4, modified]

### 6.16

#### **value chain**

all activities and stakeholders that provide or receive value from designing, developing, making, distributing, retailing, and consuming a product (or providing the service that a product renders), including the extraction and supply of raw materials, as well as activities involving the product after its useful service life has ended

Note 1 to entry: Compared with the source: the source is framed for the textile sector; the AWI draft reformulates the term in a sector-neutral form.

[SOURCE: ISO/AWI 25534-1:2026, 3.8, modified — UNEP Job no. DTI/2532/PA, modified]

## **7 Terms related to trust and verification**

### 7.1

#### **controlled DPP data**

information on digital product passport whose access is controlled based on the user’s access rights

Note 1 to entry: User in the sense of a person who interacts with a system, product or service.

[SOURCE: CEN EN 18239:2026, 3.1<sup>[60]</sup>, modified — CEN EN 18216:2026, 3.8]



**7.2**

**authentication**

verification that a claimed identity is correct

[SOURCE: ISO/IEC/IEEE 8802-1AR, 3.2, modified — CEN EN 18216:2026, 3.4]

**7.3**

**data integrity**

property that data has not been altered or destroyed in an unauthorised manner

Note 1 to entry: In the context of secure communication, data integrity ensures that data transmitted between parties remains unaltered and intact from the moment it leaves the sender to the moment it reaches the receiver. This means that the data has not been tampered with, modified, or corrupted during transmission – whether accidentally or through malicious actions.

[SOURCE: ISO 7498-2:1989, 3.3.21, modified — modified, CEN EN 18216:2026, 3.5]

**7.4**

**secure communication**

mechanism of transmitting data between systems in a way that ensures its confidentiality, integrity and authenticity

[SOURCE: CEN EN 18216:2026, 3.6<sup>[54]</sup>]

**7.5**

**system resilience**

ability to recover from security compromises or attacks

[SOURCE: ISO/IEC 29180:2012]

**7.6**

**system availability**

property of being accessible and usable on demand by an authorized entity

[SOURCE: ISO/IEC 27000]

**7.7**

**cyber resilience**

ability to maintain business continuity despite adverse conditions, attacks, or compromises on critical data flow and related information systems

[SOURCE: CEN EN 18239:2026, 3.4<sup>[60]</sup>]

**7.8**

**recovery point objective**

RPO

point in time to which data must be recovered after a disruption has occurred

[SOURCE: ISO/IEC 27031, 3.12, modified — CEN EN 18239:2026, 3.5]

**7.9**

**recovery time objective**

RTO

period of time within which minimum levels of services and/or products and the supporting systems, applications, or functions must be recovered after a disruption has occurred

[SOURCE: ISO/IEC 27031]

**7.10**

**object**

entity to which specified requirements apply

EXAMPLE Product, process, service, system, installation, project, data, design, material, claim, person, body or organization, or any combination thereof.

[SOURCE: ISO/IEC 17000:2020, 4.2, modified — modified, CEN EN 18219:2026, 3.1.12]

### 7.11

#### **PIA**

RFID privacy impact assessment process

RFID Privacy Impact Assessment Process

[SOURCE: CEN EN 18220:2026, 3.13<sup>[56]</sup>]

### 7.12

#### **claim**

high-level statement about a characteristic of a product, or about a process or an organization associated with that product (traceable asset). A sustainability claim is a claim that covers one or multiple sustainability dimensions (economic, environmental, social)

Note 1 to entry: In this document “sustainability claims” are referred to as just “claims”.

[SOURCE: UNECE Recommendation No. 46[49] ]

### 7.13

#### **state-of-the-art**

developed stage of technical capability at a given time as regards products, processes and services, based on the relevant consolidated findings of science, technology and experience

Note 1 to entry: Domain-scoped entry — the criteria of application of this concept are owned by the communities (jurisdictional, sectoral or cultural) that govern it; this entry is recorded for navigational completeness and does not harmonize those criteria across communities (see the Introduction).

[SOURCE: ISO/IEC Guide 2:2004, 1.4, modified — CEN EN 18219:2026, 3.1.21]

### 7.14

#### **access control**

protection of system resources against unauthorized access; a process by which use of system resources is regulated according to a security policy and is permitted by only authorized entities (users, programs, processes, or other systems) according to that policy

[SOURCE: IEC TS 62443-1-1:2009]

### 7.15

#### **electronically signed data construct**

structured data set containing the header, payload, signature and optional data fields

Note 1 to entry: The payload type and issuer identity are included in the header.

Note 2 to entry: An ESDC is a machine-readable code.

Note 3 to entry: An ESDC can contain non-signed data elements.

[SOURCE: CEN EN 18246:2026, 3.1<sup>[61]</sup>, modified]

### 7.16

#### **validation**

confirmation of the plausibility for a specific intended use or application through the provision of objective evidence that specified requirements have been met

Note 1 to entry: Compared with the source: numbers referencing to related sections and the accompanying note have been removed from the definition.

[SOURCE: ISO/AWI 25534-1:2026, 3.6, modified — ISO/IEC 17000:2020, 6.5, modified]

#### 7.17

##### **verification**

confirmation of the truthfulness through the provision of objective evidence that specified requirements have been fulfilled

Note 1 to entry: Compared with the source: numbers referencing to related sections and the accompanying note have been removed from the definition.

[SOURCE: ISO/AWI 25534-1:2026, 3.7, modified — ISO/IEC 17000:2020, 6.6, modified]

## 8 Terms related to semantics and profiles

### 8.1

#### **interoperability**

ability of two or more systems or applications to exchange information and to mutually use the information that has been exchanged

[SOURCE: ISO/IEC 22123-1:2023, 3.6.1, modified — CEN EN 18223:2026, 3.1, similar, ISO 18435-1:2009, 3.12, similar, CEN EN 18219:2026, 3.1.7]

### 8.2

#### **semantic interoperability**

ability for data shared by systems to be understood at the level of fully defined domain concepts

[SOURCE: ISO 18308:2011, 3.45, modified — CEN EN 18223:2026, 3.2]

### 8.3

#### **technical interoperability**

ability that covers the applications and infrastructures linking systems and services

[SOURCE: CEN EN 18223:2026, 3.3<sup>[59]</sup>]

### 8.4

#### **application programming interface**

set of methods (*method* (8.6)) provided by an application component for use by other application components

[SOURCE: CEN EN 18222:2026, 3.1<sup>[58]</sup>]

### 8.5

#### **representational state transfer application programming interface**

service that allows for interaction with resources via a stateless, client-server architecture, typically using standard HTTP calls like GET, POST, PUT, and DELETE to perform methods (*method* (8.6)) by an application component on these resources

[SOURCE: CEN EN 18222:2026, 3.1.1<sup>[58]</sup>]

### 8.6

#### **method**

particular way used to perform a specific action on a resource

EXAMPLE read a DPP

[SOURCE: CEN EN 18222:2026, 3.3<sup>[58]</sup>]

### 8.7

#### **parameter**

data provided by a client, that is needed to perform a method (*method* (8.6))

EXAMPLE      DPP ID for read DPP

[SOURCE: CEN EN 18222:2026, 3.4<sup>[58]</sup>]

## 8.8

### result

return value after the execution of a method (*method* (8.6))

EXAMPLE      the DPP

[SOURCE: CEN EN 18222:2026, 3.5<sup>[58]</sup>]

## 8.9

### data exchange

storing, accessing, transferring, and archiving of data

[SOURCE: ISO 15531-43, 3.1.5, modified — CEN EN 18216:2026, 3.2]

## 8.10

### application

software functional element specific to the solution of a problem in industrial-process measurement and control

Note 1 to entry: An application can be distributed among resources and may communicate with other applications.

[SOURCE: IEC TR 62390:2005, 3.1.2, modified — IDTA 01001-3.2:2026, 1.1.2]

## 8.11

### asset

entity owned by or under the custodial duties of an organization, which has either a perceived or actual value to the organization

EXAMPLE 1      Examples for physical entities are equipment, raw material, parts components and pieces, supplies, consumables, physical products, and waste.

EXAMPLE 2      Software is an example of a digital asset.

EXAMPLE 3      A software license is an example of an intangible asset.

Note 1 to entry: An asset can be single entity, a collection of entities, an assembly of entities or a composition of entities.

[SOURCE: IEC 63278-1:2023]

## 8.12

### attribute

data element of a property, a relation, or a class in information technology

[SOURCE: IEC 63278-1:2023]

## 8.13

### Asset Administration Shell

standardized digital representation of an asset

Note 1 to entry: Asset Administration Shell and Administration Shell are used synonymously.

[SOURCE: IEC 63278-1:2023]

## 8.14

### class

description of a set of objects that share the same attributes, operations, methods, relationships, and semantics

[SOURCE: IEC TR 62390:2005, 3.1.4, modified — IDTA 01001-3.2:2026, 1.1.6]

### 8.15

#### **capability**

implementation-independent potential of a component to achieve an effect within a domain

Note 1 to entry: Capabilities can be orchestrated and structured hierarchically.

Note 2 to entry: Capabilities can be made executable via services.

Note 3 to entry: The impact manifests itself in a measurable effect within the physical world.

[SOURCE: Glossar Industrie 4.0[47] ]

### 8.16

#### **coded value**

value that can be looked up in a dictionary and can be translated

[SOURCE: ECLASS[45] ]

### 8.17

#### **component**

product used as a constituent in an assembled product, system, or plant

[SOURCE: IEC 63278-1:2023, 3.6, modified — IDTA 01001-3.2:2026, 1.1.9]

### 8.18

#### **concept**

unit of knowledge created by a unique combination of characteristics

[SOURCE: IEC 63278-1:2023]

### 8.19

#### **digital representation**

information and services representing an entity from a given viewpoint

EXAMPLE 1 Examples of information are properties (e.g. maximum temperature), actual parameters (e.g. actual velocity), events (e.g. notification of status change), schematics (electrical), and visualization information (2D and 3D drawings).

EXAMPLE 2 Examples of services are asset services (for example providing the history of the configuration data or providing the actual velocity) and asset related services (for example providing a simulation).

EXAMPLE 3 Examples of viewpoints are mechanical, electrical, or commercial characteristics.

[SOURCE: IEC 63278-1:2023]

### 8.20

#### **digital twin**

digital representation, sufficient to meet the requirements of a set of use cases

Note 1 to entry: In this context, the entity in the definition of digital representation is typically an asset.

[SOURCE: IDTA 01001-3.2:2026, 1.1.12[50] ]

### 8.21

#### **explicit value**

commonly used concept, like numbers (e.g. 109, 25) which do not need lookup in dictionaries

[SOURCE: ECLASS[45] ]

### 8.22

#### **instance**

concrete, clearly identifiable component of a certain type

Note 1 to entry: An individual entity of a type, for example a device, is obtained by defining specific property values.

Note 2 to entry: In an object-oriented view, an instance denotes an object of a class (of a type).

[SOURCE: IEC 62890:2016]

### 8.23

#### **instance asset**

specific asset that is uniquely identifiable

EXAMPLE Examples of instance assets are material, a product, a part, a device, a machine, software, a control system, or a production system.

[SOURCE: IEC 63278-1:2023]

### 8.24

#### **operation**

executable realization of a function

Note 1 to entry: The term method is synonymous to operation.

Note 2 to entry: An operation has a name and a list of parameters [ISO 19119:2005, 4.1.3].

[SOURCE: Glossar Industrie 4.0[47] ]

### 8.25

#### **property**

defined characteristic suitable for the description and differentiation of products or components

Note 1 to entry: The concept of type and instance applies to properties.

Note 2 to entry: This definition applies to properties as described in IEC 61360/ ISO 13584-42.

Note 3 to entry: The property types are defined in dictionaries (like IEC component data dictionary or ECLASS), they do not have a value. The property type is also called data element type in some standards.

Note 4 to entry: The property instances have a value and are provided by the manufacturers. A property instance is also called property-value pair in certain standards.

Note 5 to entry: Properties include nominal value, actual value, runtime variables, measurement values, etc.

Note 6 to entry: A property describes one characteristic of a given object.

Note 7 to entry: The specification of a property can include predefined choices of values.

[SOURCE: Glossar Industrie 4.0[47] ]

### 8.26

#### **qualifier**

well-defined element associated with a property instance or SubmodelElement, restricting the value statement to a certain period of time or use case

Note 1 to entry: Qualifiers can have associated values.

[SOURCE: IEC 62569-1:2017]

### 8.27

#### **service**

distinct part of the functionality that is provided by an entity through interfaces

[SOURCE: IEC 63278-1:2023, Clause 741-01-28, modified — IDTA 01001-3.2:2026, 1.1.20]

### 8.28

#### **Submodel**

representation of an aspect of an asset

[SOURCE: IEC 63278-1:2023]

**8.29**

**SubmodelElement**

element of a Submodel

[SOURCE: IEC 63278-1:2023]

**8.30**

**Submodel template**

template for the representation of an aspect of an asset

[SOURCE: IEC 63278-1:2023]

**8.31**

**Submodel template element**

element of a Submodel template

[SOURCE: IEC 63278-1:2023]

**8.32**

**system**

interacting, interrelated, or interdependent elements forming a complex whole

[SOURCE: IEC 63278-1:2023, 3.2.123, modified — IDTA 01001-3.2:2026, 1.1.25]

**8.33**

**template**

specification of the common features of an object in sufficient detail that such object can be instantiated using it

Note 1 to entry: Object can be anything that has a type.

[SOURCE: ISO/IEC 10746-2]

**8.34**

**type**

hardware or software element which specifies the common attributes shared by all instances of the type

[SOURCE: IEC TR 62390:2005, 3.1.25, modified — IDTA 01001-3.2:2026, 1.1.27]

**8.35**

**type asset**

(abstract) representation of a set of instance assets with common characteristics and features

EXAMPLE Examples of type assets are type of material, a product type, a type of a part, a device type, a machine type, a type of software, a type of control system, a type of production system.

Note 1 to entry: The set of instance assets may exist or may not exist.

[SOURCE: IEC 63278-1:2023]

**8.36**

**variable**

software entity that may take different values, one at a time

[SOURCE: IEC 61499-1:2012]

## 9 Terms related to measurement and material flow

### 9.1

#### mass balance model

chain of custody model in which materials or products with a set of specified characteristics are mixed according to defined criteria with materials or products without that set of characteristics

Note 1 to entry: The proportion of the input with specified characteristics can only match the initial proportions on average and will typically vary across different outputs.

[SOURCE: ISO 22095:2020, 3.3.4, modified — CEN CWA 18291:2025, 3.28]

## 10 Terms related to the framework: profiles, lenses and jurisdiction

### 10.1

#### profile

registered, versioned object that binds a set of data points, transforms, cryptographic suites, trust requirements, access policies, presentation requirements and a trigger predicate to the neutral core passport, constraining and transforming, but never redefining, the single definition of each data point

Note 1 to entry: Composition is three-axial: jurisdiction, sector, characteristic.

Note 2 to entry: Each profile is a projection function, `view(twinState, profile, actor)`, whose projection may transform and not merely select.

Note 3 to entry: Profiles constrain and transform; inter-profile disagreement is expected and auditable, while intra-class contradiction is an integrity incident (single definition, many constraints).

### 10.2

#### lens

profile conceived as a calibrated measuring instrument placed on the digital twin, which selects and transforms without altering the observed scene

Note 1 to entry: The mount, the profile interface on the neutral core, is the standardized element: any registered lens by any maker attaches to it.

Note 2 to entry: A lens publishes its calibration (version and cited rules), its uncertainty and its decision rules; it is subject to pattern approval at registration and to periodic re-verification through conformance runs.

Note 3 to entry: Verification path-finds from any render through the lens and its fact chain to an anchor in the verifier's trust bundle.

### 10.3

#### lens mount

standardized interface of the neutral core through which any registered profile is attached to and operates on the record of the subject, such that profiles from any registering authority compose without proprietary binding

Note 1 to entry: The mount, not any single profile technology, is the interoperation point; standardizing it precludes lock-in to a proprietary profile mechanism.

### 10.4

#### jurisdiction profile

profile that binds the data points, transforms, cryptographic suites, trust requirements, access rules, presentation and carrier requirements enacted by the law of a given jurisdiction

Note 1 to entry: Conflicting regional rules are registered as distinct data elements harmonized to a common concept; they are not merged.



## 10.5

### **sector overlay**

profile that composes with other profiles to add the data points, transforms and rules applicable to an industry sector, such as electronics, textiles, batteries, construction, tyres or packaging

## 10.6

### **applicable law**

totality of legal rules that apply to a subject placed on a market, represented in the passport system by the corresponding jurisdiction profile and its dated applicability bindings

## 10.7

### **as-of query**

query against the event-sourced record of a subject that reconstructs the state that was legally valid at a specified past time

Note 1 to entry: As-of queries are answered from notarized snapshots, log anchoring and recorded profile-version bindings, for example to establish whether a product was compliant when sold.

## 10.8

### **trust list**

signed, registry-deposited list of the trust anchors accredited to act under a given profile or jurisdiction, served with status and revocation information

Note 1 to entry: Jurisdictional trust lists relate to one another through a multi-witnessed master list.

## 11 Terms related to the framework: projection, composition and service tiers

### 11.1

#### **projection**

deterministic, registered and legally cited view of the testimonial record of a governed digital twin, computed under a profile from the event-sourced change log

Note 1 to entry: The passport is the legal materialized view of the twin; the twin is the source of truth.

Note 2 to entry: Notarized snapshots support as-of queries, which answer what was legally true at a given time.

Note 3 to entry: Any conforming twin can emit the view; the projection is defined representation-neutrally.

### 11.2

#### **materialized view**

rendered, citable result of a projection, materialized at a point in time for serving and verification

Note 1 to entry: The digital product passport is the legal materialized view of the digital twin.

### 11.3

#### **child passport**

passport of a component or sub-product that is independently placed on the market or independently regulated, referenced by identity from the passport of the composite product

Note 1 to entry: Children join by identity reference, never by data copying; roll-up views are computed from the references.

### 11.4

#### **containment event**

typed event recording that one passport is physically or structurally contained in another, retained for genealogy and recall traversal and never transferring authority

### 11.5

#### **genealogy**

complete directed ancestry of a passport, traced through transformation and containment events from raw-material and component passports to the present subject

## 11.6

### **as-of state**

state of a subject reconstructed from its event-sourced record at a specified past time, anchored by a notarized snapshot so that queries can answer what was legally true at that time

Note 1 to entry: The two authoritative query modes are the live view (freshness-labelled) and the notarized as-of snapshot (log-anchored); legal purpose selects the mode.

Note 2 to entry: Transformation events hash-link their inputs by as-of state hash, and profile-version bindings recorded as lifecycle events make manifest history as-of-reconstructable, answering questions such as whether a product was compliant when sold.

Note 3 to entry: Mirrors and caches are always as-of stamped; the projection is computed from the record, so as-of queries are reproducible.

## 11.7

### **offline minimum**

subset of passport data and verification material specified as sufficient for offline verification of identity and status from the data carrier alone

Note 1 to entry: The Tier-A payload is the carrier-embedded realization of the offline minimum.

## 11.8

### **degradation ladder**

ordered set of service tiers by which availability and verification degrade explicitly, from the served full passport through the carrier-embedded minimum to the archival record

Note 1 to entry: Stale or offline data is always marked as such, never silently passed as current.

## 11.9

### **Tier-A payload**

carrier-embedded minimum viable passport, comprising the product identifier, the resolver URI, the economic operator identifier, the status, the critical safety or recall flag, the validity and multi-suite compressed signatures, sized to the data carrier and verifiable offline against pre-cached trust anchors

Note 1 to entry: The three-tier degradation ladder comprises Tier A (carrier-embedded minimum), Tier B (served full passport) and Tier C (archival).

Note 2 to entry: Stale or offline data degrades explicitly through freshness verdicts and never passes silently.

## 11.10

### **Tier-B payload**

full passport content, served through resolution and hosting services in accordance with the applicable profile

## 11.11

### **Tier-C archive**

notarized archival form of the passport record, retained for persistence beyond the operational lifetime of any single provider

## 12 Terms related to the framework: provenance, identity lattice and edge segments

### 12.1

#### **provenance class**

declared category of a fact according to how it entered the record: declared at type level, measured at instance level under a stated method and uncertainty, or computed by a stated transform

### 12.2

#### **precedence rule**

rule declared by a profile stating which provenance class prevails when facts about the same subject disagree

Note 1 to entry: The default precedence is instance-measured over type-declared; a genuine same-class contradiction is an integrity incident, never a silent merge.

### 12.3

#### **roll-up attestation**

signed attestation giving an aggregate over a committed traversal set of child passports, verifiable without fetching every member of the set

### 12.4

#### **traversal set**

committed, hash-identified set of passport versions over which a roll-up attestation or a graph traversal is computed

### 12.5

#### **edge segment**

part of the event-sourced record of a subject that originates on the subject's own device and is published through device commitments

Note 1 to entry: The device is a tier of the passport system, not a client; it commits now and reveals later, but never contradicts.

### 12.6

#### **device commitment**

signature by a device-bound key over the hash of a prefix of the device's local append-only event log, published so that later disclosures are inclusion-consistent with past commitments

### 12.7

#### **configuration vector**

exact combination of registered component options that, together with a model, constitutes a configured product instance

### 12.8

#### **type version**

versioned state of a type passport capturing hardware revisions and type-declared facts, referenced exactly by the instance passports derived from it

### 12.9

#### **derived type**

new type resulting from a regulated modification of an existing type, recorded as a derivation event in the identity lattice

### 12.10

#### **dormant identifier**

identifier recorded at the finest available granularity for an object class for which no passport regime yet exists, held as issuance evidence for adoption by a future regime

Note 1 to entry: When a future regime issues passports for the object class it adopts the recorded dormant identifiers rather than minting new ones, so that the installed base connects retroactively through its build records.

Note 2 to entry: Inputs are recorded even when no passport exists behind them yet; minting fresh identifiers would orphan the installed base.

### 12.11

#### **dormant-to-live adoption**

act of a future passport regime of issuing passports by adopting the identifiers already recorded as dormant for the object class, rather than minting new ones

Note 1 to entry: Adoption connects the installed base retroactively through its build records; minting fresh identifiers would orphan it.

## 13 Terms related to the framework: stamps and the transformation algebra

### 13.1

#### **stamp**

lens-scoped attestation consisting of an attester signature over the subject, the subject state commitment, the lens identity and version, the mode (live or snapshot), a verdict with coverage report, and log-anchored time

Note 1 to entry: Stamps accrete append-only and are valid under the stamper's lens regardless of the issuer's.

Note 2 to entry: Jurisdiction stamps on a foreign-issued passport correspond to visas; entry and exit stamps correspond to verifier custody events.

Note 3 to entry: Stamps may carry quantity context, inherited by downstream transformations.

### 13.2

#### **lens-scoped attestation**

attestation whose validity is defined by, and only by, the profile under which it was issued

Note 1 to entry: A stamp is the signed form of a lens-scoped attestation.

### 13.3

#### **derived passport**

passport issued as the output of a transformation event by an actor accredited for the regulated claims it contains, hash-linking its input passports

Note 1 to entry: Only accredited actors may issue derived passports for regulated claims.

Note 2 to entry: Children of a split carry a derived-from reference and quantity carve-outs, with the sum of children not exceeding the parent (remainder semantics).

### 13.4

#### **transformation event**

typed event in the provenance directed acyclic graph that records the split of one passport into many, or the combination or transformation of many passports into one

Note 1 to entry: The output issuance event carries input references of passport, quantity and as-of state hash, so the new passport hash-links its sources.

Note 2 to entry: Quantities resulting from a transformation are new measured facts with provenance "computed by transformation event", never copies; mass balance is auditable as input minus output equals loss.

Note 3 to entry: Inputs transition to consumed or transformed status: historical, still verifiable, still needed for as-of queries.

### 13.5

#### **inputReference**

record in the issuance event of a derived passport naming an input passport, the quantity consumed and the as-of state hash under which it was taken

Note 1 to entry: The new passport hash-links its sources, so that the provenance graph is reconstructable without trusting the issuing actor alone.

### 13.6

#### **quantity carve-out**

recorded allocation of input quantity to an output of a split transformation, such that the sum of the child quantities does not exceed the parent

### 13.7

#### **mass balance accounting**

bookkeeping over transformation events in which inputs and outputs of a specified characteristic are reconciled per period, with losses and taint carried explicitly

Note 1 to entry: Mass balance accounting applies a mass balance model (3.7.1) to a set of transformation events.

### 13.8

#### **consumed passport**

input passport that has reached the consumed or transformed state in a transformation event, retaining historical verifiability for as-of queries

### 13.9

#### **blind provenance**

attestation of input provenance issued by a notified or accredited body that withholds the raw input identities behind its own attestation, used where commercial confidentiality demands it

### 13.10

#### **jurisdiction stamp**

stamp issued under a jurisdiction profile on a passport issued under another jurisdiction, recording that the stamping jurisdiction's requirements were assessed

Note 1 to entry: The colloquial designation of a jurisdiction stamp on a foreign-issued passport is "visa"; entry and exit stamps are the verifier's custody events.

## 14 Terms related to the framework: characteristic profiles and orphan objects

### 14.1

#### **characteristic profile**

profile that attaches by predicate on digital twin facts, such as age, material content, heritage status or market status, rather than by law-of-place or industry

Note 1 to entry: Characteristic profiles split into regulatory-triggered profiles (for example CITES species content, cultural-goods import controls, art-market due diligence, conflict-minerals origin) and voluntary value profiles (for example provenance and grading for antiques and collectibles).

Note 2 to entry: Predicate triggers include time predicates: an object becoming older than a given age is a clock-fired applicability event handled by the dated-binding machinery.

### 14.2

#### **trigger predicate**

declared component of a profile stating the conditions under which the profile applies, evaluated against the facts of the digital twin rather than against who declares them

Note 1 to entry: Characteristic profiles attach by predicate on twin facts, namely age, material content, heritage status, market status, rather than by law-of-place or industry.

Note 2 to entry: Predicate triggers include time predicates: an object becoming older than a given age is a clock-fired applicability event, handled by the dated-binding machinery so that applicability attaches without human declaration.

Note 3 to entry: The expression "characteristic profile trigger" denotes this predicate as used by a characteristic profile and is folded into this concept rather than recorded separately.

### 14.3

#### **commissioning**

issuance act by which a qualified attestor or registrar establishes the identity of an object that predates or lies outside a manufacturer-issued regime, recording the first sighting in the event log

### 14.4

#### **qualified attestor**

actor accredited under a profile's trust list to commission identities or to attest attributes of orphan objects, such as an auction house, authentication board or registrar

### 14.5

#### **attribution**

expert statement assigning an object to a creator, workshop or period, recorded as a competing fact with provenance rather than merged with other attributions

#### 14.6

##### **provenance gap**

explicitly recorded interval in a subject's custody or provenance chain for which no evidence exists

Note 1 to entry: A provenance gap is data, not an error; it is honestly representable in the event-sourced record.

#### 14.7

##### **condition report**

dated, signed, profile-scoped assessment of the physical condition of an object

#### 14.8

##### **restitution flag**

authority-attached marker on a passport recording a claim over title, such as looting, dispossession or colonial taking, propagated as a graph event without rewriting history

### 15 Terms related to the framework: capability classes and digital twins

#### 15.1

##### **capability class**

classification of a subject by its ability to participate in its own record: silent, passive-auth, logged-contact or connected

Note 1 to entry: A profile's freshness and verification requirements shall be satisfiable by the capability class of the subject; demanding live freshness from a silent subject is an unsatisfiable profile.

#### 15.2

##### **silent subject**

subject with no connectivity, keys or self-reporting, whose record is reconstructed entirely from testimonies about it

#### 15.3

##### **passive-auth subject**

subject carrying an authentication element, such as an NFC chip, physically unclonable function or identity link, that attests identity without recording events

#### 15.4

##### **logged-contact subject**

subject that records events locally and discloses them on physical contact, without communications capability

#### 15.5

##### **connected subject**

subject that self-reports under device keys and participates with full edge segments

#### 15.6

##### **passive twin**

digital twin reconstructed from point-in-time attestations about the object, sampled when the object visits an attester, in which truth is episodic and staleness between attestations is unbounded and undetectable

Note 1 to entry: Corresponds to capability classes S0 (silent, testimony-only) and S1 (passive authentication).

Note 2 to entry: Trust rides entirely on attester authority; the twin is testimonial by default and sensorial by exception.

#### 15.7

##### **active twin**

digital twin in which the object self-reports under device keys, making truth near-continuous, freshness bounded and detectable, and shifting the binding question from who saw the object to who attests the sensor

Note 1 to entry: Corresponds to capability classes S2 (logged contact) and S3 (connected).

Note 2 to entry: Measurement validity becomes load-bearing: sensor calibration, uncertainty of self-reported values and registered units; health status is a derived verdict.

Note 3 to entry: Profiles declare, per data element, the required truth mode, namely attest-sampled, self-committed, or both with precedence.

## 15.8

### **truth mode**

declared per-data-element attribute of a profile stating which truth source the element requires, namely attest-sampled, self-committed, or both with a precedence rule

Note 1 to entry: The passive twin (concept dpp-0132) supplies attest-sampled truth and the active twin (concept dpp-0133) supplies self-committed truth; both paradigms coexist permanently in the framework.

Note 2 to entry: Precedence between a calibrated device measurement and an attester observation is itself a metrological hierarchy question.

Note 3 to entry: Freshness and verification requirements must be satisfiable by the subject's capability class: demanding live freshness from an S0 (silent) product is an unsatisfiable profile.

## 15.9

### **service-center model**

arrangement in which a subject's state is sampled and attested only when the subject visits an attester, yielding episodic truth and unbounded, undetectable staleness between attestations

## 15.10

### **self-testimony**

testimony class consisting of events asserted by the subject's own device under device-bound keys

## 15.11

### **continuous conformity monitoring**

conformity mode in which requirements are re-judged against the live state of the twin, rather than only at point-in-time inspection

## 15.12

### **state of health**

derived verdict on the condition of a subject, computed by a stated model from measured variables

Note 1 to entry: The provenance of the computing model is itself governed information; health status is not a raw fact.

## 15.13

### **sensor attestation**

attestation binding a measured value to a registered sensor identity, its calibration and its measurement uncertainty

## 16 Terms related to the framework: passport relationship algebra

### 16.1

#### **association**

typed, navigational passport relationship, such as compatibility, supply or same-maker, carrying no lifecycle impact

### 16.2

#### **installation**

typed structural relationship, and its event class, between a parent passport and an installed child component, recorded with method, slot identity, pairing, alterations, performer and time, which makes an installed component a different legal object from the standalone one

Note 1 to entry: Schema: install(child, parent, method, slotId, pairing (none, firmware, key or module), alterations, performedBy, at).

Note 2 to entry: Bidirectional parent knowledge is mandatory: the parent's manifest lists children and the child's event log records its installation interval (parent, slot, method), for recall routing, scoped service access, ownership transfer and end-of-life routing.

Note 3 to entry: Lifecycle coupling: warranty re-scope and service economics ride the parent, and the part is no longer sellable as new; custody transfer (concept dpp-0134) remains orthogonal, since ownership changes while composition stays fixed.

Note 4 to entry: The recoverability of the binding (concept dpp-0143) determines identity continuity: disassembly that restores a marketable object with identity continuity is installation, while dissolving identity is a transformation event (concept dpp-0129). Part replacement is an uninstall followed by an install, and regulated children keep their own passports through it.

### **16.3 membership**

temporal relationship between a passport and a group node, such as a shipment, consignment, kit, fleet or recall set

### **16.4 group node**

queryable grouping of passports that receives a passport of its own only when the group is itself placed on the market

### **16.5 binding strength**

declared permanence of an installation binding, ranging from reversible fastening to destructive integration

### **16.6 slot identity**

parent-scoped identifier of an installation position by which an installed child is re-identified within its parent

### **16.7 pairing**

recorded binding of a child to its parent context, by firmware, key or module, that is re-established when a component is replaced

### **16.8 absorbed component**

input whose identity dissolves into its parent and is therefore modelled as a transformation input rather than a live child, recorded at the finest available granularity as dormant identifiers

### **16.9 recoverability**

declared property of an installation binding (concept dpp-0142) stating whether and how the installed child can resume an independent existence, taking one of the values restorable, harvestable, destructive or absorbing

Note 1 to entry: Restorable: the child resumes standalone life; harvestable: recovered but altered, continuing with harvested status and parent history (concept dpp-0144); destructive: the child ceases and flows to a material passport through a transformation event (concept dpp-0129); absorbing: identity dissolves into the parent.

Note 2 to entry: Absorption is regime-temporal rather than permanent: absorbed inputs are recorded at the finest available granularity as dormant identifiers (concept dpp-0135), issuable by adoption when a future regime requires passports for the object class.

Note 3 to entry: Carried in the EXPRESS core as part of the PassportLink binding (method, recoverability).



## 16.10

### **harvested part**

component recovered from an installation (concept dpp-0142) in the harvestable state of the recoverability spectrum (concept dpp-0143), which continues to carry its own identity, harvested status and the parent history accumulated during installation

Note 1 to entry: Installation history is value-relevant provenance: a harvested battery sold standalone carries its service interval and removal reason, and the used-parts market runs on this.

Note 2 to entry: A harvested part is second-hand-once-removed: no longer sellable as new, with warranty scope and service economics that rode the parent during installation.

## 16.11

### **custody transfer**

signed ceremony recording the transfer of responsibility for an object between custodians, appended to the event chain by the custodian and the counterparty, which extends and never overwrites the trail across successive owners

Note 1 to entry: Custody links are social and control edges, orthogonal to structural composition: ownership changes while composition stays fixed.

## 16.12

### **custodian**

actor that currently holds the live event segment of a subject's record and is authorized to append custody-relevant events to it

## 17 Terms related to the framework: visibility and enumeration resistance

### 17.1

#### **blind edge**

edge on a typed passport relationship whose existence and endpoints are concealed from all observers, so that a child-to-parent reference does not reveal where a thing is, such as a household or a site

Note 1 to entry: Edge visibility classes, namely public, restricted (role-qualified), blind and escrowed, are declared on every relationship; the installation schema (concept dpp-0142) carries visibility as an edge class with escrow arrangement (concept dpp-0137) and audiences.

Note 2 to entry: Blind is the default for consumer installations, because even the object-to-household linkage is personal data requiring a GDPR or PIPL legal basis per profile.

Note 3 to entry: Rationale: a traversable graph with entitled upstream observers is surveillance infrastructure; post-sale visibility into instance state is owner-push or authority-based, never maker-pull.

### 17.2

#### **escrowed disclosure**

edge visibility arrangement in which information concealed by a blind edge (concept dpp-0136) is deposited with a threshold trustee and released only through a disclosure ceremony, namely court, regulator or consent

Note 1 to entry: The installation schema records escrow as none or trustee, with declared audiences.

Note 2 to entry: An escrow envelope under a threshold trustee may optionally accompany a proof of binding (concept dpp-0138), preserving verifiability while full disclosure remains ceremonial.

### 17.3

#### **proof of binding**

salted cryptographic commitment to the parent, recorded in the child's event log, by which a child satisfies the bidirectional parent-knowledge requirement without disclosing the identity of the parent

Note 1 to entry: Proof of binding is distinct from knowledge of parent: verifiable modes establish that the child is validly installed in some parent under a given profile (warranty, compliance) without revealing which parent; full disclosure occurs only by ceremony.

Note 2 to entry: An optional escrow envelope under a threshold trustee (concept dpp-0137) accompanies the commitment where future disclosure must remain possible.

#### 17.4

##### **enumeration resistance**

system property by which the passport system is verifiable without being browsable: resolution is by identity only, traversal requires per-edge rights, and no party, including any registry, resolver network or log operator, can enumerate the installed base of anything

Note 1 to entry: Transparency logs anchor commitments (hashes), never facts, so log operators cannot correlate edges; accumulator and blind-membership proofs give valid-standing checks without revealing which or where.

Note 2 to entry: Stated as design invariant I12, together with blind edges by default where households or sites are revealed (concept dpp-0136), proof of binding distinct from knowledge of parent (concept dpp-0138), and predicate-based recall (concept dpp-0140).

#### 17.5

##### **predicate-based recall**

recall scheme in which the recall set is never enumerated centrally: the recall predicate is published, and each custodian evaluates it locally against their own holdings, including dark and defence holdings under national procedure, and acts

Note 1 to entry: The manufacturer receives aggregates or nothing; there is no traversal-push enumeration of the installed base.

Note 2 to entry: One of the mechanisms by which enumeration resistance (concept dpp-0139) is maintained: recall propagation still notifies custodians transitively, but through local predicate evaluation rather than central construction of the recall set.

#### 17.6

##### **owner-push disclosure**

disclosure of instance state initiated by the owner, such as a warranty registration, as the default manufacturer-visibility channel

Note 1 to entry: A manufacturer-initiated pull of instance state is not a channel of the framework; authority-based compulsion of traversal is a separate, legal-basis-governed mechanism.

#### 17.7

##### **dark identity**

identity that is resolvable only within a restricted resolution domain, such as a national domain, and never enters the global resolver

#### 17.8

##### **confidential profile**

registered profile whose register item is non-public and which carries restricted resolution, edge-visibility and traversal fields, used for defence and sovereignty configurations

## **18 Terms related to the framework: trust semantics, degradation and federation**

### 18.1

#### **trust marker**

graded indicator attached to every element or event stating its trust provenance: unsigned, self-declared, third-party attested, multi-signed or log-anchored

Note 1 to entry: Trust is graded, not mandated; profiles set minimum signing per data class.

### 18.2

#### **master list**

globally multi-witnessed list of trust lists, co-signed by a quorum of independent logs, by which verifiers cross-recognize jurisdictional trust authorities

### 18.3

#### **revocation window**

explicit start and end interval carried by a distrust declaration, within which affected credentials are void and outside which they are re-validated

Note 1 to entry: The reason for revocation determines retroactivity: prospective reasons preserve earlier as-of verifications; misissuance voids validity from the beginning.

### 18.4

#### **three verification readings**

three legally distinct readings of a verification result, namely evidentiary, current-state and cryptographic, each of which a verdict states explicitly

Note 1 to entry: The evidentiary reading asks what a diligent verifier could know at the time; the current-state reading voids fraud from the beginning; the cryptographic reading covers signature and chain validity alone.

### 18.5

#### **freshness verdict**

explicit, displayable assessment of how current a served state is relative to its declared freshness bound, degrading visibly when data is stale or offline

### 18.6

#### **coverage report**

statement accompanying a verdict enumerating which elements, trust anchors and registry items the verification covered

### 18.7

#### **discovery registry**

federated registry of record for passport services and semantics, in which profile shapes, protocol bindings, verification mechanisms and service endpoints are versioned, signed, log-anchored items discoverable by any conforming client

Note 1 to entry: The registry holds descriptors of services and shapes, never records of things.

### 18.8

#### **service descriptor**

signed registry item describing a service by operator identity and credential, service class, endpoints, protocol binding, jurisdiction, residency class, status and succession pointer

### 18.9

#### **protocol binding**

registered specification of a wire grammar, media types, version and conformance suite by which an interaction with a service or a device is conducted

### 18.10

#### **verification mechanism bundle**

assembled set of registered items naming the cryptographic suite, trust framework, trust-list endpoints, revocation mechanism and acceptance-policy template under which a client verifies

### 18.11

#### **listing gate**

registered predicate evaluated by a marketplace over passport status and standing without holding passport data, admitting or refusing listings

### 18.12

#### **operator credential**

scoped, threshold-issued credential by which an operator signs registry items and service attestations

Note 1 to entry: Appends claiming a role outside the credential's scope degrade the trust marker; they do not pass silently.

**18.13**

**onboarding ceremony**

threshold admission ceremony by which an operator joins the service federation, or a trust authority joins the master list, accepting continuity and succession obligations

**18.14**

**read federation**

federation tier in which any party consumes the registry and trust bundles without an admission ceremony

**18.15**

**service federation**

federation tier in which operators register services under signed descriptors and accept continuity and succession obligations

**18.16**

**trust federation**

federation tier in which trust authorities join the master list by threshold admission and jurisdictional profiles cross-recognize one another

**18.17**

**seed bundle**

bootstrap set of registry endpoints and trust anchors with which a conforming client first initializes, resolving the circular dependence between registry discovery and trust

**18.18**

**registry pinning**

binding of a passport manifest or a verdict to exact registry items by item, version and hash, so that later registry changes never alter what a past issuance must satisfy

## Annex A (normative)

### Relationship to other standards

#### A.1 General

This annex identifies International Standards, European Standards and other publications that define or use terms related to those in Clause 3. It does not modify the definitions in Clause 3.

#### A.2 Standards defining related terms

The following documents define terms that correspond to, or are related to, entries in this document. Where an entry in Clause 3 is taken from one of these documents, that document is cited with the entry.

**Table A.1 — Related standards**

| Document                    | Subject area                                       |
|-----------------------------|----------------------------------------------------|
| EN 18216:2026               | Data exchange protocols                            |
| EN 18219:2026               | Unique identifiers                                 |
| EN 18220:2026               | Data carriers                                      |
| EN 18221:2026               | Data storage, archiving and persistence            |
| EN 18222:2026               | Application programming interfaces                 |
| EN 18223:2026               | System interoperability                            |
| EN 18239:2026               | Access rights, security and confidentiality        |
| EN 18246:2026               | Data authentication, reliability and integrity     |
| CWA 18291:2025              | Textile supply chains                              |
| ISO/AWI 25534-1             | Digital product passport — overview and principles |
| IDTA 01001-3.2:2026         | Asset Administration Shell — metamodel             |
| ISO/IEC 15459-1             | Unique identifiers — individual transport units    |
| ISO/IEC 18975:2024          | Identification link — resolution                   |
| ISO/IEC 20248:2022          | Data structures — digital signature                |
| ISO/IEC 22123-1:2023        | Cloud computing — vocabulary                       |
| ISO 18435-1:2009            | Industrial automation — diagnostics integration    |
| ISO 29404:2015              | Ships and marine technology — vocabulary           |
| ISO 5157:2023               | Textiles — environmental aspects — vocabulary      |
| ISO 59004:2024              | Circular economy — vocabulary                      |
| ISO 59040                   | Circular economy — product circularity data sheet  |
| ISO 22095:2020              | Chain of custody — terminology                     |
| ISO 8601-1:2019             | Date and time — representation                     |
| ISO 80000-3                 | Quantities and units — space and time              |
| IEC 63278-1:2023            | Asset Administration Shell — principles            |
| UNECE Recommendation No. 46 | Enhancing traceability of sustainable value chains |
| UN Transparency Protocol    | Digital product transparency                       |

### A.3 Conflicting definitions reproduced in full

The following subclauses reproduce, for each designation whose published definitions differ across sources, the verbatim definition text of each cited source, and the clause number from which it is taken. Where this document uses one definition in Clause 3, the adopted text is reproduced under “Definition adopted”. Other published texts are reproduced under “Other published definitions”. The substantive variance is described under “Variance”.

#### A.3.1 digital product passport (Clause 3.1.1)

##### Definition adopted

ISO/AWI 25534-1, 3.1 A concept or technology which enables sharing of product related information that is essential for product sustainability and circularity, including those specified in regulations, across all relevant economic actors.

##### Other published definitions

|                      |                                                                                                                                    |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------|
| EN 18223:2026, 3.4   | digital record of product characteristics throughout its life cycle                                                                |
| EN 18216:2026, 3.7   | digital record of product characteristics throughout its lifecycle                                                                 |
| EN 18221:2026, 3.2   | digital record of product characteristics throughout its life cycle                                                                |
| EN 18222:2026, 3.2   | digital record of product characteristics throughout its life cycle                                                                |
| EN 18239:2026, 3.9   | digital record of product characteristics throughout its life cycle                                                                |
| EN 18246:2026, 3.2   | digital record of product characteristics throughout its life cycle                                                                |
| EN 18219:2026, 3.1.3 | digital record of product characteristics throughout its life cycle that is accessible via electronic means through a data carrier |
| EN 18220:2026, 3.6   | digital record of product characteristics throughout its life cycle that is accessible via electronic means through a data carrier |

NOTE Example characteristics include environmental sustainability, environmental impact, and recyclability. (EN 18216:2026, 3.7; EN 18221:2026, 3.2; EN 18222:2026, 3.2; EN 18223:2026, 3.4; EN 18239:2026, 3.9; EN 18246:2026, 3.2; EN 18219:2026 and EN 18220:2026 carry the same note text.)

**Variance.** ISO/AWI 25534-1 names the subject as a **concept or technology** that **enables sharing of product-related information** across relevant economic actors. EN 18216:2026 to EN 18246:2026 name the subject as a **digital record of product characteristics** throughout the product’s **life cycle**. EN 18219:2026 and EN 18220:2026 add the qualifier “accessible via electronic means through a data carrier”.

#### A.3.2 unique identifier (Clause 3.2.2)

##### Definition adopted

|                                                     |                                                                                                                     |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| ISO 29404:2015, 3.26 (cited by CWA 18291:2025, 3.3) | identifier which is guaranteed to be unique among all identifiers used for those objects and for a specific purpose |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|

NOTE 1 For more information, see ISO/IEC 15459-1. (CWA 18291:2025, 3.3 note.)

### Other published definitions

EN 18219:2026, 3.1.24 string of characters that is required to be unique among all identifiers used for all objects for a specific purpose

NOTE 2 A unique identifier refers to unique product identifier (3.1.25), unique economic operator identifier (3.1.22) and unique facility identifier (3.1.23).

EN 18220:2026, 3.18 string of characters that is required to be unique among all identifiers used for all objects for a specific purpose

**Variance.** EN 18219:2026 and EN 18220:2026 formulate the entry in terms of a **string of characters** required to be unique among **all** identifiers for **all objects**. ISO 29404:2015 / CWA 18291:2025 / ISO/IEC 15459 family formulate the entry in terms of an **identifier** guaranteed to be unique among identifiers for **those objects** and a specific purpose. EN 18219:2026 modifies ISO 29404:2015 as follows: “identifier” is replaced by “string of characters”, “those objects” is replaced by “all objects”, and the original Note 1 to entry is replaced by a new Note 1 listing the three identifier types.

### A.3.3 economic operator (Clause 3.3.1)

#### Definition adopted

EN 18221:2026, 3.1 manufacturer, authorized representative, importer, distributor, dealer or fulfilment service provider

#### Other published definitions

EN 18219:2026, 3.1.5 manufacturer, authorized representative, importer, distributor, dealer or fulfilment service provider that places the product on the market

EN 18220:2026, 3.7 manufacturer, authorized representative, importer, distributor, dealer or fulfilment service provider that places the product onto the market

**Variance.** EN 18219:2026 and EN 18220:2026 include the qualifier “that places the product on the market” / “onto the market”; EN 18221:2026 does not.

### A.3.4 interoperability (Clause 3.6.1)

#### Definition adopted

ISO/IEC 22123-1:2023, 3.6.1 (cited by EN 18219:2026, 3.1.7) ability of two or more systems or applications to exchange information and to mutually use the information that has been exchanged

#### Other published definitions

EN 18223:2026, 3.1 (lineage: ISO 18435-1:2009, 3.12) capability of two or more entities to exchange items in accordance with a set of rules and mechanisms implemented by an interface in each entity, in order to perform their specified tasks

**Variance.** The two formulations derive from different parent vocabularies. ISO/IEC 22123-1:2023 (cloud computing) speaks of **systems or applications** that **exchange information** and **mutually use** it. ISO 18435-1:2009 (industrial automation diagnostics integration) speaks of **entities** that **exchange items** through **an interface implementing a set of rules and mechanisms**.

#### **A.4 Other standards whose definitions are related but not conflicted**

- ISO/IEC 15459-1 — framework for unique identification in transport units, cited by the ISO 29404:2015 entry for unique identifier.
- ISO 22095:2020 — chain of custody terminology, cited by the transformation-algebra framework terms in Clause 3.11.
- ISO 59004:2024 — circular economy vocabulary, alignment target for material-flow terms in Clauses 3.4 and 3.7.
- ISO 8601-1:2019, ISO 80000-3 — date-and-time and quantities-and-units, alignment targets for the time-stamping and units semantics of the framework.
- UNECE Recommendation No. 46 — traceability in value chains, cited by CWA 18291:2025 for traceable asset.
- UN Transparency Protocol (UNTP) — alignment target for identity, carrier and resolution entries in Clause 3.2 and the attestation triad in Clause 3.11.
- IDTA 01001-3.2:2026 — Asset Administration Shell metamodel, cited as a source of vocabulary for the framework's semantics-and-profiles clause.



## Bibliography

- [1] ISO 5157:2023, *Textiles — Environmental aspects — Vocabulary*
- [2] ISO 7498-2:1989, *Information processing systems — Open Systems Interconnection — Basic Reference Model — Part 2: Security Architecture*
- [3] ISO 8601-1:2019, *Date and time — Representations for information interchange — Part 1: Basic rules*
- [4] ISO 9000:2015<sup>1)</sup>, *Quality management systems — Fundamentals and vocabulary*
- [5] ISO 14025:2006<sup>2)</sup>, *Environmental labels and declarations — Type III environmental declarations — Principles and procedures*
- [6] ISO 14040:2006, *Environmental management — Life cycle assessment — Principles and framework*
- [7] ISO 15531-43, *Industrial automation systems and integration — Industrial manufacturing management data — Part 43: Manufacturing flow management data: Data model for flow monitoring and manufacturing data exchange*
- [8] ISO 18308:2011, *Health informatics — Requirements for an electronic health record architecture*
- [9] ISO 18435-1:2009, *Industrial automation systems and integration — Diagnostics, capability assessment and maintenance applications integration — Part 1: Overview and general requirements*
- [10] ISO 22095:2020, *Chain of custody — General terminology and models*
- [11] ISO 22274:2013, *Systems to manage terminology, knowledge and content — Concept-related aspects for developing and internationalizing classification systems*
- [12] ISO 23234:2021, *Buildings and civil engineering works — Security — Planning of security measures in the built environment*
- [13] ISO/TS 24533:2012, *Intelligent transport systems — Electronic information exchange to facilitate the movement of freight and its intermodal transfer — Road transport information exchange methodology*
- [14] ISO 24533-2:2022, *Intelligent transport systems — Electronic information exchange to facilitate the movement of freight and its intermodal transfer — Part 2: Common reporting system*
- [15] ISO 24619:2011, *Language resource management — Persistent identification and sustainable access (PISA)*
- [16] ISO 29404:2015, *Ships and marine technology — Offshore wind energy — Supply chain information flow*
- [17] ISO 59004:2024, *Circular economy — Vocabulary, principles and guidance for implementation*
- [18] ISO 59040, *Circular economy — Product circularity data sheet*
- [19] ISO 80000-3, *Quantities and units — Part 3: Space and time*
- [20] ISO/AWI 25534-1:2026, *Digital product passport — Part 1: Overview and fundamental principles, working draft of 2026-09-05, ISO/IEC JTC 5*

---

1) Withdrawn.

2) Withdrawn.

- [21] ISO/IEC Guide 2:2004, *Standardization and related activities — General vocabulary*
- [22] ISO/IEC Guide 77-2:2008, *Guide for specification of product properties and classes — Part 2: Technical principles and guidance*
- [23] ISO/IEC 6523-1, *Information technology — Structure for the identification of organizations and organization parts — Part 1: Identification of organization identification schemes*
- [24] ISO/IEC/IEEE 8802-1AR, *Telecommunications and exchange between information technology systems — Requirements for local and metropolitan area networks — Part 1AR: Secure device identity*
- [25] ISO/IEC 10746-2, *Information technology — Open distributed processing — Reference model: Foundations — Part 2:*
- [26] ISO/IEC 15459-1, *Information technology — Automatic identification and data capture techniques — Unique identification — Part 1: Individual transport units*
- [27] ISO/IEC 17000:2020, *Conformity assessment — Vocabulary and general principles*
- [28] ISO/IEC 18975:2024, *Information technology — Automatic identification and data capture techniques — Encoding and resolving identifiers over HTTP*
- [29] ISO/IEC 19762 (all parts)<sup>3)</sup>, *Information technology — Automatic identification and data capture (AIDC) techniques*
- [30] ISO/IEC 20248:2022, *Information technology — Automatic identification and data capture techniques — Digital signature data structure schema*
- [31] ISO/IEC 22123-1:2023, *Information technology — Cloud computing — Part 1: Vocabulary*
- [32] ISO/IEC 24760-1, *Information security, cybersecurity and privacy protection — A framework for identity management — Part 1: Core concepts and terminology*
- [33] ISO/IEC 27000, *Information technology — Security techniques — Information security management systems — Overview and vocabulary*
- [34] ISO/IEC 27031, *Cybersecurity — Information and communication technology readiness for business continuity*
- [35] ISO/IEC 29180:2012, *Information technology — Telecommunications and information exchange between systems — Security framework for ubiquitous sensor networks*
- [36] IEC 61666:2010+AMD1:2021 CSV, *Industrial systems, installations and equipment and industrial products — Identification of terminals within a system*
- [37] IEC TR 62390:2005, *Common automation device — Profile guideline*
- [38] IEC 61499-1:2012, *Function blocks — Part 1: Architecture*
- [39] IEC 62569-1:2017, *Generic specification of information on products by properties — Part 1: Principles and methods*
- [40] IEC 63278-1:2023, *Asset Administration Shell for industrial applications — Part 1: Asset Administration Shell structure*
- [41] IEC TS 62443-1-1:2009, *Industrial communication networks — Network and system security — Part 1-1: Terminology, concepts and models*

---

3) Withdrawn.

- [42] IEC 60050-741:2020, *International Electrotechnical Vocabulary (IEV) – Part 741: Internet of Things (IoT)*
- [43] IEC 61360-1:2016, *Standard data element types with associated classification scheme — Part 1: Definitions — Principles and methods*
- [44] IEC 62890:2016, *Life-cycle management for systems and products used in industrial-process measurement, control and automation*
- [45] ECLASS, *ECLASS — the reference data standard for the classification and description of products and services*, ECLASS e.V., current release
- [46] Industrial Internet Vocabulary, *Industrial Internet Vocabulary*, version V2.3 (IIC:IIVOC:V2.3:20201025), Industrial Internet Consortium
- [47] Glossar Industrie 4.0, *Glossar Industrie 4.0* [Industrie 4.0 glossary], German Industrie 4.0 community glossary, current release
- [48] UNEP/EA.4/Res.1, *Resolution adopted by the United Nations Environment Assembly*
- [49] UNECE Recommendation No. 46, *Enhancing traceability and transparency of sustainable value chains in the garment and footwear sector*, United Nations Economic Commission for Europe
- [50] IDTA 01001-3.2:2026, *Specification of the Asset Administration Shell — Part 1: Metamodel*, Industrial Digital Twin Association
- [51] UNEP, Toledano, Bauch and Arnold 2023, cited in the ISO/AWI 25534-1, 3.4 source
- [52] UNEP Job no. DTI/2532/PA, cited in the ISO/AWI 25534-1, 3.8 source
- [53] CEN CWA 18291:2025, EUROPEAN COMMITTEE FOR STANDARDIZATION. *TRICK — Guidelines on data collection from Textile supply chains for the Digital Product Passport*. Published
- [54] CEN EN 18216:2026, EUROPEAN COMMITTEE FOR STANDARDIZATION. *Digital product passport — Data exchange protocols*. Published
- [55] CEN EN 18219:2026, EUROPEAN COMMITTEE FOR STANDARDIZATION. *Digital product passport — Unique identifiers*. Published
- [56] CEN EN 18220:2026, EUROPEAN COMMITTEE FOR STANDARDIZATION. *Digital product passport — Data carriers*. Published
- [57] CEN EN 18221:2026, EUROPEAN COMMITTEE FOR STANDARDIZATION. *Digital product passport — Data storage, archiving, and data persistence*. Published
- [58] CEN EN 18222:2026, EUROPEAN COMMITTEE FOR STANDARDIZATION. *Digital Product Passport — Application Programming Interfaces (APIs) for the product passport lifecycle management and searchability*. Published
- [59] CEN EN 18223:2026, EUROPEAN COMMITTEE FOR STANDARDIZATION. *Digital Product Passport — System interoperability*. Published
- [60] CEN EN 18239:2026, EUROPEAN COMMITTEE FOR STANDARDIZATION. *Digital product passport — Access rights management, information system security, and business confidentiality*. Approved
- [61] CEN EN 18246:2026, EUROPEAN COMMITTEE FOR STANDARDIZATION. *Digital product passport — Data authentication, reliability and integrity*. Approved
- [62] CEN EN ISO 14025:2010, EUROPEAN COMMITTEE FOR STANDARDIZATION. *Environmental labels and declarations — Type III environmental declarations — Principles and procedures (ISO 14025:2006)*. Withdrawn

[63] UN/CEFACT, *UN Transparency Protocol (UNTP)*, current development draft



**ICS 35.240.63**  
Price based on 38 pages

© ISO 2026  
All rights reserved