Current Transducer LTS 6-NP

I_{PN} = 2 - 3 - 6 A

For the electronic measurement of currents : DC, AC, pulsed, mixed, with a galvanic isolation between the primary circuit (high power) and the secondary circuit (electronic circuit).



Electrical data

I_{PN}	Primary nominal r.m.s. current		6	At
I_P	Primary current, measuring range		0 .. ± 19.2	At
V_{OUT}	Analog output voltage @ I_P		2.5 ± (0.625·I_P/I_{PN})	V
	I_P = 0		2.5 [1]	V
N_S	Number of secondary turns (± 0.1 %)		2000	
R_L	Load resistance		≥ 2	kΩ
R_{IM}	Internal measuring resistance (± 0.5 %)		208.33	Ω
TCR_{IM}	Thermal drift of R_{IM}		< 50	ppm/K
V_C	Supply voltage (± 5 %)		5	V
I_C	Current consumption @ V_C = 5 V	Typ	20+I_S [2]+(V_{OUT}/R_L)	mA
V_d	R.m.s. voltage for AC isolation test, 50/60 Hz, 1 mn		3	kV
V_b	R.m.s. rated voltage		525 [3]	V

Accuracy - Dynamic performance data

X	Accuracy @ I_{PN} , T_A = 25°C		± 0.2		%
X	Accuracy with R_{IM} @ I_{PN} , T_A = 25°C		± 0.7		%
ε_L	Linearity		< 0.1		%
			Typ	Max	
TCV_{OUT}	Thermal drift of V_{OUT} @ I_P = 0	- 10°C .. + 85°C	200	300	ppm/K
$TC\varepsilon_G$	Thermal drift of the gain	- 10°C .. + 85°C		50 [4]	ppm/K
V_{OM}	Residual voltage @ I_P = 0, after an overload of 3 x I_{PN}			± 0.5	mV
	5 x I_{PN}			± 2.0	mV
	10 x I_{PN}			± 2.0	mV
t_{ra}	Reaction time @ 10 % of I_{PN}		< 50		ns
t_r	Response time @ 90 % of I_{PN}		< 400		ns
di/dt	di/dt accurately followed		> 15		A/µs
f	Frequency bandwidth (0 .. - 0.5 dB)		DC .. 100		kHz
	(- 0.5 .. 1 dB)		DC .. 200		kHz

General data

T_A	Ambient operating temperature	- 10 .. + 85	°C
T_S	Ambient storage temperature	- 25 .. + 100	°C
m	Mass	10	g
	Standards	EN 50178	
		EN 60950	

Features

- Closed loop (compensated) multi-range current transducer using the Hall effect
- Unipolar voltage supply
- Compact design for PCB mounting
- Insulated plastic case recognized according to UL 94-V0
- Incorporated measuring resistance
- Extended measuring range.

Advantages

- Excellent accuracy
- Very good linearity
- Very low temperature drift
- Optimized response time
- Wide frequency bandwidth
- No insertion losses
- High immunity to external interference
- Current overload capability.

Applications

- AC variable speed drives and servo motor drives
- Static converters for DC motor drives
- Battery supplied applications
- Uninterruptible Power Supplies (UPS)
- Switched Mode Power Supplies (SMPS)
- Power supplies for welding applications.

Notes : [1] Absolute value @ T_A = 25°C, 2.475 < V_{OUT} < 2.525
[2] Please see the operation principle on the other side
[3] Pollution class 2, Overvoltage category III
[4] Only due to TCR_{IM}

Dimensions LTS 6-NP (in mm. 1 mm = 0.0394 inch)

Bottom view



Operation principle



$I_S = I_P / N_S = \pm 3$ mA @ $I_P = \pm 6$ At



Back view



Right view



Front view

Number of primary turns	Primary nominal r.m.s. current I_{PN} [A]	Nominal output voltage V_{OUT} [V]	Primary resistance R_P [mΩ]	Primary insertion inductance L_P [µH]	Recommended connections
1	± 6	2.5 ± 0.625	0.18	0.013	
2	± 3	2.5 ± 0.625	0.81	0.05	
3	± 2	2.5 ± 0.625	1.62	0.12	

Mechanical characteristics

- General tolerance ± 0.2 mm
- Fastening & connection of primary 6 pins 0.7 x 0.8 mm
  Recommended PCB hole 1.3 mm
- Fastening & connection of secondary 3 pins 0.5 x 0.35 mm
  Recommended PCB hole 0.8 mm
- Additional primary through-hole ∅ 3.2 mm

Output Voltage - Primary Current



Remark

- V_{OUT} is positive when I_P flows from terminals 1, 2, 3 to terminals 6, 5, 4.