

Course 6


Problem: Parsing (construct the parse tree)

if the *source program is syntactically correct*
 then construct syntax tree
 else "syntax error"

source program is syntactically correct = $w \in L(G) \Leftrightarrow S \overset{*}{\Rightarrow} w$

Parsing

- How:
 1. Top-down vs. Bottom-up
 2. Recursive vs. linear




	Descendent	Ascendent
Recursive	Descendent recursive parser	Ascendent recursive parser
Linear	LL(k): LL(1)	LR(k): LR(0), SLR, LR(1), LALR

Result – parse tree -representation

- Arbitrary tree – child sybling representation
- Sequence of derivations $S \Rightarrow \alpha_1 \Rightarrow \alpha_2 \Rightarrow \dots \Rightarrow \alpha_n = w$
- String of production – index associated to prod – which prod is used at each derivation step: 1,4,3,...

index	Info	Parent	Right sibling
1	S	0	0
2	a	1	0
3	S	1	2
4	b	1	3
5	S	1	4
6	c	3	0
7	c	5	0



Descendent recursive parser

- Example

Formal model

- Configuration

(s, i, α, β)

where:

- s = state of the parsing, can be:
 - q = normal state
 - b = back state
 - f = final state - corresponding to success: $w \in L(G)$
 - e = error state – corresponding to insuccess: $w \notin L(G)$
- i – position of current symbol in input sequence
 $w = a_1a_2...a_n, i \in \{1,...,n+1\}$
- α = working stack, stores the way the parse is built
- β = input stack, part of the tree to be built

Define moves between configurations

Initial configuration:
 $(q, 1, \varepsilon, S)$

Final configuration:
 $(f, n+1, \alpha, \varepsilon)$

Expand

WHEN: head of input stack is a nonterminal

$$(q, i, \alpha, A\beta) \vdash (q, i, \alpha A_1, \gamma_1\beta)$$

where:

$A \rightarrow \gamma_1 \mid \gamma_2 \mid \dots$ represents the productions corresponding to A

1 = first prod of A

Advance

WHEN: head of input stack is a terminal = current symbol from input

$$(q, i, \alpha, a_i \beta) \vdash (q, i+1, \alpha a_i, \beta)$$

Momentary insuccess

WHEN: head of input stack is a terminal \neq current symbol from input

$$(q, i, \alpha, a_i \beta) \vdash (\textcolor{red}{b}, i, \alpha, a_i \beta)$$

Back

WHEN: head of working stack is a terminal

$$(b, i, \alpha a, \beta) \vdash (b, i-1, \alpha, a\beta)$$

Another try

WHEN: head of working stack is a nonterminal

$(b, i, \alpha A_j, \gamma_j \beta) \vdash (q, i, \alpha A_{j+1}, \gamma_{j+1} \beta)$, if $\exists A \rightarrow \gamma_{j+1}$
 $(b, i, \alpha, A \beta)$, otherwise with the exception
 (e, i, α, β) , if $i=1$, $A=S$, **ERROR**

Success

$$(q, n+1, \alpha, \varepsilon) \vdash (\textcolor{red}{f}, n+1, \alpha, \varepsilon)$$

Algorithm

Algorithm Descendent Recursive

INPUT: $G, w = a_1a_2...a_n$

OUTPUT: string of productions and message

$config = (q, 1, \varepsilon, S);$

//initial configuration (s, i, α, β)

while ($s \neq f$) and ($s \neq e$) **do**

if $s = q$

then if ($i = n + 1$) and $IsEmpty(\beta)$

then $Success(config)$

else

if $Head(\beta) = A$

then $Expand(config)$

else

if $Head(\beta) = a_i$

then $Advance(config)$

else $MomentaryInsucces(config)$

else

if $s = b$

then

if $Head(\alpha) = a$

then $Back(config)$

else $AnotherTry(config)$

$endWhile$

if $s = e$ **then** $message "Error"$

else $message "Sequence accepted";$

$BuildStringOfProd(\alpha)$


$w \in L(G)$ - HOW

- Process α :
 - From left to right (reverse if stored as stack)
 - Skip terminal symbols
 - Nonterminals – index of prod
- Example: $\alpha = S_1 a S_2 a S_3 c b S_3 c$

When the algorithm never stops?

- $S \rightarrow S\alpha$ – expand infinitely (left recursive)

LL(1) Parser



Linear algorithm

FIRST_k

- \approx first k terminal symbols that can be generated from α
- **Definition:**

$$FIRST_k : (N \cup \Sigma)^* \rightarrow \mathcal{P}(\Sigma^k)$$

$$FIRST_k(\alpha) = \{u | u \in \Sigma^k, \alpha \xRightarrow{*} ux, |u| = k \text{ sau } \alpha \xRightarrow{*} u, |u| \leq k\}$$

Construct FIRST

➤ $FIRST_1$ denoted FIRST

➤ Remarks:

- If L_1, L_2 are 2 languages over alphabet Σ , then : $L_1 \oplus L_2 = \{w | x \in L_1, y \in L_2, xy = w, |w| \leq 1 \text{ sau } xy = wz, |w| = 1\}$ and

- $FIRST(\alpha\beta) = FIRST(\alpha) \oplus FIRST(\beta)$

$$FIRST(X_1 \dots X_n) = FIRST(X_1) \oplus \dots \oplus FIRST(X_n)$$

Concatenation
of length 1



$$L1 = \{aa, ab, ba\}$$

$$L2 = \{00, 01\}$$

$$L1L2 = \{\}$$

$$L1 \oplus L2 = \{\}$$

$$L1 = \{a, b\}$$

$$L2 = \{0, 1\}$$

$$L1 \oplus L2 = \{\}$$

$$L1 = \{a, \epsilon\}$$

$$L2 = \{0, 1\}$$

$$L1 \oplus L2 = \{\}$$

Algoritmul 3.3 FIRST


INPUT: G **OUTPUT:** $FIRST(X), \forall X \in N \cup \Sigma$ **for** $\forall a \in \Sigma$ **do** $F_i(a) = \{a\}, \forall i \geq 0$ **end for** $i := 0;$ $F_0(A) = \{x | x \in \Sigma, A \rightarrow x\alpha \text{ sau } A \rightarrow x \in P\}; \{\text{inițializare}\}$ **repeat** $i := i+1;$

A

for $\forall X \in N$ **do****if** F_{i-1} au fost calculate $\forall X \in N \cup \Sigma$ **then** $\{\text{dacă } \exists Y_j, F_{i-1}(Y_j) = \emptyset \text{ atunci nu se poate aplica}\}$ $F_i(A) = F_{i-1}(A) \cup$ $\{x | A \rightarrow Y_1 \dots Y_n \in P, x \in F_{i-1}(Y_1) \oplus \dots \oplus F_{i-1}(Y_n)\}$ **end if****end for****until** $F_{i-1}(A) = F_i(A)$ $FIRST(X) := F_i(X), \forall X \in N \cup \Sigma$

FOLLOW

$$A \rightarrow \varepsilon$$



➤ $FOLLOW_k(A) \approx$ next k symbols generated after/ following A

$$FOLLOW : (N \cup \Sigma)^* \rightarrow \mathcal{P}(\Sigma)$$

$$FOLLOW(\beta) = \{w \in \Sigma \mid S \xRightarrow{*} \alpha\beta\gamma, w \in FIRST(\gamma)\}$$

Algorithm FOLLOW

INPUT: G , $\text{FIRST}(X)$, $\forall X \in N \cup \Sigma$

OUTPUT: $\text{FOLLOW}(A)$, $\forall A \in N$

```
for  $A \in N - \{S\}$  do {init}
     $L_0(A) = \Phi$ ;
endFor;
 $L_0(S) = \{\epsilon\}$ ; {init}
 $i = 0$ ;
repeat
     $i = i + 1$ ;
    for  $B \in N$  do
        for  $A \rightarrow \alpha B \gamma \in P$  do
            for  $\forall a \in \text{FIRST}(\gamma)$  do
                if  $a = \epsilon$  then  $F_i(B) = F_i(B) \cup F_{i-1}(A)$ 
                else  $F_i(B) = F_{i-1}(B) \cup \text{First}(\gamma)$ 
                endif
            endFor
        endFor
    endFor
until  $F_i(X) = F_{i-1}(X)$ ,  $\forall X \in N$ 
 $\text{FOLLOW}(X) = F_i(X)$ ,  $\forall X \in N$ 
```

$S \Rightarrow^0 S // \epsilon \text{ after } S$

$S \Rightarrow aAc \Rightarrow abBc$
 $A \rightarrow bB$