Software Systems Verification and Validation



Vescan Andreea, PHD, Assoc. Prof.



Faculty of Mathematics and Computer Science Babeș-Bolyai University





Software Systems Verification and Validation

"Tell me and I forget, teach me and I may remember, involve me and I learn."

(Benjamin Franklin)

(Next)/Today Lecture

- Testing. Test planning.
- Test case design Black-box testing
- Testing Management Tool TestLink
- Continuous integration Jenkins

Outline

- Testing fundamental questions
- Black-box testing (domain testing)
 - Equivalence partitioning (EP)
 - Boundary-value analysis (BVA)
 - Advantages/Disadvantages
- Example black-box testing
 - Example EP+BVA
- Test management tool Testlink
- Maven
- Continous integration tool Jenkins

Domain testing

- The problem you have to solve
 - You cannot afford to run every possible test.
 - You need a method for choosing a few powerful tests that will represent the rest.
- Domain testing
 - Provides a sampling strategy
 - It provides **heuristics** for choosing a small number of tests that are powerful enough to represent the larger domain.
 - Equivalence
 - Boundaries
- Input versus output variables
 - Domain definitions
 - Specification:
 - Data (X) + preconditions
 - Result (Z)+ postcondition
- Primary dimension versus secondary dimension [BBST]
 - Primary dimension reflects the reason you are entering data into the field
 - Secondary dimension reflects the other ways the input can vary

- Equivalence partitioning
- Boundary-value analysis

Domain testing (Black-box testing) Equivalence partitioning

- Equivalence class (EC) definition [Mye04]
 - a partition of input domain of a program.
- Equivalence partitioning
 - to partition the input domain of a program into a finite number of equivalence classes such that you can reasonably assume that a test of a representative value of each class is equivalent to a test of any other value.

Test-case design by equivalence partitioning - steps

- Identifying the equivalence classes (EC)
 - Valid equivalence classes.
 - Invalid equivalence classes.
 - Default, empty, blank, null, zero, none.
 - Invalid, wrong, incorrect, garbage date.
- Defining the test cases
 - assign a unique number to each equivalence class;
 - Until all valid/invalid equivalence classes have been covered by (incorporated into) test cases:
 - write a new test case covering as many of the uncovered valid equivalence classes as possible;
 - write a test case that covers one, and only one, of the uncovered invalid equivalence classes.

Test-case design by equivalence partitioning - guidelines

- An input condition specifies a range of values [a,b].
 - → 1 valid EC, 2 invalid EC
- An input condition specifies the number of values "1 to 3 possibilities".
 - → 1 valid EC and 2 invalid EC
- An input condition specifies a set of input values.
 - → 1 valid EC for each element in the set, 1 invalid EC
- An input condition specifies a must be situation.
 - → 1 valid EC, 1 invalid EC
- If there is any reason to believe that the program does not handle elements in an equivalence class identically, split the equivalence class into smaller equivalence classes.

Domain testing (Black-box testing) Boundary-value analysis

- Boundary-value analysis definition [Mye04]
 - focuses on the boundary areas of a programs input domain
- Boundary conditions
 - Situations directly on, above, and beneath the edges of input EC and output EC.
 - One or more elements should be selected such that each edge of the EC is the subject of a test.
 - BVA explores situations on and around the edges of the EP.

Test-case design by boundary-value analysis -guidelines

- An input condition specifies a range of values [a,b].
 - → the ends of the range, situations just beyond the ends;
- An input condition specifies the number of values "1 to 3 possibilities".
- → the minimum and maximum number of values, one beneath and beyond these values;
- An input condition specifies an ordered set of input values.
 - → the first, the last elements of the set;
- The above rules are applied to the output conditions.

Advantages

- No knowledge of implementation.
- Tester independent of programmer.
- User's point of view.
- Ambiguities in spec.
- After specifications is completed.

Disadvantages

- A small number of inputs.
- No clear spec.
- Hard to design.
- Unnecessary repetition of test.
- Many program paths untested.
- Specific segments of code?

Example

- Problem statement: Compute the number of participants with the maximum score (0 to 100 points possible) at a competition.
- Applied:
 - EP
 - BVA
- See example files
- Lecture02_Demo

Example

- Maven
 - goal to allow a developer to comprehend the complete state of a development effort in the shortest period of time
 - https://maven.apache.org/what-is-maven.html
 - The Failsafe Plugin is designed to run integration tests.
 - Maven 2 Integration
- Testlink
 - Test management tool
- Jenkins
 - Continuous integration tool

Outline

- Testing fundamental questions
- Black-box testing (domain testing)
 - Equivalence partitioning (EP)
 - Boundary-value analysis (BVA)
 - Advantages/Disadvantages
- Example black-box testing
 - Example EP+BVA
- Test management tool Testlink
- Maven
- Continous integration tool Jenkins



Go to www.menti.com and use the code 3011 9020

- Research Study2
 - Questionnaire2

References

- [PY08] M. Pezzand and M. Young. Software Testing and Analysis: Process, Principles and Techniques. John Wiley and Sons, 2008.
- [Mye04] Glenford J. Myers, *The Art of Software Testing*, John Wiley & Sons, Inc., 2004
- [You79] E. Yourdon, Structured Walkthroughs, Prentice-Hall, Englewood Cliffs, NJ, 1979
- [Fre10] M. Frentiu, Verificarea si validarea sistemelor soft, Presa Universitara Clujeana, 2010
- [BBST] BBST Testing course, http://testingeducation.org/BBST/
 - Test design,
 - Lecture 5: Domain testing
- Tutorials
 - Module Tutorials in canvas

Next Lecture

Test case design - White-box testing





Software Systems Verification and Validation

"Tell me and I forget, teach me and I may remember, involve me and I learn."

(Benjamin Franklin)