

# TRADITIONAL AND HEAVY-TAILED SELF REGULARIZATION IN NEURAL NETWORK MODELS

CHARLES H. MARTIN (CHARLES@CALCULATIONCONSULTING.COM) AND MICHAEL W. MAHONEY (MMAHONEY@STAT.BERKELEY.EDU)



## MOTIVATION

**Theoretical:** deeper insight into *Why Deep Learning Works?*

- convex versus non-convex optimization?
- explicit/implicit regularization?
- is / why is / when is deep better?
- VC theory versus Statistical Mechanics theory?
- ...

**Practical:** use insights to improve engineering of DNNs?

- when is a network fully optimized?
- can we use labels and/or domain knowledge more efficiently?
- large batch versus small batch in optimization?
- designing better ensembles?
- ...

## HOW WE STUDY REGULARIZATION

The Energy Landscape is *determined* by layer weight matrices  $\mathbf{W}_L$ :

$$E_{DNN} = h_L(\mathbf{W}_L \times h_{L-1}(\mathbf{W}_{L-1} \times h_{L-2}(\dots) + \mathbf{b}_{L-1}) + \mathbf{b}_L)$$

Traditional regularization is applied to  $\mathbf{W}_L$ :


$$\min_{\mathbf{W}_L, \mathbf{b}_L} \mathcal{L} \left( \sum_i E_{DNN}(d_i) - y_i \right) + \alpha \sum_l \|\mathbf{W}_l\|$$

*Different types of regularization, e.g., different norms  $\|\cdot\|$ , leave different empirical signatures on  $\mathbf{W}_L$ .*

What we do:


- Turn off “all” regularization.
- Systematically turn it back on, explicitly with  $\alpha$  or implicitly with knobs/switches.
- **Study empirical properties of  $\mathbf{W}_L$ .**

## PHENOMENOLOGICAL THEORY: 5+1 PHASES OF TRAINING



## OLD/SMALL MODELS ...

... exhibit “Bulk+Spike” ~ Tikhonov regularization



Simple scale threshold

$$\mathbf{x} = (\hat{\mathbf{X}} + \alpha \mathbf{I})^{-1} \hat{\mathbf{W}}^T \mathbf{y}$$


Eigenvalues  $> \alpha$  (Spikes) carry most of the signal/information

Corresponds to usual “signal+noise” model

**Smaller, older models** like LeNet5 exhibit **traditional regularization**

## NEW/LARGE MODELS ...

... exhibit novel **Heavy-Tailed Self-Regularization**



$\mathbf{W}$  is *strongly-correlated* and highly non-random:


- **Can model strongly-correlated systems by heavy-tailed random matrices**

Use known results from Gaussian Random Matrix Theory, Heavy-Tailed Random Matrix Theory, and Polymer Theory


“All” **larger, modern DNNs** exhibit novel **Heavy-tailed self-regularization**

## REMARKABLY UNIVERSAL

All these ImageNet models display remarkable Heavy Tailed Universality:



The pretrained BERT model is *not* optimal (has large exponents and displays rank collapse)



## USES, IMPLICATIONS, EXTENSIONS

- **Generalization gap.** Exhibit all phases of training by varying just the batch size (“explaining” the generalization gap).
- **Toy statistical mechanics model.** A Very Simple Deep Learning (VSDL) model (with load-like parameters  $\alpha$ , & temperature-like parameters  $\tau$ ) that exhibits a non-trivial phase diagram.
- **Energy landscapes.** Connections with minimizing frustration, energy landscape theory, and the spin glass of minimal frustration.
- **Rugged convexity.** A “rugged convexity” since local minima do *not* concentrate near the ground state of heavy-tailed spin glasses.
- **Capacity control metric.** A novel capacity control metric (the weighted sum of power law exponents) to predict trends in generalization performance for state-of-the-art models.