



Notebook - Maratona de Programação

[UnB] HatsuneMiku não manda WA

Contents

1 Misc	2	5 Geometria	6
1.1 Submask	2	5.1 Mindistpair	6
1.2 Safe Map	2	5.2 Inside Polygon	6
1.3 Ordered Set	2	5.3 3d	7
1.4 Bitwise	2	5.4 Convex Hull	8
2 DP	2	5.5 Linear Transformation	8
2.1 Knapsack	2	5.6 Voronoi	8
2.2 Lis	2	5.7 Polygon Area	8
2.3 Dp Digitos	3	5.8 Intersect Polygon	9
3 ED	3	5.9 Sort By Angle	9
3.1 Prefixsum2d	3	5.10 2d	9
3.2 Sparse Table	3	6 Grafos	11
3.3 Dsu	4	6.1 Dfs Tree	11
3.4 Minqueue	4	6.2 Kosaraju	11
3.5 Segtree Implicita Lazy	4	6.3 Topological Sort	11
3.6 Delta Encoding	5	6.4 Dijkstra	12
4 Strings	5	6.5 Dinic	12
4.1 Z Func	5	6.6 Hungarian	12
4.2 Edit Distance	5	6.7 Floyd Warshall	13
4.3 Lcsubseq	5	6.8 Lca	13
4.4 Kmp	5	6.9 Kruskal	14
4.5 Hash	5	6.10 Ford	14
4.6 Aho Corasick	6	7 Algoritmos	14
4.7 Lcs	6	7.1 Ternary Search	14
		8 Math	15
		8.1 Totient	15
		8.2 Inverso Mult	15

8.3	Miller Habin	15
8.4	Matrix Exponentiation	15
8.5	Division Trick	16
8.6	Crivo	16
8.7	Bigmod	16
8.8	Linear Diophantine Equation	16

1 Misc

1.1 Submask

```
1 // 0(3^n)
2 for (int m = 0; m < (1<<n); m++) {
3     for (int s = m; s; s = (s-1) & m) {
4         // s is every submask of m
5     }
6 }
7
8 // 0(2^n * n) SOS dp like
9 for (int b = n-1; b >= 0; b--) {
10     for (int m = 0; m < (1 << n); m++) {
11         if (j & (1 << b)) {
12             // propagate info through submasks
13             amount[j ^ (1 << b)] += amount[j];
14         }
15     }
16 }
```

1.2 Safe Map

```
1 struct custom_hash {
2     static uint64_t splitmix64(uint64_t x) {
3         // http://xorshift.di.unimi.it/splitmix64.c
4         x += 0x9e3779b97ff4a7c15;
5         x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
6         x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
7         return x ^ (x >> 31);
8     }
9
10     size_t operator()(uint64_t x) const {
11         static const uint64_t FIXED_RANDOM = chrono::
12         steady_clock::now().time_since_epoch().count();
13         return splitmix64(x + FIXED_RANDOM);
14     };
15
16     unordered_map<long long, int, custom_hash> safe_map;
17
18     // when using pairs
19     struct custom_hash {
20         inline size_t operator()(const pii & a) const {
21             return (a.first << 6) ^ (a.first >> 2) ^
22             2038074743 ^ a.second;
23         };
24     };
25 }
```

1.3 Ordered Set

```
1 #include <bits/extc++.h>
2 // or
3 #include <ext/pb_ds/assoc_container.hpp>
4 #include <ext/pb_ds/tree_policy.hpp>
5
6 using namespace __gnu_pbds; // or pb_ds;
7 template<typename T, typename B = null_type>
8 using ordered_set = tree<T, B, less<T>, rb_tree_tag,
9     tree_order_statistics_node_update>;
10
11 // order_of_key(k) : Number of items strictly
12 // smaller than k
13 // find_by_order(k) : K-th element in a set (counting
14 // from zero)
15
16 // to swap two sets, use a.swap(b);
```

1.4 Bitwise

```
1 // Least significant bit (lsb)
```

```
2 int lsb(int x) { return x&-x; }
3 int lsb(int x) { return __builtin_ctz(x); } //
4 // bit position
5 int msb(int x) { return 32-1-__builtin_clz(x); }
6 // bit position
7
8 // Power of two
9 bool isPowerOfTwo(int x){ return x && (!(x&(x-1))
10 ); }
11
12 // floor(log2(x))
13 int flog2(int x) { return 32-1-__builtin_clz(x); }
14 int flog2ll(ll x) { return 64-1-__builtin_clzll(x); }
15
16 // Built-in functions
17 // Number of bits 1
18 __builtin_popcount()
19 __builtin_popcountll()
20
21 // Number of leading zeros
22 __builtin_clz()
23 __builtin_clzll()
24
25 // Number of trailing zeros
26 __builtin_ctz()
27 __builtin_ctzll()
```

2 DP

2.1 Knapsack

```
1 // Caso base, como i == n
2 dp[0][0] = 0;
3
4 // Itera por todos os estados
5 for(int i = 1; i <= n; ++i)
6     for(int P = 0; P <= w; ++P){
7         int &temp = dp[i][P];
8         // Primeira possibilidade, não pega i
9         temp = dp[i - 1][P];
10
11         // Segunda possibilidade, se puder, pega o
12         // item
13         if(P - p[i] >= 0)
14             temp = max(temp, dp[i - 1][P - p[i]] + v[i]);
15
16         ans = max(ans, temp);
17     }
18 }
```

2.2 Lis

```
1 multiset<int> S;
2 for(int i=0;i<n;i++){
3     auto it = S.upper_bound(vet[i]); // low for inc
4     if(it != S.end())
5         S.erase(it);
6     S.insert(vet[i]);
7 }
8
9 // size of the lis
10 int ans = S.size();
11
12 vi LIS(const vi &elements){
13     auto compare = [&](int x, int y) {
14         return elements[x] < elements[y];
15     };
16     set< int, decltype(compare) > S(compare);
17
18     vi previous( elements.size(), -1 );
19     for(int i=0; i<int( elements.size() ); ++i){
```

```

19         auto it = S.insert(i).first;
20         if(it != S.begin())
21             previous[i] = *prev(it);
22         if(*it == i and next(it) != S.end())
23             S.erase(next(it));
24     }
25
26     vi answer;
27     answer.push_back( *S.rbegin() );
28     while ( previous[answer.back()] != -1 )
29         answer.push_back( previous[answer.back()] );
30     reverse( answer.begin(), answer.end() );
31     return answer;
32 }

```

2.3 Dp Digitos

```

1 // dp de quantidade de numeros <= r com ate qt
  // digitos diferentes de 0
2 ll dp(int idx, string& r, bool menor, int qt, vector<
  vector<vi>>& tab) {
3     if(qt > 3) return 0;
4     if(idx >= r.size()) {
5         return 1;
6     }
7     if(tab[idx][menor][qt] != -1)
8         return tab[idx][menor][qt];
9
10    ll res = 0;
11    for(int i = 0; i <= 9; i++) {
12        if(menor or i <= r[idx] - '0') {
13            res += dp(idx+1, r, menor or i < (r[idx] -
14                '0'), qt+(i>0), tab);
15        }
16    }
17    return tab[idx][menor][qt] = res;
18 }

```

3 ED

3.1 Prefixsum2d

```

1 ll find_sum(vector<vi> &mat, int x1, int y1, int x2,
  int y2){
2     // superior-esq(x1,y1) (x2,y2)inferior-dir
3     return mat[x2][y2]-mat[x2][y1-1]-mat[x1-1][y2]+
4     mat[x1-1][y1-1];
5 }
6 int main(){
7
8     for(int i=1;i<=n;i++)
9         for(int j=1;j<=n;j++)
10            mat[i][j]+=mat[i-1][j]+mat[i][j-1]-mat[i
11            -1][j-1];
12 }

```

3.2 Sparse Table

```

1 int logv[N+1];
2 void make_log() {
3     logv[1] = 0; // pre-comutar tabela de log
4     for (int i = 2; i <= N; i++)
5         logv[i] = logv[i/2] + 1;
6 }
7 struct Sparse {
8     int n;
9     vector<vector<int>> st;
10

```

```

11     Sparse(vector<int>& v) {
12         n = v.size();
13         int k = logv[n];
14         st.assign(n+1, vector<int>(k+1, 0));
15
16         for (int i=0;i<n;i++) {
17             st[i][0] = v[i];
18         }
19
20         for(int j = 1; j <= k; j++) {
21             for(int i = 0; i + (1 << j) <= n; i++) {
22                 st[i][j] = f(st[i][j-1], st[i + (1 <<
23                     (j-1))][j-1]);
24             }
25         }
26     }
27
28     int f(int a, int b) {
29         return min(a, b);
30     }
31
32     int query(int l, int r) {
33         int k = logv[r-l+1];
34         return f(st[l][k], st[r - (1 << k) + 1][k]);
35     };
36
37     struct Sparse2d {
38         int n, m;
39         vector<vector<vector<int>>> st;
40
41         Sparse2d(vector<vector<int>>> mat) {
42             n = mat.size();
43             m = mat[0].size();
44             int k = logv[min(n, m)];
45
46             st.assign(n+1, vector<vector<int>>(m+1,
47                 vector<int>(k+1)));
48             for(int i = 0; i < n; i++)
49                 for(int j = 0; j < m; j++)
50                     st[i][j][0] = mat[i][j];
51
52             for(int j = 1; j <= k; j++) {
53                 for(int x1 = 0; x1 < n; x1++) {
54                     for(int y1 = 0; y1 < m; y1++) {
55                         int delta = (1 << (j-1));
56                         if(x1+delta >= n or y1+delta >= m
57                             ) continue;
58
59                         st[x1][y1][j] = st[x1][y1][j-1];
60                         st[x1][y1][j] = f(st[x1][y1][j],
61                             st[x1+delta][y1][j-1]);
62                         st[x1][y1][j] = f(st[x1][y1][j],
63                             st[x1][y1+delta][j-1]);
64                         st[x1+delta][y1+delta][j-1]);
65                     }
66                 }
67             }
68
69             // so funciona para quadrados
70             int query(int x1, int y1, int x2, int y2) {
71                 assert(x2-x1+1 == y2-y1+1);
72                 int k = logv[x2-x1+1];
73                 int delta = (1 << k);
74
75                 int res = st[x1][y1][k];
76                 res = f(res, st[x2 - delta+1][y1][k]);
77                 res = f(res, st[x1][y2 - delta+1][k]);
78                 res = f(res, st[x2 - delta+1][y2 - delta+1][k
79                     ]);

```

```

77     return res;
78 }
79
80 int f(int a, int b) {
81     return a | b;
82 }
83
84 };

```

3.3 Dsu

```

1 struct DSU {
2     int n;
3     vector<int> parent, size;
4
5     DSU(int n): n(n) {
6         parent.resize(n, 0);
7         size.assign(n, 1);
8
9         for(int i=0; i<n; i++)
10             parent[i] = i;
11     }
12
13     int find(int a) {
14         if(a == parent[a]) return a;
15         return parent[a] = find(parent[a]);
16     }
17
18     void join(int a, int b) {
19         a = find(a); b = find(b);
20         if(a != b) {
21             if(size[a] < size[b]) swap(a, b);
22             parent[b] = a;
23             size[a] += size[b];
24         }
25     }
26 };

```

3.4 Minqueue

```

1 struct MinQ {
2     stack<pair<ll, ll>> in;
3     stack<pair<ll, ll>> out;
4
5     void add(ll val) {
6         ll minimum = in.empty() ? val : min(val, in.
7         top().ss);
8         in.push({val, minimum});
9     }
10
11     ll pop() {
12         if(out.empty()) {
13             while(!in.empty()) {
14                 ll val = in.top().ff;
15                 in.pop();
16                 ll minimum = out.empty() ? val : min(
17                 val, out.top().ss);
18                 out.push({val, minimum});
19             }
20             ll res = out.top().ff;
21             out.pop();
22             return res;
23         }
24
25         ll minn() {
26             ll minimum = LLINF;
27             if(in.empty() || out.empty())
28                 minimum = in.empty() ? (ll)out.top().ss :
29                 (ll)in.top().ss;
30             else
31                 minimum = min((ll)in.top().ss, (ll)out.
32                 top().ss);
33         }
34     }
35 };

```

```

30
31     return minimum;
32 }
33
34 ll size() {
35     return in.size() + out.size();
36 }
37 };

```

3.5 Segtree Implicita Lazy

```

1 struct node{
2     pll val;
3     ll lazy;
4     ll l, r;
5     node(){
6         l=-1; r=-1; val={0,0}; lazy=0;
7     }
8 };
9
10 node tree[40*MAX];
11 int id = 2;
12 ll N=1e9+10;
13
14 pll merge(pll A, pll B){
15     if(A.ff==B.ff) return {A.ff, A.ss+B.ss};
16     return (A.ff<B.ff ? A:B);
17 }
18
19 void prop(ll l, ll r, int no){
20     ll mid = (l+r)/2;
21     if(l!=r){
22         if(tree[no].l==-1){
23             tree[no].l = id++;
24             tree[tree[no].l].val = {0, mid-l+1};
25         }
26         if(tree[no].r==-1){
27             tree[no].r = id++;
28             tree[tree[no].r].val = {0, r-(mid+1)+1};
29         }
30         tree[tree[no].l].lazy += tree[no].lazy;
31         tree[tree[no].r].lazy += tree[no].lazy;
32     }
33     tree[no].val.ff += tree[no].lazy;
34     tree[no].lazy=0;
35 }
36
37 void update(int a, int b, int x, ll l=0, ll r=2*N, ll
38 no=1){
39     prop(l, r, no);
40     if(a<=l and r<=b){
41         tree[no].lazy += x;
42         prop(l, r, no);
43         return;
44     }
45     if(r<a or b<l) return;
46     int m = (l+r)/2;
47     update(a, b, x, l, m, tree[no].l);
48     update(a, b, x, m+1, r, tree[no].r);
49
50     tree[no].val = merge(tree[tree[no].l].val, tree[
51     tree[no].r].val);
52 }
53
54 pll query(int a, int b, int l=0, int r=2*N, int no=1)
55 {
56     prop(l, r, no);
57     if(a<=l and r<=b) return tree[no].val;
58     if(r<a or b<l) return {INF, 0};
59     int m = (l+r)/2;
60     int left = tree[no].l, right = tree[no].r;
61 }

```

```

59     return tree[no].val = merge(query(a, b, l, m,
60                                query(a, b, m+1, r,
61                                right));

```

3.6 Delta Encoding

```

1 // Delta encoding
2
3 for(int i=0;i<q;i++){
4     int l,r,x;
5     cin >> l >> r >> x;
6     delta[l] += x;
7     delta[r+1] -= x;
8 }
9
10 int atual = 0;
11
12 for(int i=0;i<n;i++){
13     atual += delta[i];
14     v[i] += atual;
15 }

```

4 Strings

4.1 Z Func

```

1 vector<int> Z(string s) {
2     int n = s.size();
3     vector<int> z(n);
4     int l = 0, r = 0;
5     for (int i = 1; i < n; i++) {
6         z[i] = max(0, min(z[i - l], r - i + 1));
7         while (i + z[i] < n and s[z[i]] == s[i + z[i]
8     ]) {
9         l = i; r = i + z[i]; z[i]++;
10    }
11    return z;
12 }

```

4.2 Edit Distance

```

1 int edit_distance(int a, int b, string& s, string& t)
2 {
3     // indexado em 0, transforma s em t
4     if(a == -1) return b+1;
5     if(b == -1) return a+1;
6     if(tab[a][b] != -1) return tab[a][b];
7
8     int ins = INF, del = INF, mod = INF;
9     ins = edit_distance(a-1, b, s, t) + 1;
10    del = edit_distance(a, b-1, s, t) + 1;
11    mod = edit_distance(a-1, b-1, s, t) + (s[a] != t[
12    b]);
13
14    return tab[a][b] = min(ins, min(del, mod));
15 }

```

4.3 Lcs subseq

```

1 // Longest Common Subsequence
2 string lcs(string x, string y){
3     int n = x.size(), m = y.size();
4     vector<vi> dp(n+1, vi(m+1, 0));
5
6     for(int i=0;i<=n;i++){
7         for(int j=0;j<=m;j++){
8             if(!i or !j)

```

```

9             dp[i][j]=0;
10            else if(x[i-1] == y[j-1])
11                dp[i][j]=dp[i-1][j-1]+1;
12            else
13                dp[i][j]=max(dp[i-1][j], dp[i][j-1]);
14        }
15    }
16
17    // int len = dp[n][m];
18    string ans="";
19
20    // recover string
21    int i = n-1, j = m-1;
22    while(i>=0 and j>=0){
23        if(x[i] == y[j]){
24            ans.pb(x[i]);
25            i--; j--;
26        }else if(dp[i][j+1]>dp[i+1][j])
27            i--;
28        else
29            j--;
30    }
31
32    reverse(ans.begin(), ans.end());
33
34    return ans;
35 }

```

4.4 Kmp

```

1 string p;
2 int neighbor[N];
3 int walk(int u, char c) { // leader after inputting '
4     while (u != -1 && (u+1 >= (int)p.size() || p[u +
5     1] != c)) // leader doesn't match
6         u = neighbor[u];
7     return p[u + 1] == c ? u+1 : u;
8 }
9 void build() {
10    neighbor[0] = -1; // -1 is the leftmost state
11    for (int i = 1; i < (int)p.size(); i++)
12        neighbor[i] = walk(neighbor[i-1], p[i]);
13 }

```

4.5 Hash

```

1 // String Hash template
2 // constructor(s) - O(|s|)
3 // query(l, r) - returns the hash of the range [l,r]
4 // from left to right - O(1)
5 // query_inv(l, r) from right to left - O(1)
6 struct Hash {
7     const ll P = 31;
8     int n; string s;
9     vector<ll> h, hi, p;
10    Hash() {}
11    Hash(string s): s(s), n(s.size()), h(n), hi(n), p
12    (n) {
13        for (int i=0;i<n;i++) p[i] = (i ? P*p[i-1]:1)
14        % MOD;
15        for (int i=0;i<n;i++)
16            h[i] = (s[i] + (i ? h[i-1]:0) * P) % MOD;
17        for (int i=n-1;i>=0;i--)
18            hi[i] = (s[i] + (i+1<n ? hi[i+1]:0) * P)
19            % MOD;
20    }
21    int query(int l, int r) {
22        ll hash = (h[r] - (l ? h[l-1]*p[r-l+1]:0) % MOD :
23        0));
24        return hash < 0 ? hash + MOD : hash;
25    }

```

```

21     }
22     int query_inv(int l, int r) {
23         ll hash = (hi[l] - (r+1 < n ? hi[r+1]*p[r-1
24         +1] % MOD : 0));
25         return hash < 0 ? hash + MOD : hash;
26     };

```

4.6 Aho Corasick

```

1 // https://github.com/joseleite19/icpc-notebook/blob/
  master/code/string/aho_corasick.cpp
2 const int A = 26;
3 int to[N][A];
4 int ne = 2, fail[N], term[N];
5 void add_string(string str, int id){
6     int p = 1;
7     for(auto c: str){
8         int ch = c - 'a'; // !
9         if(!to[p][ch]) to[p][ch] = ne++;
10        p = to[p][ch];
11    }
12    term[p]++;
13 }
14 void init(){
15     for(int i = 0; i < ne; i++) fail[i] = 1;
16     queue<int> q; q.push(1);
17     int u, v;
18     while(!q.empty()){
19         u = q.front(); q.pop();
20         for(int i = 0; i < A; i++){
21             if(to[u][i]){
22                 v = to[u][i]; q.push(v);
23                 if(u != 1){
24                     fail[v] = to[ fail[u] ][i];
25                     term[v] += term[ fail[v] ];
26                 }
27             }
28             else if(u != 1) to[u][i] = to[ fail[u] ][i];
29         }
30         else to[u][i] = 1;
31     }
32 }

```

4.7 Lcs

```

1 string LCSUBSTR(string X, string Y)
2 {
3     int m = X.size();
4     int n = Y.size();
5
6     int result = 0, end;
7     int len[2][n];
8     int currRow = 0;
9
10    for(int i=0;i<=m;i++){
11        for(int j=0;j<=n;j++){
12            if(i==0 || j==0)
13                len[currRow][j] = 0;
14            else if(X[i-1] == Y[j-1]){
15                len[currRow][j] = len[1-currRow][j-1]
16                + 1;
17                if(len[currRow][j] > result){
18                    result = len[currRow][j];
19                    end = i - 1;
20                }
21            }
22            else
23                len[currRow][j] = 0;
24        }
25    }
26 }

```

```

25         currRow = 1 - currRow;
26     }
27
28     if(result==0)
29         return string();
30
31     return X.substr(end - result + 1, result);
32 }

```

5 Geometria

5.1 Mindistpair

```

1 ll MinDistPair(vp &vet){
2     int n = vet.size();
3     sort(vet.begin(), vet.end());
4     set<point> s;
5
6     ll best_dist = LLINF;
7     int j=0;
8     for(int i=0;i<n;i++){
9         ll d = ceil(sqrt(best_dist));
10        while(j<n and vet[i].x-vet[j].x >= d){
11            s.erase(point(vet[j].y, vet[j].x));
12            j++;
13        }
14
15        auto it1 = s.lower_bound({vet[i].y - d, vet[i]
16        ].x});
17        auto it2 = s.upper_bound({vet[i].y + d, vet[i]
18        ].x});
19
20        for(auto it=it1; it!=it2; it++){
21            ll dx = vet[i].x - it->y;
22            ll dy = vet[i].y - it->x;
23            if(best_dist > dx*dx + dy*dy){
24                best_dist = dx*dx + dy*dy;
25                // vet[i] e inv(it)
26            }
27        }
28
29        s.insert(point(vet[i].y, vet[i].x));
30    }
31    return best_dist;
32 }

```

5.2 Inside Polygon

```

1 // Convex O(logn)
2
3 bool insideT(point a, point b, point c, point e){
4     int x = ccw(a, b, e);
5     int y = ccw(b, c, e);
6     int z = ccw(c, a, e);
7     return !((x==1 or y==1 or z==1) and (x==-1 or y
8     ==-1 or z==-1));
9 }
10 bool inside(vp &p, point e){ // ccw
11     int l=2, r=(int)p.size()-1;
12     while(l<r){
13         int mid = (l+r)/2;
14         if(ccw(p[0], p[mid], e) == 1)
15             l=mid+1;
16         else{
17             r=mid;
18         }
19     }
20     // bordo
21     // if(r==(int)p.size()-1 and ccw(p[0], p[r], e)
22     ==0) return false;

```

```

22 // if(r==2 and ccw(p[0], p[1], e)==0) return
false;
23 // if(ccw(p[r], p[r-1], e)==0) return false;
24 return insideT(p[0], p[r-1], p[r], e);
25 }
26
27 // Any O(n)
28
29 int inside(vp &p, point pp){
30 // 1 - inside / 0 - boundary / -1 - outside
31 int n = p.size();
32 for(int i=0; i<n; i++){
33 int j = (i+1)%n;
34 if(line({p[i], p[j]}).inside_seg(pp))
35 return 0;
36 }
37 int inter = 0;
38 for(int i=0; i<n; i++){
39 int j = (i+1)%n;
40 if(p[i].x <= pp.x and pp.x < p[j].x and ccw(p
[i], p[j], pp)==1)
41 inter++; // up
42 else if(p[j].x <= pp.x and pp.x < p[i].x and
ccw(p[i], p[j], pp)==-1)
43 inter++; // down
44 }
45 if(inter%2==0) return -1; // outside
46 else return 1; // inside
47 }
48
49 }

```

5.3 3d

```

1 // typedef ll cod;
2 // bool eq(cod a, cod b){ return (a==b); }
3
4 const ld EPS = 1e-6;
5 #define vp vector<point>
6 typedef ld cod;
7 bool eq(cod a, cod b){ return fabs(a - b) <= EPS; }
8
9 struct point
10 {
11 cod x, y, z;
12 point(cod x=0, cod y=0, cod z=0): x(x), y(y), z(z
) {}
13
14 point operator+(const point &o) const {
15 return {x+o.x, y+o.y, z+o.z};
16 }
17 point operator-(const point &o) const {
18 return {x-o.x, y-o.y, z-o.z};
19 }
20 point operator*(cod t) const {
21 return {x*t, y*t, z*t};
22 }
23 point operator/(cod t) const {
24 return {x/t, y/t, z/t};
25 }
26 bool operator==(const point &o) const {
27 return eq(x, o.x) and eq(y, o.y) and eq(z, o
.z);
28 }
29 cod operator*(const point &o) const { // dot
30 return x*o.x + y*o.y + z*o.z;
31 }
32 point operator^(const point &o) const { // cross
33 return point(y*o.z - z*o.y,
34 z*o.x - x*o.z,
35 x*o.y - y*o.x);
36 }
37 };

```

```

38 ld norm(point a) { // Modulo
39 return sqrt(a * a);
40 }
41
42 cod norm2(point a) {
43 return a * a;
44 }
45 bool nulo(point a) {
46 return (eq(a.x, 0) and eq(a.y, 0) and eq(a.z, 0))
;
47 }
48 ld proj(point a, point b) { // a sobre b
49 return (a*b)/norm(b);
50 }
51 ld angle(point a, point b) { // em radianos
52 return acos((a*b) / norm(a) / norm(b));
53 }
54
55 cod triple(point a, point b, point c) {
56 return (a * (b^c)); // Area do paralelepipedo
57 }
58
59 point normilize(point a) {
60 return a/norm(a);
61 }
62
63 struct plane {
64 cod a, b, c, d;
65 point p1, p2, p3;
66 plane(point p1=0, point p2=0, point p3=0): p1(p1
), p2(p2), p3(p3) {
67 point aux = (p1-p3)^(p2-p3);
68 a = aux.x; b = aux.y; c = aux.z;
69 d = -a*p1.x - b*p1.y - c*p1.z;
70 }
71 plane(point p, point normal) {
72 normal = normilize(normal);
73 a = normal.x; b = normal.y; c = normal.z;
74 d = -(p*normal);
75 }
76
77 // ax+by+cz+d = 0;
78 cod eval(point &p) {
79 return a*p.x + b*p.y + c*p.z + d;
80 }
81
82
83 cod dist(plane pl, point p) {
84 return fabs(pl.a*p.x + pl.b*p.y + pl.c*p.z + pl.d
) / sqrt(pl.a*pl.a + pl.b*pl.b + pl.c*pl.c);
85 }
86
87 point rotate(point v, point k, ld theta) {
88 // Rotaciona o vetor v theta graus em torno do
eixo k
89 // theta *= PI/180; // graus
90 return (
91 v*cos(theta)) +
92 ((k^v)*sin(theta)) +
93 (k*(k^v))*(1-cos(theta)
94 );
95 }
96
97 // 3d line inter / mindistance
98 cod d(point p1, point p2, point p3, point p4) {
99 return (p2-p1) * (p4-p3);
100 }
101 vector<point> inter3d(point p1, point p2, point p3,
point p4) {
102 cod mua = ( d(p1, p3, p4, p3) * d(p4, p3, p2, p1)
- d(p1, p3, p2, p1) * d(p4, p3, p4, p3) )
103 / ( d(p2, p1, p2, p1) * d(p4, p3, p4, p3)
- d(p4, p3, p2, p1) * d(p4, p3, p2, p1) );

```



```

104     cod mub = ( d(p1, p3, p4, p3) + mua * d(p4, p3,
105     p2, p1) ) / d(p4, p3, p4, p3);
106     point pa = p1 + (p2-p1) * mua;
107     point pb = p3 + (p4-p3) * mub;
108     if (pa == pb) return {pa};
109     return {};

```

5.4 Convex Hull

```

1  vp convex_hull(vp P)
2  {
3      sort(P.begin(), P.end());
4      vp L, U;
5      for(auto p: P){
6          while(L.size()>=2 and ccw(L.end()[-2], L.back
7          (), p)!=1)
8              L.pop_back();
9          L.push_back(p);
10     }
11     reverse(P.begin(), P.end());
12     for(auto p: P){
13         while(U.size()>=2 and ccw(U.end()[-2], U.back
14         (), p)!=1)
15             U.pop_back();
16         U.push_back(p);
17     }
18     L.pop_back();
19     L.insert(L.end(), U.begin(), U.end()-1);
20     return L;

```

5.5 Linear Transformation

```

1  // Apply linear transformation (p -> q) to r.
2  point linear_transformation(point p0, point p1, point
3  q0, point q1, point r) {
4      point dp = p1-p0, dq = q1-q0, num((dp^dq), (dp^dq
5      ));
6      return q0 + point((r-p0)^(num), (r-p0)*(num))/(dp
7      *dp);

```

5.6 Voronoi

```

1  bool polygonIntersection(line &seg, vp &p) {
2      long double l = -1e18, r = 1e18;
3      for(auto ps : p) {
4          long double z = seg.eval(ps);
5          l = max(l, z);
6          r = min(r, z);
7      }
8      return l - r > EPS;
9  }
10
11  int w, h;
12
13  line getBisector(point a, point b) {
14      line ans(a, b);
15      swap(ans.a, ans.b);
16      ans.b *= -1;
17      ans.c = ans.a * (a.x + b.x) * 0.5 + ans.b * (a.y
18      + b.y) * 0.5;
19      return ans;
20  }
21
22  vp cutPolygon(vp poly, line seg) {
23      int n = (int) poly.size();
24      vp ans;
25      for(int i = 0; i < n; i++) {
26          double z = seg.eval(poly[i]);
27          if(z > -EPS) {

```

```

28              ans.push_back(poly[i]);
29          }
30          double z2 = seg.eval(poly[(i + 1) % n]);
31          if((z > EPS && z2 < -EPS) || (z < -EPS && z2
32          > EPS)) {
33              ans.push_back(inter_line(seg, line(poly[i
34              ], poly[(i + 1) % n]))[0]);
35          }
36      }
37      return ans;
38  }
39
40  // BE CAREFUL!
41  // the first point may be any point
42  // O(N^3)
43  vp getCell(vp pts, int i) {
44      vp ans;
45      ans.emplace_back(0, 0);
46      ans.emplace_back(1e6, 0);
47      ans.emplace_back(1e6, 1e6);
48      ans.emplace_back(0, 1e6);
49      for(int j = 0; j < (int) pts.size(); j++) {
50          if(j != i) {
51              ans = cutPolygon(ans, getBisector(pts[i],
52              pts[j]));
53          }
54      }
55      return ans;
56  }
57
58  // O(N^2) expected time
59  vector<vp> getVoronoi(vp pts) {
60      // assert(pts.size() > 0);
61      int n = (int) pts.size();
62      vector<int> p(n, 0);
63      for(int i = 0; i < n; i++) {
64          p[i] = i;
65      }
66      shuffle(p.begin(), p.end(), rng);
67      vector<vp> ans(n);
68      ans[0].emplace_back(0, 0);
69      ans[0].emplace_back(w, 0);
70      ans[0].emplace_back(w, h);
71      ans[0].emplace_back(0, h);
72      for(int i = 1; i < n; i++) {
73          ans[i] = ans[0];
74      }
75      for(auto i : p) {
76          for(auto j : p) {
77              if(j == i) break;
78              auto bi = getBisector(pts[j], pts[i]);
79              if(!polygonIntersection(bi, ans[j]))
80                  continue;
81              ans[j] = cutPolygon(ans[j], getBisector(
82              pts[j], pts[i]));
83              ans[i] = cutPolygon(ans[i], getBisector(
84              pts[i], pts[j]));
85          }
86      }
87      return ans;
88  }

```

5.7 Polygon Area

```

1  ll area = 0;
2
3  for(int i = 0; i < n - 1; ++i){
4      area += pontos[i].x*pontos[i+1].y - pontos[i+1].x
5      *pontos[i].y;
6  }
7  area += pontos[n-1].x*pontos[0].y - pontos[0].x*
8  pontos[n-1].y;

```

```
8 area = abs(area);
```

5.8 Intersect Polygon

```
1 bool intersect(vector<point> A, vector<point> B) //
  Ordered ccw
2 {
3     for(auto a: A)
4         if(inside(B, a))
5             return true;
6     for(auto b: B)
7         if(inside(A, b))
8             return true;
9
10    if(inside(B, center(A)))
11        return true;
12
13    return false;
14 }
```

5.9 Sort By Angle

```
1 // Comparator function for sorting points by angle
2
3 int ret[2][2] = {{3, 2},{4, 1}};
4 inline int quad(point p) {
5     return ret[p.x >= 0][p.y >= 0];
6 }
7
8 bool comp(point a, point b) { // ccw
9     int qa = quad(a), qb = quad(b);
10    return (qa == qb ? (a ^ b) > 0 : qa < qb);
11 }
12
13 // only vectors in range [x+0, x+180)
14 bool comp(point a, point b){
15     return (a ^ b) > 0; // ccw
16     // return (a ^ b) < 0; // cw
17 }
```

5.10 2d

```
1 #define vp vector<point>
2 #define ld long double
3 const ld EPS = 1e-6;
4 const ld PI = acos(-1);
5
6 typedef ld T;
7 bool eq(T a, T b){ return abs(a - b) <= EPS; }
8
9 struct point{
10     T x, y;
11     int id;
12     point(T x=0, T y=0): x(x), y(y){}
13
14     point operator+(const point &o) const{ return {x
+ o.x, y + o.y}; }
15     point operator-(const point &o) const{ return {x
- o.x, y - o.y}; }
16     point operator*(T t) const{ return {x * t, y * t
}; }
17     point operator/(T t) const{ return {x / t, y / t
}; }
18     operator*(const point &o) const{ return x * o.x
+ y * o.y; }
19     operator^(const point &o) const{ return x * o.y
- y * o.x; }
20     bool operator<(const point &o) const{
21         return (eq(x, o.x) ? y < o.y : x < o.x);
22     }
23     bool operator==(const point &o) const{
24         return eq(x, o.x) and eq(y, o.y);
```

```
25     }
26     friend ostream& operator<<(ostream& os, point p)
27     {
28         return os << "(" << p.x << "," << p.y << ")";
29     }
30
31 int ccw(point a, point b, point e){ // -1=dir; 0=
collinear; 1=esq;
32 T tmp = (b-a) ^ (e-a); // vector from a to b
33 return (tmp > EPS) - (tmp < -EPS);
34 }
35
36 ld norm(point a){ // Modulo
37     return sqrt(a * a);
38 }
39
40 T norm2(point a){
41     return a * a;
42 }
43
44 bool nulo(point a){
45     return (eq(a.x, 0) and eq(a.y, 0));
46 }
47
48 point rotccw(point p, ld a){
49     // a = PI*a/180; // graus
50     return point((p.x*cos(a)-p.y*sin(a)), (p.y*cos(a)
+p.x*sin(a)));
51 }
52
53 point rot90cw(point a) { return point(a.y, -a.x); };
54 point rot90ccw(point a) { return point(-a.y, a.x); };
55
56 ld proj(point a, point b){ // a sobre b
57     return a*b/norm(b);
58 }
59
60 ld angle(point a, point b){ // em radianos
61     ld ang = a*b / norm(a) / norm(b);
62     return acos(max(min(ang, (ld)1), (ld)-1));
63 }
64
65 ld angle_vec(point v){
66     // return 180/PI*atan2(v.x, v.y); // graus
67     return atan2(v.x, v.y);
68 }
69
70 ld order_angle(point a, point b){ // from a to b ccw
71     (a in front of b)
72     ld aux = angle(a,b)*180/PI;
73     return ((a^b)<=0 ? aux:360-aux);
74 }
75
76 bool angle_less(point a1, point b1, point a2, point
b2){ // ang(a1,b1) <= ang(a2,b2)
77     point p1((a1*b1), abs((a1^b1)));
78     point p2((a2*b2), abs((a2^b2)));
79     return (p1^p2) <= 0;
80 }
81
82 ld area(vp &p){ // (points sorted)
83     ld ret = 0;
84     for(int i=2;i<(int)p.size();i++)
85         ret += (p[i]-p[0])^(p[i-1]-p[0]);
86     return abs(ret/2);
87 }
88
89 ld areaT(point &a, point &b, point &c){
90     return abs((b-a)^(c-a))/2.0;
91 }
92
93 point center(vp &A){
94     point c = point();
95     int len = A.size();
96     for(int i=0;i<len;i++)
97         c=c+A[i];
98     return c/len;
99 }
100
101 point forca_mod(point p, ld m){
102     ld cm = norm(p);
```

```

92     if(cm<EPS) return point();
93     return point(p.x*m/cm,p.y*m/cm);
94 }
95
96 ld param(point a, point b, point v){
97     // v = t*(b-a) + a // return t;
98     // assert(line(a, b).inside_seg(v));
99     return ((v-a) * (b-a)) / ((b-a) * (b-a));
100 }
101
102 bool simetric(vp &a){ //ordered
103     int n = a.size();
104     point c = center(a);
105     if(n&1) return false;
106     for(int i=0;i<n/2;i++)
107         if(ccw(a[i], a[i+n/2], c) != 0)
108             return false;
109     return true;
110 }
111
112 point mirror(point m1, point m2, point p){
113     // mirror point p around segment m1m2
114     point seg = m2-m1;
115     ld t0 = ((p-m1)*seg) / (seg*seg);
116     point ort = m1 + seg*t0;
117     point pm = ort-(p-ort);
118     return pm;
119 }
120
121
122 ///////////////
123 // Line //
124 ///////////////
125
126 struct line{
127     point p1, p2;
128     T a, b, c; // ax+by+c = 0;
129     // y-y1 = ((y2-y1)/(x2-x1))(x-x1)
130     line(point p1=0, point p2=0): p1(p1), p2(p2){
131         a = p1.y - p2.y;
132         b = p2.x - p1.x;
133         c = p1 ^ p2;
134     }
135     line(T a=0, T b=0, T c=0): a(a), b(b), c(c){
136         // Gera os pontos p1 p2 dados os coeficientes
137         // isso aqui eh um lixo mas quebra um galho
138         kkkkkk
139         if(b==0){
140             p1 = point(1, -c/a);
141             p2 = point(0, -c/a);
142         }else{
143             p1 = point(1, (-c-a*1)/b);
144             p2 = point(0, -c/b);
145         }
146     }
147     T eval(point p){
148         return a*p.x+b*p.y+c;
149     }
150     bool inside(point p){
151         return eq(eval(p), 0);
152     }
153     point normal(){
154         return point(a, b);
155     }
156
157     bool inside_seg(point p){
158         return (
159             ((p1-p) ^ (p2-p)) == 0 and
160             ((p1-p) * (p2-p)) <= 0
161         );
162     }
163
164 };
165
166 // be careful with precision error
167 vp inter_line(line l1, line l2){
168     ld det = l1.a*l2.b - l1.b*l2.a;
169     if(det==0) return {};
170     ld x = (l1.b*l2.c - l1.c*l2.b)/det;
171     ld y = (l1.c*l2.a - l1.a*l2.c)/det;
172     return {point(x, y)};
173 }
174
175 // segments not collinear
176 vp inter_seg(line l1, line l2){
177     vp ans = inter_line(l1, l2);
178     if(ans.empty() or !l1.inside_seg(ans[0]) or !l2.
179         inside_seg(ans[0]))
180         return {};
181     return ans;
182 }
183
184 bool seg_has_inter(line l1, line l2){
185     return ccw(l1.p1, l1.p2, l2.p1) * ccw(l1.p1, l1.
186         p2, l2.p2) < 0 and
187         ccw(l2.p1, l2.p2, l1.p1) * ccw(l2.p1, l2.
188         p2, l1.p2) < 0;
189 }
190
191 ld dist_seg(point p, point a, point b){ // point -
192     seg
193     if((p-a)*(b-a) < EPS) return norm(p-a);
194     if((p-b)*(a-b) < EPS) return norm(p-b);
195     return abs((p-a)^(b-a)) / norm(b-a);
196 }
197
198 ld dist_line(point p, line l){ // point - line
199     return abs(l.eval(p))/sqrt(1.a*1.a + 1.b*1.b);
200 }
201
202 line bisector(point a, point b){
203     point d = (b-a)*2;
204     return line(d.x, d.y, a*a - b*b);
205 }
206
207 line perpendicular(line l, point p){ // passes
208     through p
209     return line(l.b, -l.a, -l.b*p.x + l.a*p.y);
210 }
211
212 struct circle{
213     point c; T r;
214     circle(): c(0, 0), r(0){}
215     circle(const point o): c(o), r(0){}
216     circle(const point a, const point b){
217         c = (a+b)/2;
218         r = norm(a-c);
219     }
220     circle(const point a, const point b, const point
221         cc){
222         assert(ccw(a, b, cc) != 0);
223         c = inter_line(bisector(a, b), bisector(b, cc
224         ))[0];
225         r = norm(a-c);
226     }
227     bool inside(const point &a) const{
228         return norm(a - c) <= r + EPS;
229     }
230 };
231
232 pair<point, point> tangent_points(circle cr, point p)

```

```

    {
230     ld d1 = norm(p-cr.c), theta = asin(cr.r/d1);
231     point p1 = rotccw(cr.c-p, -theta);
232     point p2 = rotccw(cr.c-p, theta);
233     assert(d1 >= cr.r);
234     p1 = p1 * (sqrt(d1*d1-cr.r*cr.r) / d1) + p;
235     p2 = p2 * (sqrt(d1*d1-cr.r*cr.r) / d1) + p;
236     return {p1, p2};
237 }
238
239
240 circle incircle(point p1, point p2, point p3){
241     ld m1 = norm(p2-p3);
242     ld m2 = norm(p1-p3);
243     ld m3 = norm(p1-p2);
244     point c = (p1*m1 + p2*m2 + p3*m3)*(1/(m1+m2+m3));
245     ld s = 0.5*(m1+m2+m3);
246     ld r = sqrt(s*(s-m1)*(s-m2)*(s-m3)) / s;
247     return circle(c, r);
248 }
249
250 circle circumcircle(point a, point b, point c) {
251     circle ans;
252     point u = point((b-a).y, -(b-a).x);
253     point v = point((c-a).y, -(c-a).x);
254     point n = (c-b)*0.5;
255     ld t = (u^n)/(v^u);
256     ans.c = ((a+c)*0.5) + (v*t);
257     ans.r = norm(ans.c-a);
258     return ans;
259 }
260
261 vp inter_circle_line(circle C, line L){
262     point ab = L.p2 - L.p1, p = L.p1 + ab * ((C.c-L.
263     p1)*(ab) / (ab*ab));
264     ld s = (L.p2-L.p1)^(C.c-L.p1), h2 = C.r*C.r - s*s
265     / (ab*ab);
266     if (h2 < -EPS) return {};
267     if (eq(h2, 0)) return {p};
268     point h = (ab/norm(ab)) * sqrt(h2);
269     return {p - h, p + h};
270 }
271
272 vp inter_circle(circle c1, circle c2){
273     if (c1.c == c2.c) { assert(c1.r != c2.r); return
274     {}; }
275     point vec = c2.c - c1.c;
276     ld d2 = vec * vec, sum = c1.r + c2.r, dif = c1.r
277     - c2.r;
278     ld p = (d2 + c1.r * c1.r - c2.r * c2.r) / (2 * d2
279     );
280     ld h2 = c1.r * c1.r - p * p * d2;
281     if (sum * sum < d2 or dif * dif > d2) return {};
282     point mid = c1.c + vec * p, per = point(-vec.y,
283     vec.x) * sqrt(fmax(0, h2) / d2);
284     if (eq(per.x, 0) and eq(per.y, 0)) return {mid};
285     return {mid + per, mid - per};
286 }
287
288 // minimum circle cover O(n) amortizado
289 circle min_circle_cover(vp v){
290     random_shuffle(v.begin(), v.end());
291     circle ans;
292     int n = v.size();
293     for(int i=0;i<n;i++){
294         if(!ans.inside(v[i])){
295             ans = circle(v[i]);
296             for(int j=0;j<i;j++){
297                 if(!ans.inside(v[j])){
298                     ans = circle(v[i], v[j]);
299                     for(int k=0;k<j;k++){
300                         if(!ans.inside(v[k])){
301                             ans = circle(v[i], v[j], v[k]);
302                         }
303                     }
304                 }
305             }
306         }
307     }
308 }

```

```

295     }
296     return ans;
297 }

```

6 Grafos

6.1 Dfs Tree

```

1 int desce[N], sobe[N], vis[N], h[N];
2 int backedges[N], pai[N];
3
4 // backedges[u] = backedges que comecam embaixo de (
5 // ou =) u e sobem pra cima de u; backedges[u] == 0
6 // => u eh ponte
7 void dfs(int u, int p) {
8     if(vis[u]) return;
9     pai[u] = p;
10    h[u] = h[p]+1;
11    vis[u] = 1;
12
13    for(auto v : g[u]) {
14        if(p == v or vis[v]) continue;
15        dfs(v, u);
16        backedges[u] += backedges[v];
17    }
18    for(auto v : g[u]) {
19        if(h[v] > h[u]+1)
20            desce[u]++;
21        else if(h[v] < h[u]-1)
22            sobe[u]++;
23    }
24    backedges[u] += sobe[u] - desce[u];
25 }

```

6.2 Kosaraju

```

1 vector<int> g[N], gi[N]; // grafo invertido
2 int vis[N], comp[N]; // componente conexo de cada
3 // vertice
4 stack<int> S;
5
6 void dfs(int u){
7     vis[u] = 1;
8     for(auto v: g[u]) if(!vis[v]) dfs(v);
9     S.push(u);
10 }
11
12 void scc(int u, int c){
13     vis[u] = 1; comp[u] = c;
14     for(auto v: gi[u]) if(!vis[v]) scc(v, c);
15 }
16
17 void kosaraju(int n){
18     for(int i=0;i<n;i++) vis[i] = 0;
19     for(int i=0;i<n;i++) if(!vis[i]) dfs(i);
20     for(int i=0;i<n;i++) vis[i] = 0;
21     while(S.size()){
22         int u = S.top();
23         S.pop();
24         if(!vis[u]) scc(u, u);
25     }
26 }

```

6.3 Topological Sort

```

1 int n; // number of vertices
2 vector<vector<int>> adj; // adjacency list of graph
3 vector<bool> visited;
4 vector<int> ans;
5
6 void dfs(int v) {

```

```

7     visited[v] = true;
8     for (int u : adj[v]) {
9         if (!visited[u])
10            dfs(u);
11    }
12    ans.push_back(v);
13 }
14
15 void topological_sort() {
16     visited.assign(n, false);
17     ans.clear();
18     for (int i = 0; i < n; ++i) {
19         if (!visited[i]) {
20             dfs(i);
21         }
22     }
23     reverse(ans.begin(), ans.end());
24 }

```

6.4 Dijkstra

```

1 #define pii pair<int, int>
2 vector<vector<pii>> g(N);
3 vector<bool> used(N);
4 vector<ll> d(N, LLINF);
5 priority_queue< pii, vector<pii>, greater<pii> > fila
6 ;
7 void dijkstra(int k) {
8     d[k] = 0;
9     fila.push({0, k});
10
11     while (!fila.empty()) {
12         auto [w, u] = fila.top();
13         fila.pop();
14         if (used[u]) continue;
15         used[u] = true;
16
17         for (auto [v, w]: g[u]) {
18             if (d[v] > d[u] + w) {
19                 d[v] = d[u] + w;
20                 fila.push({d[v], v});
21             }
22         }
23     }
24 }

```

6.5 Dinic

```

1 const int N = 300;
2
3 struct Dinic {
4     struct Edge{
5         int from, to; ll flow, cap;
6     };
7     vector<Edge> edge;
8
9     vector<int> g[N];
10    int ne = 0;
11    int lvl[N], vis[N], pass;
12    int qu[N], px[N], qt;
13
14    ll run(int s, int sink, ll minE) {
15        if(s == sink) return minE;
16
17        ll ans = 0;
18
19        for(; px[s] < (int)g[s].size(); px[s]++) {
20            int e = g[s][px[s]];
21            auto &v = edge[e], &rev = edge[e^1];
22            if(lvl[v.to] != lvl[s]+1 || v.flow >= v.
cap)

```

```

23                continue; // v.cap - v.flow
24            < lim
25                ll tmp = run(v.to, sink, min(minE, v.cap-v
26                .flow));
27                v.flow += tmp, rev.flow -= tmp;
28                ans += tmp, minE -= tmp;
29                if(minE == 0) break;
30            }
31            return ans;
32        }
33    }
34    bool bfs(int source, int sink) {
35        qt = 0;
36        qu[qt++] = source;
37        lvl[source] = 1;
38        vis[source] = ++pass;
39        for(int i = 0; i < qt; i++) {
40            int u = qu[i];
41            px[u] = 0;
42            if(u == sink) return true;
43            for(auto& ed : g[u]) {
44                auto v = edge[ed];
45                if(v.flow >= v.cap || vis[v.to] ==
pass)
46                    continue; // v.cap - v.flow < lim
47                vis[v.to] = pass;
48                lvl[v.to] = lvl[u]+1;
49                qu[qt++] = v.to;
50            }
51            return false;
52        }
53    }
54    ll flow(int source, int sink) {
55        reset_flow();
56        ll ans = 0;
57        //for(lim = (1LL << 62); lim >= 1; lim /= 2)
58        while(bfs(source, sink))
59            ans += run(source, sink, LLINF);
60        return ans;
61    }
62    void addEdge(int u, int v, ll c, ll rc) {
63        Edge e = {u, v, 0, c};
64        edge.pb(e);
65        g[u].push_back(ne++);
66
67        e = {v, u, 0, rc};
68        edge.pb(e);
69        g[v].push_back(ne++);
70    }
71    void reset_flow() {
72        for(int i = 0; i < ne; i++)
73            edge[i].flow = 0;
74        memset(lvl, 0, sizeof(lvl));
75        memset(vis, 0, sizeof(vis));
76        memset(qu, 0, sizeof(qu));
77        memset(px, 0, sizeof(px));
78        qt = 0; pass = 0;
79    }
80    vector<pair<int, int>> cut() {
81        vector<pair<int, int>> cuts;
82        for (auto [from, to, flow, cap]: edge) {
83            if (flow == cap and vis[from] == pass and
84            vis[to] < pass and cap>0) {
85                cuts.pb({from, to});
86            }
87        }
88        return cuts;
89    }
90 }
91
92 // Hungarian Algorithm
93 //

```

6.6 Hungarian

```

1 // Hungarian Algorithm
2 //

```

```

3 // Assignment problem
4 // Put the edges in the 'a' matrix (negative or
  positive)
5 // assignment() returns a pair with the min
  assignment,
6 // and the column chosen by each row
7 // assignment() - O(n^3)
8
9 template<typename T>
10 struct hungarian {
11     int n, m;
12     vector<vector<T>> a;
13     vector<T> u, v;
14     vector<int> p, way;
15     T inf;
16
17     hungarian(int n_, int m_) : n(n_), m(m_), u(m+1),
18         v(m+1), p(m+1), way(m+1) {
19         a = vector<vector<T>>(n, vector<T>(m));
20         inf = numeric_limits<T>::max();
21     }
22     pair<T, vector<int>> assignment() {
23         for (int i = 1; i <= n; i++) {
24             p[0] = i;
25             int j0 = 0;
26             vector<T> minv(m+1, inf);
27             vector<int> used(m+1, 0);
28             do {
29                 used[j0] = true;
30                 int i0 = p[j0], j1 = -1;
31                 T delta = inf;
32                 for (int j = 1; j <= m; j++) if (!
33                     used[j]) {
34                     T cur = a[i0-1][j-1] - u[i0] - v[
35                         j];
36                     if (cur < minv[j]) minv[j] = cur;
37                     way[j] = j0;
38                     if (minv[j] < delta) delta = minv
39                         [j], j1 = j;
40                 }
41                 for (int j = 0; j <= m; j++)
42                     if (used[j]) u[p[j]] += delta, v[
43                         j] -= delta;
44                 else minv[j] -= delta;
45                 j0 = j1;
46             } while (p[j0] != 0);
47             do {
48                 int j1 = way[j0];
49                 p[j0] = p[j1];
50                 j0 = j1;
51             } while (j0);
52             vector<int> ans(m);
53             for (int j = 1; j <= n; j++) ans[p[j]-1] = j
54                 -1;
55             return make_pair(-v[0], ans);
56         }
57     };

```

6.7 Floyd Warshall

```

1 // Floyd Warshall
2
3 int dist[N][N];
4
5 for(int k = 1; k <= n; k++)
6     for(int i = 1; i <= n; i++)
7         for(int j = 1; j <= n; j++)
8             dist[i][j] = min(dist[i][j], dist[i][k] +
9                 dist[k][j]);

```

6.8 Lca

```

1 const int LOG = 22;
2 vector<vector<int>> g(N);
3 int t, n;
4 vector<int> in(N), height(N);
5 vector<vector<int>> up(LOG, vector<int>(N));
6 void dfs(int u, int h=0, int p=-1) {
7     up[0][u] = p;
8     in[u] = t++;
9     height[u] = h;
10    for (auto v: g[u]) if (v != p) dfs(v, h+1, u);
11 }
12
13 void blift() {
14     up[0][0] = 0;
15     for (int j=1; j<LOG; j++) {
16         for (int i=0; i<n; i++) {
17             up[j][i] = up[j-1][up[j-1][i]];
18         }
19     }
20 }
21
22 int lca(int u, int v) {
23     if (u == v) return u;
24     if (in[u] < in[v]) swap(u, v);
25     for (int i=LOG-1; i>=0; i--) {
26         int u2 = up[i][u];
27         if (in[u2] > in[v])
28             u = u2;
29     }
30     return up[0][u];
31 }
32
33 t = 0;
34 dfs(0);
35 blift();
36 // lca O(1)
37
38 template<typename T> struct rmq {
39     vector<T> v;
40     int n; static const int b = 30;
41     vector<int> mask, t;
42
43     int op(int x, int y) { return v[x] < v[y] ? x : y
44         ; }
45     int msb(int x) { return __builtin_clz(1)-
46         __builtin_clz(x); }
47     rmq() {}
48     rmq(const vector<T>& v_) : v(v_), n(v.size()),
49         mask(n), t(n) {
50         for (int i = 0, at = 0; i < n; mask[i++] = at
51             |= 1) {
52             at = (at<<1)&((1<<b)-1);
53             while (at and op(i, i-msb(at&-at)) == i)
54                 at ^= at&-at;
55         }
56         for (int i = 0; i < n/b; i++) t[i] = b*i+b-1-
57             msb(mask[b*i+b-1]);
58         for (int j = 1; (1<<j) <= n/b; j++) for (int
59             i = 0; i+(1<<j) <= n/b; i++)
60             t[n/b*j+i] = op(t[n/b*(j-1)+i], t[n/b*(j
61                 -1)+i+(1<<(j-1))]);
62     }
63     int small(int r, int sz = b) { return r-msb(mask[
64         r]&((1<<sz)-1)); }
65     T query(int l, int r) {
66         if (r-l+1 <= b) return small(r, r-l+1);
67         int ans = op(small(l+b-1), small(r));
68         int x = l/b+1, y = r/b-1;
69         if (x <= y) {
70             int j = msb(y-x+1);
71             ans = op(ans, op(t[n/b*j+x], t[n/b*j+y
72                 -(1<<j)+1]));
73         }
74     }

```

```

64     }
65     return ans;
66 }
67 };
68
69 namespace lca {
70     vector<int> g[N];
71     int v[2*N], pos[N], dep[2*N];
72     int t;
73     rmq<int> RMQ;
74
75     void dfs(int i, int d = 0, int p = -1) {
76         v[t] = i, pos[i] = t, dep[t++] = d;
77         for (int j : g[i]) if (j != p) {
78             dfs(j, d+1, i);
79             v[t] = i, dep[t++] = d;
80         }
81     }
82     void build(int n, int root) {
83         t = 0;
84         dfs(root);
85         RMQ = rmq<int>(vector<int>(dep, dep+2*n-1));
86     }
87     int lca(int a, int b) {
88         a = pos[a], b = pos[b];
89         return v[RMQ.query(min(a, b), max(a, b))];
90     }
91     int dist(int a, int b) {
92         return dep[pos[a]] + dep[pos[b]] - 2*dep[pos[lca(a, b)]];
93     }
94 }

```

6.9 Kruskal

```

1 struct DSU {
2     int n;
3     vector<int> parent, size;
4
5     DSU(int n): n(n) {
6         parent.resize(n, 0);
7         size.assign(n, 1);
8
9         for(int i=0; i<n; i++)
10             parent[i] = i;
11     }
12
13     int find(int a) {
14         if(a == parent[a]) return a;
15         return parent[a] = find(parent[a]);
16     }
17
18     void join(int a, int b) {
19         a = find(a); b = find(b);
20         if(a != b) {
21             if(size[a] < size[b]) swap(a, b);
22             parent[b] = a;
23             size[a] += size[b];
24         }
25     }
26 };
27
28 struct Edge {
29     int u, v, weight;
30     bool operator<(Edge const& other) {
31         return weight < other.weight;
32     }
33 };
34
35 vector<Edge> kruskal(int n, vector<Edge> edges) {
36     vector<Edge> mst;
37     DSU dsu = DSU(n+1);
38

```

```

39     sort(edges.begin(), edges.end());
40
41     for(Edge e : edges) {
42         if(dsu.find(e.u) != dsu.find(e.v)) {
43             mst.push_back(e);
44             dsu.join(e.u, e.v);
45         }
46     }
47
48     return mst;
49 }

```

6.10 Ford

```

1 const int N = 2000010;
2
3 struct Ford {
4     struct Edge {
5         int to, f, c;
6     };
7
8     int vis[N];
9     vector<int> adj[N];
10    vector<Edge> edges;
11    int cur = 0;
12
13    void addEdge(int a, int b, int cap, int rcap) {
14        Edge e;
15        e.to = b; e.c = cap; e.f = 0;
16        edges.pb(e);
17        adj[a].pb(cur++);
18
19        e = Edge();
20        e.to = a; e.c = rcap; e.f = 0;
21        edges.pb(e);
22        adj[b].pb(cur++);
23    }
24
25    int dfs(int s, int t, int f, int tempo) {
26        if(s == t)
27            return f;
28        vis[s] = tempo;
29
30        for(int e : adj[s]) {
31            if(vis[edges[e].to] < tempo and (edges[e].c - edges[e].f) > 0) {
32                if(int a = dfs(edges[e].to, t, min(f, edges[e].c - edges[e].f), tempo)) {
33                    edges[e].f += a;
34                    edges[e^1].f -= a;
35                    return a;
36                }
37            }
38        }
39        return 0;
40    }
41
42    int flow(int s, int t) {
43        int mflow = 0, tempo = 1;
44        while(int a = dfs(s, t, INF, tempo)) {
45            mflow += a;
46            tempo++;
47        }
48        return mflow;
49    }
50 };

```

7 Algoritmos

7.1 Ternary Search

```

1 // Ternary
2 ld l = -1e4, r = 1e4;
3 int iter = 100;
4 while(iter--){
5     ld m1 = (2*l + r) / 3;
6     ld m2 = (l + 2*r) / 3;
7     if(check(m1) > check(m2))
8         l = m1;
9     else
10        r = m2;
11 }

```

8 Math

8.1 Totient

```

1 // phi(p^k) = (p^(k-1))*(p-1) com p primo
2 // O(sqrt(m))
3 ll phi(ll m){
4     ll res = m;
5     for(ll d=2;d*d<=m;d++){
6         if(m % d == 0){
7             res = (res/d)*(d-1);
8             while(m%d == 0)
9                 m /= d;
10        }
11    }
12    if(m > 1) {
13        res /= m;
14        res *= (m-1);
15    }
16    return res;
17 }
18
19 // modificacao do crivo, O(n*log(log(n)))
20 vector<ll> phi_to_n(ll n){
21     vector<bool> isprime(n+1, true);
22     vector<ll> tot(n+1);
23     tot[0] = 0; tot[1] = 1;
24     for(ll i=1;i<=n; i++){
25         tot[i] = i;
26     }
27
28     for(ll p=2;p<=n;p++){
29         if(isprime[p]){
30             tot[p] = p-1;
31             for(ll i=p+p;i<=n;i+=p){
32                 isprime[i] = false;
33                 tot[i] = (tot[i]/p)*(p-1);
34             }
35         }
36     }
37     return tot;
38 }

```

8.2 Inverso Mult

```

1 // gcd(a, m) = 1 para existir solucao
2 // ax + my = 1, ou a*x = 1 (mod m)
3 ll inv(ll a, ll m) { // com gcd
4     ll x, y;
5     gcd(a, m, x, y);
6     return ((x % m) + m) % m;
7 }
8
9 ll inv(ll a, ll phim) { // com phi(m), se m for primo
10    entao phi(m) = p-1
11    ll e = phim-1;
12    return fexp(a, e);

```

8.3 Miller Habin

```

1 ll mul(ll a, ll b, ll m) {
2     return (a*b-ll(a*(long double)b/m+0.5)*m+m)%m;
3 }
4
5 ll expo(ll a, ll b, ll m) {
6     if (!b) return 1;
7     ll ans = expo(mul(a, a, m), b/2, m);
8     return b%2 ? mul(a, ans, m) : ans;
9 }
10
11 bool prime(ll n) {
12     if (n < 2) return 0;
13     if (n <= 3) return 1;
14     if (n % 2 == 0) return 0;
15
16     ll d = n - 1;
17     int r = 0;
18     while (d % 2 == 0) {
19         r++;
20         d /= 2;
21     }
22
23     // com esses primos, o teste funciona garantido
24     // para n <= 2^64
25     // funciona para n <= 3*10^24 com os primos ate
26     // 41
27     for (int i : {2, 325, 9375, 28178, 450775,
28         9780504, 795265022}) {
29         if (i >= n) break;
30         ll x = expo(i, d, n);
31         if (x == 1 or x == n - 1) continue;
32
33         bool composto = 1;
34         for (int j = 0; j < r - 1; j++) {
35             x = mul(x, x, n);
36             if (x == n - 1) {
37                 composto = 0;
38                 break;
39             }
40         }
41         if (composto) return 0;
42     }
43     return 1;
44 }

```

8.4 Matrix Exponentiation

```

1 struct Matrix {
2     vector<vl> m;
3     int r, c;
4
5     Matrix(vector<vl> mat) {
6         m = mat;
7         r = mat.size();
8         c = mat[0].size();
9     }
10
11     Matrix(int row, int col, bool ident=false) {
12         r = row; c = col;
13         m = vector<vl>(r, vl(c, 0));
14         if(ident) {
15             for(int i = 0; i < min(r, c); i++) {
16                 m[i][i] = 1;
17             }
18         }
19     }
20
21     Matrix operator*(const Matrix &o) const {
22         assert(c == o.r); // garantir que da pra
23         multiplicar

```



```

23     vector<vl> res(r, vl(o.c, 0));
24
25     for(int i = 0; i < r; i++) {
26         for(int k = 0; k < c; k++) {
27             for(int j = 0; j < o.c; j++) {
28                 res[i][j] = (res[i][j] + m[i][k]*
29                 o.m[k][j]) % MOD;
30             }
31         }
32     }
33     return Matrix(res);
34 }
35 };
36
37 Matrix fexp(Matrix b, int e, int n) {
38     if(e == 0) return Matrix(n, n, true); //
39     identidade
40     Matrix res = fexp(b, e/2, n);
41     res = (res * res);
42     if(e%2) res = (res * b);
43     return res;
44 }

```

8.5 Division Trick

```

1  for(int l = 1, r; l <= n; l = r + 1) {
2      r = n / (n / l);
3      // n / i has the same value for l <= i <= r
4  }

```

8.6 Crivo

```

1  vi p(N, 0);
2  p[0] = p[1] = 1;
3  for(ll i=4; i<N; i+=2) p[i] = 2;
4  for(ll i=3; i<N; i+=2)
5      if(!p[i])
6          for(ll j=i*i; j<N; j+=2*i)

```

```

7      p[j] = i;

```

8.7 Bigmod

```

1  ll mod(string a, ll p) {
2      ll res = 0, b = 1;
3      reverse(all(a));
4
5      for(auto c : a) {
6          ll tmp = (((ll)c-'0')*b) % p;
7          res = (res + tmp) % p;
8
9          b = (b * 10) % p;
10     }
11
12     return res;
13 }

```

8.8 Linear Diophantine Equation

```

1  // Linear Diophantine Equation
2  array<ll, 3> exgcd(int a, int b) {
3      if (a == 0) return {0, 1, b};
4      auto [x, y, g] = exgcd(b % a, a);
5      return {y - b / a * x, x, g};
6  }
7
8  array<ll, 4> find_any_solution(ll a, ll b, ll c) {
9      auto [x, y, g] = exgcd(a, b);
10     if (c % g) return {false, 0, 0, 0};
11     x *= c / g;
12     y *= c / g;
13     return {true, x, y, g};
14 }
15
16 // All solutions
17 // x' = x + k*b/g
18 // y' = y - k*a/g

```