



# Notebook - Maratona de Programação

Tiago de Souza Fernandes

## Sumário

|   |          |   |           |
|---|----------|---|-----------|
| <b>1 Algoritmos</b>                                   | <b>2</b> | <b>4 ED</b>                                 | <b>8</b>  |
| 1.1 Mochila . . . . .                                 | 2        | 4.1 Trie . . . . .                          | 8         |
| 1.2 Kadane-DP . . . . .                               | 2        | 4.2 Range-query-bigger-than-k-BIT . . . . . | 8         |
| 1.3 Iterative-BS . . . . .                            | 2        | 4.3 Iterative-SegTree . . . . .             | 9         |
| <b>2 Grafos</b>                                       | <b>2</b> | 4.4 Recursive-SegTree . . . . .             | 10        |
| 2.1 BFS . . . . .                                     | 2        | 4.5 Delta-Encoding . . . . .                | 10        |
| 2.2 Find-bridges . . . . .                            | 2        | 4.6 Seg-Tree-Farao . . . . .                | 10        |
| 2.3 Dijkstra . . . . .                                | 2        | 4.7 BIT-2D . . . . .                        | 11        |
| 2.4 LCA . . . . .                                     | 3        | 4.8 BIT . . . . .                           | 11        |
| 2.5 Floyd-Warshall . . . . .                          | 3        | 4.9 Sparse-Table . . . . .                  | 11        |
| 2.6 Kruskal . . . . .                                 | 3        | 4.10 Union-Find . . . . .                   | 12        |
| 2.7 DFS . . . . .                                     | 4        | 4.11 Mo . . . . .                           | 12        |
| 2.8 Topological-sort . . . . .                        | 4        | <b>5 Math</b>                               | <b>12</b> |
| 2.9 Kosaraju . . . . .                                | 4        | 5.1 Totient . . . . .                       | 12        |
| 2.10 Centroid . . . . .                               | 4        | 5.2 Sqrt-BigInt . . . . .                   | 13        |
| 2.11 Prim . . . . .                                   | 4        | 5.3 Linear-Diophantine-Equation . . . . .   | 13        |
| <b>3 Geometria</b>                                    | <b>5</b> | 5.4 Sum-n2 . . . . .                        | 13        |
| 3.1 Convex-polygon-intersection . . . . .             | 5        | 5.5 Factorization-sqrt . . . . .            | 13        |
| 3.2 Angle-adjacent-vertices-regular-polygon . . . . . | 5        | 5.6 Modular-Exponentiation . . . . .        | 13        |
| 3.3 Inside-polygon . . . . .                          | 5        | 5.7 Miller-Habin . . . . .                  | 13        |
| 3.4 Pick's-theorem . . . . .                          | 6        | 5.8 Inverso-Mult . . . . .                  | 14        |
| 3.5 linesweep . . . . .                               | 6        | 5.9 Pollard-Rho . . . . .                   | 14        |
| 3.6 Center-polygon . . . . .                          | 6        | 5.10 Verif-primo . . . . .                  | 15        |
| 3.7 Intersect-polygon . . . . .                       | 6        | 5.11 Crivo . . . . .                        | 15        |
| 3.8 Sort-by-Angle . . . . .                           | 6        | 5.12 Simpson's-formula . . . . .            | 15        |
| 3.9 Cross-properties . . . . .                        | 6        | 5.13 FFT . . . . .                          | 15        |
| 3.10 Inter-Retangulos . . . . .                       | 6        | 5.14 Next-Permutation . . . . .             | 16        |
| 3.11 Heron . . . . .                                  | 6        | 5.15 Fast-Exponentiation . . . . .          | 16        |
| 3.12 3D . . . . .                                     | 6        | 5.16 Recursao-linear . . . . .              | 16        |
| 3.13 Dot-properties . . . . .                         | 7        | 5.17 Raiz-primitiva . . . . .               | 17        |
| 3.14 Minkowski-Sum . . . . .                          | 7        | 5.18 Kamenetsky . . . . .                   | 17        |
| 3.15 2D . . . . .                                     | 7        | <b>6 Misc</b>                               | <b>17</b> |
|   |          | 6.1 2SAT . . . . .                          | 17        |
|   |          | 6.2 LIS . . . . .                           | 18        |
|   |          | 6.3 Bitwise . . . . .                       | 18        |
|   |          | 6.4 Template . . . . .                      | 18        |

|          |                    |           |
|----------|--------------------|-----------|
| <b>7</b> | <b>Strings</b>     | <b>19</b> |
| 7.1      | Trie . . . . .     | 19        |
| 7.2      | KMP . . . . .      | 19        |
| 7.3      | LCS . . . . .      | 19        |
| 7.4      | Pal-int . . . . .  | 19        |
| 7.5      | Z-Func . . . . .   | 19        |
| 7.6      | Hash . . . . .     | 20        |
| 7.7      | Manacher . . . . . | 20        |

# 1 Algoritmos

## 1.1 Mochila

```
1 int val[MAXN], peso[MAXN], dp[MAXN][MAXS]
2
3 int knapsack(int N, int M) // Objetos | Peso max
4 {
5     for(i=0; i<=N; i++)
6     {
7         for(j=0; j<=M; j++)
8         {
9             if (i==0 || j==0)
10                dp[i][j] = 0;
11             else if (peso[i-1] <= j)
12                dp[i][j] = max(val[i-1]+dp[i-1][j-
13                    peso[i-1]], dp[i-1][j]);
14             else
15                dp[i][j] = dp[i-1][j];
16         }
17     }
18     return dp[N][M];
19 }
```

## 1.2 Kadane-DP

```
1 // Largest Sum Contiguous Subarray
2
3 int maxSubArraySum(vector<int> a)
4 {
5     int size = a.size();
6     int max_so_far = a[0];
7     int curr_max = a[0];
8
9     for (int i=1; i<size; i++)
10     {
11         curr_max = max(a[i], curr_max+a[i]);
12         max_so_far = max(max_so_far, curr_max);
13     }
14     return max_so_far;
15 }
```

## 1.3 Iterative-BS

```
1 int main()
2 {
3     int l=1, r=N;
4     int res=-1;
5
6     while(l <= r)
7     {
8         int m = (l + r)/2;
9         if(!ver(m))
10         {
11             l = m+1;
12         }
13         else
14         {
15             res = m;
16             r = m-1;
17         }
18     }
19     cout << res << endl;
20
21     return 0;
22 }
```

# 2 Grafos

## 2.1 BFS

```
1 //BFS (Breadth First Search) O(V+A)
2
3 vector<vector<int>> adj; // adjacency list
4 // representation
5 int n; // number of nodes
6 int s; // source vertex
7
8 queue<int> q;
9 vector<int> d(n, INF);
10 d[s]=0;
11
12 q.push(s);
13 used[s] = true;
14 while (!q.empty()) {
15     int v = q.front();
16     q.pop();
17     for (int u : adj[v]) {
18         if (d[u] > d[v] + 1) {
19             q.push(u);
20             d[u] = d[v] + 1;
21         }
22     }
23 }
```

## 2.2 Find-bridges

```
1 #define vi vector<int>
2
3 vector< vector<int> > grafo;
4 vector<bool> visited;
5 vi t, low;
6 int timer=0;
7
8 void find_bridges(int v, int p=-1){
9     visited[v] = true;
10     t[v] = low[v] = timer++;
11     for(int i=0; i<(int)grafo[v].size(); i++){
12         int vert = grafo[v][i];
13         if(vert == p)
14             continue;
15         if(visited[vert])
16             low[v] = min(low[v], t[vert]);
17         else{
18             find_bridges(vert, v);
19             low[v] = min(low[v], low[vert]);
20             if(low[vert] > t[v])
21                 IS_BRIDGE(v, vert);
22         }
23     }
24 }
25
26 int main()
27 {
28     timer = 0;
29     visited.assign(N+1, false);
30     t.assign(N+1, 0);
31     low.assign(N+1, 0);
32
33     for(int i=0; i<N; i++)
34         if(!visited[i])
35             find_bridges(i);
36
37     return 0;
38 }
```

## 2.3 Dijkstra

```
1 // Dijkstra - Shortest Path
2
3 #define pii pair<int, int>
4 #define vi vector<int>
5 #define vii vector< pair<int,int> >
```

```

6 #define INF 0x3f3f3f3f
7
8 vector<vii> grafo(N+1, vii());
9 vi distancia(N+1, INF);
10 priority_queue< pii, vii, greater<pii> > fila;
11
12 void dijkstra(int k){
13     int dist, vert, aux;
14     distancia[k]=0;
15
16     fila.push(mp(k, 0));
17
18     while(!fila.empty()){
19         aux=fila.top().f;
20         fila.pop();
21
22         for(auto v: grafo[aux]){
23             vert=v.f;
24             dist=v.s;
25             if(distancia[vert]>distancia[aux]+dist){
26                 distancia[vert]=distancia[aux]+dist;
27                 fila.push(mp(vert, distancia[vert]));
28             }
29         }
30     }
31 }
32
33 int main()
34 {
35     for(int i=0; i<M; i++){
36         cin >> a >> b >> p;
37         grafo[a].pb(mp(b, p));
38         grafo[b].pb(mp(a, p));
39     }
40 }

```

## 2.4 LCA

```

1 const int K = 100;
2 int logv[MAX+1];
3 int st[MAX][K];
4 vector<vi> grafo(200010, vi());
5
6 void make(){
7     logv[1] = 0; // pre-computar tabela de log
8     for (int i = 2; i <= MAX; i++)
9         logv[i] = logv[i/2] + 1;
10 }
11
12 void precompute(int N, int array[]) { //
13     for (int i = 0; i < N; i++)
14         st[i][0] = array[i];
15
16     int k = logv[N];
17     for (int j = 1; j <= k; j++)
18         for (int i = 0; i + (1 << j) <= N; i++)
19             st[i][j] = min(st[i][j-1], st[i + (1 << (j
20 - 1))][j - 1]);
21 }
22
23 int query(int L, int R) {
24     int j = logv[R - L + 1];
25     int minimum = min(st[L][j], st[R - (1 << j) + 1][j]);
26
27     return minimum;
28 }
29
30 int start[MAX+1], dfs_time;
31 int tour[2*MAX+1], id[2*MAX+1];
32 void dfs(int u, int pai=-1){

```

```

33     start[u] = dfs_time;
34     id[dfs_time] = u;
35     tour[dfs_time++] = start[u];
36     for(int v : grafo[u]){
37         if(v==pai)
38             continue;
39         dfs(v, u);
40         id[dfs_time] = u;
41         tour[dfs_time++] = start[u];
42     }
43 }
44
45 int LCA(int u, int v)
46 {
47     if(start[u] > start[v])
48         swap(u, v);
49     return id[query(start[u], start[v])];
50 }
51
52 int main()
53 {
54     int N, k, a, b;
55     cin >> N;
56
57     for(int i=0; i<N-1; i++)
58     {
59         cin >> a >> b;
60         grafo[a].pb(b);
61         grafo[b].pb(a);
62     }
63     dfs(1);
64
65     make();
66     precompute(2*N, tour);
67
68
69     cin >> k;
70     for(int i=0; i<k; i++)
71     {
72         cin >> a >> b;
73         cout << LCA(a, b) << endl;
74     }
75
76     return 0;
77 }

```

## 2.5 Floyd-Warshall

```

1 // Floyd Warshall
2
3 int dist[MAX][MAX];
4
5 void Floydwarshall()
6 {
7     for(int k = 1; k <= n; k++)
8         for(int i = 1; i <= n; i++)
9             for(int j = 1; j <= n; j++)
10                 dist[i][j] = min(dist[i][j], dist[i][k] + dist[k][j]);
11 }

```

## 2.6 Kruskal

```

1 // deve-se ter dsu codada com as funcoes make_set,
2 find_set e union_sets
3 struct Edge {
4     int u, v, weight;
5     bool operator<(Edge const& other) {
6         return weight < other.weight;
7     }
8 };

```

```

9 int n;
10 vector<Edge> edges;
11
12 int cost = 0;
13 vector<Edge> result;
14 for (int i = 0; i < n; i++)
15     make_set(i);
16
17 sort(edges.begin(), edges.end());
18
19 for (Edge e : edges) {
20     if (find_set(e.u) != find_set(e.v)) {
21         cost += e.weight;
22         result.push_back(e); // vector com as arestas
23         da MST
24         union_sets(e.u, e.v);
25     }
26 }

```

## 2.7 DFS

```

1 //DFS (Depth First Search) O(V+A)
2
3 void DFS(int x){
4     for(int i=0; i<(int)vizinhos[x].size(); i++){
5         int v = vizinhos[x][i];
6         if(componente[v] == -1){
7             componente[v] = componente[x];
8             DFS(v);
9         }
10    }
11 }

```

## 2.8 Topological-sort

```

1 vector<vi> grafo(MAX, vi());
2 int grau[MAX]; // Quantas arestas chegam no indice i
3
4 vi topological_sort(int N)
5 {
6     vi resp;
7     for(int i=0; i<N; i++){
8         if(!grau[i])
9             resp.push_back(i);
10
11     int k=0;
12     while(k < (int)resp.size()){
13         int u = resp[k];
14         k++;
15         for(auto v: grafo[u]){
16             grau[v]--;
17             if(!grau[v])
18                 resp.pb(v);
19         }
20     }
21     return resp;
22 }

```

## 2.9 Kosaraju

```

1 // KOSARAJU - O(V+E) - encontra componentes
2 // g -> grafo, gt -> grafo tempo
3 // vis -> visitado, cor -> componente fortemente
4 // conexo ordenado topologicamente
5 vector<int> g[N], gt[N], S; int vis[N], cor[N];
6 void dfs(int u){
7     vis[u] = 1; for(int v : g[u]) if(!vis[v]) dfs(v);
8     S.push_back(u);
9 }
10 void dfst(int u, int e){
11     cor[u] = e;

```

```

11     for(int v : gt[u]) if(!cor[v]) dfst(v, e);
12 }
13 void kosaraju(){
14     for(int i = 1; i <= n; i++) if(!vis[i]) dfs(i);
15     for(int i = 1; i <= n; i++) for(int j : g[i])
16         gt[j].push_back(i);
17     int e = 0; reverse(S.begin(), S.end());
18     for(int u : S) if(!cor[u]) dfst(u, ++e);
19 }

```

## 2.10 Centroid

```

1 vi g[MAX];
2 int size[MAX];
3 bool erased[MAX]; // vetor dos vertices apagados na
4 // decomp.
5
6 int sz(int u, int p) {
7     int s = 1;
8     for(auto prox : g[u]) {
9         if(prox != p and !erased[prox])
10             s += sz(prox, u);
11     }
12     return size[u] = s;
13 }
14
15 int centroid(int u, int p, int n) {
16     // chamar funcao sz antes, n = size[u]
17     for(auto prox : g[u]) {
18         if(prox != p and !erased[prox]) {
19             if(size[prox] > n/2) {
20                 return centroid(prox, u, n);
21             }
22         }
23     }
24     return u;
25 }

```

## 2.11 Prim

```

1 // Prim Algorithm
2 #define MAXN 10100
3 #define INFINTO 999999999
4
5 int n, m;
6 int distancia[MAXN];
7 int processado[MAXN];
8 vector<pii> vizinhos[MAXN];
9
10 int Prim()
11 {
12     for(int i = 2; i <= n; i++) distancia[i] = INFINTO;
13     distancia[1] = 0;
14
15     priority_queue< pii, vector<pii>, greater<pii> >
16     fila;
17     fila.push( pii(distancia[1], 1) );
18
19     while(1){
20         int davez = -1;
21
22         while(!fila.empty()){
23             int atual = fila.top().second;
24             fila.pop();
25
26             if(!processado[atual]){
27                 davez = atual;
28                 break;
29             }
30         }

```

```

31         if(davez == -1)
32             break;
33
34         processado[davez] = true;
35
36         for(int i = 0; i < (int)vizinhos[davez].size()
37 ;i++){
38             int dist = vizinhos[davez][i].first;
39             int atual = vizinhos[davez][i].second;
40
41             if( distancia[atual] > dist && !
42 processado[atual])
43             {
44                 distancia[atual] = dist;
45                 fila.push( pii(distancia[atual],
46 atual) );
47             }
48         }
49
50         int custo_arvore = 0;
51         for(int i = 1; i <= n; i++){
52             custo_arvore += distancia[i];
53         }
54
55         return custo_arvore;
56     }
57
58     int main(){
59         cin >> n >> m;
60
61         for(int i = 1; i <= m; i++){
62             int x, y, tempo;
63             cin >> x >> y >> tempo;
64
65             vizinhos[x].pb( pii(tempo, y) );
66             vizinhos[y].pb( pii(tempo, x) );
67         }
68
69         cout << Prim() << endl;
70
71         return 0;
72     }

```

## 3 Geometria

### 3.1 Convex-polygon-intersection

```

1  cod cross(point a, point b){
2      return a.x*b.y - a.y*b.x;
3  }
4
5  int ccw(point a, point b, point e) //-1=esq; 0=
6      collinear; 1=dir;
7  {
8      cod tmp = cross(b-a, e-a); // from a to b
9      return (tmp > EPS) - (tmp < -EPS);
10 }
11
12 int n=4;
13 vector<point> A, B;
14
15 bool intersect()
16 {
17     A.pb(A[0]);
18     B.pb(B[0]);
19     point centerA=point();
20     point centerB=point();
21
22     for(int i=0; i<n; i++){

```

```

23         centerA=centerA+A[i];
24         centerB=centerB+B[i];
25     }
26     centerA=centerA/n;
27     centerB=centerB/n;
28     A.pb(centerA);
29     B.pb(centerB);
30
31     bool d, e;
32
33     for(int j=1; j<n+2; j++)
34     {
35         d=false, e=false;
36         for(int i=0; i<n; i++)
37         {
38             int t = esq(A[i], A[i+1], B[j]);
39             if(t==1) e=true;
40             else if(t==-1) d=true;
41         }
42
43         if(!(e and d))
44             return 1;
45     }
46
47     for(int j=1; j<n+2; j++)
48     {
49         d=false, e=false;
50         for(int i=0; i<n; i++)
51         {
52             int t = esq(B[i], B[i+1], A[j]);
53             if(t==1) e=true;
54             else if(t==-1) d=true;
55         }
56
57         if(!(e and d))
58             return 1;
59     }
60
61     return 0;
62 }

```

### 3.2 Angle-adjacent-vertices-regular-polygon

$$a = 180/N$$

### 3.3 Inside-polygon

```

1  bool inside(vector<point> vet, point ext) //ccw
2  {
3      int l=2, r=(int)vet.size()-1;
4      int res=r;
5      while(l<r){
6          int mid = (l+r)/2;
7          if(esq(vet[0], vet[mid], ext)==-1){
8              l=mid+1;
9          }else
10         {
11             r=mid;
12             res=mid;
13         }
14     }
15     int a = esq(vet[0], vet[res-1], ext);
16     int b = esq(vet[res-1], vet[res], ext);
17     int c = esq(vet[res], vet[0], ext);
18
19     if((a==1 or b==1 or c==1) and (a==-1 or b==-1 or
20 c==-1)) return false;
21     else return true;
22 }

```

### 3.4 Pick's-theorem

- The area of a polygon with integer coordinates:  $A = i + \frac{b}{2} - 1$
- $i$  is the number of points inside the polygon;
- $b$  is the number of points on the boundary;
- $2A$  is necessarily an integer value.

### 3.5 linesweep

```
1 typedef pair<double, double> dd;
2
3 bool compare(dd a, dd b){
4     return a.st < b.st;
5 }
6
7 double closest(dd v[], int n){
8     sort(v, v+n, compare);
9     double best = FLT_MAX;
10    set<dd> box;
11    box.insert(v[0]);
12    int left = 0;
13    rep2(i, 1, n){
14        while(left < i && v[i].st-v[left].st > best){
15            box.erase(v[left++]);
16        }
17        for(set<dd>::iterator it = box.lower_bound(mp
18            (v[i].nd-best, v[i].st-best)); it!=box.end() && v[
19            i].nd + best >= it->nd; it++){
20            best = min(best, sqrt(pow(v[i].nd - it->
21            nd, 2.0) + pow(v[i].st - it->st, 2.0)));
22        }
23        box.insert(v[i]);
24    }
25    return best;
26 }
```

### 3.6 Center-polygon

```
1 point center(vector<point> A)
2 {
3     point centerA = point();
4     for(int i=0;i<(int)A.size();i++){
5         centerA=centerA+A[i];
6     }
7     return centerA/(int)A.size();
8 }
```

### 3.7 Intersect-polygon

```
1 bool intersect(vector<point> A, vector<point> B) //
2     Ordered ccw
3 {
4     for(auto a: A)
5         if(inside(B, a))
6             return true;
7     for(auto b: B)
8         if(inside(A, b))
9             return true;
10    if(inside(B, center(A)))
11        return true;
12    return false;
13 }
14 }
```

### 3.8 Sort-by-Angle

```
1 int quarter(point a)
2 {
3     if(a.x>=0 and a.y>0) return 0;
4     if(a.x<0 and a.y>=0) return 1;
5     if(a.x<=0 and a.y<0) return 2;
6     return 3;
7 }
8
9 point c;
10 bool comp(point a, point b) //ccw
11 {
12     a=a-c;b=b-c;
13     int qa = quarter(a);
14     int qb = quarter(b);
15     if(qa==qb)
16         return cross(a,b)>0;
17     else
18         return qa<qb;
19 }
20
21 c = center(A);
22 sort(A.begin(), A.end(), comp);
```

### 3.9 Cross-properties

- It equals zero if the vectors **a** and **b** are collinear (coplanar in triple product).
- It is negative if the rotation from the first to the second vector is clockwise and positive otherwise.

### 3.10 Inter-Retangulos

```
1 bool doOverlap(point l1, point r1, point l2, point r2
2 )
3 {
4     if (l1.x>r2.x or l2.x>r1.x or l1.y<r2.y or l2.y<
5     r1.y)
6         return false;
7     return true;
8 }
```

### 3.11 Heron

$$A_{\text{triangulo}} = \sqrt{s(s-a)(s-b)(s-c)}$$
$$A_{\text{quadrilatero}} = \sqrt{(s-a)(s-b)(s-c)(s-d)}$$

### 3.12 3D

```
1 typedef ld cod;
2
3 bool eq(cod a, cod b){ return abs(a - b) <= EPS; }
4
5 struct point
6 {
7     cod x, y, z;
8     point(cod x=0, cod y=0, cod z=0): x(x), y(y), z(z)
9     {}
10
11     point operator+(const point &o) const{
12         return {x+o.x, y+o.y, z+o.z};
13     }
14     point operator-(const point &o) const{
15         return {x-o.x, y-o.y, z-o.z};
16     }
17     point operator*(cod t) const{
18         return {x*t, y*t, z*t};
19     }
20     point operator/(cod t) const{
```

```

20     return {x/t, y/t, z/t};
21 }
22 bool operator==(const point &o) const{
23     return eq(x, o.x) and eq(y, o.y) and eq(z, o.
24     z);
25 };
26
27 // Produto Escalar
28 cod dot(point a, point b){
29     return a.x*b.x + a.y*b.y + a.z*b.z;
30 }
31
32 // Produto Vetorial
33 point cross(point a, point b){
34     return point(a.y*b.z - a.z*b.y,
35                 a.z*b.x - a.x*b.z,
36                 a.x*b.y - a.y*b.x);
37 }
38
39 ld abs(point a){ // Modulo
40     return sqrt(dot(a, a));
41 }
42 ld proj(point a, point b){ // a sobre b
43     return dot(a, b)/abs(b);
44 }
45 ld angle(point a, point b){ // em radianos
46     return acos(dot(a, b) / abs(a) / abs(b));
47 }
48
49 cod triple(point a, point b, point c){
50     return dot(a, cross(b, c)); // Area do
    paralelepipedo
51 }

```

### 3.13 Dot-properties

- Length of **a**:  $|a| = \sqrt{a \cdot a}$ .
- Projection of **a** onto **b**:  $\frac{a \cdot b}{|b|}$ .
- Angle between vectors:  $\arccos\left(\frac{a \cdot b}{|a| \cdot |b|}\right)$ .
- The dot product is positive if the angle between them is acute, negative if it is obtuse and it equals zero if they are orthogonal, i.e. they form a right angle.

### 3.14 Minkowski-Sum

```

1 vector<point> mk(const vector<point> &a, const vector<
    point> &b){
2     int i = 0, j = 0;
3     for(int k = 0; k < (int)a.size(); k++){ if(a[k]<a[i]
    ]){
4         i = k;
5     }
6     for(int k = 0; k < (int)b.size(); k++){ if(b[k]<b[j]
    ]){
7         j = k;
8     }
9     vector<point> c;
10    c.reserve(a.size() + b.size());
11    for(int k = 0; k < int(a.size()+b.size()); k++){
12        point pt{a[i] + b[j]};
13        if((int)c.size() >= 2 and !ccw(c[c.size()-2],
    c.back(), pt))
14            c.pop_back();
15        c.pb(pt);
16        int q = i+1, w = j+1;
17        if(q == int(a.size())) q = 0;
18        if(w == int(b.size())) w = 0;

```

```

18        if(ccw(c.back(), a[i]+b[w], a[q]+b[j]) < 0) i
    = q;
19        else j = w;
20    }
21
22    if(!ccw(c[0], c[(int)c.size()-1], c[(int)c.size()
    -2]))
23        c.pop_back();
24    if(!ccw(c.back(), c[0], c[1])){
25        c[0]=c.back();
26        c.pop_back();
27    }
28    c.shrink_to_fit();
29
30    return c;
31 }

```

### 3.15 2D

```

1 ld max(ld a, ld b){ return(a>b ? a:b);}
2 ld min(ld a, ld b){ return(a<b ? a:b);}
3
4 typedef ld cod;
5 bool eq(cod a, cod b){ return fabs1(a - b) <= EPS; }
6
7 // typedef int cod;
8 // bool eq(cod a, cod b){ return (a==b); }
9
10 struct point
11 {
12     cod x, y;
13     int id;
14     point(cod x=0, cod y=0): x(x), y(y){}
15
16
17     point operator+(const point &o) const{
18         return {x+o.x, y+o.y};
19     }
20     point operator-(const point &o) const{
21         return {x-o.x, y-o.y};
22     }
23     point operator*(cod t) const{
24         return {x*t, y*t};
25     }
26     point operator/(cod t) const{
27         return {x/t, y/t};
28     }
29     bool operator<(const point &o) const{
30         if(!eq(x, o.x)) return x < o.x;
31         return y < o.y;
32     }
33     bool operator==(const point &o) const{
34         return eq(x, o.x) and eq(y, o.y);
35     }
36 }
37
38 struct line
39 {
40     point fp, sp;
41     point(point fp=0, point sp=0): fp(fp), sp(sp){}
42
43     //a=y1-y2;
44     //b=x2-x1;
45     //c=x2*y1-y2*x1;
46
47
48
49
50
51 // Produto Escalar
52 cod dot(point a, point b){
53     return a.x*b.x + a.y*b.y;
54 }

```



```

55 // Produto Vetorial
56 cod cross(point a, point b){
57     return a.x*b.y - a.y*b.x;
58 }
59
60 ld norm(point a){ // Modulo
61     return sqrt(dot(a, a));
62 }
63 ld proj(point a, point b){ // a sobre b
64     return dot(a, b)/norm(b);
65 }
66 ld max(ld a, ld b){ return (a>b ? a:b); }
67 ld min(ld a, ld b){ return (a<b ? a:b); }
68 ld angle(point a, point b){ // em radianos
69     ld ang = dot(a, b) / norm(a) / norm(b);
70     return acos(max(min(ang, 1), -1));
71 }
72 int ccw(point a, point b, point e) //-1=dir; 0=
    collinear; 1=esq;
73 {
74     cod tmp = cross(b-a, e-a); // from a to b
75     return (tmp > EPS) - (tmp < -EPS);
76 }
77 ld order_angle(point a, point b) // from a to b ccw (
    a in front of b)
78 {
79     ld aux = angle(a,b)*180/PI;
80     return (cross(a,b)<=0 ? aux:360-aux);
81 }
82
83 bool collinear(point a, point b, point c){
84     return eq(cross(a-c, b-c), 0);
85 }
86
87 point rotccw(point p, ld a) // em radianos
88 {
89     //a = a*acos(0.0)/90; // graus
90     return point((p.x*cos(a)-p.y*sin(a)), (p.y*cos(a)
    +p.x*sin(a)));
91 }
92
93 point rot90cw(point a) { return {a.y, -a.x} };
94 point rot90ccw(point a) { return {-a.y, a.x} };
95
96 // Area de um poligono (pontos ordenados por
    adjacencia)
97 ld area(vector <point> p){
98     ld ret = 0;
99     for(int i=2;i<(int)p.size();i++)
100         ret += cross(p[i] - p[0], p[i-1] - p[0]);
101     return fabs1(ret/2);
102 }
103
104 // Dist entre ponto e reta
105 cod distr(point a, line b){
106     cod crs = cross(point(a - b.fp), point(b.sp - b.
    fp));
107     return norm(crs/dist(b.fp, b.sp));
108 }

```

## 4 ED

### 4.1 Trie

```

1 class Trie {
2 private:
3     struct Node {
4         map<char, Node*> children;
5         int qt = 0;
6         ll size = 0;
7     };
8

```

```

9     Node* root;
10
11     void dfs(Node* cur) {
12         ll sz = 1;
13
14         for(auto prox : cur->children) {
15             dfs(prox.second);
16             sz += (prox.second->size);
17         }
18
19         cur->size = sz;
20     }
21
22     void del(Node* cur, int dep, string &s) {
23         if(dep >= 32)
24             return;
25
26         Node* prox = cur->children[s[dep]];
27         prox->qt--;
28         del(prox, dep+1, s);
29
30         if(prox->qt == 0)
31             cur->children.erase(s[dep]);
32     }
33
34 public:
35     Trie() {
36         root = new Node();
37         root->qt = 1;
38     }
39
40     void add(string s) {
41         Node* cur = root;
42
43         for(auto c : s) {
44             if(cur->children.count(c) == 0) {
45                 cur->children[c] = new Node();
46             }
47             cur->children[c]->qt++;
48             cur = cur->children[c];
49         }
50     }
51
52     void del(string &s) {
53         Node* cur = root;
54         del(cur, 0, s);
55     }
56
57     void size() {
58         this->dfs(root);
59     }
60 };

```

### 4.2 Range-query-bigger-than-k-BIT

```

1 // C++ program to print the number of elements
2 // greater than k in a subarray of range L-R.
3 #include <bits/stdc++.h>
4 using namespace std;
5
6 // Structure which will store both
7 // array elements and queries.
8 struct node{
9     int pos;
10    int l;
11    int r;
12    int val;
13 };
14
15 // Boolean comparator that will be used
16 // for sorting the structural array.
17 bool comp(node a, node b){
18     // If 2 values are equal the query will

```

```

19 // occur first then array element
20 if (a.val == b.val)
21     return a.l > b.l;
22
23 // Otherwise sorted in descending order.
24 return a.val > b.val;
25 }
26
27 // Updates the node of BIT array by adding
28 // 1 to it and its ancestors.
29 void update(int* BIT, int n, int idx){
30     while (idx <= n){
31         BIT[idx]++;
32         idx += idx & (-idx);
33     }
34 }
35 // Returns the count of numbers of elements
36 // present from starting till idx.
37 int query(int* BIT, int idx){
38     int ans = 0;
39     while (idx){
40         ans += BIT[idx];
41
42         idx -= idx & (-idx);
43     }
44     return ans;
45 }
46
47 // Function to solve the queries offline
48 void solveQuery(int arr[], int n, int QueryL[],
49                 int QueryR[], int QueryK[], int q){
50     // create node to store the elements
51     // and the queries
52     node a[n + q + 1];
53     // 1-based indexing.
54
55     // traverse for all array numbers
56     for(int i = 1; i <= n; ++i){
57         a[i].val = arr[i - 1];
58         a[i].pos = 0;
59         a[i].l = 0;
60         a[i].r = i;
61     }
62
63     // iterate for all queries
64     for(int i = n + 1; i <= n + q; ++i){
65         a[i].pos = i - n;
66         a[i].val = QueryK[i - n - 1];
67         a[i].l = QueryL[i - n - 1];
68         a[i].r = QueryR[i - n - 1];
69     }
70
71     // In-built sort function used to
72     // sort node array using comp function.
73     sort(a + 1, a + n + q + 1, comp);
74
75     // Binary Indexed tree with
76     // initially 0 at all places.
77     int BIT[n + 1];
78
79     // initially 0
80     memset(BIT, 0, sizeof(BIT));
81
82     // For storing answers for each query( 1-based
83     // indexing ).
84     int ans[q + 1];
85
86     // traverse for numbers and query
87     for (int i = 1; i <= n + q; ++i){
88         if (a[i].pos != 0) {
89             // call function to returns answer for
90             // each query

```

```

90         int cnt = query(BIT, a[i].r) - query(BIT,
91         a[i].l - 1);
92
93         // This will ensure that answer of each
94         // query
95         // are stored in order it was initially
96         // asked.
97         ans[a[i].pos] = cnt;
98     }
99     else{
100         // a[i].r contains the position of the
101         // element in the original array.
102         update(BIT, n, a[i].r);
103     }
104 }
105 // Output the answer array
106 for (int i = 1; i <= q; ++i){
107     cout << ans[i] << endl;
108 }
109 // Driver Code
110 int main()
111 {
112     int arr[] = { 7, 3, 9, 13, 5, 4 };
113     int n = sizeof(arr) / sizeof(arr[0]);
114
115     // 1-based indexing
116     int QueryL[] = { 1, 2 };
117     int QueryR[] = { 4, 6 };
118
119     // k for each query
120     int QueryK[] = { 6, 8 };
121
122     // number of queries
123     int q = sizeof(QueryL) / sizeof(QueryL[0]);
124
125     // Function call to get
126     solveQuery(arr, n, QueryL, QueryR, QueryK, q);
127
128     return 0;
129 }

```

### 4.3 Iterative-SegTree

```

1 // Segment Tree Iterativa - Range maximum query
2
3 #define N 100010
4
5 struct Segtree{
6     int t[2*N]={0};
7
8     void build(){
9         for(int i=N-1; i>0; i--){
10             t[i]=max(t[i<<1], t[1<<1|1]);
11         }
12
13     int query(int l, int r){
14         int ans=0;
15         for(i+=N, r+=N; l<r; l>>=1, r>>=1)
16         {
17             if(l&1)
18                 ans=max(ans, t[l++]);
19             if(r&1)
20                 ans=max(ans, t[--r]);
21         }
22
23         return ans;
24     }
25
26     void update(int p, int value){
27         for(t[p+=N]=value; p>1; p>>=1)
28             t[p>>1]= max(t[p], t[p^1]);

```

```

29     }
30
31 };
32
33 int main()
34 {
35     Segtree st;
36
37     for(int i=0;i<n;i++){
38         cin >> aux;
39         st.t[N+i]=aux; //Leaves are stored in
40         continuous nodes with indices starting with N
41     }
42
43     st.build();
44     x = st.query(inicio, fim);
45     st.update(ind, value);
46 }

```

## 4.4 Recursive-SegTree

```

1 // Segment Tree Recursiva - Range maximum query
2
3 vector<int> val(MAX, 0);
4 vector<int> vet(N);
5
6 void monta(int i, int j, int no){
7     if(i==j){
8         val[no]=vet[i];
9         return;
10    }
11
12    int esq = 2*no;
13    int dir = 2*no+1;
14    int meio = (i+j)/2;
15
16    monta(i, meio, esq);
17    monta(meio+1, j, dir);
18
19    val[no]=max(val[esq], val[dir]);
20 }
21
22 void atualiza(int no, int i, int j, int pos, int
23 novo_valor){
24     if(i==j){
25         val[no]=novo_valor;
26     }else{
27         int esq = 2*no;
28         int dir = 2*no+1;
29         int meio = (i+j)/2;
30
31         if(pos<=meio)
32             atualiza(esq, i, meio, pos, novo_valor);
33         else
34             atualiza(dir, meio+1, j, pos, novo_valor)
35     }
36
37     if(val[esq]>val[dir])
38         val[no]=val[esq];
39     else
40         val[no]=val[dir];
41 }
42
43 int consulta(int no, int i, int j, int A, int B){
44     if(i>B || j<A)
45         return -1;
46     if(i>=A and j<=B)
47         return val[no];
48
49     int esq = 2*no;
50     int dir = 2*no+1;

```

```

50     int meio = (i+j)/2;
51
52     int resp_esq = consulta(esq, i, meio, A, B);
53     int resp_dir = consulta(dir, meio+1, j, A, B);
54
55     if(resp_dir==-1)
56         return resp_esq;
57     if(resp_esq==-1)
58         return resp_dir;
59
60     if(resp_esq>resp_dir)
61         return resp_esq;
62     else
63         return resp_dir;
64 }
65
66 int main()
67 {
68     monta(1, N, 1);
69     atualiza(1, 1, N, pos, valor);
70     x = consulta(1, 1, N, inicio, fim);
71 }

```

## 4.5 Delta-Encoding

```

1 // Delta encoding
2
3 for(int i=0;i<q;i++){
4     int l,r,x;
5     cin >> l >> r >> x;
6     delta[l] += x;
7     delta[r+1] -= x;
8 }
9
10 int atual = 0;
11
12 for(int i=0;i<n;i++){
13     atual += delta[i];
14     v[i] += atual;
15 }

```

## 4.6 Seg-Tree-Farao

```

1 typedef struct
2 {
3     pii prefix, sufix, total, maximo;
4 } no;
5
6 int noleft[MAX], noright[MAX]; //Guarda os valores
7 dos nos para que nao sejam calculados novamente
8 nas querys
9
10 int v[MAX];
11 no arvore[MAX];
12
13 pii somar(pii a, pii b) // une pairs
14 {
15     return mp(a.f+b.f, a.s+b.s);
16 }
17
18 no une(no l, no r)
19 {
20     if(l.total.s==0)
21         return r;
22     if(r.total.s==0)
23         return l;
24
25     no m;
26
27     m.prefix = max(l.prefix, somar(l.total, r.prefix)
28 ); //prefixo
29     m.sufix = max(r.sufix, somar(r.total, l.sufix));
30     //sufixo

```

```

26     m.total = somar(l.total, r.total); //Soma de
    todos os elementos da subarvore
27     m.maximo = max(max(l.maximo, r.maximo), somar(l.
    sufix, r.prefix)); //Resultado para cada
    subarvore
28
29     return m;
30 }
31
32 no makenozero()
33 {
34     no m;
35     m.prefix=m.sufix=m.total=m.maximo=mp(0,0);
36     return m;
37 }
38
39 no makeno(int k)
40 {
41     no m;
42     m.prefix=m.sufix=m.total=m.maximo=mp(k,1);
43     return m;
44 }
45
46 void monta(int n)
47 {
48     if(noleft[n]==noright[n])
49     {
50         arvore[n]=makeno(v[noleft[n]]);
51         return;
52     }
53
54     int mid = (noleft[n]+noright[n])/2;
55     noleft[2*n]=noleft[n]; noright[2*n]=mid;
56     noleft[2*n+1]=mid+1; noright[2*n+1]=noright[n];
57
58     monta(2*n);
59     monta(2*n+1);
60
61     arvore[n]=une(arvore[2*n], arvore[2*n+1]);
62 }
63
64 no busca(int n, int esq, int dir)
65 {
66     if(noleft[n]>=esq and noright[n]<=dir)
67         return arvore[n];
68     if(noright[n]<esq or noleft[n]>dir)
69         return makenozero();
70
71     return une(busca(2*n, esq, dir),busca(2*n+1, esq,
    dir));
72 }
73
74 int main()
75 {
76     int T, N, Q, A, B;
77     no aux;
78
79     scanf("%d", &T);
80
81     while(T--)
82     {
83         scanf("%d", &N);
84         for(int i=1;i<=N;i++)
85             scanf("%d", &v[i]); //Elementos da arvore
86
87         noleft[1]=1;noright[1]=N;
88         monta(1);
89
90         cin >> Q;
91         while(Q--)
92         {
93             scanf("%d%d", &A, &B); //Intervalo da
    query

```

```

94         aux = busca(1, A, B);
95         printf("%d %d\n", aux.maximo.f, aux.
    maximo.s);
96     }
97 }
98
99
100     return 0;
101 }

```

## 4.7 BIT-2D

```

1 // BIT 2D
2
3 int bit[MAX][MAX];
4
5 int sum(int x, int y)
6 {
7     int resp=0;
8
9     for(int i=x;i>0;i-=i&-i)
10         for(int j=y;j>0;j-=j&-j)
11             resp+=bit[i][j];
12
13     return resp;
14 }
15
16 void update(int x, int y, int delta)
17 {
18     for(int i=x;i<MAX;i+=i&-i)
19         for(int j=y;j<MAX;j+=j&-j)
20             bit[i][j]+=delta;
21 }
22
23 int query(int x1, y1, x2, y2)
24 {
25     return sum(x2,y2) - sum(x2,y1) - sum(x1,y2) + sum
    (x1,y1);
26 }

```

## 4.8 BIT

```

1 struct FT {
2     vector<int> bit; // indexado em 1
3     int n;
4
5     FT(int n) {
6         this->n = n + 1;
7         bit.assign(n + 1, 0);
8     }
9
10    int sum(int idx) {
11        int ret = 0;
12        for (++idx; idx > 0; idx -= idx & -idx)
13            ret += bit[idx];
14        return ret;
15    }
16
17    int sum(int l, int r) {
18        return sum(r) - sum(l - 1);
19    }
20
21    void add(int idx, int delta) {
22        for (++idx; idx <= n; idx += idx & -idx)
23            bit[idx] += delta;
24    }
25 };

```

## 4.9 Sparse-Table

```

1 int logv[MAX+1];
2 void make_log() {

```

```

3     logv[1] = 0; // pre-computar tabela de log
4     for (int i = 2; i <= MAX; i++)
5         logv[i] = logv[i/2] + 1;
6 }
7
8 struct Sparse {
9     int n;
10    vector<vector<int>> st;
11
12    Sparse(int n, vi array) {
13        this->n = n;
14        int k = logv[n];
15        st.assign(n+1, vector<int>(k+1, 0));
16
17        for (int i = 0; i < n; i++)
18            st[i][0] = array[i];
19
20        for (int j = 1; j <= k; j++)
21            for (int i = 0; i + (1 << j) <= n; i++)
22                st[i][j] = f(st[i][j-1], st[i + (1 << j) - 1][j - 1]);
23    }
24
25    int f(int a, int b) {
26        return min(a, b);
27    }
28
29    int query(int L, int R) {
30        int j = logv[R - L + 1];
31        int res = f(st[L][j], st[R - (1 << j) + 1][j]);
32        return res;
33    }
34 };

```

## 4.10 Union-Find

```

1 struct DSU {
2     int n;
3     vector<int> parent, size;
4
5     DSU(int n) {
6         this->n = n;
7         parent.assign(n+1, 0);
8         size.assign(n+1, 1);
9
10        for(int i = 0; i <= n; i++)
11            parent[i] = i;
12    }
13
14    int find(int v) {
15        if(v == parent[v])
16            return v;
17        return find(parent[v]);
18    }
19
20    void join(int a, int b) {
21        a = find(a);
22        b = find(b);
23
24        if(a != b) {
25            if(size[a] < size[b])
26                swap(a, b);
27
28            parent[b] = a;
29            size[a] += size[b];
30        }
31    }
32 };

```

## 4.11 Mo

```

1 const int BLK = 500; // tamanho do bloco, algo entre
   300 e 500 e nice
2
3 struct Query {
4     int l, r, idx;
5     Query(int l, int r, int idx) {
6         this->l = l;
7         this->r = r;
8         this->idx = idx;
9     }
10    bool operator<(Query other) const {
11        return make_pair(l / BLK, r) <
12            make_pair(other.l / BLK, other.r);
13    }
14 };
15
16 void add() void remove() // implementar operacoes de
   acordo com o problema, cuidado com TLE ao
   utilizar MAP
17
18 vector<int> mo(vector<Query> queries) {
19     vector<int> res(queries.size());
20     sort(queries.begin(), queries.end());
21     resposta = 0;
22
23     int l = 0, r = -1;
24     for(Query q : queries) {
25         while(l > q.l) {
26             l--;
27             add(l);
28         }
29         while(r < q.r) {
30             r++;
31             add(r);
32         }
33         while(l < q.l) {
34             remove(l);
35             l++;
36         }
37         while(r > q.r) {
38             remove(r);
39             r--;
40         }
41         res[q.idx] = resposta; // adicionar resposta
   de acordo com o problema
42     }
43     return res; // ordenar o vetor pelo indice e
   responder queries na ordem
44 }

```

## 5 Math

### 5.1 Totient

```

1 // phi(p^k) = (p^(k-1))*(p-1) com p primo
2 // O(sqrt(m))
3 ll phi(ll m) {
4     ll res = m;
5     for(ll d = 2; d*d <= m; d++) {
6         if(m % d == 0) {
7             res = (res/d) * (d-1);
8             while(m % d == 0) {
9                 m /= d;
10            }
11        }
12    }
13    if(m > 1) {
14        res /= m;
15        res *= (m-1);
16    }
17
18    return res;

```

```

19 }
20
21 // modificacao do crivo, O(n*log(log(n)))
22 vector<ll> phi_to_n(ll n) {
23     vector<bool> isprime(n+1, true);
24     vector<ll> tot(n+1);
25     tot[0] = 0; tot[1] = 1;
26     for(ll i = 1; i <= n; i++) {
27         tot[i] = i;
28     }
29
30     for(ll p = 2; p <= n; p++) {
31         if(isprime[p]) {
32             tot[p] = p-1;
33             for(ll i = p+p; i <= n; i += p) {
34                 isprime[i] = false;
35                 tot[i] = (tot[i]/p)*(p-1);
36             }
37         }
38     }
39
40     return tot;
41 }

```

## 5.2 Sqrt-BigInt

```

1 public static BigInteger isqrtNewton(BigInteger n) {
2     BigInteger a = BigInteger.ONE.shiftLeft(n.
3         bitLength() / 2);
4     boolean p_dec = false;
5     for (;;) {
6         BigInteger b = n.divide(a).add(a).shiftRight
7         (1);
8         if (a.compareTo(b) == 0 || a.compareTo(b) < 0
9         && p_dec)
10             break;
11         p_dec = a.compareTo(b) > 0;
12         a = b;
13     }
14     return a;
15 }

```

## 5.3 Linear-Diophantine-Equation

```

1 // Linear Diophantine Equation
2 int gcd(int a, int b, int &x, int &y)
3 {
4     if (a == 0)
5     {
6         x = 0; y = 1;
7         return b;
8     }
9     int x1, y1;
10    int d = gcd(b%a, a, x1, y1);
11    x = y1 - (b / a) * x1;
12    y = x1;
13    return d;
14 }
15
16 bool find_any_solution(int a, int b, int c, int &x0,
17 int &y0, int &g)
18 {
19     g = gcd(abs(a), abs(b), x0, y0);
20     if (c % g)
21         return false;
22
23     x0 *= c / g;
24     y0 *= c / g;
25     if (a < 0) x0 = -x0;
26     if (b < 0) y0 = -y0;
27     return true;
28 }

```

```

28
29 // All solutions
30 // x = x0 + k*b/g
31 // y = y0 - k*a/g

```

## 5.4 Sum-n2

Soma dos n primeiros números ao quadrado =  $\frac{(2N^3+3N^2+N)}{6}$

## 5.5 Factorization-sqrt

```

1 // Factorization of a number in sqrt(n)
2
3 int main()
4 {
5     ll N;
6     vector<int> div;
7
8     cin >> N;
9
10    for(ll i=2;i*i<=N;i++)
11    {
12        if(N%i==0)
13        {
14            vet.pb(i);
15            while(N%i==0)
16                N/=i;
17        }
18    }
19    if(N!=1)
20        vet.pb(N);
21
22    return 0;
23 }

```

## 5.6 Modular-Exponentiation

```

1 ll fexp(ll b, ll e, ll mod) {
2     if(e == 0) return 1LL;
3     ll res = fexp(b, e/2LL, mod);
4     res = (res*res)%mod;
5     if(e%2LL)
6         res = (res*b)%mod;
7
8     return res%mod;
9 }

```

## 5.7 Miller-Habin

```

1 ll llrand()
2 {
3     ll tmp = rand();
4     return (tmp << 31) | rand();
5 }
6
7 ll add(ll a, ll b, ll c)
8 {
9     return (a + b)%c;
10 }
11
12 ll mul(ll a, ll b, ll c)
13 {
14     ll ans = 0;
15     while(b)
16     {
17         if(b & 1)
18             ans = add(ans, a, c);
19         a = add(a, a, c);
20         b /= 2;
21     }
22     return ans;
23 }

```

```

23 }
24
25 ll fexp(ll a, ll b, ll c)
26 {
27     ll ans = 1;
28     while(b)
29     {
30         if(b & 1)
31             ans = mul(ans, a, c);
32         a = mul(a, a, c);
33         b /= 2;
34     }
35     return ans;
36 }
37
38 bool rabin(ll n)
39 {
40     if(n <= 1)
41         return 1;
42     if(n <= 3)
43         return 1;
44
45     ll s=0, d=n-1;
46     while(d%2==0)
47     {
48         d/=2;
49         s++;
50     }
51
52     for(int k = 0; k < 64*4; k++)
53     {
54         ll a = (llrand()%(n - 3)) + 2;
55         ll x = fexp(a, d, n);
56         if(x != 1 and x != n-1)
57         {
58             for(int r = 1; r < s; r++)
59             {
60                 x = mul(x, x, n);
61                 if(x == 1)
62                     return 0;
63                 if(x == n-1)
64                     break;
65             }
66             if(x != n-1)
67                 return 0;
68         }
69     }
70
71     return 1;
72 }
73
74
75 int main()
76 {
77     ll N;
78     cin >> N;
79
80     cout << rabin(N) << endl;
81
82     return 0;
83
84 }
85

```

## 5.8 Inverso-Mult

```

1 // gcd(a, m) = 1 para existir solucao
2 // ax + my = 1, ou a*x = 1 (mod m)
3 ll inv(ll a, ll m) { // com gcd
4     ll x, y;
5     gcd(a, m, x, y);
6     return ((x % m) + m) % m;
7 }

```

```

8
9 ll inv(ll a, ll phim) { // com phi(m), se m for primo
10     entao phi(m) = p-1
11     ll e = phim-1;
12     return fexp(a, e);
13 }

```

## 5.9 Pollard-Rho

```

1 // Pollard Rho Algorithm
2
3 #include <bits/stdc++.h>
4 #define ll long long
5
6 using namespace std;
7
8 ll llrand()
9 {
10     ll tmp = rand();
11     return (tmp << 31) | rand();
12 }
13
14 ll add(ll a, ll b, ll c)
15 {
16     return (a + b)%c;
17 }
18
19 ll mul(ll a, ll b, ll c)
20 {
21     ll ans = 0;
22     while(b)
23     {
24         if(b & 1)
25             ans = add(ans, a, c);
26         a = add(a, a, c);
27         b /= 2;
28     }
29     return ans;
30 }
31
32 ll rho(ll n)
33 {
34     ll x, c, y, d, k;
35     int i;
36     do{
37         i = 1;
38         x = llrand()%n;
39         c = llrand()%n;
40         y = x, k = 4;
41         do{
42             if(++i == k)
43             {
44                 y = x;
45                 k *= 2;
46             }
47             x = add(mul(x, x, n), c, n);
48             d = __gcd(abs(x - y), n);
49         }
50         while(d == 1);
51     }
52     while(d == n);
53
54     return d;
55 }
56
57 int main()
58 {
59     srand(time(0));
60
61     ll N;
62     cin >> N;
63
64     ll div = rho(N);

```

```

65     cout << div << " " << N/div << endl;
66
67     // Finding all divisors
68
69     vector<ll> div;
70
71     while(N>1 and !rabin(N))
72     {
73         ll d = rho(N);
74         div.pb(d);
75         while(N%d==0)
76             N/=d;
77     }
78     if(N!=1)
79         div.pb(N);
80
81     return 0;
82
83 }
84

```

## 5.10 Verif-primo

```

1 // prime verification sqrt(N)
2
3 bool eh_primo(long long N)
4 {
5     if(N==2)
6         return true;
7     else if(N==1 or N%2==0)
8         return false;
9     for(long long i=3;i*i<=N;i+=2)
10         if(N%i==0)
11             return false;
12     return true;
13 }

```

## 5.11 Crivo

```

1 // Sieve of Eratosthenes
2
3 int N;
4 vector<bool> primos(100010, true);
5 cin >> N;
6
7 primos[0]=false;
8 primos[1]=false;
9
10 for(int i=2;i<=N;i++)
11     if(primos[i])
12         for(int j=i+i; j<=N; j+=i)
13             primos[j]=false;

```

## 5.12 Simpson's-formula

```

1 inline ld simpson(ld fl, ld fr, ld fmid, ld l, ld r){
2     return (fl+fr+4*fmid)*(r-l)/6;
3 }
4
5 ld rsimpson(ld slr, ld fl, ld fr, ld fmid, ld l, ld r
6 )
7 {
8     ld mid = (l+r)/2;
9     ld fml = f((l+mid)/2), fmr = f((mid+r)/2);
10    ld slm = simpson(fl,fmid,fml,l,mid);
11    ld smr = simpson(fmid,fr,fmr,mid,r);
12    if(fabs(slr-slm-smr) < EPS) return slm+smr; //
13    aprox. good enough
14    return rsimpson(slm,fl,fmid,fml,l,mid)+rsimpson(
15    smr,fmid,fr,fmr,mid,r);
16 }

```

```

15 ld integrate(ld l, ld r)
16 {
17     ld mid = (l+r)/2;
18     ld fl = f(l), fr = f(r);
19     ld fmid = f(mid);
20     return rsimpson(simpson(fl,fr,fmid,l,r),fl,fr,
21     fmid,l,r);
22 }

```

## 5.13 FFT

```

1 struct num{
2     double x, y;
3     num() { x = y = 0; }
4     num(double x, double y) : x(x), y(y) {}
5 };
6
7 inline num operator+(num a, num b) { return num(a.x +
8     b.x, a.y + b.y); }
9 inline num operator-(num a, num b) { return num(a.x -
10     b.x, a.y - b.y); }
11 inline num operator*(num a, num b) { return num(a.x *
12     b.x - a.y * b.y, a.x * b.y + a.y * b.x); }
13 inline num conj(num a) { return num(a.x, -a.y); }
14
15 int base = 1;
16 vector<num> roots = {{0, 0}, {1, 0}};
17 vector<int> rev = {0, 1};
18
19 const double PI = acos(-1.0);
20
21 void ensure_base(int nbase){
22     if(nbase <= base)
23         return;
24
25     rev.resize(1 << nbase);
26     for(int i = 0; i < (1 << nbase); i++)
27         rev[i] = (rev[i >> 1] >> 1) + ((i & 1) << (
28         nbase - 1));
29
30     roots.resize(1 << nbase);
31
32     while(base < nbase){
33         double angle = 2*PI / (1 << (base + 1));
34         for(int i = 1 << (base - 1); i < (1 << base);
35         i++){
36             roots[i << 1] = roots[i];
37             double angle_i = angle * (2 * i + 1 - (1
38             << base));
39             roots[(i << 1) + 1] = num(cos(angle_i),
40             sin(angle_i));
41         }
42         base++;
43     }
44 }
45
46 void fft(vector<num> &a, int n = -1){
47     if(n == -1)
48         n = a.size();
49
50     assert((n & (n-1)) == 0);
51     int zeros = __builtin_ctz(n);
52     ensure_base(zeros);
53     int shift = base - zeros;
54     for(int i = 0; i < n; i++){
55         if(i < (rev[i] >> shift))
56             swap(a[i], a[rev[i] >> shift]);
57     }
58
59     for(int k = 1; k < n; k <= 1)
60         for(int i = 0; i < n; i += 2 * k)
61             for(int j = 0; j < k; j++){
62                 num z = a[i+j+k] * roots[j+k];
63                 a[i+j+k] = a[i+j] - z;
64             }
65     }

```



```

56         a[i+j] = a[i+j] + z;
57     }
58 }
59
60 vector<num> fa, fb;
61 vector<int> multiply(vector<int> &a, vector<int> &b){
62     int need = a.size() + b.size() - 1;
63     int nbase = 0;
64     while((1 << nbase) < need) nbase++;
65     ensure_base(nbase);
66     int sz = 1 << nbase;
67     if(sz > (int) fa.size())
68         fa.resize(sz);
69
70     for(int i = 0; i < sz; i++){
71         int x = (i < (int) a.size() ? a[i] : 0);
72         int y = (i < (int) b.size() ? b[i] : 0);
73         fa[i] = num(x, y);
74     }
75     fft(fa, sz);
76     num r(0, -0.25 / sz);
77     for(int i = 0; i <= (sz >> 1); i++){
78         int j = (sz - i) & (sz - 1);
79         num z = (fa[j] * fa[j] - conj(fa[i] * fa[i]))
80             * r;
81         if(i != j) {
82             fa[j] = (fa[i] * fa[i] - conj(fa[j] * fa[
83 j])) * r;
84         }
85         fa[i] = z;
86     }
87     fft(fa, sz);
88     vector<int> res(need);
89     for(int i = 0; i < need; i++)
90         res[i] = fa[i].x + 0.5;
91
92     return res;
93 }
94
95 int main()
96 {sws;
97
98     //FFT
99     vector<int> fx{1, 2, 3}; // 1+2x+3x^2
100     vector<int> gx{4, 5}; // 4+5x
101     vector<int> res;
102
103     res = multiply(fx,gx); //4 + 13x + 22x^2 + 15x^3
104
105     return 0;
106 }

```

## 5.14 Next-Permutation

```

1 vector<int> a = {1, 2, 3};
2 int n = a.size();
3 do{
4     display(a, n); // 1,2,3; 1,3,2; 2,1,3; 3,1,2;
5     2,3,1; 3,2,1;
6 }while(next_permutation(a.begin(), a.begin() + n));

```

## 5.15 Fast-Exponentiation

```

1 // Modular exponentiaion - (x^y)%mod in O(log y)
2 ll power(ll x, ll y, ll mod)
3 {
4     ll res = 1;
5     x%=mod;
6
7     while(y)
8     {

```

```

9         if(y&1)
10             res=(res*x)%mod;
11
12         y=y>>1;
13         x=(x*x)%mod;
14     }
15     return res;
16 }

```

## 5.16 Recursao-linear

```

1 vector<vl> id(int n) {
2     vector<vl> res(n, vl(n, 0));
3     for(int i = 0; i < n; i++) res[i][i] = 1;
4     return res;
5 }
6
7 vector<vl> mult(vector<vl> a, vector<vl> b, int n) {
8     vector<vl> res(n, vl(n, 0));
9
10    for(int row = 0; row < n; row++) {
11        for(int col = 0; col < n; col++) {
12            ll val = 0;
13            for(int k = 0; k < n; k++) {
14                ll delta = (a[row][k] * b[k][col]) %
15                MOD;
16                val = (val + delta) % MOD;
17            }
18            res[row][col] = val;
19        }
20    }
21    return res;
22 }
23
24 vector<vl> fexp(vector<vl> b, ll e, int n) {
25     if(e == 0) {
26         return id(n);
27     }
28
29     vector<vl> res = fexp(b, e/2, n);
30     res = mult(res, res, n);
31
32     if(e%2)
33         res = mult(res, b, n);
34
35     return res;
36 }
37
38 // k = tamanho da recorrência/matriz, n = n-esimo
39 // termo
40 // f(n) = c1*f(n-1) + c2*f(n-2) + ... + ck*f(n-k)
41 // base -> [f(k-1), f(k-2), ..., f(0)]
42 // coeficientes -> [c1, c2, ..., ck]
43 vl solve(int k, int n, vl base, vl coef) {
44     vector<vl> inicial;
45     inicial.pb(coef);
46     for(int row = 0; row < k-1; row++) {
47         vl tmp;
48         for(int col = 0; col < k; col++) {
49             if(col == row)
50                 tmp.pb(1);
51             else
52                 tmp.pb(0);
53         }
54         inicial.pb(tmp);
55     }
56
57     vector<vl> matexp = fexp(inicial, max(0, n-k+1),
58     k);
59     vl res(k);
60
61     for(int row = 0; row < k; row++) {

```

```

60         ll val = 0;
61         for(int aux = 0; aux < k; aux++) {
62             val += matexp[row][aux]*base[aux];
63         }
64         res[row] = val; // res = (f(n), f(n-1), ...,
        f(n-k+1))
65     }
66
67     return res;
68 }

```

## 5.17 Raiz-primitiva

```

1  ll fexp(ll b, ll e, ll mod) {
2      if(e == 0) return 1LL;
3      ll res = fexp(b, e/2LL, mod);
4      res = (res*res)%mod;
5      if(e%2LL)
6          res = (res*b)%mod;
7
8      return res%mod;
9  }
10
11 vl fatorar(ll n) { // fatora em primos
12     vl fat;
13     for(int i = 2; i*i <= n; i++) {
14         if(n%i == 0) {
15             fat.pb(i);
16             while(n%i == 0)
17                 n /= i;
18         }
19     }
20     return fat;
21 }
22
23 // O(log(n) ^ 2)
24 bool raiz_prim(ll a, ll mod, ll phi, vl fat) {
25     if(__gcd(a, mod) != 1 or fexp(a, phi/2, mod) ==
26     1) // phi de euler sempre eh PAR
27         return false;
28
29     for(auto f : fat) {
30         if(fexp(a, phi/f, mod) == 1)
31             return false;
32     }
33
34     return true;
35 }
36 // mods com raizes primitivas: 2, 4, p^k, 2*p^k, p eh
37 // primo impar, k inteiro --- O(n log^2(n))
38 ll achar_raiz(ll mod, ll phi) {
39     if(mod == 2) return 1;
40     vl fat, elementos;
41     fat = fatorar(phi);
42
43     for(ll i = 2; i <= mod-1; i++) {
44         if(raiz_prim(i, mod, phi, fat))
45             return i;
46     }
47
48     return -1; // retorna -1 se nao existe
49 }
50 vl todas_raizes(ll mod, ll phi, ll raiz) {
51     vl raizes;
52     if(raiz == -1) return raizes;
53     ll r = raiz;
54     for(ll i = 1; i <= phi-1; i++) {
55         if(__gcd(i, phi) == 1) {
56             raizes.pb(r);
57         }
58         r = (r * raiz) % mod;
59     }
60 }

```

```

59     }
60
61     return raizes;
62 }

```

## 5.18 Kamenetsky

```

1 // Number of digits in n! O(1)
2
3 #define Pi 3.14159265358979311599796346854
4 #define Eul 2.71828182845904509079559829842
5
6 long long findDigits(int n)
7 {
8     double x;
9
10    if (n < 0)
11        return 0;
12    if (n == 1)
13        return 1;
14
15    x = ((n * log10(n / euler) + log10(2 * Pi * n)
16         / 2.0));
17
18    return floor(x) + 1;
19 }

```

## 6 Misc

### 6.1 2SAT

```

1 vector<int> g[MAX], gt[MAX], S; int vis[MAX], cor[MAX]
2 ];
3
4 int val(int n, bool tvalue) {
5     if(tvalue) return 2*n;
6     return 2*n + 1;
7 }
8
9 void dfs(int u) {
10    vis[u] = 1; for(int v : g[u]) if(!vis[v]) dfs(v);
11    S.push_back(u);
12 }
13
14 void dfst(int u, int e) {
15     cor[u] = e;
16     for(int v : gt[u]) if(!cor[v]) dfst(v, e);
17 }
18
19 void kosaraju(int n) {
20     for(int i = 0; i <= n; i++) if(!vis[i]) dfs(i);
21     for(int i = 0; i <= n; i++) for(int j : g[i])
22         gt[j].push_back(i);
23     int e = 0; reverse(S.begin(), S.end());
24     for(int u : S) if(!cor[u]) dfst(u, ++e);
25 }
26
27 // antes de chamar essa funcao, colocar as arestas do
28 // grafo
29 bool solve(int n, vi &res) {
30     kosaraju(2*n); // MAX > 2*N
31     vi r;
32
33     forn(i, n) {
34         int t = val(i, true), f = val(i, false);
35         if(cor[t] == cor[f]) {
36             return false;
37         }
38         else {
39             if(cor[t] > cor[f])
40                 r.pb(1);
41         }
42     }
43 }

```

```

39         else
40             r.pb(0);
41     }
42 }
43 swap(r, res);
44 return true;
45 }

```

## 6.2 LIS

```

1 multiset<int> S;
2 for(int i = 0; i < n; i++){
3     auto it = S.upper_bound(vet[i]); // low for inc
4     if(it != S.end())
5         S.erase(it);
6     S.insert(vet[i]);
7 }
8 // size of the lis
9 int ans = S.size();

```

## 6.3 Bitwise

```

1 // Bitwise
2 #pragma GCC target("popcnt")
3 unsigned char a = 5, b = 9; // a = (00000101), b
4 = (00001001)
5
6 AND -          a&b    // The result is 00000001
7 (1)
8 OR -           a|b    // The result is 00001101
9 (13)
10 XOR -          a^b    // The result is 00001100
11 (12)
12 NOT -          ~a     // The result is 11111010
13 (250)
14 Left shift -   b<<1   // The result is 00010010
15 (18)
16 Right shift -  b>>1   // The result is 00000100
17 (4)
18
19 // Exchange two int variables
20
21     a^=b;
22     b^=a;
23     a^=b;
24
25 // Even or Odd
26
27     (x & 1)? printf("Odd"): printf("Even");
28
29 // Turn on the j-th bit
30
31     int S = 34; //(100010)
32     int j = 3;
33
34     S = S | (1<<j);
35
36 // Turn off the j-th bit
37
38     int S = 42; //(101010)
39     int j = 1;
40
41     S &= ~(1<<j)
42
43     S == 40 //(101000)
44
45 // Check the j-th element
46
47     int S = 42; //(101010)
48     int j = 3;
49
50     T = S & (1<<j); // T = 0

```

```

44
45 // Least significant bit (lsb)
46
47     int lsb(int x){ return x&-x; }
48
49 // Exchange o j-th element
50
51     S ^= (1<<j)
52
53 // Position of the first bit on
54
55     T = (S & (-S))
56     T -> 4 bit ligado //(1000)
57
58 // Most significant digit of N
59
60     double K = log10(N);
61     K = K - floor(K);
62     int X = pow(10, K);
63
64 // Number of digits in N
65
66     X =floor(log10(N)) + 1;
67
68 // Power of two
69
70     bool isPowerOfTwo(int x){ return x && (!(x&(x
71 -1))); }
72
73 // Turn off the first bit 1
74     m = m & (m-1);
75
76 // Built-in functions
77
78 // Number of bits 1
79 __builtin_popcount()
80 __builtin_popcountll()
81
82 // Number of leading zeros
83 __builtin_clz()
84 __builtin_clzll()
85
86 // Number of trailing zeros
87 __builtin_ctz()
88 __builtin_ctzll()
89
90 // floor(log2(x))
91
92     int flog2(int x){ return 32-1-__builtin_clz(x
93 ); }
94
95     int flog2ll(ll x){ return 64-1-
96 __builtin_clzll(x); }

```

## 6.4 Template

```

1 #include <bits/stdc++.h>
2 #define ff first
3 #define ss second
4 #define ll long long
5 #define ld long double
6 #define pb push_back
7 #define eb emplace_back
8 #define mp make_pair
9 #define mt make_tuple
10 #define pii pair<int, int>
11 #define vi vector<int>
12 #define sws ios_base::sync_with_stdio(false);cin.tie(
13 NULL)
14 #define endl '\n'
15 #define teto(a, b) (a+b-1)/(b)
16
17 const int MAX = 400010;

```

```

17 const int MOD = 1e9+7;
18 const int INF = 0x3f3f3f3f;
19 const ll LLINF = 0x3f3f3f3f3f3f3f3f;
20 const ld EPS = 1e-7;
21
22 using namespace std;

```

## 7 Strings

### 7.1 Trie

```

1 int trie[MAX][26];
2 bool finish[MAX];
3 int nxt = 1;
4
5 void Add(string &str){
6     int node = 0;
7     for(auto s: str){
8         if(trie[node][s-'a'] == 0){
9             node = trie[node][s-'a'] = nxt;
10            nxt++;
11        }else
12            node = trie[node][s-'a'];
13    }
14    finish[node] = true;
15 }
16
17 bool Find(string &str){
18     int idx = 0;
19     for(auto s: str)
20         if(trie[idx][s-'a'] == 0)
21             return false;
22         else
23             idx = trie[idx][s-'a'];
24     return finish[idx];
25 }

```

### 7.2 KMP

```

1 vector<int> prefix_function(const string &s){
2     int n = s.size(); vector<int> b(n+1);
3     b[0] = -1; int i = 0, j = -1;
4     while(i < n){
5         while(j >= 0 && s[i] != s[j]) j = b[j];
6         b[++i] = ++j;
7     }
8     return b;
9 }
10
11 void kmp(const string &t, const string &p){
12     vector<int> b = prefix_function(p);
13     int n = t.size(), m = p.size();
14     int j = 0;
15     for(int i = 0; i < n; i++){
16         while(j >= 0 && t[i] != p[j]) j = b[j];
17         j++;
18         if(j == m) {
19             j = b[j];
20         }
21     }
22 }

```

### 7.3 LCS

```

1 string LCSSubStr(string X, string Y)
2 {
3     int m = X.size();
4     int n = Y.size();
5
6     int result = 0, end;
7     int len[2][n];

```

```

8     int currRow = 0;
9
10    for(int i=0; i<=m; i++){
11        for(int j=0; j<=n; j++){
12            if(i==0 || j==0)
13                len[currRow][j] = 0;
14            else if(X[i-1] == Y[j-1]){
15                len[currRow][j] = len[1-currRow][j-1]
16                + 1;
17                if(len[currRow][j] > result){
18                    result = len[currRow][j];
19                    end = i - 1;
20                }
21            }else
22                len[currRow][j] = 0;
23        }
24        currRow = 1 - currRow;
25    }
26
27    if(result==0)
28        return string();
29
30    return X.substr(end - result + 1, result);
31 }
32 }

```

### 7.4 Pal-int

```

1 bool ehpalindromo(ll n) {
2     if(n<0)
3         return false;
4
5     int divisor = 1;
6     while(n/divisor >= 10)
7         divisor *= 10;
8
9     while(n != 0) {
10        int leading = n / divisor;
11        int trailing = n % 10;
12
13        if(leading != trailing)
14            return false;
15
16        n = (n % divisor)/10;
17
18        divisor = divisor/100;
19    }
20
21    return true;
22 }

```

### 7.5 Z-Func

```

1 vector<int> z_algo(const string &s)
2 {
3     int n = s.size();
4     int L = 0, R = 0;
5     vector<int> z(n, 0);
6     for(int i = 1; i < n; i++){
7         {
8             if(i <= R)
9                 z[i] = min(z[i-L], R - i + 1);
10            while(z[i]+i < n && s[z[i]+i] == s[i+z[i]])
11                z[i]++;
12            if(i+z[i]-1 > R)
13                {
14                    L = i;
15                    R = i + z[i] - 1;
16                }
17        }
18    }
19    return z;
20 }

```

## 7.6 Hash

```
1 ll compute_hash(string const& s) {
2     const ll p = 31; // primo, melhor = perto da
      quantidade de caracteres
3     const ll m = 1e9 + 9; // maior mod = menor
      probabilidade de colisao
4     ll hash_value = 0;
5     ll p_pow = 1;
6     for (char c : s) {
7         hash_value = (hash_value + (c - 'a' + 1) *
      p_pow) % m;
8         p_pow = (p_pow * p) % m;
9     }
10    return hash_value;
11 }
```

## 7.7 Manacher

```
1 // O(n), d1 -> palindromo impar, d2 -> palindromo par
      (centro da direita)
2 void manacher(string &s, vi &d1, vi &d2) {
3     int n = s.size();
4     for(int i = 0, l = 0, r = -1; i < n; i++) {
5         int k = (i > r) ? 1 : min(d1[l + r - i], r -
      i + 1);
```

```
6         while(0 <= i - k && i + k < n && s[i - k] ==
      s[i + k]) {
7             k++;
8         }
9         d1[i] = k--;
10        if(i + k > r) {
11            l = i - k;
12            r = i + k;
13        }
14    }
15
16    for(int i = 0, l = 0, r = -1; i < n; i++) {
17        int k = (i > r) ? 0 : min(d2[l + r - i + 1],
      r - i + 1);
18        while(0 <= i - k - 1 && i + k < n && s[i - k
      - 1] == s[i + k]) {
19            k++;
20        }
21        d2[i] = k--;
22        if(i + k > r) {
23            l = i - k - 1;
24            r = i + k ;
25        }
26    }
27 }
```