

LetsDefend

Official Write Up

Event ID: 101

Rule Name: SOC153 - Suspicious Powershell Script Executed

LetsDefend	1
Official Write Up	1
Event ID: 101	1
Rule Name: SOC153 - Suspicious Powershell Script Executed	1
ALERT	3
DETECTION	4
ANALYSIS	6
Initial Access	6
Execution	9
Exfiltration	26
CONTAINMENT	30
ERADICATION	31
LESSON LEARNED	32
APPENDIX	33
MITRE	33
Cyber Kill Chain	34
Artifacts	35

ALERT

High

Sept. 5, 2021, 12:43 p.m.

★ SOC153 - Suspicious Powershell Script Executed

101

Malware

★ This alert was generated from a real cyber attack.

EventID:

101

Event Time:

Sept. 5, 2021, 12:43 p.m.

Rule:

SOC153 - Suspicious Powershell Script Executed

Hostname

Matt

IP Address

172.31.34.35

EDR Action

Allowed

File Path

C://Users//Public//Documents//endpoint.ps1

Username

Administrator

L1 Note

When I tried to decode the Powershell script on base64decode.org, it said it was Cobalt Strike.

Download (Password:infected):

b9a7a76320ebfc19ae65c56c45f311e.rar

When Tier 1 analyst investigated the powershell script named “endpoint.ps1”, he/she saw that powershell commands are encoded and he/she uploaded the encoded commands to base64decode.org website. When the analyst tried to decode the commands he determined that decoded code belongs to Cobalt Strike.

< DECODE >

Number System

TV Show and Movie

Success!

CLICK OR TAP HERE

Please note that this

decoded-20210916174943.txt - Notepad

File Edit Format View Help

BLOCKED! The Base64 decoded data contains the following harmful code: Win.Trojan.CobaltStrike-7917400-0

About

Meet Base64 Decode

and easily. Base64 enc

Base64 encoding sch

transferred over media

transport. Base64 is us

Advanced options

Character set: In c

used during the en

auto-detect option

displayed properly

Ln 1, Col 1

100%

Windows (CRLF)

UTF-8

DETECTION

Verify

Normally alarms that have been escalated from Tier 1 to Tier 2 should be really harmful events. But due to lack of technical knowledge, lack of technical analysis, and authorization problems not all of the escalated alarms are True Positive.

Before starting the Incident Response process we should make sure the escalated event is due to a harmful action.

Initially we should decide whether we need an advanced level analysis by looking into the data included in the details of the alarm.

The screenshot shows a SIEM alert interface. At the top, it says 'High' in red, followed by the time 'Sept. 5, 2021, 12:43 p.m.', a star icon, the rule name 'SOC153 - Suspicious Powershell Script Executed', the event ID '101', and the category 'Malware'. Below this, a message states: '★ This alert was generated from a real cyber attack.' The main body of the alert lists the following details: EventID: 101, Event Time: Sept. 5, 2021, 12:43 p.m., Rule: SOC153 - Suspicious Powershell Script Executed, Hostname: Matt, IP Address: 172.31.34.35, EDR Action: Allowed, CommandLine: powershell.exe endpoint.ps1, File Path: C://Users//Public//Documents//endpoint.ps1, Username: Administrator, L1 Note: When I tried to decode the Powershell script on base64decode.org, it said it was Cobalt Strike. Download (Password:infected): b9a7a76320ebefc19ae65c56c45f311e.rar

When we look into the Command Line parameters we see that a Powershell script named “endpoint.ps1” has been run. Since there is not any other Command Line parameter related to the process we cannot make any assumptions without looking into the script.

Download (Password:infected): b9a7a76320ebefc19ae65c56c45f311e.rar

We should start the analysis by downloading the Powershell script named “endpoints.ps1” through SIEM by clicking the “Download” button. (To keep your device safe and uninfected you should investigate the files in an isolated environment. Because the alarms on the LetsDefend are from real life incidents, and malwares are real malicious softwares.)

```
1 $s=New-Object IO.MemoryStream(,[Convert]::FromBase64String("H4sIAAAAAAAAAOy9W6/ySLIq+tz9K+phSlUlaJcGgzEjbnA3GxsGzEXQ0+rBTYYG7DxDZOeM//9REQa1
2 IEX (New-Object IO.StreamReader(New-Object IO.Compression.GzipStream($s,[IO.Compression.CompressionMode]::Decompress))).ReadToEnd();
```

When we open the Powershell script named “endpoint.ps1” on a text editor we can access the commands within it. In the script we see that a string encoded with Base64 is decoded and assigned to a variable named “\$s”. Later on, the decoded string is decompressed (meaning unzipped) and commands are run.

Base64 decoding and Zip decompression processes increase the probability of the script being malicious since those are not behaviors of a legitimate application.

We need to access the Powershell commands in order to analyse it deeper. First base64 decoding and then Zip decompression steps will allow us to access the malicious commands. To automate the process you can use the following Python script.

```
import io
import gzip
import base64
data = io.BytesIO(base64.b64decode("[REDACTED]"))
fout = gzip.GzipFile(fileobj=data)
print(fout.read())
```

After the decoding process we can confirm the file named "endpoints.ps1" is malicious.

Since we confirm the escalated alarm and it is a harmful Powershell script that has been run on a machine we should start the Incident Response process.

ANALYSIS

Initial Access

It has been confirmed that a harmful Powershell script has been run on a device named "Matt". Detection of the attacker's initial access to the system is necessary.

The root cause detection is the most important step of the Incident Response. The root cause of initial access needs to be determined quickly and "open door" must be closed.

The attacker could have established the initial access by phishing or a service that is open to the internet. Correctly identifying the root cause of initial access depends on determining how the device is being used and to what purpose it has been used.

Initially the services that are open to the internet should be determined. A tool called Netstat can be used to determine the listening ports and names of the services belonging to those ports can be learned.

```
C:\Windows\system32>netstat -ano | find /i "listening"
TCP    0.0.0.0:81          0.0.0.0:*        LISTENING      4024
TCP    0.0.0.0:135        0.0.0.0:*        LISTENING      540
TCP    0.0.0.0:433        0.0.0.0:*        LISTENING      3720
TCP    0.0.0.0:443        0.0.0.0:*        LISTENING      4024
TCP    0.0.0.0:445        0.0.0.0:*        LISTENING      4
TCP    0.0.0.0:3389       0.0.0.0:*        LISTENING      1048
TCP    0.0.0.0:5900       0.0.0.0:*        LISTENING      2832
TCP    0.0.0.0:5985       0.0.0.0:*        LISTENING      4
TCP    0.0.0.0:47001      0.0.0.0:*        LISTENING      4
TCP    0.0.0.0:49664      0.0.0.0:*        LISTENING      660
TCP    0.0.0.0:49665      0.0.0.0:*        LISTENING      1304
TCP    0.0.0.0:49666      0.0.0.0:*        LISTENING      1560
TCP    0.0.0.0:49667      0.0.0.0:*        LISTENING      2412
TCP    0.0.0.0:49668      0.0.0.0:*        LISTENING      2548
TCP    0.0.0.0:49671      0.0.0.0:*        LISTENING      2336
TCP    0.0.0.0:49672      0.0.0.0:*        LISTENING      804
TCP    0.0.0.0:49687      0.0.0.0:*        LISTENING      824
TCP    172.31.34.35:139   0.0.0.0:*        LISTENING      4
TCP    [::]:135          [::]:*          LISTENING      540
TCP    [::]:433          [::]:*          LISTENING      3720
TCP    [::]:445          [::]:*          LISTENING      4
TCP    [::]:3389         [::]:*          LISTENING      1048
TCP    [::]:5985         [::]:*          LISTENING      4
TCP    [::]:47001        [::]:*          LISTENING      4
TCP    [::]:49664        [::]:*          LISTENING      660
TCP    [::]:49665        [::]:*          LISTENING      1304
TCP    [::]:49666        [::]:*          LISTENING      1560
TCP    [::]:49667        [::]:*          LISTENING      2412
```

According to the Netstat command it could be seen that the device does not have any services (like Web, Email, FTP) open other than standard Windows operating system services.

It could be seen that port 3369 is open to the internet. This port is used as the RDP (remote desktop protocol) port by default Windows OS settings. By RDP protocol users can access and control the Windows machines through graphical user interface.

As System Admins know, there are many attackers on the internet scanning the 22 (SSH) and 3389 (RDP) ports. Attackers use “brute force” techniques on authorized accounts through mentioned services that come with operating systems’ default settings.


Since RDP service is open, it would be the correct approach to check the RDP log events first to determine the attackers initial access.

If the logs are not deleted by the attacker, we can determine the successful/unsuccessful login attempts from the log sources below:

- Windows Security Logs
- Microsoft-Windows-Terminal-Services-RemoteConnectionManager
- Microsoft-Windows-TerminalServices-LocalSessionManager
- Sysmon Operational

Going through the details of the alarm on the SIEM, it can be seen that the Powershell script is run by an “Administrator” account. We need to determine whether the administrator account has been the target of brute force attack and whether there is a successful login. Since the Powershell script is run on the date 05.09.2021, we should filter down the logs to the same date to start our investigation so that we would not get lost in the Windows Security Event logs.

When a successful RDP session is created an event ID 21 called “Microsoft-Windows-TerminalServices-LocalSessionManager/Operational” is created. When we look into the event ID 21 on 05.09.2021 we can see that an RDP session is being created with an “Administrator” account from the IP address of 3.16.42.241.




We determined that the attacker had a successful login to the device name “Matt” on the date 05.09.2021 at 12:12 using the IP address of 3.16.42.241. To finalize the root cause analysis, we need to determine how the attacker gets the Administrator password. To date, we still often see brute force attacks on RDP services as initial access methods.

The failed login attempts create a Windows Security event with ID number of 4625. So we should be investigating the events that are created before 12:12 and have the ID number of 4625.

When event ID 4625 is investigated under Windows Security, we can see that there are many records of failed login attempts. Since the RDP is open to the internet, there are many scanners doing brute-force attacks. To determine the root cause clearly, we need to determine whether we had an attack from the IP address of 3.16.42.241.

We can see that there are failed login attempts from the aforementioned IP address. So it has been determined that the attacker got the Administrator password by brute-force attack.



Execution

We have determined the root cause successfully. We should be looking for the attacker's actions on the system.

On the devices that have Sysmon installed, it can be easily determined what actions have been taken by attackers by looking at the event ID number 1 on the Sysmon Operational. But before looking into the ID number 1 Sysmon Operational events, let's start with determining the files that have been written on the file system.

When there is a file written on the file system event with ID number 11 is being created on Sysmon Operational. By using this event ID the files that have been written by the attacker can be determined.

To do so let's filter events by the ID number of 11.

Filter Current Log

Filter XML

Logged: From 9/5/2021 12:00:00 AM to 9/5/2021 11:59:59 PM

Event level: ☐ Critical ☐ Warning ☐ Verbose
☐ Error ☐ Information

☒ By log Event logs: Security

☐ By source Event sources:

Includes/Excludes Event IDs: Enter ID numbers and/or ID ranges separated by commas. To exclude criteria, type a minus sign first. For example 1,3,5-99,-76

11

Task category:

Keywords:

User: <All Users>

Computer(s): <All Computers>


Clear

OK Cancel


When event ID 11 is investigated on the date of the attack, we can see the following files are being written on the file system. To create a successful timeline report, it is important to determine the dates when the files have been written.

Date	File Name
05.09.2021 12:30	new1.bat
05.09.2021 12:32	Advanced_Port_Scanner_2.5.3869.exe
05.09.2021 12:39	nc111nt.zip
05.09.2021 12:43	endpoint.ps1


At 12:30, we can see that a file named "new1.bat" has been written to the file system by Notepad.exe.




At 12:32, a file named Advanced_Port_Scanner_2.5.3869.exe was created by Chrome.



At 12:39, a file named nc111nt.zip was created by Chrome.exe.




At 12:43, a file named endpoints.ps1 was created.



We have determined which files have been created and when they have been created. We can assume that these files are being used by the attacker. But assuming can lead us to a mistake, so we need to determine which processes are being executed by the attacker.

From Sysmon Operational events we look into the ones with evenID of 1 to see which processes are created. This will inform us about what the attacker was doing in the system.



We can see that the attacker has run the file named “new1.bat” at 12:31 with cmd.exe that he created at 12:30. The easiest way to understand what purpose does New1.bat serve is to open it in a text editor and read it. But since the file is being deleted from the file system we cannot see the content of the file.

Under these circumstances, to find what the “new1.bat” file does, the best method would be looking into the child processes. To determine the child processes we need to determine the PID number of the parent process which is the process run on cmd.exe as new1.bat. Within the Sysmon evenID number 1 events, we can see the parent process ID is 4360.

After finding the parent process ID number, what needs to be done is to locate those Sysmon Operational events with process ID number 1 that has parent process ID number of. So we can understand the purpose of the new1.bat file.

After investigating the Sysmon Operational events with ID value of 1 and PID value of 4360, we can observe that the new1.bat file collects data on the system. It collects data on applications on the system, list of processes, active internet connections and so on.

Event Viewer

FileActionViewHelp

SMBClient

SMBDirect

SMBServer

SMBWitnessCl

StateRepositor

Storage-Tierin

StorageManag

StorageManag

StorageSpaces

StorageSpaces

StorageSpaces

StorDiag

Store

StorPort

Sysmon

Operationz

SystemDataAn

SystemSetting

TaskScheduler

TCPIP

TerminalServic

TerminalServic

TerminalServic

Admin

Operationz

TerminalServic

TerminalServic

TerminalServic

Time-Service

Time-Service-I

TZSync

Operational

Number of events: 2,443 (!) New events available

Filtered: Log: Microsoft-Windows-Sysmon/Operational; Source: ; Event ID: 1. Number of events: 637

Level	Date and Time	Source	Event ID	Task Category
Information	9/5/2021 12:31:47 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:50 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:50 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:50 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:50 PM	Sysmon	1	Process Creat...

Event 1, Sysmon

General

Details

CommandLine: netstat -an
CurrentDirectory: C:\Users\Public\Documents\
User: EC2AMAZ-ILGVOIN\Administrator
LogonGuid: {a584806d-b41f-6134-88cd-760000000000}
LogonId: 0x76CD88
TerminalSessionId: 2
IntegrityLevel: High
Hashes: MD5=9244576DD106438CEABE63EC36950E6,SHA256=
9372044B501FEFAE7333A59624379DBFC7E4ECCBEA965EE7058F2583709C2287,IMPHASH=F495C58FFEE
3A623AD7AAA6BE78756D5
ParentProcessGuid: {a584806d-b887-6134-9502-000000005101}
ParentProcessId: 4360

Log Name:

Microsoft-Windows-Sysmon/Operational

Source:

Sysmon

Logged:

9/5/2021 12:31:50 PM

Event ID:

1

Task Category:

Process Create (rule: ProcessCreate)

Level:

Information

Keywords:

User:

SYSTEM

Computer:

EC2AMAZ-ILGVOIN

OpCode:

Info

More Information:

Event Log Online Help

Actions

Operational

Open Saved Log...

Create Custom View...

Import Custom View...

Clear Log...

Filter Current Log...

Clear Filter

Properties

Disable Log

Find...

Save Filtered Log File A...

Attach a Task To this L...

Save Filter to Custom ...

View

Refresh

Help

Event 1, Sysmon

Event Properties


Attach Task To This Ev...

Save Selected Events...

Copy

Refresh

Help



Additionally, it has been observed that several domain names have been searched within the file system. Users keep their passwords on a txt file so that they would not forget them. So by searching domain names, the attacker expects to find such a document to further expand his/her exploits.

Event Viewer

File Action View Help

SMBClient

SMBDirect

SMBServer

SMBWitnessCl

StateRepositor

Storage-Tierin

StorageManag

StorageSpaces

StorageSpaces

StorageSpaces

StorageSpaces

StorageSpaces

StorDiag

Store

StorPort

Sysmon

Operations

SystemDataAn

SystemSetting

TaskScheduler

TCPIP

TerminalServic

TerminalServic

TerminalServic

TerminalServic

TerminalServic

Time-Service

Time-Service-I

TZSync

Operational Number of events: 2,443 (1) New events available

Filtered: Log: Microsoft-Windows-Sysmon/Operational; Source: ; Event ID: 1. Number of events: 637

Level	Date and Time	Source	Event ID	Task Category
Information	9/5/2021 12:31:52 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:52 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:52 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:53 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:53 PM	Sysmon	1	Process Creat...

Event 1, Sysmon

General Details

Process Create:

RuleName: -

UtcTime: 2021-09-05 12:31:53.008

ProcessGuid: {a584806d-b8b9-6134-f202-000000005101}

ProcessId: 6688

Image: C:\Windows\System32\findstr.exe

FileVersion: 10.0.17763.1 (WinBuild.160101.0800)

Description: Find String (QGREP) Utility

Product: Microsoft® Windows® Operating System

Company: Microsoft Corporation

OriginalFileName: FINDSTR.EXE

CommandLine: findstr /m cookie.check.oavpal.com *

Log Name: Microsoft-Windows-Sysmon/Operational

Source: Sysmon

Logged: 9/5/2021 12:31:53 PM

Event ID: 1

Task Category: Process Create (rule: ProcessCreate)

Level: Information

Keywords:

User: SYSTEM

Computer: EC2AMAZ-ILGVOIN

OpCode: Info

More Information: [Event Log Online Help](#)

Actions

Operational

Open Saved Log...

Create Custom View...

Import Custom View...

Clear Log...

Filter Current Log...

Clear Filter

Properties

Disable Log

Find...

Save Filtered Log File A...

Attach a Task To this L...

Save Filter to Custom ...

View

Refresh

Help

Event 1, Sysmon

Event Properties

Attach Task To This Ev...

Save Selected Events...

Copy

Refresh

Help

Creates a filter.

Event Viewer

File Action View Help

Operational Number of events: 2,443 (!) New events available

Filtered Log: Microsoft-Windows-Sysmon/Operational; Source: ; Event ID: 1. Number of events: 637

Level	Date and Time	Source	Event ID	Task Category
Information	9/5/2021 12:31:52 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:52 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:52 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:52 PM	Sysmon	1	Process Creat...
Information	9/5/2021 12:31:52 PM	Sysmon	1	Process Creat...

Event 1, Sysmon

General Details

ProcessGuid: {a584806d-b8b8-6134-e202-000000005101}
ProcessId: 4396
Image: C:\Windows\System32\findstr.exe
FileVersion: 10.0.17763.1 (WinBuild.160101.0800)
Description: Find String (QGREP) Utility
Product: Microsoft® Windows® Operating System
Company: Microsoft Corporation
OriginalFileName: FINDSTR.EXE
CommandLine: findstr /m coinbase.com *
CurrentDirectory: C:\Users\Public\Documents\
User: EC2AMAZ-ILGVOIN\Administrator
ProcessGuid: {a584806d-b8b8-6134-e202-000000005101}

Log Name: Microsoft-Windows-Sysmon/Operational
Source: Sysmon
Event ID: 1
Level: Information
User: SYSTEM
OpCode: Info
Task Category: Process Create (rule: ProcessCreate)
Keywords:
Computer: EC2AMAZ-ILGVOIN
More Information: [Event Log Online Help](#)


Actions

Operational


- Open Saved Log...
- Create Custom View...
- Import Custom View...
- Clear Log...
- Filter Current Log...
- Clear Filter
- Properties
- Disable Log
- Find...
- Save Filtered Log File A...
- Attach a Task To this L...
- Save Filter to Custom ...
- View
- Refresh
- Help

Event 1, Sysmon

- Event Properties
- Attach Task To this Ev...
- Save Selected Events...
- Copy
- Refresh
- Help



It has been determined that the attacker executed the “Advanced_Port_Scanner_2.5.3869.exe” file at 12:32 which is written to the file system at 12:32.



Sysmon Operation event ID 3 is dedicated for the port scanning activities. We can identify the scanning activity by using event ID number 3.

Event Viewer

FileActionViewHelp

<>🔍📄🔧🔗🔗

>Volume

>VolumeSnapsh

>Vpn Plugin Pla

>VPN-Client

>Wcmsvc

>WebAuth

>WebAuthN

>WebIO

>WEPHOSTSVC

>WER-PayloadH

>WFP

>Win32k

>Windows Defe

>Windows Firew

>Windows Rem

>WindowsColor

>WindowsSyste

>WindowsUllm

>WindowsUpda

>WinHttp

>WinINet

>WinINet (Micr

>Winlogon

>WinNat

>Winsock Catal

>Winsock Nam

>Winsock Netw

>Wired-AutoCo

>WMI-Activity

>WMPNSS-Serv

>Wordpad

>Workplace Joi

>WPD-ClassInst

>WPD-Compos

Operational

Number of events: 2,474 (!) New events available

Filtered: Log: Microsoft-Windows-Sysmon/Operational; Source: ; Event ID: 3. Number of events: 972

Level	Date and Time	Source	Event ID	Task Category
Information	9/5/2021 12:34:01 PM	Sysmon	3	Network conn...
Information	9/5/2021 12:34:01 PM	Sysmon	3	Network conn...
Information	9/5/2021 12:34:01 PM	Sysmon	3	Network conn...
Information	9/5/2021 12:34:01 PM	Sysmon	3	Network conn...
Information	9/5/2021 12:34:01 PM	Sysmon	3	Network conn...

Event 3, Sysmon

GeneralDetails

Protocol: tcp

Initiated: true

SourceIspv6: false

SourceIp: 172.31.17.135

SourceHostname: EC2AMAZ-ILGVOIN.us-east-2.compute.internal

SourcePort: 50758

SourcePortName: -

DestinationIspv6: false

DestinationIp: 172.31.17.135

DestinationHostname: EC2AMAZ-ILGVOIN.us-east-2.compute.internal

DestinationPort: 139

DestinationPortName: netbios-ssn

Log Name: Microsoft-Windows-Sysmon/Operational

Source: Sysmon

Event ID: 3

Level: Information

User: SYSTEM

OpCode: Info

More Information: [Event Log Online Help](#)

Logged: 9/5/2021 12:34:01 PM

Task Category: Network connection detected (rule: Netw

Keywords:

Computer: EC2AMAZ-ILGVOIN

Actions

Operational

Open Saved Log...

Create Custom View...

Import Custom View...

Clear Log...

Filter Current Log...

Clear Filter

Properties

Disable Log

Find...

Save Filtered Log File A...

Attach a Task To this L...

Save Filter to Custom ...

View

Refresh

Help

Event 3, Sysmon

Event Properties

Attach Task To this Ev...

Save Selected Events...

Copy

Refresh

Help

Event Viewer

File Action View Help

Volume
VolumeSnapsh
Vpn Plugin Pla
VPN-Client
Wcmsvc
WebAuth
WebAuthN
WebIO
WEPHOSTSVC
WER-PayloadH
WFP
Win32k
Windows Defe
Windows Firew
Windows Rem
WindowsColoi
WindowsSyste
WindowsUlm
WindowsUpda
WinHttp
WinINet
WinINet (Micr
Winlogon
WinNat
Winsock Catal
Winsock Nam
Winsock Netw
Wired-AutoCo
WMI-Activity
WMPNSS-Serv
Wordpad
Workplace Joi
WPD-ClassInst
WPD-Compos

Operational Number of events: 2,474 (!) New events available

Filtered: Log: Microsoft-Windows-Sysmon/Operational; Source: ; Event ID: 3. Number of events: 972

Level	Date and Time	Source	Event ID	Task Category
Information	9/5/2021 12:34:01 PM	Sysmon	3	Network conn...
Information	9/5/2021 12:34:01 PM	Sysmon	3	Network conn...
Information	9/5/2021 12:34:01 PM	Sysmon	3	Network conn...
Information	9/5/2021 12:34:01 PM	Sysmon	3	Network conn...
Information	9/5/2021 12:34:01 PM	Sysmon	3	Network conn...

Event 3, Sysmon

General Details

Protocol: tcp
Initiated: true
SourceIsIpv6: false
SourceIp: 172.31.17.135
SourceHostname: EC2AMAZ-ILGVOIN.us-east-2.compute.internal
SourcePort: 50754
SourcePortName: -
DestinationIsIpv6: false
DestinationIp: 172.31.17.135
DestinationHostname: EC2AMAZ-ILGVOIN.us-east-2.compute.internal
DestinationPort: 135
DestinationPortName: epmap

Log Name: Microsoft-Windows-Sysmon/Operational
Source: Sysmon Logged: 9/5/2021 12:34:01 PM
Event ID: 3 Task Category: Network connection detected (rule: Netw
Level: Information Keywords:
User: SYSTEM Computer: EC2AMAZ-ILGVOIN
OpCode: Info
More Information: [Event Log Online Help](#)

Actions


Operational

- Open Saved Log...
- Create Custom View...
- Import Custom View...
- Clear Log...
- Filter Current Log...
- Clear Filter
- Properties
- Disable Log
- Find...
- Save Filtered Log File A...
- Attach a Task To this L...
- Save Filter to Custom ...
- View
- Refresh
- Help

Event 3, Sysmon

- Event Properties
- Attach Task To This Ev...
- Save Selected Events...
- Copy
- Refresh
- Help


Creates a filter.



Events with ID 3 show helps us to identify that the attacker scanned the ports in the internal network. So the attacker is scanning the ports so that he can make a lateral movement and expands his exploits to the other systems.

When other Sysmon Operational events with ID 1 are investigated, it can be observed that the attacker has run the Powershell script named “endpoints.ps1” at 12:43.

“endpoint.ps1” file triggered a rule on SIEM solution.




Up to this point, we know the root cause of the initial access, when and how the attacker accessed the system, and the purpose of the attack.

Exfiltration

There are multiple purposes behind cyber threat actors' hijacking of systems. Some threat actors want to steal the information on the system, some want to gain reputation by sharing the system on the Internet, and some want to make the systems unusable.


In the cyber security incident we reviewed, we observed that the attacker used the findstr tool to detect sensitive information after entering the system. We can assume that the cyber threat actor wants to exfiltrate this information after detecting it. For this reason, we need to determine whether there is exfiltration and what information, if any, is exfiltrated by the cyber threat actor.

Cyber threat actors frequently use netcat to upload/download files. During the execution phase, we detected that the cyber threat actor downloaded the "netcat" application through Chrome. In order to determine for what purpose the Netcat application is used, we need to find the netcat application among the Sysmon Operational events with the ID number 1.




It has been determined that the netcat application is run among the Sysmon Operational events with the ID number 1. When the CommandLine parameters of the related process are examined, it is seen that the IP address 3.16.42.144 is connected to port 4444, but not all CommandLine parameters can be displayed.


When Sysmon Operational events with the ID number 3 are examined, it is seen that the attacker has created a successful communication with the IP address of 3.16.42.144 through port number of 4444.



When “Terminal History” of Matt is investigated through “Endpoint Security”, the complete netcat command can be seen. The attacker exfiltrated an SQL file named “user-db-backup.sql”.



Aforementioned file is located under the “Documents” file of the Administrator user.




CONTAINMENT

According to the Incident Response procedure published by NIST, there are 4 stages. These are: Preperation, Detection and Analysis, Containment/Eradication/Recovery and Post Incident Activity.

In order to cut off the attacker's access to the device and prevent the attack from spreading to other devices in the network, the device must be disconnected from the network. During Forensics examinations, the open device should not be turned off and the closed device should not be turned on. For this reason, disconnecting the device from the network is a recommended method to cut off the attacker's access and prevent the attack from spreading.

In order to disconnect the device from the network and isolate the device, a device named "Matt" must be found on the "Endpoint Security" page and the device must be isolated with the "Request Containment" button.

HOSTNAME	IP ADDRESS	OS	CLIENT / SERVER	REQUEST CONTAINMENT
Matt	172.31.34.35	Windows 10	Server	 Host Contained

ERADICATION

- Administrator account password should be changed.
- If it is not necessary, the Administrator account should be removed from the Remote Desktop Users group.
- The files that are downloaded by the attacker should be removed from the file system.

LESSON LEARNED

- If it is not necessary RDP service should not be open to the internet. If it needs to be open, IP limitations should be implemented.
- Use of generic passwords should not be allowed.
- Users that do not need to use the RDP service should be removed from the Remote Desktop Users group.

MITRE

MITRE Tactics	MITRE Techniques
Initial Access	External Remote Services
Initial Access	Valid Accounts
Initial Access	Local Accounts
Execution	Command and Scripting Interpreter
Execution	Software Deployment Tools
Defense Evasion	Indicator Removal on Host
Exfiltration	Exfiltration Over Alternative Protocol

Cyber Kill Chain

Cyber Kill Chain Steps	Technique used in the attack
Reconnaissance	Port Scanning
Weaponization	
Delivery	Via RDP Service
Exploitation	Brute force
Installation	Cobalt Strike
Command and Control	
Action on Objectives	Exfiltration DB backup

Artifacts

Field	Value
IP Address	3.16.42.241
File Name	endpoint.ps1
File Name	new1.bat
File Name	Advanced_Port_Scanner_2.5.3869.exe
File Name	nc111nt.zip