Connect PHX-DAQ 24 to your system

Standard Ethernet and Modbus TCP: read strain, load and temperature into a PLC, SCADA, HMI, NI LabVIEW or your own software, without extra hardware or proprietary drivers.

Sensors
strain · load · pressure · NTC

→

PHX-DAQ 24
24-bit · 100 Hz

→

Ethernet
Modbus TCP · stream

→

Your system
PLC · SCADA · LabVIEW · PC

THREE WAYS IN

PHX-SENSE STUDIO

SETUP · MONITORING · RECORDING

- Finds every module on the network
- Live plots, readouts, calibration and tare
- CSV recording of many modules at once
- Shows "OPEN" on a channel with no sensor
- Firmware updates over the network

PLC · SCADA · HMI

MODBUS TCP

- Any standard Modbus TCP client
- Averaged values in mV/V, ready to scale in the PLC
- Temperatures in °C
- Status word: data fresh, overload, sensor open
- Up to 4 polling clients per module

NI LABVIEW

PHX-DAQ LABVIEW TOOLKIT

- Find Modules VI
- Live Monitor VI: mV/V, temperatures, chart
- Data Logger VI: every sample to CSV
- .NET driver for your own VIs
- Runs alongside PHX-Sense Studio

AT A GLANCE

Protocol	Modbus TCP over Ethernet 10/100, standard port 502. Factory IP 192.168.10.10; DHCP or static set in PHX-Sense Studio
Values per channel	Averaged mV/V (32-bit float), raw converter code, gain; plus 4 temperatures and a status word
Averaging	1 to 100 samples, set in PHX-Sense Studio. The default (10 samples at 100 Hz) removes 50 and 60 Hz mains pick-up
Update rate	Values refresh 100 times per second; poll as often as your system needs (100 ms to 1 s typical)
Full-rate data	Continuous TCP stream of every sample, for up to 3 receivers at once (PHX-Sense Studio, LabVIEW logger, custom software)
Simultaneous use	PLCs, LabVIEW and PHX-Sense Studio can all read the same module at the same time
Settings	Changed only from PHX-Sense Studio with the site access key, or reset on site with the on-board button; a PLC can read but never change a running unit
Tested with	Generic Modbus TCP clients, QModMaster and NI LabVIEW

WHAT YOU RECEIVE

- PHX-Sense Studio for Windows 10 / 11, with every unit
- **Modbus integration guide**: register map, data formats and scaling to load, strain and pressure
- **PHX-DAQ LabVIEW toolkit**: VIs, driver and documentation
- Help with your specific PLC or SCADA package

The integration guide and LabVIEW toolkit are provided to customers and integration partners on request. Contact us with your PLC or SCADA make and we will help you connect.

PHOENIXTEK SOLUTIONS

Request the integration guide, a demo or a pilot deployment

www.phoenixtek.in
info@phoenixtek.in

LabVIEW is a trademark of National Instruments. Integration overview, October 2026.