

FastAPI (0.1.0)

Download OpenAPI specification: [Download](#)

Players

Get Players

Retrieves all players in the database.

Parameters:

- db (Session): Database session.

Returns:

- List[Player]: All player records.

Example Request: GET /players

Example Response: [{"id": 1, "name": "Erling Haaland", "team_id": 3}, {"id": 2, "name": "Kevin De Bruyne", "team_id": 3}]

Responses

> **200** Successful Response

GET /players/

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "name": "string",
    "age": 0,
    "position": "string",
    "team_id": 0,
    "id": 0
  }
]
```

Create Player

Creates a new player and assigns them to an existing team.

Parameters:

- player (PlayerCreate): Player data including name and team_id.
- db (Session): Database session.

Returns:

- Player: The newly created player record.

Example Request: POST /players { "name": "Bukayo Saka", "team_id": 1 }

Example Response: { "id": 12, "name": "Bukayo Saka", "team_id": 1 }

REQUEST BODY SCHEMA: application/json
required

name required	string (Name)
age required	integer (Age)
position required	string (Position)
team_id required	integer (Team Id)

Responses

> 200 Successful Response

> 422 Validation Error

POST /players/

Request samples

Payload

Content type
application/json

Copy

```
{
  "name": "string",
  "age": 0,
  "position": "string",
  "team_id": 0
}
```

Response samples

200

422

Content type
application/json

Copy

```
{
  "name": "string",
  "age": 0,
  "position": "string",
  "team_id": 0,
  "id": 0
}
```

Get Player

Retrieves a single player by their ID.

Parameters:

- `player_id` (int): Unique player identifier.
- `db` (Session): Database session.

Returns:

- `Player`: Player record matching the ID.

Example Request: GET `/players/5`

Example Response: `{ "id": 5, "name": "Martin Ødegaard", "team_id": 1 }`

PATH PARAMETERS

<code>player_id</code> <i>required</i>	integer (Player Id)
---	---------------------

Responses

> **200** Successful Response

> **422** Validation Error

GET `/players/{player_id}`

Response samples

200

422

Content type
application/json

```
{  
  "name": "string",  
  "age": 0,  
}
```

Copy

```
"position": "string",  
"team_id": 0,  
"id": 0  
}
```

Get Players By Name

Searches for players whose names contain the given text.

Parameters:

- name (str): Partial or full player name to search for.
- db (Session): Database session.

Returns:

- List[Player]: Players whose names match the search query.

Example Request: GET /players/by-name/harry

Example Response: [{"id": 7, "name": "Harry Kane", "team_id": 2}]

PATH PARAMETERS

name	string (Name)
required	

Responses

> **200** Successful Response

> **422** Validation Error

GET /players/by-name/{name}

Response samples

200

422

Content type

application/json

Copy

Expand all

Collapse all

```
[
  - {
    "name": "string",
    "age": 0,
    "position": "string",
    "team_id": 0,
    "id": 0
  }
]
```

Teams

Get Teams

Retrieves all teams in the database.

Parameters:

- db (Session): Database session.

Returns:

- List[Team]: All team records.

Example Request: GET /teams

Example Response: [{"id": 1, "name": "Arsenal"}, {"id": 2, "name": "Chelsea"}]

Responses

> **200** Successful Response

GET /teams/

Response samples

200

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "name": "string",
    "league": "string",
    "id": 0
  }
]
```

Create Team

Creates a new team and stores it in the database.

Parameters:

- team (TeamCreate): Team data including name.
- db (Session): Database session.

Returns:

- Team: The newly created team record.

Example Request: POST /teams { "name": "Arsenal" }

Example Response: { "id": 1, "name": "Arsenal" }

REQUEST BODY SCHEMA: application/json
required

name required	string (Name)
league >	League (string) or League (null) (League)

Responses

> 200 Successful Response

> 422 Validation Error

POST /teams/

Request samples

Payload

Content type
application/json

Copy

```
{
  "name": "string",
  "league": "string"
}
```

Response samples

200

422

Content type
application/json

Copy

```
{
  "name": "string",
  "league": "string",
  "id": 0
}
```

Get Team

Retrieves a single team by its ID.

Parameters:

- `team_id` (int): Unique team identifier.
- `db` (Session): Database session.

Returns:

- Team: Team record matching the ID.

Example Request: GET /teams/2

Example Response: { "id": 2, "name": "Chelsea" }

PATH PARAMETERS

<code>team_id</code> <i>required</i>	integer (Team Id)
---	-------------------

Responses

> **200** Successful Response

> **422** Validation Error

GET /teams/{team_id}

Response samples

200

422

Content type

application/json

Copy

```
{
  "name": "string",
  "league": "string",
  "id": 0
}
```

Performances

Create Performance

Creates a new performance record for a player in a specific match.

Parameters:

- perf (PerformanceCreate): Performance details including player_id, match_id, goals, assists, minutes, etc.
- db (Session): Database session.

Returns:

- Performance: The newly created performance record.

Example Request: POST /performances { "player_id": 12, "match_id": 5, "minutes": 90, "goals": 1, "assists": 0, "shots": 3, "shots_on_target": 2, "tackles_won": 1, "crosses": 4, "fouls": 1, "yellow_cards": 0, "red_cards": 0 }

Example Response: { "id": 44, "player_id": 12, "match_id": 5, "minutes": 90, "goals": 1, "assists": 0, "shots": 3, "shots_on_target": 2, "tackles_won": 1, "crosses": 4, "fouls": 1, "yellow_cards": 0, "red_cards": 0 }

REQUEST BODY SCHEMA: application/json
required

player_id required	integer (Player Id)
match_id required	integer (Match Id)
minutes required	integer (Minutes)
goals required	integer (Goals)
assists required	integer (Assists)
shots required	integer (Shots)

shots_on_target required	integer (Shots On Target)
crosses required	integer (Crosses)
offsides required	integer (Offsides)
tackles_won required	integer (Tackles Won)
interceptions required	integer (Interceptions)
fouls required	integer (Fouls)
fouled required	integer (Fouled)
yellow_cards required	integer (Yellow Cards)
red_cards required	integer (Red Cards)

Responses

> 200 Successful Response

> 422 Validation Error

POST /performances/

Request samples

Payload

Content type
application/json

Copy

```
{
  "player_id": 0,
  "match_id": 0,
```

```
"minutes": 0,  
"goals": 0,  
"assists": 0,  
"shots": 0,  
"shots_on_target": 0,  
"crosses": 0,  
"offsides": 0,  
"tackles_won": 0,  
"interceptions": 0,  
"fouls": 0,  
"fouled": 0,  
"yellow_cards": 0,  
"red_cards": 0  
}
```

Response samples

200**422**

Content type

application/json

Copy

```
{  
  "player_id": 0,  
  "match_id": 0,  
  "minutes": 0,  
  "goals": 0,  
  "assists": 0,  
  "shots": 0,  
  "shots_on_target": 0,  
  "crosses": 0,  
  "offsides": 0,  
  "tackles_won": 0,  
  "interceptions": 0,  
  "fouls": 0,  
  "fouled": 0,  
  "yellow_cards": 0,  
  "red_cards": 0,  
  "id": 0  
}
```

Get Performances For Player

Retrieves all performance records for a specific player.

Parameters:

- `player_id` (int): Unique player identifier.
- `db` (Session): Database session.

Returns:

- `List[Performance]`: All performances recorded for the player.

Example Request: `GET /performances/player/12`

Example Response: `[{"id": 44, "player_id": 12, "match_id": 5, "minutes": 90, "goals": 1, "assists": 0, "shots": 3, "shots_on_target": 2, "tackles_won": 1, "crosses": 4, "fouls": 1, "yellow_cards": 0, "red_cards": 0}]`

PATH PARAMETERS

<code>player_id</code> required	integer (Player Id)
---	---------------------

Responses

> **200** Successful Response

> **422** Validation Error

`GET /performances/player/{player_id}`

Response samples

200

422

Content type
application/json

```
[
  - {
    "player_id": 0,
    "match_id": 0,
    "minutes": 0,
    "goals": 0,
    "assists": 0,
    "shots": 0,
    "shots_on_target": 0,
    "crosses": 0,
    "offsides": 0,
    "tackles_won": 0,
    "interceptions": 0,
    "fouls": 0,
    "fouled": 0,
    "yellow_cards": 0,
    "red_cards": 0,
    "id": 0
  }
]
```

Get Performances For Match

Retrieves all performance records for a specific match.

Parameters:

- match_id (int): Unique match identifier.
- db (Session): Database session.

Returns:

- List[Performance]: All performances recorded in the match.

Example Request: GET /performances/match/5

Example Response: [{ "id": 44, "player_id": 12, "match_id": 5, "minutes": 90, "goals": 1, "assists": 0, "shots": 3, "shots_on_target": 2, "tackles_won": 1, "crosses": 4, "fouls": 1, "yellow_cards": 0, "red_cards": 0 }]

PATH PARAMETERS

match_id	integer (Match Id)
required	

Responses

> 200 Successful Response

> 422 Validation Error

GET /performances/match/{match_id}

Response samples

200

422

Content type
application/json

Copy Expand all Collapse all

```
[
  - {
    "player_id": 0,
    "match_id": 0,
    "minutes": 0,
    "goals": 0,
    "assists": 0,
    "shots": 0,
    "shots_on_target": 0,
    "crosses": 0,
    "offsides": 0,
    "tackles_won": 0,
    "interceptions": 0,
    "fouls": 0,
    "fouled": 0,
    "yellow_cards": 0,
    "red_cards": 0,
    "id": 0
  }
]
```

Matches

Get Matches

Retrieves all matches in the database.

Parameters:

- db (Session): Database session.

Returns:

- List[Match]: All match records.

Example Request: GET /matches

Example Response: [{ "id": 1, "home_team_id": 1, "away_team_id": 3, "home_goals": 3, "away_goals": 1, "date": "2024-02-10" }]

Responses

> **200** Successful Response

GET /matches/

Response samples

200

Content type

application/json

Copy

Expand all

Collapse all


```
[
  - {
    "date": "2019-08-24",
    "home_team_id": 0,
    "away_team_id": 0,
    "home_goals": 0,
    "away_goals": 0,
    "competition": "string",
    "id": 0
  }
]
```

Create Match

Creates a new match between two teams.

Parameters:

- match (MatchCreate): Match details including team IDs, goals, and date.
- db (Session): Database session.

Returns:

- Match: The newly created match record.

Example Request: POST /matches { "home_team_id": 1, "away_team_id": 2, "home_goals": 2, "away_goals": 1, "date": "2024-05-12" }

Example Response: { "id": 15, "home_team_id": 1, "away_team_id": 2, "home_goals": 2, "away_goals": 1, "date": "2024-05-12" }

REQUEST BODY SCHEMA: application/json
required

date required	string <date> (Date)
home_team_id required	integer (Home Team Id)
away_team_id required	integer (Away Team Id)
home_goals required	integer (Home Goals)
away_goals required	integer (Away Goals)

competition >

Competition (string) or Competition (null) (Competition)

Responses

> **200** Successful Response> **422** Validation Error

POST /matches/

Request samples

Payload**Content type**

application/json

Copy

```
{
  "date": "2019-08-24",
  "home_team_id": 0,
  "away_team_id": 0,
  "home_goals": 0,
  "away_goals": 0,
  "competition": "string"
}
```

Response samples

200**422****Content type**

application/json

Copy

```
{
  "date": "2019-08-24",
  "home_team_id": 0,
  "away_team_id": 0,
```

```
"home_goals": 0,  
"away_goals": 0,  
"competition": "string",  
"id": 0  
}
```

Get Match

Retrieves a single match by its ID.

Parameters:

- `match_id` (int): Unique match identifier.
- `db` (Session): Database session.

Returns:

- Match: Match record matching the ID.

Example Request: GET /matches/12

Example Response: { "id": 12, "home_team_id": 4, "away_team_id": 6, "home_goals": 1, "away_goals": 1, "date": "2024-03-18" }

PATH PARAMETERS

<code>match_id</code> <code>required</code>	integer (Match Id)
--	--------------------

Responses

> **200** Successful Response

> **422** Validation Error

GET /matches/{match_id}

Response samples

200

422

Content type

application/json

Copy

```
{
  "date": "2019-08-24",
  "home_team_id": 0,
  "away_team_id": 0,
  "home_goals": 0,
  "away_goals": 0,
  "competition": "string",
  "id": 0
}
```

Stats

Top Scorers

Returns the top goal scorers in the league based on total goals.

Parameters:

- limit (int): Maximum number of players to return.
- db (Session): Database session.

Returns:

- player_id: Unique ID of the player.
- player_name: Player's name.
- goals: Total goals scored across all performances.

Example Request: GET /stats/top-scorers?limit=2

Example Response: [{"player_id": 1, "player_name": "Erling Haaland", "goals": 28}, {"player_id": 7, "player_name": "Mohamed Salah", "goals": 21}]

QUERY PARAMETERS

limit

integer (Limit)

Default:

Responses

> **200** Successful Response

> **422** Validation Error

GET /stats/top-scorers

Response samples

200

422

Content type

application/json

Copy Expand all Collapse all

```
[
  - {
    "player_id": 0,
    "player_name": "string",
    "goals": 0
  }
]
```

Player Summary

Returns a player's aggregated season statistics across all matches.

Parameters:

- identifier (str): Player ID or name.
- db (Session): Database session.

Returns:

- `player_id`: Unique player identifier.
- `name`: Player name.
- `appearances`: Number of matches played.
- `minutes`: Total minutes played.
- `goals`: Total goals scored.
- `assists`: Total assists.
- `shots`: Total shots taken.
- `tackles`: Total tackles won.
- `crosses`: Total crosses attempted.

Example Request: GET `/stats/players/Saka/summary`

Example Response: `{ "player_id": 12, "name": "Bukayo Saka", "appearances": 32, "minutes": 2650, "goals": 14, "assists": 9, "shots": 55, "tackles": 28, "crosses": 42 }`

PATH PARAMETERS

`identifier`
`required`

string (Identifier)

Responses

> **200** Successful Response

> **422** Validation Error

GET `/stats/players/{identifier}/summary`

Response samples

200

422

Content type
application/json

Copy

```
{
  "player_id": 0,
  "name": "string",
  "appearances": 0,
  "minutes": 0,
```

```
    "goals": 0,  
    "assists": 0,  
    "shots": 0,  
    "tackles": 0,  
    "crosses": 0  
}
```

Team Summary

Returns aggregated season statistics for a team, including goals and shots.

Parameters:

- identifier (str): Team ID or team name.
- db (Session): Database session.

Returns:

- team_id: Unique team identifier.
- team_name: Team name.
- goals_for: Total goals scored by the team.
- goals_against: Total goals conceded.
- shots_for: Total shots taken by the team.
- shots_against: Total shots conceded.

Example Request: GET /stats/teams/Arsenal/summary

Example Response: { "team_id": 1, "team_name": "Arsenal", "goals_for": 68, "goals_against": 32, "shots_for": 410, "shots_against": 295 }

PATH PARAMETERS

identifier required	string (Identifier)
------------------------	---------------------

Responses

> **200** Successful Response

> **422** Validation Error

GET /stats/teams/{identifier}/summary

Response samples

200

422

Content type

application/json

Copy

```
{
  "team_id": 0,
  "team_name": "string",
  "goals_for": 0,
  "goals_against": 0,
  "shots_for": 0,
  "shots_against": 0
}
```

Match Analytics

Returns detailed analytics for a specific match, including goals, shots, and tackles for both teams.

Parameters:

- match_id (int): Unique match identifier.
- db (Session): Database session.

Returns:

- match_id: Match identifier.
- home_team: Name of the home team.
- away_team: Name of the away team.
- home_goals: Goals scored by the home team.
- away_goals: Goals scored by the away team.
- home_shots: Total shots by the home team.
- away_shots: Total shots by the away team.
- home_tackles: Tackles won by the home team.
- away_tackles: Tackles won by the away team.

Example Request: GET /stats/matches/42/analytics

Example Response: { "match_id": 42, "home_team": "Arsenal", "away_team": "Liverpool", "home_goals": 2, "away_goals": 2, "home_shots": 14, "away_shots": 11, "home_tackles": 19, "away_tackles": 17 }

PATH PARAMETERS

<code>match_id</code> <code>required</code>	integer (Match Id)
--	--------------------

Responses

- > 200 Successful Response
- > 422 Validation Error

GET /stats/matches/{match_id}/analytics

Response samples

200

422

Content type
application/json

Copy

```
{
  "match_id": 0,
  "home_team": "string",
  "away_team": "string",
  "home_goals": 0,
  "away_goals": 0,
  "home_shots": 0,
  "away_shots": 0,
  "home_tackles": 0,
  "away_tackles": 0
}
```

Analytics

Get Player Form

Computes a player's recent form score based on weighted performance metrics.

Parameters:

- identifier (str): Player ID or player name.
- matches (int): Number of recent performances to include.
- db (Session): Database session.

Returns:

- player: Player name.
- form_score: Weighted form score based on goals, assists, shots, and discipline.

Example Request: GET /analytics/players/Saka/form?matches=5

Example Response: { "player": "Bukayo Saka", "form_score": 7.85 }

PATH PARAMETERS

identifier required	string (Identifier)
------------------------	---------------------

QUERY PARAMETERS

matches	integer (Matches) Default: 5
---------	--

Responses

> **200** Successful Response

> **422** Validation Error

GET /analytics/players/{identifier}/form

Response samples

200

422

Content type
application/json

Copy

null

Get Team Form

Calculates a team's recent form score using weighted match results.

Parameters:

- identifier (str): Team ID or team name.
- matches (int): Number of recent matches to include.
- db (Session): Database session.

Returns:

- team: Team name.
- form_score: Weighted form score based on points and goal difference.

Example Request: GET /analytics/teams/Arsenal/form?matches=5

Example Response: { "team": "Arsenal", "form_score": 1.42 }

PATH PARAMETERS

identifier required	string (Identifier)
------------------------	---------------------

QUERY PARAMETERS

matches	integer (Matches) Default: 5
---------	---------------------------------

Responses

> **200** Successful Response

> **422** Validation Error

GET /analytics/teams/{identifier}/form

Response samples

200

422

Content type

application/json

null

Copy

Predict Match

Predicts the outcome of a match between two teams using recent form, head-to-head results, and a three-way probability model.

Parameters:

- `home_team` (str): Home team ID or name.
- `away_team` (str): Away team ID or name.
- `db` (Session): Database session.

Returns:

- `home_team`: Name of the home team.
- `away_team`: Name of the away team.
- `home_win_probability`: Probability of a home win.
- `draw_probability`: Probability of a draw.
- `away_win_probability`: Probability of an away win.
- `predicted_scoreline`: Expected scoreline based on goal trends.

Example Request: GET /analytics/predict?home_team=Arsenal&away_team=Chelsea

Example Response: { "home_team": "Arsenal", "away_team": "Chelsea", "home_win_probability": 0.58, "draw_probability": 0.24, "away_win_probability": 0.18, "predicted_scoreline": "2-1" }

QUERY PARAMETERS

home_team required	string (Home Team)
away_team required	string (Away Team)

Responses

> 200 Successful Response

> 422 Validation Error

GET /analytics/predict

Response samples

200

422

Content type
application/json

Copy

null

Root

Root endpoint confirming the API is running.

Returns:

- message: Status message.
- endpoints: Key route groups in the API.

Responses

> **200** Successful Response

GET /

Response samples

200

Content type

application/json

null

Copy