

# MySQL Cheat Sheet

MySQL is a popular open-source relational database management system known for its ease of use and scalability. Sometimes, you will need a little help while working on a project. That's why we created this MySQL Cheat Sheet.

## CONNECTING TO A MYSQL SERVER

Connect to a MySQL server with a username and a password using the mysql command-line client. MySQL will prompt for the password:  
`mysql -u [username] -p`

To connect to a **specific database** on a MySQL server using a username and a password:  
`mysql -u [username] -p [database]`

To **export data** using the mysqldump tool:  
`mysqldump -u [username] -p \[database] > data_backup.sql`

To exit the client:  
`quit` or `exit`

For a full list of commands:  
`help`

## CREATING AND DISPLAYING DATABASES

To create a database:  
`CREATE DATABASE zoo;`

To list all the databases on the server:  
`SHOW DATABASES;`

To use a specified database:  
`USE zoo;`

To delete a specified database:  
`DROP DATABASE zoo;`

To list all tables in the database:  
`SHOW TABLES;`

To get information about a specified table:  
`DESCRIBE animal;`  
It outputs column names, data types, default values, and more about the table.

## CREATING TABLES

To create a table:  
`CREATE TABLE habitat (  
 id INT,  
 name VARCHAR(64)  
);`

Use AUTO\_INCREMENT to increment the ID automatically with each new record. An AUTO\_INCREMENT column must be defined as a primary or unique key:  
`CREATE TABLE habitat (  
 id INT PRIMARY KEY AUTO_INCREMENT,  
 name VARCHAR(64)  
);`

To create a table with a foreign key:  
`CREATE TABLE animal (  
 id INT PRIMARY KEY AUTO_INCREMENT,  
 name VARCHAR(64),  
 species VARCHAR(64),  
 age INT,  
 habitat_id INT,  
 FOREIGN KEY (habitat_id)  
 REFERENCES habitat(id)  
);`

## MODIFYING TABLES

Use the ALTER TABLE statement to modify the table structure.

To change a table name:  
`ALTER TABLE animal RENAME pet;`

To add a column to the table:  
`ALTER TABLE animal  
ADD COLUMN name VARCHAR(64);`

To change a column name:  
`ALTER TABLE animal  
RENAME COLUMN id TO identifier;`

To change a column data type:  
`ALTER TABLE animal  
MODIFY COLUMN name VARCHAR(128);`

To delete a column:  
`ALTER TABLE animal  
DROP COLUMN name;`

To delete a table:  
`DROP TABLE animal;`

## QUERYING DATA

To select data from a table, use the SELECT command. An example of a single-table query:  
`SELECT species, AVG(age) AS average_age  
FROM animal  
WHERE id != 3  
GROUP BY species  
HAVING AVG(age) > 3  
ORDER BY AVG(age) DESC;`

An example of a multiple-table query:  
`SELECT city.name, country.name  
FROM city  
[INNER | LEFT | RIGHT] JOIN country  
 ON city.country_id = country.id;`

Use +, -, \*, / to do some basic math.  
To get the number of seconds in a week:  
`SELECT 60 * 60 * 24 * 7; -- result: 604800`

## AGGREGATION AND GROUPING

- **AVG**(expr) – average value of expr for the group.
- **COUNT**(expr) – count of expr values within the group.
- **MAX**(expr) – maximum value of expr values within the group.
- **MIN**(expr) – minimum value of expr values within the group.
- **SUM**(expr) – sum of expr values within the group.

To count the rows in the table:  
`SELECT COUNT(*)  
FROM animal;`

To count the non-NULL values in a column:  
`SELECT COUNT(name)  
FROM animal;`

To count unique values in a column:  
`SELECT COUNT(DISTINCT name)  
FROM animal;`

### GROUP BY

To count the animals by species:  
`SELECT species, COUNT(id)  
FROM animal  
GROUP BY species;`

To get the average, minimum, and maximum ages by habitat:  
`SELECT habitat_id, AVG(age),  
 MIN(age), MAX(age)  
FROM animal  
GROUP BY habitat_id;`

## INSERTING DATA

To insert data into a table, use the INSERT command:  
`INSERT INTO habitat VALUES  
(1, 'River'),  
(2, 'Forest');`

You may specify the columns in which the data is added. The remaining columns are filled with default values or NULLs.  
`INSERT INTO habitat (name) VALUES  
( 'Savanna');`

## UPDATING DATA

To update the data in a table, use the UPDATE command:  
`UPDATE animal  
SET  
 species = 'Duck',  
 name = 'Quack'  
WHERE id = 2;`

## DELETING DATA

To delete data from a table, use the DELETE command:  
`DELETE FROM animal  
WHERE id = 1;`

This deletes all rows satisfying the WHERE condition.  
To delete all data from a table, use the TRUNCATE TABLE statement:  
`TRUNCATE TABLE animal;`

## CASTING

From time to time, you need to change the type of a value. Use the CAST() function to do this.  
In MySQL, you can cast to these data types:  
CHAR NCHAR BINARY DATE DATETIME  
DECIMAL DOUBLE FLOAT REAL SIGNED  
UNSIGNED TIME YEAR JSON spatial\_type

To get a number as a signed integer:  
`SELECT CAST(1234.567 AS signed);  
-- result: 1235`

To change a column type to double:  
`SELECT CAST(column AS double);`

# MySQL Cheat Sheet

## TEXT FUNCTIONS

### FILTERING THE OUTPUT

To fetch the city names that are not Berlin:

```
SELECT name
FROM city
WHERE name != 'Berlin';
```

### TEXT OPERATORS

To fetch the city names that start with a 'P' or end with an 's':

```
SELECT name
FROM city
WHERE name LIKE 'P%' OR name LIKE '%s';
```

To fetch the city names that start with any letter followed by 'ublin' (like Dublin in Ireland or Lublin in Poland):

```
SELECT name
FROM city
WHERE name LIKE '_ublin';
```

### CONCATENATION

Use the CONCAT () function to concatenate two strings:

```
SELECT CONCAT('Hi ', 'there!');
-- result: Hi there!
```

If any of the string is NULL, the result is NULL:

```
SELECT CONCAT(Great ', 'day', NULL);
-- result: NULL
```

MySQL allows specifying a separating character (separator) using the CONCAT\_WS () function. The separator is placed between the concatenated values:

```
SELECT CONCAT_WS(' ', 1, 'Olivier',
'Norris'); -- result: 1 Olivier Norris
```

### OTHER USEFUL TEXT FUNCTIONS

To get the count of characters in a string:

```
SELECT LENGTH('LearnSQL.com');
-- result: 12
```

To convert all letters to lowercase:

```
SELECT LOWER('LEARNSQL.COM');
-- result: learnsql.com
```

To convert all letters to uppercase:

```
SELECT UPPER('LearnSQL.com');
-- result: LEARNSQL.COM
```

To get just a part of a string:

```
SELECT SUBSTRING('LearnSQL.com', 9);
-- result: .com
SELECT SUBSTRING('LearnSQL.com', 1, 5);
-- result: Learn
```

To replace a part of a string:

```
SELECT REPLACE('LearnSQL.com', 'SQL',
'Python');
-- result: LearnPython.com
```

## NUMERIC FUNCTIONS

To get the remainder of a division:

```
SELECT MOD(13, 2); -- result: 1
```

To round a number to its nearest integer:

```
SELECT ROUND(1234.56789); -- result: 1235
```

To round a number to three decimal places:

```
SELECT ROUND(1234.56789, 3);
-- result: 1234.568
```

To round a number up:

```
SELECT CEIL(13.1); -- result: 14
SELECT CEIL(-13.9); -- result: -13
```

The CEIL (x) function returns the smallest integer not less than x. To round the number down:

```
SELECT FLOOR(13.8); -- result: 13
SELECT FLOOR(-13.2); -- result: -14
```

The FLOOR (x) function returns the greatest integer not greater than x. To round towards 0 irrespective of the sign of a number:

```
SELECT TRUNCATE(13.56, 0); -- result: 13
SELECT TRUNCATE(-13.56, 1); -- result: -13.5
```

To get the absolute value of a number:

```
SELECT ABS(-12); -- result: 12
```

To get the square root of a number:

```
SELECT SQRT(9); -- result: 3
```

## USEFUL NULL FUNCTIONS

To fetch the names of the cities whose rating values are not missing:

```
SELECT name
FROM city
WHERE rating IS NOT NULL;
```

### COALESCE(x, y, ...)

To replace NULL in a query with something meaningful:

```
SELECT domain,
COALESCE(domain, 'domain missing')
FROM contacts;
```

The COALESCE () function takes any number of arguments and returns the value of the first argument that is not NULL.

### NULLIF(x, y)

To save yourself from *division by 0* errors:

```
SELECT last_month, this_month,
this_month * 100.0
/ NULLIF(last_month, 0)
AS better_by_percent
FROM video_views;
```

The NULLIF (x, y) function returns NULL if x equals y, else it returns the value of x value.

## DATE AND TIME

There are 5 main time-related types in MySQL:

```
DATE    TIME    DATETIME    TIMESTAMP    YEAR
```

**DATE** – stores the year, month, and day in the YYYY-MM-DD format.

**TIME** – stores the hours, minutes, and seconds in the HH:MM:SS format.

**DATETIME** – stores the date and time in the YYYY-MM-DD HH:MM:SS format. The supported range is '1000-01-01 00:00:00' to '9999-12-31 23:59:59'.

**TIMESTAMP** – stores the date and time. The range is '1970-01-01 00:00:01' UTC to '2038-01-19 03:14:07' UTC. MySQL converts TIMESTAMP values from the current time zone to UTC for storage, and back from UTC to the current time zone for retrieval.

**YEAR** – stores the year in the YYYY format.

### INTERVALS

An interval is the duration between two points in time.

To define an interval: **INTERVAL 1 DAY**

This syntax consists of the INTERVAL keyword, a value, and a time part keyword (YEAR, QUARTER, MONTH, WEEK, DAY, HOUR, MINUTE, SECOND, MICROSECOND).

You may combine different INTERVALs using the + or – operator:

```
INTERVAL 1 YEAR + INTERVAL 3 MONTH
```

You may also use the standard SQL syntax:

```
INTERVAL '1-3' YEAR_MONTH
```

```
-- 1 year and 3 months
```

```
INTERVAL '3-12' HOUR_MINUTE
```

```
-- 3 hours 12 minutes
```

### WHAT TIME IS IT?

To answer this question, use:

- CURRENT\_TIME or CURTIME – to get the current time.
- CURRENT\_DATE or CURDATE – to get the current date.
- NOW () or CURRENT\_TIMESTAMP – to get the current timestamp with both of the above.

### CREATING VALUES

To create a date, time, or datetime, write the value as a string and cast it to the proper type.

```
SELECT CAST('2021-12-31' AS date),
CAST('15:31' AS time),
CAST('2021-12-31 23:59:29' AS datetime);
```

You may skip casting in simple conditions; the database knows what you mean.

```
SELECT airline, flight_no, departure_time
FROM airport_schedule
WHERE departure_time < '12:00';
```

## EXTRACTING PARTS OF DATES

To extract a part of a date, use the functions YEAR, MONTH, WEEK, DAY, HOUR, and so on.

```
SELECT YEAR(CAST('2021-12-31' AS date));
-- result: 2021
SELECT MONTH(CAST('2021-12-31' AS date));
-- result: 12
SELECT DAY(CAST('2021-12-31' AS date));
-- result: 31
```

### DATE ARITHMETICS

To add or subtract an interval from a DATE, use the ADDDATE () function:

```
ADDDATE('2021-10-31', INTERVAL 2 MONTH);
-- result: '2021-12-31'
ADDDATE('2014-04-05', INTERVAL -3 DAY);
-- result: '2014-04-02'
```

To add or subtract an interval from a TIMESTAMP or DATETIME, use the TIMESTAMPADD () function:

```
TIMESTAMPADD(MONTH, 2,
'2014-06-10 07:55:00');
-- result: '2014-08-10 07:55:00'
TIMESTAMPADD(MONTH, -2,
'2014-06-10 07:55:00');
-- result: '2014-04-10 07:55:00'
```

To add or subtract TIME from a DATETIME, use the ADDTIME () function:

```
ADDTIME('2018-02-12 10:20:24', '12:43:02');
-- result: '2018-02-12 23:03:26'
ADDTIME('2018-02-12 10:20:24', '-12:43:02');
-- result: '2018-02-11 21:37:22'
```

To find the difference between two dates, use the DATEDIFF () function:

```
DATEDIFF('2015-01-01', '2014-01-02');
-- result: 364
```

To find the difference between two times, use the TIMEDIFF () function:

```
SELECT TIMEDIFF('09:30:00', '07:55:00');
-- result: '01:35:00'
```

To find the difference between two datetimes (in a given unit of time), use the TIMESTAMPDIFF () function. Here's an example with the difference given in weeks:

```
SELECT TIMESTAMPDIFF(
WEEK, '2018-02-26', '2018-03-21'
); -- result: 3
```