

LASER INTERFEROMETER GRAVITATIONAL WAVE OBSERVATORY  
- LIGO -  
CALIFORNIA INSTITUTE OF TECHNOLOGY  
MASSACHUSETTS INSTITUTE OF TECHNOLOGY

Technical Note	LIGO-T22xxxxx-	2025/05/14
<b>Minimizing Noise in WOPA (Waveguided Optical Parametric Amplification) by Optimizing Mode Matching</b>		
Rana Adhikari, Peter G. Carney, Nora Dreslin		

California Institute of Technology  
LIGO Project, MS 18-34  
Pasadena, CA 91125  
Phone (626) 395-2129  
Fax (626) 304-9834  
E-mail: [info@ligo.caltech.edu](mailto:info@ligo.caltech.edu)

Massachusetts Institute of Technology  
LIGO Project, Room NW22-295  
Cambridge, MA 02139  
Phone (617) 253-4824  
Fax (617) 253-7014  
E-mail: [info@ligo.mit.edu](mailto:info@ligo.mit.edu)

LIGO Hanford Observatory  
Route 10, Mile Marker 2  
Richland, WA 99352  
Phone (509) 372-8106  
Fax (509) 372-8137  
E-mail: [info@ligo.caltech.edu](mailto:info@ligo.caltech.edu)

LIGO Livingston Observatory  
19100 LIGO Lane  
Livingston, LA 70754  
Phone (225) 686-3100  
Fax (225) 686-7189  
E-mail: [info@ligo.caltech.edu](mailto:info@ligo.caltech.edu)

<http://www.ligo.caltech.edu/>

Contents

1	Introduction	2
2	Objective	2
3	Approach	2
4	Timeline	3

# 1 Introduction

LIGO (Laser Interferometer Gravitational-Wave Observatory) detects gravitational waves from astronomical phenomena such as black holes and binary neutron star collisions by using interferometry to measure the movement of test masses as a result of a gravitational wave. LIGO consists of two L-shaped interferometers located 3000 km apart whose arms are orthogonal 4 km Michelson interferometers. A 1064nm wavelength laser is split at a beamsplitter and sent down the arms so that when a gravitational wave passes and squeezes one arm while compressing the other, the beams will have a phase difference. The level of sensitivity required to detect gravitational waves (strain of gravitational wave is on the order of  $10^{-22}$ ) also makes LIGO's measurements susceptible to noise. To optimize the accuracy and sensitivity of LIGO, we aim to limit noise from as many sources as possible. One way noise is minimized in the laser is through quantum squeezing.

Quantum squeezing is a method in which we can minimize the laser shot noise. This shot noise arises from the uncertainty between phase and amplitude. We are able to reduce the uncertainty in phase by increasing the uncertainty in amplitude and vice versa. Currently, both amplitude and phase squeezing is being used to reduce noise in LIGO, depending on the frequency. This project aims to improve on the squeezing process by using a periodically poled lithium niobate (PPLN) crystal to generate 1064nm squeezed light from 532nm wavelength light which we can combine with the 1064nm signal in LIGO to squeeze the light being detected.

# 2 Objective

Within the squeezing process itself there are sources of noise. One of which is a result of mode mismatch between the squeezed beam coming from the crystal and the non-squeezed beam. Loss of mode matching results in loss of measured squeezed light, given by

$$dB_{measured} = 10 \log((1 - \eta) + (\eta)10^{(dB/10)})$$

Where  $\eta$  is the mode matching with 1 being perfectly mode matched. 0.95% mode matching only allows for measurement of a maximum 99.77% of actual squeezing. This project aims to measure and minimize noise as a result of mode mismatch between squeezed and non-squeezed beams to optimize the accuracy and sensitivity of LIGO detections. We hope to mode match our local oscillator (LO) beam and signal beam to within  $\eta = 0.97$  and generate 6dB+ of squeezing.

# 3 Approach

Using a periodically poled lithium niobate crystal (PPLN) we will generate 1064nm wavelength squeezed light from 532nm wavelength light. This signal beam will be mixed with our LO and squeeze it.

To maximize the measured dB of squeezing, we will focus on optimizing the mode matching between the signal and LO. Using ABCD matrices and FINESSE, an interferometer simula-

tion program, we will model the LO and signal beams as they propagate through the setup shown above and adjust the WOPA setup until the beams are mode matched in the TEM00 mode. We match the beams by aligning their profiles and the positions of the beam waists which are given by

$$w(z) = w_0 \sqrt{1 + \left(\frac{z}{z_R}\right)^2}$$

where  $w_0$  is the waist radius and  $z_R$  is the Rayleigh range.

## 4 Timeline

Week 1 (6/18-6/25)	Measure the laser polarization drift, a possible source of noise in the system. We
Weeks 2-3 (6/25-7/9)	Take nonlinear gain measu
Weeks 4-5 (7/9-7/23)	Measure the squee
Weeks 6-7 (7/23-8/6)	Mode matching our beams an
Weeks 8-9 (8/6-8/20)	Coherent phase locking the system to op

## References

- [1] Barry C. Barish and Rainer Weiss. *LIGO and the Detection of Gravitational Waves*. Physics Today, 52, p. 44-50 (1999).
- [2] F. Kaiser et. al. *A Fully Guided-Wave Squeezing Experiment for Fiber Quantum Networks*. Optica, Vol. 3, p. 362 (2016).