

NAME

WhatsApi

FONCTIONS

list_util()

ajouter_util()

info_util()

DESCRIPTION

list_util()

Cette fonction permet d'afficher tous les utilisateurs de WhatsAPI.

OUTPUT

Type Dict {

status :

data : []

}

status -> data :

0 -> [{id_utilisateur : (type INT), pseudo_utilisateur : (type STR)}, . . .]

1 -> 'INPUT Type incorrect'

2 -> 'INPUT Length incorrect'

3 -> 'INPUT Not Correspond'

ajouter_util(pseudo_utilisateur)

Cette fonction permet d'ajouter un nouvel utilisateur à la base de donnée.

INPUT

pseudo_utilisateur type STR

OUTPUT

Type Dict {

status :

data : []

}

status -> data :

0 -> None

1 -> 'INPUT Type not STR'

2 -> 'INPUT Length not between 5, 20'

3 -> 'INPUT already in database'

info_util(pseudo_utilisateur)

Cette fonction permet d'afficher les informations relatives à un utilisateur.

INPUT

pseudo_utilisateur type STR

OUTPUT

Type Dict {

status :

data : []

}

status :

0 -> (id_utilisateur type INT, pseudo_utilisateur type STR)

1 -> 'INPUT Type not STR'

2 -> 'INPUT Length not between 5, 20'

3 -> 'INPUT Not in database'

AUTHOR

Written by Tom CALVO, Dorian JOSSERAND and Lucas NGUYEN.

COPYRIGHT

Copyright © 2022 WhatsAPI

This is free software: you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.