

# export/page.tsx — Line-by-Line Reference

## File Purpose

The Quick Export Tool page. Staff select a **reporting period** (1 month → all time) and a **data type** (Survey or Route), then click a single button to fetch and download a CSV. No table is shown — the export fires directly to the browser's download prompt.

## Line-by-Line Breakdown

### Lines 1–8 — Directives and Imports

```
"use client";
```

Client component — required for `useState` and event handlers.

Imports:

- UI components from `components.tsx` : logo, header, buttons, checkboxes, labels
- `fetchSurveyDataByDateRange` from `surveyDatafetchService.ts` — used for Survey Report exports
- `fetchRouteStatsByDateRange` from `routeDataFetchService.ts` — used for Route Report exports
- `exportToCsv` , `exportRouteStatsToCsv` from `csvExportService.ts` — trigger the download

### Lines 10–21 — `periodToStartDate` (helper)

```
function periodToStartDate(period: string): string
```

Converts a period key into a start date string ( `YYYY-MM-DD` ). The end date is always today.

| Period key | Start date                             |
|------------|----------------------------------------|
| "1month"   | 1 month ago                            |
| "3months"  | 3 months ago                           |
| "6months"  | 6 months ago                           |
| "1year"    | 1 year ago                             |
| "3years"   | 3 years ago                            |
| "alltime"  | "2020-01-01" (hardcoded project epoch) |

Uses `setMonth` / `setFullYear` on a `new Date()` instance, then returns `toISOString().slice(0, 10)` .

### Lines 23–28 — State Declarations

| State          | Initial | Purpose                                                     |
|----------------|---------|-------------------------------------------------------------|
| selectedPeriod | null    | Which period checkbox is active ("1month", "3months", etc.) |
| selectedData   | null    | Which data type is selected ("survey" or "route")           |
| loading        | false   | Disables the Export button during the fetch                 |
| error          | null    | Error message shown below the Export button                 |

### Line 30 — canExport

```
const canExport = selectedPeriod !== null && selectedData !== null;
```

Both a period and a data type must be selected before the Export button is enabled.

### Lines 32–51 — handleExport

```
async function handleExport()
```

The export handler:

| Lines | What happens                                                               |
|-------|----------------------------------------------------------------------------|
| 33    | Guards: returns early if either selection is missing                       |
| 36    | Converts selectedPeriod to a start date via periodToStartDate              |
| 37    | Sets end date to today                                                     |
| 39–41 | If selectedData === "survey": fetches survey rows and calls exportToCsv    |
| 42–45 | Otherwise (route): fetches route stat rows and calls exportRouteStatsToCsv |
| 46–48 | Catches any error and stores it in error state                             |
| 49–50 | finally clears loading                                                     |

The CSV filename includes the period key (e.g., `survey-report-3months.csv`, `route-report-1year.csv` ).

### Lines 53–106 — JSX Layout

The page is structured as a `<table className="page_table">` with these rows:

| Row        | Contents                           |
|------------|------------------------------------|
| Logo row   | LogoImage                          |
| Nav row    | HomeButton → /menu                 |
| Header row | PortalHeader — "Quick Export Tool" |

|             |                                                                                                |
|-------------|------------------------------------------------------------------------------------------------|
| Options row | Two columns (period + data type) each with SearchHeader, ExportText, and OptionCheckbox groups |
| Export row  | InteractiveButton + optional error <span>                                                      |

**Period column (left, lines 73–79):** Six `OptionCheckbox` components, one per period. Each uses `checked={selectedPeriod === "<key>"}` and `onChange={(val) => setSelectedPeriod(val ? "<key>" : null)}` — checking one automatically unchecks the others because only one string can equal `selectedPeriod` at a time.

**Data type column (right, lines 86–93):** Two `OptionCheckbox` components for Survey and Route, using the same single-select pattern with `selectedData` .

**Export button (line 99):**

- Label switches to "Exporting..." while `loading` is true
- `disabled={!canExport || loading}` — blocked until both selections are made and no fetch is in flight
- Error message rendered inline with `role="alert"` if present (line 100)

---

## Summary

| Concern                       | Handled by                                                                  |
|-------------------------------|-----------------------------------------------------------------------------|
| Period → date conversion      | <code>periodToStartDate</code>                                              |
| Single-select checkbox groups | <code>selectedPeriod/selectedData</code> string state compared per checkbox |
| Survey data fetch             | <code>fetchSurveyDataByDateRange</code>                                     |
| Route stats fetch             | <code>fetchRouteStatsByDateRange</code>                                     |
| CSV download                  | <code>exportToCsv</code> / <code>exportRouteStatsToCsv</code>               |
| Navigation                    | <code>useRouter</code> → <code>/menu</code> via <code>HomeButton</code>     |