DigiKey

Product Index > Fans, Thermal Management > Fans > DC Brushless Fans (BLDC) > Sunon Fans MF40101VX-1000U-G99

Dark Mode ⬤ Share ✦

MF40101VX-1000U-G99

DigiKey Part Number	259-1808-ND
Manufacturer	**Sunon Fans**
Manufacturer Product Number	MF40101VX-1000U-G99
Description	FAN AXIAL 40X10MM 12VDC WIRE
Manufacturer Standard Lead Time	38 Weeks
Customer Reference	
Detailed Description	Fan Tubeaxial 12VDC Square - 40mm L x 40mm H Vapo-Bearing™ 9.9 CFM (0.277m³/min) 3 Wire Leads
Datasheet	📄 **Datasheet**

Image shown is a representation only. Exact specifications should be obtained from the product data sheet.

In-Stock: 1,000

Can ship immediately

QUANTITY

Add to List   Add to Cart

All prices are in USD

Bulk

QUANTITY	UNIT PRICE	EXT PRICE
📦 1	$7.39000	$7.39
10	$7.14200	$71.42
25	$6.93520	$173.38
50	$6.52260	$326.13
100	$5.86200	$586.20
250	$5.77948	$1,444.87
500	$5.40794	$2,703.97

📦 **Manufacturers Standard Package**

Import Tariff may apply to this part if shipping to the United States

Product Attributes

TYPE	DESCRIPTION	SELECT ALL ☐
Category	**Fans, Thermal Management** ⚪ **Fans** ⚪ **DC Brushless Fans (BLDC)** 🔴	
Mfr	**Sunon Fans**	☐

Series	MagLev® MF	☐
Package	Bulk ⦵	☐
Product Status	Active	☐
Voltage - Rated	12VDC	☐
Size / Dimension	Square - 40mm L x 40mm H	☐
Width	10.00mm	☐
Air Flow	9.9 CFM (0.277m³/min)	☐
Static Pressure	0.250 in H2O (62.3 Pa)	☐
Bearing Type	Vapo-Bearing™	☐
Fan Type	Tubeaxial	☐
Features	Auto Restart, Speed Sensor (Tach)	☐
Noise	31.4dB(A)	☐
Power (Watts)	1.05 W	☐
RPM	8500 RPM	☐
Termination	3 Wire Leads	☐
Ingress Protection	-	☐
Operating Temperature	14 ~ 158°F (-10 ~ 70°C)	☐
Approval Agency	cURus, TUV	☐
Weight	0.035 lb (15.88 g)	☐
Current Rating (Amps)	0.087A	☐
Voltage Range	4.5 ~ 13.8VDC	☐
Material - Frame	Polybutylene Terephthalate (PBT)	☐
Material - Blade	Polybutylene Terephthalate (PBT)	☐
Lifetime @ Temp.	70000 Hrs @ 40°C	☐
Base Product Number	MF40101VX	☐

Report Product Information Error

View Similar

Documents & Media

RESOURCE TYPE	LINK
Datasheets	**DC Brushless Fan, Blower Catalog MF40101VX-1000U-G99**
Video File	**SUNON Fan Temperature Overview** **SUNON Mounting and Bearing Considerations** **Sunon Demonstrates the Autorestart and Reverse Airflow Features**
Environmental Information	**Sunon Fans REACH201 Cert** **Sunon Fans RoHS Cert**

Environmental & Export Classifications

ATTRIBUTE	DESCRIPTION
RoHS Status	ROHS3 Compliant
Moisture Sensitivity Level (MSL)	1 (Unlimited)
REACH Status	REACH Unaffected
ECCN	EAR99
HTSUS	8414.59.6590

You May Also Be Interested In See All 20

15 Items

MF40101V1-1000U-G99
FAN AXIAL 40X10MM 12VDC WIRE

MF40101VX-1000U-A99
FAN AXIAL 40X10MM 12VDC WIRE

Sunon Fans

$5.33000 | Details

Sunon Fans

$4.25000 | Details

Associated Product

1 Items

FG-4

FAN GUARD 40MM METAL

Sunon Fans

$1.25000 | Details

Product Questions and Answers

Take a look at our new Q&A!

See what engineers are asking, ask your own questions, or help out a member of the DigiKey engineering community by participating in our new product questions and answers feature!

Check it out

Additional Resources

ATTRIBUTE	DESCRIPTION
Other Names	259-1808
Standard Package	1 ⓘ

💬 Chat   📞 1-800-344-4539   218-681-6674   ✉ Email Us   👥 Co-Browse

🇺🇸 United States | Copyright © 1995-2024, DigiKey. | All Rights Reserved.
Local Support: 701 Brooks Avenue South, Thief River Falls, MN 56701 USA

Do Not Sell / Do Not Share My Personal Information