2025 6th International Conference on Recent Advances in Information Technology (RAIT) | 979-8-3315-2480-7/25/$31.00 ©2025 IEEE | DOI: 10.1109/RAIT65068.2025.11089072

A Comparative Analysis of SDN Controller Placement Problem: IoT-Specific Tactics and Generalized Solutions

Tangudu Harsha Vardhan
Department of Computer Science and Engineering
Amrita School of Computing, Coimbatore
Amrita Vishwa Vidyapeetham, India
cb.en.u4cse21062@cb.students.amrita.edu

Yellina SriBhargav
Department of Computer Science and Engineering
Amrita School of Computing, Coimbatore
Amrita Vishwa Vidyapeetham, India
cb.en.u4cse21670@cb.students.amrita.edu

Jahnavi Anala
Department of Computer Science and Engineering
Amrita School of Computing, Coimbatore
Amrita Vishwa Vidyapeetham, India
cb.en.u4cse21024@cb.students.amrita.edu

Yejnakshari Meghana K
Department of Computer Science and Engineering
Amrita School of Computing, Coimbatore
Amrita Vishwa Vidyapeetham, India
cb.en.u4cse21669@cb.students.amrita.edu

N Radhika
Department of Computer Science and Engineering
Amrita School of Computing, Coimbatore
Amrita Vishwa Vidyapeetham, India
n_radhika@cb.amrita.edu

***Abstract*—Software-Defined Networking (SDN) revolutionizes network management by decoupling control and data planes, presenting the challenge of the Controller Placement Problem (CPP). This paper compares various approaches to CPP, focusing on strategies for IoT environments and general SDN networks. The IoT-centric study highlights the importance of adaptive, energy-efficient placements using heuristic methods like Particle Swarm Optimization, tailored to resource-constrained scenarios. In contrast, broader SDN strategies involve computationally intensive methods like Integer Linear Programming and machine learning for large-scale networks. Identified research gaps include the need for dynamic real-time placement, energy-efficient solutions, and multi-domain coordination. The paper proposes enhancements using reinforcement learning and collaborative approaches to optimize controller placement. These solutions aim to improve network performance, scalability, and fault tolerance in diverse SDN applications, providing a foundation for future research in SDN architecture optimization.**

***Index Terms*—Software-Defined Networking, Controller Placement Problem, IoT Networks, Optimization Techniques, Reinforcement Learning, Latency Minimization, Load Balancing, Energy Efficiency, Multi-Domain Coordination, Heuristic Algorithms, Metaheuristic Algorithms, Machine Learning, Dynamic Reconfiguration, Network Topology.**

I. Introduction

Software-Defined Networking (SDN) is a transformative technology that separates the control and data planes, allowing centralized management and control of network resources. A crucial challenge in SDN is the Controller Placement Problem (CPP), which involves determining the optimal locations for controllers—the "brains" of the network to maximize load balancing and fault tolerance and minimize latency [3].

Software-defined networking (SDN) is revolutionary Technologies that separate control and data planes, allowing centralized management and control of the network equipment. One of the most important challenges in SDN is the controller The placement problem (CPP), which involves decision making The best places for controllers—the "brains" of the network. To increase and reduce load balancing and fault tolerance Latency [3]. This research paper provides a comparative analysis Several research studies on CPP separately The Method of Making. One study focuses on IoT environments, where. Resource constraints and device differences are the key anxiety [1], while the other provides a comprehensive assessment of this Controller placement methods for different SDNs Settings [2] .

This survey paper provides a comparative analysis of several research studies that address CPP from different perspectives. One study focuses on IoT environments, where resource constraints and device heterogeneity are the primary concerns [1], while another offers a comprehensive survey of controller placement strategies applicable across various SDN settings [2].

979-8-3315-2480-7/25/$31.00 © 2025 IEEE

Authorized licensed use limited to: University of Zululand. Downloaded on March 25,2026 at 01:19:26 UTC from IEEE Xplore. Restrictions apply.

II. Problem Definition and Scope

The main problem addressed in the research papers is to determine the optimal controller placement to minimize latency, maximize fault tolerance, and distribute the load [1], [2] efficiently A study, . entitled *SDN Controller Placement in IoT Networks: An Optimization Perspective* , focusing on unique IoT network challenges and, where heterogeneous devices and limited resources require specialized solutions Approaches is more efficient considering device limitations and dynamic network conditions [1] is needed in this case.

Another paper, *Comprehensive Review of SDN Controller Placement Strategies*, provides a comprehensive framework for handling CPP in SDN systems. This study discusses the basic trade-off between reducing latency, adding more controllers, and controlling network costs [2]. This applies to a wide range of SDN applications, including large cloud infrastructures, data centers and enterprise networks.

III. LITERATURE SURVEY

In this section, we review existing research on SDN controller placement, focusing on methodologies, evaluation metrics, and optimization techniques. The reviewed literature reveals a variety of approaches to CPP, ranging from heuristic and metaheuristic approaches to machine learning-based solutions.

A. IoT-Specific Research

SDN Controller Placement in IoT Networks: An Optimization Approach explores heuristic metaheuristic approaches such as particle-set optimization (PSO) and genetic algorithm (GA) designed for resource-constrained IoT environments [1] Other studies emphasize the need for adaptive solutions that account for device heterogeneity and dynamic network conditions, making them suitable for highly variable IoT environments [4], [5].

B. SDN General Studies

A Comprehensive Review of SDN Controller Placement Strategies provides a comprehensive overview of current optimization techniques, including Integer Linear Programming (ILP), clustering algorithms, and hybrid techniques that combine several techniques to achieve better network performance conditions include [6]. The study also highlights the widespread use of machine learning models for predictive placement, especially in cases where [7] needs to make real-time or near-real-time decisions.

IV. Optimization Techniques

The papers reviewed cover various methods for optimizing controller placement. Studies focusing primarily on the IoT use heuristic meta-research methods that are well suited for dynamic environments and limited resources. Methods such as PSO and GA are used to predict controller placement dynamically based on device properties and network conditions [1], [4]. These methods are highly scalable, making them ideal for environments where traffic patterns and network topologies are constantly changing.

On the other hand, advanced SDN studies typically use computationally intensive methods such as ILP to find optimal solutions, although these can be expensive to compute on large networks [2], [6] Hybrid methods that combine various methods including clustering algorithms with machine learning models, are explored as In network environment For better performance, use [7].

V. Proposed Algorithm for Dynamic Real-Time Controller Placement using Reinforcement Learning

The following is a high-level algorithm leveraging reinforcement learning for dynamic controller placement:

A. Algorithm: Adaptive Controller Placement using Reinforcement Learning

1) **Initialize Environment:**
   - Define the network topology as a graph $G = (V, E)$, where V represents switches and potential controller locations, and E represents the links.
   - Define states S based on network metrics (e.g., latency, bandwidth, energy levels).
   - Define actions A, which involve shifting the controller to a new location or modifying the number of controllers.
2) **Define Reward Function:**
   - The reward function $R(s, a)$ should consider multiple factors:
     - Minimization of latency.
     - Energy efficiency (especially for IoT environments).
     - Load balancing across controllers.
3) **Learning Process (Training Phase):**
   - Use a Q-learning or Deep Q-Network (DQN) approach:

$$Q(s,a) \leftarrow Q(s,a) + \alpha \left[R(s,a) + \gamma \max_{a'} Q(s',a') - Q(s,a) \right] \tag{1}$$

     where α is the learning rate and γ is the discount factor.
4) **Adaptive Controller Placement:**
   - At each time step:
     - Observe the current network state s.
     - Select an action a (e.g., move a controller to a different location) based on the learned Q-values (e.g., using an ϵ-greedy strategy).
     - Apply the action and monitor the new state s'.
     - Calculate the reward based on the performance metrics (e.g., latency reduction and energy efficiency).
     - Update the Q-values based on the observed results.
5) **Dynamic Adjustment:**

Authorized licensed use limited to: University of Zululand. Downloaded on March 25,2026 at 01:19:26 UTC from IEEE Xplore. Restrictions apply.

- Periodically reassess the network state to determine whether the controllers should be reallocated or if additional controllers are needed to meet changing traffic demands.
- Implement a feedback loop for continuous learning, allowing the model to adapt to new traffic patterns.

6) **Convergence and Deployment:**
   - The algorithm converges when the Q-values stabilize, indicating that optimal or near-optimal controller placement decisions are being made.
   - Use the known pattern on the SDN controller to handle real-time dynamic transfer.

B. Reward functionality and importance in SDN controller installation

The reward function plays a pivotal role in guiding reinforcement learning-based methods for adaptive SDN controller placement. In this framework, the reward function balances critical objectives such as load balancing (weighted 0.2), energy efficiency (weighted 0.3), and time delay (weighted 0.5), reflecting the primary goals of reducing latency, conserving energy, and evenly distributing traffic among controllers. By assigning appropriate weights, the function ensures trade-offs are made to optimize overall network performance.

During the training phase, the reinforcement learning agent uses this reward function to evaluate its actions and refine placement strategies, progressively improving the network's performance. Post-training, the algorithm dynamically adjusts controller placement in real-world environments, adapting to live network conditions to maintain efficiency and scalability. The reward function's design ensures the approach is robust and aligned with modern SDN requirements, such as low latency, energy conservation, and traffic optimization. This makes it indispensable for scalable and future-ready SDN controller installation, enabling seamless integration with advanced technologies like 5G and edge computing. [1], [16].

The chosen reward function ensures that the algorithm considers trade-offs among multiple critical factors, and provides a robust and scalable method for controller placement in SDN environments

VI. Evaluation Metrics and Criteria

Evaluation metrics are important for evaluating the effectiveness of different controller placement strategies. IoT-specific research prioritizes key performance indicators (KPIs) such as latency, energy efficiency, and network flexibility [1], [4]. Due to limited resources in IoT environments, the emphasis is on reducing energy consumption while maintaining acceptable performance levels. Since many IoT applications are latency-sensitive, latency is considered a very important parameter [8].

In contrast, normal SDN learns more extensive search methods, where the matrix of [2], [6] etc. is introduced,



Fig. 1. Methodology of Proposed Solution.

especially in sdn-capable cases, especially in major -sdn-enabled, though the multi-control . Both emphasize latency as the deciding factor, however, other areas of focus differ. IoT studies prioritize flexibility and energy efficiency due to the specific features of IoT networks, while advanced SDN studies address broader issues such as fault tolerance, scalability, and dynamic capacity is handled [9].

VII. Evaluation and Simulation Parameters

Evaluating and simulating SDN controller placement strategies requires a well-defined set of metrics, configurations, and performance criteria. The key settings and parameters considered in our study are detailed in Table I. These parameters include network topology, controller parameters, traffic load, reward function weights, Q-learning/Deep Q-Network (reinforcement learning algorithm) parameters, performance metrics, convergence criteria, and the simulation environment.

VIII. Research Gaps and Proposed Enhancements

A. Dynamic and Real-Time Controller Placement

While optimization techniques are covered in the surveyed literature, there is a significant gap in the dynamic reconfiguration of controllers in response to real-time changes in network traffic, topology, and device behavior [1], [15]. This is particularly important in highly dynamic environments like IoT and edge computing.

Proposed Improvement: Implement a reinforcement learning-based adaptive controller placement mechanism that

Authorized licensed use limited to: University of Zululand. Downloaded on March 25,2026 at 01:19:26 UTC from IEEE Xplore. Restrictions apply.



Fig. 2. Comparison of Evaluation Metrics for SDN Controller Placement Strategies.

dynamically reallocates controllers in response to real-time network feedback. This approach would continuously learn and adapt, reducing latency and enhancing fault tolerance [10].

B. Energy-Efficient Controller Placement

Energy efficiency is crucial in IoT networks, yet many existing methods overlook energy constraints in favor of minimizing delay and fault tolerance [4], [16]. Incorporating energy-aware algorithms could significantly enhance the overall performance of IoT devices with limited battery life.

Proposed Improvement Develop an energy-aware controller placement algorithm that prioritizes energy consumption alongside latency, optimizing the management of battery-powered devices without compromising performance [8].

C. Multi-Domain Controller Placement

The complexity of distributing controllers across multiple administrative domains (e.g., different organizations or cloud providers) is discussed in some studies, but research on optimizing controller placement in multi-domain scenarios remains limited [13].

Proposed Improvement Implement a collaborative multi-domain SDN controller placement method that utilizes game theory or blockchain-based consensus mechanisms to ensure efficient coordination between domains [14].

IX. Future Work

The reviewed studies highlight several emerging trends and suggest directions for future research. IOT-Central Research talks about good management of the machine learning process as repetitive programming can configure the [10] sdn as the responsibility of the machine. does, his The research has also been [11].

There is growing interest in hybrid approaches combining AI, heuristic methods, optimal estimation and [2], [12] in SDN research in general The challenge of implementing controller placement techniques in 5G is edge computing environments, which introduces ultra-low latency and high throughput requirements at new levels of complexity, [13] In addition to being addressed, the integration of network function virtualization (NFV) and SDN can enable network infrastructure flexible and resilient [14] .

X. Conclusion

This review paper explores various approaches to the software-defined network (SDN) controller placement problem (CPP), with a particular focus on IoT-specific strategies and generalized SDN solutions. It focuses on the important role of optimization techniques in maximizing load balancing, and ensuring fault tolerance [1], [2], [7].

IoT-focused research emphasizes the importance of efficiently implementing flexible controller placement strategies, especially in environments where resources are complex

Authorized licensed use limited to: University of Zululand. Downloaded on March 25,2026 at 01:19:26 UTC from IEEE Xplore. Restrictions apply.

TABLE I
SIMULATION PARAMETERS

Category	Details
Network Topology	• **Number of switches (V):** 10 to 100 • **Number of links (E):** Based on network density (sparse, moderate, dense) • **Topology types:** Mesh, Ring, Star, Random, Fat-Tree (for data centers)
Controller Parameters	• **Number of controllers:** Start with 1, increase based on demand • **Controller placement options:** All potential nodes in V
Traffic Load	• **Traffic patterns:** Uniform, Gaussian, or real-world traffic traces • **Traffic volume:** Low, medium, high
Reward Function Weights	• **Latency:** 0.5 • **Energy efficiency:** 0.3 • **Load balancing:** 0.2
Q-learning/DQN Parameters	• **Learning rate (α):** 0.1 to 0.3 • **Discount factor (γ):** 0.9 • **Exploration rate (ϵ):** Start at 0.9, decay over time
Performance Metrics	• **Latency:** Average and maximum end-to-end delay • **Energy Consumption:** Total power usage by controllers and switches • **Load Distribution:** Variance or Gini coefficient of load across controllers
Convergence Criteria	• **Threshold for Q-value change:** 0.001 • **Maximum iterations:** 10,000 to 50,000 episodes
Simulation Environment	• **Simulator:** Mininet or ns-3 • **Reinforcement learning framework:** Python with TensorFlow or PyTorch for DQN

and dynamic [4], [15] On the other hand, general SDN solutions include fault tolerance for predictive establishment [2], [12], Emphasize broader concepts such as scalability and integration of machine learning models

Key research gaps identified including the need for dynamic real-time controller placement, energy efficiency techniques and multi-domain coordination In order to address this gap the paper uses reinforcement learning for adaptive placement, formulate strength awareness algorithms, collaborative multidomain -Strategies [10], [13], [14] and other proposed improvements

Overall, this paper highlights the importance of context-specific solutions for quality SDN systems. Future research should continue to explore AI-driven adaptive techniques, energy efficient design, and multi-domain collaboration that can further advance SDN capabilities in unique and universal contexts.It can help in increasing network performance, scalability, and fault tolerance in modern SDN deployments.

REFERENCES

[1] J. Kim, J. Kim, and S. Choi, "SDN Controller Placement in IoT Networks: An Optimisation Perspective," *IEEE Internet of Things Journal*, vol. 6, no. 3, pp. 4565-4576, June 2019.

[2] A. Khan, W. Kellerer, K. Kozu, and M. Yabusaki, "A Comprehensive Review of SDN Controller Placement Strategies," *IEEE Transactions on Network and Service Management*, vol. 15, no. 4, pp. 1573-1586, Dec. 2018.

[3] X. Hu, Y. Li, and M. Luo, "Dynamic Controller Placement in Software-Defined Networks with Latency Constraint," *IEEE Transactions on Network and Service Management*, vol. 12, no. 3, pp. 392-403, Sept. 2015.

[4] P. Medhi and A. Mohapatra, "An Efficient Heuristic Approach to SDN Controller Placement in IoT Networks," *IEEE Access*, vol. 7, pp. 143164-143176, Nov. 2019.

[5] B. K. Ryu and H. J. Chao, "A Scalable Approach for Optimal SDN Controller Placement," *Computer Networks*, vol. 91, pp. 381-396, Nov. 2015.

[6] S. R. Chowdhury, M. F. Bari, R. Ahmed, and R. Boutaba, "PayLess: A Low Cost Network Monitoring Framework for Software Defined Networks," *IEEE/ACM Transactions on Networking*, vol. 24, no. 5, pp. 2712-2725, Oct. 2016.

[7] Y. Li and M. Chen, "Software-Defined Network Function Virtualization: A Survey," *IEEE Access*, vol. 3, pp. 2542-2553, Nov. 2015.

[8] T. Luo, H. Tan, T. Quek, and W. Zhang, "Sensor OpenFlow: Enabling Software-Defined Wireless Sensor Networks," *IEEE Communications Letters*, vol. 16, no. 11, pp. 1896-1899, Nov. 2012.

[9] X. Xu, S. Zhao, and J. Zhao, "An Adaptive Controller Placement Strategy in Software-Defined Networks," *IEEE Internet of Things Journal*, vol. 7, no. 3, pp. 2018-2027, Mar. 2020.

[10] G. Sun, V. Anand, and A. Machuca, "A Survey of OpenFlow Technologies in Software Defined Networking," *IEEE Communications Surveys & Tutorials*, vol. 17, no. 4, pp. 2214-2241, Fourthquarter 2015.

[11] M. Al-Fares, S. Radhakrishnan, B. Raghavan, N. Huang, and A. Vahdat, "Hedera: Dynamic Flow Scheduling for Data Center Networks," in *Proc. USENIX NSDI*, Apr. 2010, pp. 19-19.

[12] F. Hu, Q. Hao, and K. Bao, "A Survey on Software-Defined Network and OpenFlow: From Concept to Implementation," *IEEE Communications Surveys & Tutorials*, vol. 16, no. 4, pp. 2181-2206, Fourthquarter 2014.

[13] R. Mijumbi, J. Serrat, J. L. Gorricho, S. Latré, M. Charalambides, and D. Lopez, "Management and Orchestration Challenges in Network Functions Virtualization," *IEEE Communications Magazine*, vol. 54, no. 1, pp. 98-105, Jan. 2016.

[14] K. K. Yap, M. Motiwala, M. Yu, W. Feamster, N. McKeown, and V. K. Sekar, "Separating Control and Data in Software-Defined Networks: A Survey," *Computer Networks*, vol. 57, no. 5, pp. 1206-1227, Apr. 2013.

Authorized licensed use limited to: University of Zululand. Downloaded on March 25,2026 at 01:19:26 UTC from IEEE Xplore. Restrictions apply.

[15] B. Heller, R. Sherwood, and N. McKeown, ”The Controller Placement Problem,” in *Proc. ACM SIGCOMM HotSDN*, Aug. 2012, pp. 7-12.

[16] M. Canini, D. Venzano, P. Peresini, D. Kostic, and J. Rexford, ”A NICE Way to Test OpenFlow Applications,” in *Proc. USENIX NSDI*, Apr. 2012, pp. 127-140.

[17] J. Uma, P. Vivekanandan, S Shankar, ”Optimized Intellectual Resource Scheduling using Deep Reinforcement Q-Learning in Cloud Computing”, Volume33, Issue5 in Transactions on Emerging Telecommunications Technologies, Wiley Publications with Impact factor:2.638

[18] V. A. Priya and Dr. Radhika N., “Performance comparison of SDN OpenFlow controllers”, International Journal of Computer Aided Engineering and Technology, vol. 11, no. 4-5, pp. 467-479, 2019.

[19] Dr. Radhika N., V., A., K.N., K., P., M., and N.C., S. Ram, “Dynamic bandwidth allocation in an sdn environment using qos queues and open flow”, International Journal of Pharmaceutical Research, vol. Vol. 12, no. 1, pp. 1060-1073, 2020.

[20] K. Nalinadevi, Sriram, S., Raahul, C., Raaj, H., and Sangeetha, B., “Server load balancing with path selection in virtualized software defined networks”, International Journal of Pure and Applied Mathematics, vol. 114, pp. 715-729, 2017.

Authorized licensed use limited to: University of Zululand. Downloaded on March 25,2026 at 01:19:26 UTC from IEEE Xplore. Restrictions apply.