The spin-transport documentation

Rico A.R. Picone*
Aug 28, 2017

Abstract

The *spin-transport* software (GitHub) is for the dynamic simulation of bulk spin transport—diffusion and separation—in solid media. The project is open-source and still in development.

Contents

1 Installation

This repository contains the (developing) open-source code for simulating bulk spin transportmdash;diffusion and separationmdash;in solid media. Multi-spin-species and magnetic resonance simulations are in development.

This is a [Python](https://www.python.org/) and [FEniCS](https://fenicsproject.org/) project. FEniCS is used to numerically solve the spin transport governing partial differential equations.

End users of this project write Python code to interface with FEniCS.

One must first have a working installation of FEniCS. This README assumes the use of [Docker](https://www.docker.com/) for installation, which is documented [here](http://fenics.readthedocs.io/projects/containers/en/latest/).

Then [clone](https://help.github.com/articles/cloning-a-repository/) this repository to the host machine.

The FEniCS docs have a section on [workflow](http://fenics.readthedocs.io/projects/containers/en/latest/work $_f$ lows.htmixsystem, thefollowing may be the easiest.

With the cloned spin-transport repository as your working directory, create a link in your path to **spin-transport**'s fenics executable bash script.

 $[\]hbox{``Email: rpicone@stmartin.edu. Department of Mechanical Engineering, Saint Martin's University.}$

"bash In fenics /usr/local/bin "

Now a FEniCS Python script foo.py can be started with the command fenics foo.py **from the host** instead of manually starting it from a Docker container. This has several advantages, including that there is no need to move scripts into the container and that the complicated syntax need not be remembered.

To verify that everything is installed correctly, run the Poisson equation demo ft01_poisson.py ([source](https://fenicsproject.org/pub/tutorial/html/.ftut1004.html))inyourcontainer.

If you installed the fenics bash script per the instructions above, you can use the following command (working directory: spin-transport).

"console fenicsft01poisson.py"

If everything is working fine, the output should look something like the following.

"console fenicsft01 $_p$ oisson.pyCallingDOLFINjust - in - time(JIT)compiler, thismaytakesometime. - - Instant: compiling - - CallingFFCjust - in - time(JIT)compiler, thismaytakesometime. CallingFFCjust - in - time(JIT)compiler, thismaytakesometime.

in-time(JIT) compiler, this may take sometime. Calling FFC just-in-time(JIT) compiler, this may take sometime in-time(JIT) compiler, this may take sometime. error L2 = 0.00823509807335 error max = 1.33226762955 e-15"'

The directory spin-transport/poisson should have been created and should contain two files: solution.pvd and solution000000.vtu. These files contain the solution data.

This work is supported by a grant from the Army Research Office, Materials Science Division under grant proposal **Nanoscale Spin Hyperpolarization and Imaging** <!TODO: grant number -> with PI [John Marohn, PhD](http://marohn.chem.cornell.edu/).
This project stems from a collaboration among three institutions:

[Cornell University (http://www.cornell.edu/),

[Saint Martin's University (https://www.stmartin.edu/), and the

[University of Washington (http://www.washington.edu/).

The lead contributor to this project is [Rico Picone, PhD](http://ricopic.one) of Saint Martin's University, co-PI on the ARO grant. Other contributors include [John Marohn, PhD](http://marohn.chem.cornell.edu/) (Cornell, PI), John A. Sidles, PhD (Washington), Joseph L. Garbini, PhD (Washington), and Corinne Isaac (Cornell).

2 Short theoretical introduction

References

[1] Jean-Philippe Grivet. Simulation of Magnetic Resonance Experiments. *American Journal of Physics*, 61(12):1133–1139, 1993.