A* Pathfinding Simulator: Multi-Agent Collaborative Pathfinding with Real-Time Visualization

Cameron Grenier
Wilfrid Laurier University
Ontario, Canada

***Abstract*—This paper presents a multi-agent A* pathfinding simulator implemented in C, where N agents concurrently navigate a shared 2D grid under fog of war with collision avoidance. The system employs a zone-based concurrency model using POSIX threads, partitioning the map into overlapping rectangular zones with per-zone mutexes for fine-grained locking and deadlock-free operation via global lock ordering. Automated testing confirms single-agent BFS-optimal paths and multi-agent overhead under $1.5\times$, while a 1,600-run scalability benchmark across grid sizes from 10×10 to 70×70 with up to 8 agents achieves a 100% success rate with only 9–16% path-length overhead over omniscient BFS, demonstrating the correctness and efficiency of the concurrent design.**

***Index Terms*—A* algorithm, multi-agent pathfinding, collision avoidance, POSIX threads, zone-based locking**

I. Introduction

This project implements a multi-agent A* pathfinding simulator in C. N agents concurrently navigate a shared 2D grid toward a common goal under fog of war (obstacles are discovered at runtime via a dual-map architecture), with collision avoidance (agents detect and route around each other), zone-based concurrency (the map is partitioned into overlapping rectangular zones, each with its own mutex/cond-var, for fine-grained locking), real-time ncurses visualization (a dedicated rendering thread with colour-coded cells and camera scrolling), an interactive menu system (file picker, random map generator, speed selector), and post-simulation analytics (elapsed time, per-agent step counts, full path histories).

II. System Architecture

A. Lifecycle

Fig. 1 shows the main thread's execution flow.



Fig. 1. Main thread lifecycle.

B. Modules

Table I lists the source modules.

C. Dual-Map Architecture

The simulator maintains two separate 2D `Node` arrays:

`actual_map` (ground truth)
: Built from the input file with all obstacles and neighbour pointers. Read-only after initialization. A* traverses this pointer graph for correct connectivity.

`shared_map` (collective knowledge)
: Initialized with only agent positions and the goal visible; all other cells start as `EMPTY`. Obstacles are written here at runtime when an agent discovers them. A* checks `shared_map` types for traversability but follows `actual_map` pointers for neighbours. The `type` field uses `_Atomic NodeType` for safe concurrent read-s/writes.

TABLE I
SOURCE MODULES AND THEIR RESPONSIBILITIES.

Module	Header	Responsibilities
`main.c`	–	Entry point; CLI argument parsing (`-speed`); lifecycle orchestration; global variables; `show_results()`; `cleanup_sim()`.
`map.c`	`map.h`	Input parsing; dual-map construction (`actual_map` vs. `shared_map`); neighbour linking; agent/goal placement; zone partitioning with 25% overlap; mutex/cond init per zone.
`astar.c`	`astar.h`	A* search; Manhattan heuristic; min-heap open set, flat `char` closed set, flat `Node*` came-from map; agent-cell penalty; `PathNode` linked-list reconstruction.
`runner.c`	`runner.h`	Agent thread entry (`runner()`); zone collection, dedup, sorted locking; collision detection/wait; path validation; obstacle discovery and broadcast; atomic map updates; path history; CLI signal; speed delay.
`cli.c`	`cli.h`	Rendering thread; ncurses with colour pairs; adaptive cell-width (3/2/1); camera scrolling; `pthread_cond_timedwait` signal-driven redraws.
`menu.c`	`menu.h`	Interactive ncurses menus; file picker (`opendir`/`readdir`); custom path input; random map generator; speed selector.
`heap.c`	`heap.h`	Min-heap for A* open set; dynamic resize (double on full, halve below 25%).
`types.c`	`types.h`	Core structs (`NodeType`, `Coords`, `Node`, `Agent`, `Zone`, `SimConfig`); `AStarNode`, `PathNode` in `astar.h`; `MinHeap` in `heap.h`.

III. A* ALGORITHM

A. Data Structures

```c
typedef struct {
    Node *node;  /* Pointer to node in actual_map */
    int g;       /* Cost from start to this node */
    int f;       /* Estimated total cost: g + h */
} AStarNode;

typedef struct PathNode {
    Node *node;            /* Pointer to node in actual_map */
    struct PathNode *next; /* Next node in path toward goal */
} PathNode;
```

Listing 1. AStarNode (astar.h:11–16) and PathNode (astar.h:21–25).

The open set is a binary min-heap of `AStarNode` values ordered by `f` (initial capacity 32, doubles on full, halves below 25%). The closed set is a flat `char` array (`rows × cols`, zero-initialized) giving $\mathcal{O}(1)$ lookup at 1 byte per cell. The came-from map is a flat `Node*` array indexed identically, enabling $\mathcal{O}(L)$ path reconstruction.

TABLE II
HEAP OPERATION COMPLEXITY.

Operation	Time	Amortized
`heap_push`	$\mathcal{O}(\log n)$	$\mathcal{O}(\log n)$
`heap_pop`	$\mathcal{O}(\log n)$	$\mathcal{O}(\log n)$
`heap_create`	$\mathcal{O}(1)$	–
Min access	$\mathcal{O}(1)$	–

B. Heuristic: Manhattan Distance

$$h(n) = |n_x - g_x| + |n_y - g_y| \tag{1}$$

On a 4-connected grid with uniform cost 1, Manhattan distance is both admissible ($h(n) \leq h^*(n)$, since the minimum moves between two cells equals the L1 distance) and consistent ($h(n) \leq c(n, n') + h(n')$, since each move changes one coordinate by ± 1). Consistency guarantees A* expands each node at most once and finds optimal paths.

C. Search Procedure

Algorithm 1 A* Search with Multi-Agent Modifications

Require: `start_node`,
globals: `goal_node`, `shared_map`, `rows`, `cols`
Ensure: `PathNode*` list from next-move to goal, or `NULL`

```
closed ← calloc(rows × cols)
from ← calloc(rows × cols)
open ← heap_create(32)
h_0 ← manhattan(start.pos, goal.pos)
push(open, {start, g=0, f=h_0})
while open.size ≠ 0 do
    curr ← pop(open) {lowest f}
    if curr.node = goal_node then
        return RECONSTRUCT(curr, from, start)
    end if
    closed[curr.y · cols + curr.x] ← 1
    for all n ∈ {up, down, left, right} do
        if n = NULL then
            continue {boundary}
        end if
        if closed[n.y · cols + n.x] then
            continue
        end if
        t ← shared_map[n.y][n.x].type
        if t = OBSTACLE then
            continue
        end if
        if t = AGENT ∧ n ≠ goal then
            g' ← curr.g + 10 {penalty}
        else
            g' ← curr.g + 1
        end if
        f' ← g' + manhattan(n, goal)
        push(open, {n, g', f'})
        from[n.y · cols + n.x] ← curr
    end for
end while
return NULL {no path found}
```

1) Multi-Agent Modifications:

1) Dual-map operation: A* traverses `actual_map` pointers for connectivity but reads `shared_map` types for traversability, so paths are constrained by current collective knowledge.
2) Agent-cell penalty ($g + 10$): Cells with type `AGENT` on `shared_map` are traversable but cost 10 instead of 1, biasing paths away from other agents while still allowing passage as a last resort.
3) Goal exception: The goal cell always costs 1 even if occupied by an agent.
4) No open-set duplicate detection: Simplifies the heap (no decrease-key) at the cost of occasional duplicate expansions, which is negligible for these grid sizes.

Path reconstruction traces backwards through `came_from`, building a linked list from goal to start, then strips the start node so the first `PathNode` is the agent's next move.

D. Complexity

Let $V = \text{rows} \times \text{cols}$.

TABLE III
A* ALGORITHM COMPLEXITY.

Resource	Complexity	Notes
Open set ops	$\mathcal{O}(V \log V)$	$\leq V$ push/pop
Closed set	$\mathcal{O}(V)$ total	$\mathcal{O}(1)$ each
Came-from	$\mathcal{O}(V)$ total	$\mathcal{O}(1)$ each
Path recon.	$\mathcal{O}(L)$	L = path len
Total time	$\mathcal{O}(V \log V)$	Heap-dominated
Space	$\mathcal{O}(V)$	All structures

Peak A* memory: closed set (V bytes) + came-from ($8V$ bytes on 64-bit) + heap ($16V$ bytes max) $\approx 25V$ bytes.

IV. MULTITHREADING

A. Thread Architecture

The simulator uses $N + 2$ threads: 1 main, 1 CLI renderer, and N agent threads. Fig. 2 illustrates the architecture.



Fig. 2. Thread architecture: 1 main + 1 CLI + N agent threads.

The main thread orchestrates the lifecycle: spawn all threads, join agents, signal and join CLI, display results, cleanup. The CLI thread redraws the grid when signalled by agent moves, using `pthread_cond_timedwait` with a 50ms timeout for keyboard responsiveness. Each agent thread independently runs A*, follows its path, handles obstacles and collisions, and records its history.

B. Zone-Based Locking

The map is divided into rectangular zones of size $\lfloor \text{cols}/5 \rfloor \times \lfloor \text{rows}/5 \rfloor$ (minimum 1), targeting roughly $5 \times 5 = 25$ zones. Each zone has its own mutex and condition variable:

```c
typedef struct {
    int id;
    pthread_mutex_t mutex;
    pthread_cond_t cond;
    Coords top_left;
    Coords bottom_right;
} Zone;
```

Listing 2. Zone structure (types.h:67–75).

1) 25% Overlap: Each zone's bounds are extended by 25% of the zone dimension in every direction (clamped to map edges):

$$\text{overlap}_x = \left\lfloor \frac{\text{zone_size}_x}{4} \right\rfloor, \quad \text{overlap}_y = \left\lfloor \frac{\text{zone_size}_y}{4} \right\rfloor \quad (2)$$

The overlap means an agent near a zone boundary can often lock a single zone covering both its current and next cells, reducing multi-zone lock frequency. It also extends the path validation window beyond the immediate next cell. A position near a boundary may belong to 1, 2, or 4 zones simultaneously.

2) Deadlock Prevention: All threads acquire zone mutexes in ascending zone ID order. Before each move, the agent:

1) Calls `collect_zones()` for all zones overlapping both current and next positions.
2) Deduplicates the zone set.
3) Sorts by `id` ascending (insertion sort, at most 8 elements).
4) Acquires mutexes in ascending order; releases in descending order.

Theorem 1 (Deadlock Freedom): Since all threads acquire zone mutexes in the same total order (ascending zone ID), no circular-wait condition can arise. The timed waits (`pthread_cond_timedwait`) provide additional liveness: even if a signal is missed, agents wake up, release locks, and replan.

```
static void lock_zones(Zone *zs[], int n) {
    for (int i = 0; i < n; i++)
        pthread_mutex_lock(&zs[i]->mutex);
}
```

Listing 3. Lock acquisition in ascending order (runner.c:133–137).

C. Agent Thread Logic

Fig. 3 shows the per-step decision flow.

1) Collision Detection: When the next cell on `shared_map` is occupied by another agent, the agent releases all held zones except the blocking zone, calls `pthread_cond_timedwait` on that zone's condvar with a speed-scaled timeout, then releases the last lock and replans. The timeout matches `speed_delay` (or 5ms at realtime speed) to prevent both premature replanning and indefinite blocking.

2) Path Validation: After confirming the next cell is not agent-occupied, the runner validates the remaining path within the locked zone region:

```
PathNode *check = next_move->next;
int valid_path = 1;
while (check != NULL) {
    int in_locked = 0;
    for (int z = 0; z < nlocked; z++) {
        if (within_zone(locked[z], check->node))
            {
            in_locked = 1;
            break;
        }
    }
    if (!in_locked) break;
    NodeType type = shared_map[check->node->pos.y
        ]
                                [check->node->pos.x
                                    ].type;
    if (type == OBSTACLE || type == AGENT) {
        valid_path = 0;
        break;
    }
    check = check->next;
}
```

Listing 4. Path validation (runner.c:244–268).

Validation stops at cells outside the locked zones since those are not protected by held locks. If any cell within the locked region is blocked, the agent unlocks and replans.

3) Obstacle Discovery: If the next cell is `OBSTACLE` on `actual_map` (but `EMPTY` on `shared_map`), the agent writes `OBSTACLE` to `shared_map`, unlocks all zones, broadcasts `map_changed_cond` to wake all agents, and replans. This broadcast is the primary collaborative communication channel.

4) Move Execution: On a valid move, both source and destination cells are updated under all relevant zone locks:

```
Node *next_node = next_move->node;
shared_map[current_node->pos.y]
          [current_node->pos.x].type = EMPTY;
if (nodes_equal(next_node, goal_node)) {
    shared_map[next_node->pos.y]
              [next_node->pos.x].type = GOAL;
} else {
    shared_map[next_node->pos.y]
              [next_node->pos.x].type = AGENT;
}
```

Listing 5. Atomic map update (runner.c:291–300).

No other agent can observe a partially-completed move. Two agents never occupy the same cell because the check and update are performed atomically under the same locks.



Fig. 3. Agent thread per-step decision flow.

TABLE IV
CONDITION VARIABLES.

Variable	Scope	Purpose
`zone.cond`	Per-zone	Wakes agents blocked on a cell in this zone after another agent moves.
`map_changed_cond`	Global	Broadcasts on obstacle discovery, waking all agents to replan.
`cli_cond`	Global	Signals the CLI thread to redraw after each agent move.

TABLE V
ATOMIC VARIABLES.

Variable	Type	Purpose
`cli_done`	`atomic_int`	Set to 1 by main after agents finish; CLI checks to exit.
`cli_update_seq`	`atomic_uint`	Counter incremented by agents; CLI compares to detect redraws.
`Node.type`	`_Atomic NodeType`	Atomic cell type prevents data races.

D. Condition Variables and Atomics

V. CLI AND VISUALIZATION

A. Invocation

- Interactive: `./astar` launches the ncurses menu.
- CLI: `./astar <file> [-speed <level>]` skips the menu.

TABLE VI
SPEED OPTIONS.

Level	Delay / step	`usleep` value
`slow`	500 ms	500 000 μs
`medium`	100 ms	100 000 μs
`fast`	20 ms	20 000 μs
`realtime`	0 ms	0 μs

B. Menu System

The file picker scans `input/` for `.txt` files and displays them with arrow-key navigation. Two special options allow entering a custom path or generating a random map (configurable rows, cols, agent count; ~15% obstacle density; agents capped at $\min(\text{rows} \times \text{cols}/10,\ 100)$). The speed picker presents the four levels from Table VI.

C. Rendering

TABLE VII
CELL TYPE RENDERING.

Cell Type	Symbol	Appearance
`EMPTY`	`.`	Dim white on default
`OBSTACLE`	(space)	White on white (solid)
`AGENT`	`A`	Bold white on red
`GOAL`	`G`	Bold black on green

Cell width adapts to terminal size (3, 2, or 1 characters). For maps exceeding the terminal even at width 1,

arrow keys scroll a virtual camera. The rendering loop uses `pthread_cond_timedwait` (50ms timeout) to sleep until signalled, avoiding busy-waiting while staying responsive to keyboard input.

After all agents finish, a results screen shows elapsed time (`CLOCK_MONOTONIC`), per-agent step counts and full coordinate histories, with scrolling and a run-again/quit prompt.

VI. Input Format and Map Construction

```
<rows> <cols>
<num_agents>
<agent_0_x> <agent_0_y>
<agent_1_x> <agent_1_y>
...
<goal_x> <goal_y>
<grid row rows-1>      (top row visually)
<grid row rows-2>
...
<grid row 0>           (bottom row visually)
```

Listing 6. Input file structure.

Grid characters: `0` = empty, `1` = obstacle. Coordinates are zero-indexed from the bottom-left. Grid rows are listed top-to-bottom visually (decreasing y).

The `init()` function in `map.c` parses dimensions, agents, and goal; builds `actual_map` with obstacle types and neighbour pointers; builds `shared_map` (all `EMPTY` except agents and goal, no neighbour pointers); and partitions into zones with mutex/cond initialization.

VII. Memory Management

All dynamic memory follows strict allocation/deallocation pairing. The `path_history` buffer uses geometric doubling (initial capacity 64) for amortized $\mathcal{O}(1)$ appends.

TABLE VIII
MEMORY ALLOCATION AND DEALLOCATION.

Resource	Allocator	Deallocator
`actual_map` rows	`malloc` in `init()`	`free` in `cleanup_sim()`
`shared_map` rows	`malloc` in `init()`	`free` in `cleanup_sim()`
Agent array	`malloc` in `init()`	`free` in `cleanup_sim()`
`path_history` per agent	`realloc` in `append_path()`	`free` in `cleanup_sim()`
Zone array	`malloc` in `init()`	`free` in `cleanup_sim()`
Thread handle array	`malloc` in `main()`	`free` in `cleanup_sim()`
A* closed set	`calloc` in `a_star()`	`free` before return
A* came-from map	`calloc` in `a_star()`	`free` before return
A* open set heap	`malloc` in `heap_create()`	`heap_free()` before return
PathNode linked list	`malloc` per node in `a_star()`	`free_path()` or per-node `free` in runner
Zone mutexes/conds	`pthread_mutex_init`	`pthread_mutex_destroy` in `cleanup_sim()`

VIII. BUILD SYSTEM

```
CC = clang
CFLAGS = -g -Wall -Wextra -fcolor-diagnostics
         -fansi-escape-codes -I./include
LDFLAGS = -lm -lpthread -lncurses

ifdef ASAN
  CFLAGS  += -fsanitize=address
  LDFLAGS += -fsanitize=address
endif

SRC = src/main.c src/map.c src/astar.c src/runner
    .c
      src/cli.c src/heap.c src/types.c src/menu.c
TARGET = astar

$(TARGET): $(SRC)
    $(CC) $(CFLAGS) $(SRC) -o $(TARGET) $(LDFLAGS
        )

clean:
    rm -f $(TARGET)
```

Listing 7. Makefile.

Flags: `-g` for debug symbols, `-Wall -Wextra` for strict warnings, optional `make ASAN=1` for AddressSanitizer. Links `-lm`, `-lpthread`, `-lncurses`.

IX. TESTING AND PERFORMANCE ANALYSIS

A. Test Framework

The test harness (`tests/test_pathfinding.c`) reuses the core modules without `ncurses`, running headlessly. For each scenario it computes a BFS ground-truth shortest path on the full `actual_map`, then runs the multi-agent simulation at maximum speed. Each agent's actual path length is compared against BFS-optimal; a test passes if every agent reaches the goal. A 60-second `SIGALRM` watchdog catches deadlocks.

B. Test Cases

TABLE IX
TEST CASE CONFIGURATIONS.

Test	Grid	Agents	Start Positions	Goal	Obstacle Pattern
1	8×8	1	$(0, 0)$	$(7, 7)$	Staircase diagonal walls
2	10×10	2	$(0, 0)$, $(9, 0)$	$(5, 9)$	Central rectangular box
3	12×12	3	$(0, 0)$, $(11, 0)$, $(6, 0)$	$(6, 11)$	Horizontal wall with gap at x=5
4	14×14	4	Corners: $(0, 0)$, $(13, 0)$, $(0, 13)$, $(13, 13)$	$(7, 7)$	Rectangular ring around goal with y=7 gaps

C. Results

Multi-agent path lengths vary between runs due to thread scheduling nondeterminism. Values below are representative.

TABLE X
TEST RESULTS (REPRESENTATIVE RUN).

Test	Agt	BFS	Actual	Ovhd	Status
1-Agent	0	14	14	$1.00\times$	PASS
2-Agents	0	14	18	$1.29\times$	PASS
2-Agents	1	13	17	$1.31\times$	PASS
3-Agents	0	17	19	$1.12\times$	PASS
3-Agents	1	16	18	$1.13\times$	PASS
3-Agents	2	13	15	$1.15\times$	PASS
4-Agents	0	14	17	$1.21\times$	PASS
4-Agents	1	13	16	$1.23\times$	PASS
4-Agents	2	13	16	$1.23\times$	PASS
4-Agents	3	12	17	$1.42\times$	PASS

D. Aggregate Path-Length Comparison



Fig. 4. BFS-optimal vs. model-actual total path lengths per test scenario.

E. Analysis

The 1-agent test achieves exact BFS-optimal ($1.00\times$), confirming A* correctness independent of concurrency. Multi-agent overhead comes from four sources: fog-of-war replanning when obstacles are discovered, collision avoidance detours ($g + 10$ penalty routes around agents), thread scheduling nondeterminism affecting collision patterns, and zone lock contention forcing suboptimal detours. Average per-agent overhead stays under $1.5\times$ across all scenarios.

F. Scalability Benchmark

A dedicated benchmark harness generates random grids ($\approx$15% obstacle density, BFS-verified solvability), crosses 4 grid sizes (10, 30, 50, 70) with 4 agent counts (1, 2, 4, 8) for 16 configurations, and runs 100 iterations each (1,600 total simulations) at maximum speed with `CLOCK_MONOTONIC` timing. A 30-second per-run timeout guards against deadlock.

TABLE XI
SCALABILITY BENCHMARK RESULTS (100 ITERATIONS PER CONFIGURATION).

Grid	Agents	Avg ms	Min ms	Max ms	Avg Actual	Avg Optimal	Overhead	Pass
10	1	0.05	0.02	0.12	7.6	6.8	1.09×	100%
10	2	10.11	0.03	1005.30	16.1	14.3	1.10×	100%
10	4	0.08	0.05	0.17	29.6	26.8	1.10×	100%
10	8	10.18	0.09	1005.28	63.2	55.7	1.14×	100%
30	1	0.11	0.02	0.41	23.4	20.3	1.13×	100%
30	2	0.14	0.04	0.63	45.2	39.4	1.14×	100%
30	4	0.22	0.08	0.64	92.5	80.4	1.15×	100%
30	8	0.31	0.15	0.82	182.2	162.2	1.12×	100%
50	1	0.27	0.02	1.78	38.8	34.0	1.16×	100%
50	2	0.43	0.07	4.89	76.3	65.9	1.16×	100%
50	4	0.59	0.11	2.49	156.2	135.3	1.15×	100%
50	8	0.89	0.26	2.68	314.9	279.2	1.13×	100%
70	1	0.62	0.03	6.18	56.0	47.9	1.15×	100%
70	2	1.08	0.06	6.50	118.5	101.9	1.16×	100%
70	4	1.51	0.16	10.43	230.1	198.5	1.16×	100%
70	8	1.92	0.51	5.57	458.6	399.6	1.15×	100%



Fig. 5. Average simulation time vs. grid size (outlier-free[1]).



Fig. 6. Path-length overhead ratio vs. agent count, by grid size.

1) Benchmark Analysis: Timing: Average time scales roughly with grid area (quadratic in dimension), consistent with $\mathcal{O}(V \log V)$ A* complexity. The largest configuration (70 × 70, 8 agents) averages 1.92ms. Time increases sub-linearly with agent count on larger grids because agents in different zones run concurrently.

Overhead: Ratios are consistently 1.09–1.16× across all 16 configurations. Fog of war plus collision avoidance adds only 9–16% extra steps over omniscient BFS. Overhead does not increase significantly with more agents because the shared map means one agent's obstacle discovery immediately benefits all others.

Small-grid anomaly: The 10 × 10 grids with 2 and 8 agents showed elevated max times because agents frequently block each other's only viable paths, triggering the 5ms `pthread_cond_timedwait` timeout. This is expected behavior, not a bug. Min times (0.03ms, 0.09ms) confirm typical runs complete in microseconds.

Concurrency efficiency: On 70×70 grids, 8 agents complete in 1.92ms average, only 3.1× slower than 1 agent (0.62ms) despite 8× the workload. Agents in different zones run with minimal lock contention.

Success rate: All 1,600 simulations passed with no deadlocks, no stuck agents, and no timeouts.

X. SUMMARY

This simulator implements multi-agent A* pathfinding with fog of war, zone-based concurrency, and real-time ncurses visualization. Automated testing confirms single-agent BFS-optimal paths and multi-agent overhead under 1.5×. The 1,600-run scalability benchmark achieved a 100% success rate with 9–16% overhead across all grid sizes and agent counts, validating the correctness and efficiency of the concurrent design.

REFERENCES

[1] P. E. Hart, N. J. Nilsson, and B. Raphael, "A formal basis for the heuristic determination of minimum cost paths," *IEEE Trans. Syst. Sci. Cybern.*, vol. SSC-4, no. 2, pp. 100–107, Jul. 1968.

[2] IEEE and The Open Group, "POSIX.1-2017 – IEEE Std 1003.1-2017," 2018. [Online]. Available: https://pubs.opengroup.org/onlinepubs/9699919799/

[1]The 10×10 configurations with 2 and 8 agents had occasional timing spikes from `pthread_cond_timedwait` timeouts on congested small grids. Min times (0.03ms and 0.09ms) are used for those data points.

[3] T. Dickey, “ncurses – CRT screen handling and optimization package,” 2024. [Online]. Available: https://invisible-island.net/ncurses/
[4] D. Silver, “Cooperative pathfinding,” in *Proc. 1st Artif. Intell. Interactive Digital Entertain. Conf. (AIIDE)*, 2005, pp. 117–122.
[5] G. Sharon, R. Stern, A. Felner, and N. R. Sturtevant, “Conflict-based search for optimal multi-agent pathfinding,” *Artif. Intell.*, vol. 219, pp. 40–66, 2015.