MEASUREMENT/ADJUSTMENT VALUE INPUT SHEET [FW6A-EL/FW6AX-EL]

id0517006653z3

Differential Backlash Measurement/Adjustment

Symbol	Item	Formula	Unit	First time		Second time		Third time	
A	FRONT SIDE GEAR AND PINION GEAR BACKLASH	—	mm {in}						
B	REAR SIDE GEAR AND PINION GEAR BACKLASH	—	mm {in}						
C	FRONT DIFFERENTIAL BACKLASH	Average value of A	mm {in}						
D	REAR DIFFERENTIAL BACKLASH	Average value of B	mm {in}						
E	STANDARD DIFFERENTIAL BACKLASH	—	mm {in}	0.030—0.150 {0.0012—0.0059}					
F	MEASUREMENT RESULT OF FRONT DIFFERENTIAL BACKLASH	—	mm {in}	OK/NG		OK/NG		OK/NG	
G	MEASUREMENT RESULT OF REAR DIFFERENTIAL BACKLASH	—	mm {in}	OK/NG		OK/NG		OK/NG	
H	THICKNESS OF REMOVED FRONT THRUST WASHER	—	mm {in}						
I	THICKNESS OF REMOVED REAR THRUST WASHER	—	mm {in}						
J	MEDIAN VALUE OF DIFFERENTIAL BACKLASH SPECIFICATION	—	mm {in}	0.090 {0.00354}					
K	FRONT DIFFERENTIAL BACKLASH GAP	C - J	mm {in}						
L	REAR DIFFERENTIAL BACKLASH GAP	D - J	mm {in}						
M	FRONT THRUST WASHER THICKNESS GAP	K × 0.1 mm {0.00394 in} / 0.08 mm {0.00315 in}	mm {in}						
N	REAR THRUST WASHER THICKNESS GAP	L × 0.1 mm {0.00394 in} / 0.08 mm {0.00315 in}	mm {in}						
O	THICKNESS OF OPTIMUM FRONT THRUST WASHER	H + M	mm {in}						
P	THICKNESS OF OPTIMUM REAR THRUST WASHER	I + N	mm {in}						

azzzcw00000074

Description example

Symbol	Item	Formula	Unit	First time		Second time		Third time	
A	FRONT SIDE GEAR AND PINION GEAR BACKLASH	—	mm {in}	0.160 {0.00630}	0.170 {0.00669}	0.110 {0.00433}	0.100 {0.00394}		
B	REAR SIDE GEAR AND PINION GEAR BACKLASH	—	mm {in}	0.160 {0.00630}	0.150 {0.00591}	0.085 {0.00335}	0.075 {0.00295}		
C	FRONT DIFFERENTIAL BACKLASH	Average value of A	mm {in}	0.165 {0.00650}		0.105 {0.00413}			
D	REAR DIFFERENTIAL BACKLASH	Average value of B	mm {in}	0.155 {0.00610}		0.080 {0.00315}			
E	STANDARD DIFFERENTIAL BACKLASH	—	mm {in}	0.030—0.150 {0.0012—0.0059}					
F	MEASUREMENT RESULT OF FRONT DIFFERENTIAL BACKLASH	—	mm {in}	OK/(NG)		(OK)/NG		OK/NG	
G	MEASUREMENT RESULT OF REAR DIFFERENTIAL BACKLASH	—	mm {in}	OK/(NG)		(OK)/NG		OK/NG	
H	THICKNESS OF REMOVED FRONT THRUST WASHER	—	mm {in}	0.810 {0.03189}					
I	THICKNESS OF REMOVED REAR THRUST WASHER	—	mm {in}	0.795 {0.0313}					
J	MEDIAN VALUE OF DIFFERENTIAL BACKLASH SPECIFICATION	—	mm {in}	0.090 {0.00354}					
K	FRONT DIFFERENTIAL BACKLASH GAP	C - J	mm {in}	0.075 {0.00295}					
L	REAR DIFFERENTIAL BACKLASH GAP	D - J	mm {in}	0.065 {0.00256}					
M	FRONT THRUST WASHER THICKNESS GAP	K × 0.1 mm {0.00394 in} / 0.08 mm {0.00315 in}	mm {in}	0.094 {0.00369}					
N	REAR THRUST WASHER THICKNESS GAP	L × 0.1 mm {0.00394 in} / 0.08 mm {0.00315 in}	mm {in}	0.081 {0.00320}					
O	THICKNESS OF OPTIMUM FRONT THRUST WASHER	H + M	mm {in}	0.904 {0.03559}					
P	THICKNESS OF OPTIMUM REAR THRUST WASHER	I + N	mm {in}	0.876 {0.03449}					

bfw2za00000003

High Clutch Clearance Measurement/Adjustment

cardiagn.com

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}			
B	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}			
C	HIGH CLUTCH CLEARANCE	A - B	mm {in}			
D	HIGH CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.300—1.500 {0.05119—0.05905}		
E	MEASUREMENT RESULT OF HIGH CLUTCH CLEARANCE	—	mm {in}	OK/NG	OK/NG	OK/NG
F	THICKNESS OF REMOVED SNAP RING	—	mm {in}			
G	RANGE	C + F	mm {in}			

azzzcw00000066

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}	1.605 {0.06319}	1.245 {0.04902}	
B	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}	0.055 {0.00217}	-0.090 {-0.00354}	
C	HIGH CLUTCH CLEARANCE	A - B	mm {in}	1.550 {0.06102}	1.335 {0.05256}	
D	HIGH CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.300—1.500 {0.05119—0.05905}		
E	MEASUREMENT RESULT OF HIGH CLUTCH CLEARANCE	—	mm {in}	OK/(NG)	(OK)/NG	OK/NG
F	THICKNESS OF REMOVED SNAP RING	—	mm {in}	1.615 {0.06358}		
G	RANGE	C + F	mm {in}	3.165 {0.12461}		

azzzcw00000067

Low Clutch Clearance Measurement/Adjustment

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	WEIGHT OF WEIGHT	—	N {kgf, lbf}			
B	CORRECTION VALUE OF LOW CLUTCH CLEARANCE (WEIGHT OF UNIT N)	(A - 98 N) × 0.00157 mm {0.0000618 in}	mm {in}			
	CORRECTION VALUE OF LOW CLUTCH CLEARANCE (WEIGHT OF UNIT kgf)	(A - 9.99 kgf) × 0.01537 mm {0.0006051 in}	mm {in}			
	CORRECTION VALUE OF LOW CLUTCH CLEARANCE (WEIGHT OF UNIT lbf)	(A - 22.03 lbf) × 0.00698 mm {0.0002748 in}	mm {in}			
C	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}			
D	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}			
E	LOW CLUTCH CLEARANCE	C - D - B	mm {in}			
F	LOW CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.400—1.600 {0.05512—0.06299}		
G	MEASUREMENT RESULT OF LOW CLUTCH CLEARANCE	—	mm {in}	OK/NG	OK/NG	OK/NG
H	THICKNESS OF REMOVED SNAP RING	—	mm {in}			
I	RANGE	E + H	mm {in}			

bfw2za00000018

carmagn.com

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	WEIGHT OF WEIGHT	—	N {kgf, lbf}	150 {15.30, 33.72}	150 {15.30, 33.72}	
B	CORRECTION VALUE OF LOW CLUTCH CLEARANCE (WEIGHT OF UNIT N)	(A - 98 N) × 0.00157 mm {0.0000618 in}	mm {in}	0.0816 {0.00321}	0.0816 {0.00321}	
	CORRECTION VALUE OF LOW CLUTCH CLEARANCE (WEIGHT OF UNIT kgf)	(A - 9.99 kgf) × 0.01537 mm {0.0006051 in}	mm {in}			
	CORRECTION VALUE OF LOW CLUTCH CLEARANCE (WEIGHT OF UNIT lbf)	(A - 22.03 lbf) × 0.00698 mm {0.0002748 in}	mm {in}			
C	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}	2.320 {0.09134}	2.115 {0.08327}	
D	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}	0.595 {0.02343}	0.480 {0.01890}	
E	LOW CLUTCH CLEARANCE	C - D - B	mm {in}	1.6434 {0.064701}	1.5534 {0.061158}	
F	LOW CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.400—1.600 {0.05512—0.06299}		
G	MEASUREMENT RESULT OF LOW CLUTCH CLEARANCE	—	mm {in}	OK/(NG)	(OK)/NG	OK/NG
H	THICKNESS OF REMOVED SNAP RING	—	mm {in}	1.705 {0.06713}		
I	RANGE	E + H	mm {in}	3.3484 {0.13183}		

bfw2za00000019

R-3-5 Brake Clearance Measurement/Adjustment

Symbol	Item	Formula	Unit	First time
A	RETAINER THICKNESS OF SPRINGS AND RETAINER COMPONENT	—	mm{in}	
B	DIAL GAUGE VALUE WITH R-3-5 BRAKE PISTON OPERATED	—	mm{in}	
C	DIAL GAUGE VALUE WITHOUT R-3-5 BRAKE PISTON OPERATED	—	mm{in}	
D	R-3-5 BRAKE CLEARANCE ADJUSTMENT VALUE	B - C	mm{in}	
E	THICKNESS OF SNAP RING (FZ01 19 469) FOR R-3-5 BRAKE CLEARANCE MEASUREMENT/ ADJUSTMENT	—	mm{in}	
F	RANGE	D + E - A	mm{in}	

azzzcw00000072

Description example

Symbol	Item	Formula	Unit	First time
A	RETAINER THICKNESS OF SPRINGS AND RETAINER COMPONENT	—	mm{in}	1.225 {0.04823}
B	DIAL GAUGE VALUE WITH R-3-5 BRAKE PISTON OPERATED	—	mm{in}	2.280 {0.08976}
C	DIAL GAUGE VALUE WITHOUT R-3-5 BRAKE PISTON OPERATED	—	mm{in}	0.205 {0.00807}
D	R-3-5 BRAKE CLEARANCE ADJUSTMENT VALUE	B - C	mm{in}	2.075 {0.08169}
E	THICKNESS OF SNAP RING (FZ01 19 469) FOR R-3-5 BRAKE CLEARANCE MEASUREMENT/ ADJUSTMENT	—	mm{in}	2.625 {0.10335}
F	RANGE	D + E - A	mm{in}	3.475 {0.13681}

azzzcw00000073

2-6 Brake Clearance Measurement/Adjustment

cardiagn.com

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	RETAINER THICKNESS OF SPRINGS AND RETAINER COMPONENT	—	mm {in}		←	←
B	DISTANCE A	—	mm {in}			
C	AVERAGE VALUE OF DISTANCE A	Average value of B	mm {in}			
D	2-6 BRAKE CLEARANCE	C - A	mm {in}			
E	2-6 BRAKE CLEARANCE SPECIFICATION	—	mm {in}	0.960—1.160 {0.0378—0.0417}		
F	MEASUREMENT RESULT OF 2-6 BRAKE CLEARANCE	—	mm {in}	OK/NG	OK/NG	OK/NG
G	THICKNESS OF REMOVED RETAINING PLATE	—	mm {in}			
H	RANGE	D + G	mm {in}			

bfw2za00000020

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	RETAINER THICKNESS OF SPRINGS AND RETAINER COMPONENT	—	mm {in}	1.425 {0.05610}	←	←
B	DISTANCE A	—	mm {in}	2.675 {0.10532} / 2.650 {0.10433} / 2.665 {0.10492} / 2.670 {0.10512}	2.580 {0.10157} / 2.555 {0.10059} / 2.560 {0.10079} / 2.565 {0.10098}	
C	AVERAGE VALUE OF DISTANCE A	Average value of B	mm {in}	2.665 {0.10492}	2.565 {0.10098}	
D	2-6 BRAKE CLEARANCE	C - A	mm {in}	1.240 {0.04882}	1.140 {0.04488}	
E	2-6 BRAKE CLEARANCE SPECIFICATION	—	mm {in}	0.960—1.160 {0.0378—0.0417}		
F	MEASUREMENT RESULT OF 2-6 BRAKE CLEARANCE	—	mm {in}	OK/(NG)	(OK)/NG	OK/NG
G	THICKNESS OF REMOVED RETAINING PLATE	—	mm {in}	2.015 {0.07933}		
H	RANGE	D + G	mm {in}	3.255 {0.12815}		

bfw2za00000021

Low and Reverse Brake Clearance Measurement/Adjustment

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}			
B	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}			
C	LOW AND REVERSE BRAKE CLEARANCE	A - B	mm {in}			
D	AVERAGE VALUE OF LOW AND REVERSE BRAKE CLEARANCE	Average value of C	mm {in}			
E	LOW AND REVERSE BRAKE CLEARANCE SPECIFICATION	—	mm {in}	1.500—1.700 {0.05906—0.06692}		
F	MEASUREMENT RESULT OF LOW AND REVERSE BRAKE CLEARANCE	—	mm {in}	OK/NG	OK/NG	OK/NG
G	THICKNESS OF REMOVED SNAP RING	—	mm {in}			
H	RANGE	D + G	mm {in}			

bfw2za00000022

cardiagn.com

Description example

Symbol	Item	Formula	Unit	First time				Second time				Third time			
A	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}	2.470 {0.09724}	2.665 {0.10492}	2.070 {0.08150}	1.840 {0.07244}	1.570 {0.06181}	1.845 {0.07264}	1.695 {0.06673}	1.760 {0.06929}				
B	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}	0.595 {0.02343}	0.765 {0.03012}	0.205 {0.00807}	-0.035 {-0.00138}	-0.105 {-0.00413}	0.155 {0.00610}	0.010 {0.00039}	0.090 {0.00354}				
C	LOW AND REVERSE BRAKE CLEARANCE	A - B	mm {in}	1.875 {0.07382}	1.900 {0.07480}	1.865 {0.07343}	1.875 {0.07382}	1.675 {0.06594}	1.690 {0.06654}	1.685 {0.06634}	1.670 {0.06575}				
D	AVERAGE VALUE OF LOW AND REVERSE BRAKE CLEARANCE	Average value of C	mm {in}	1.879 {0.07398}				1.680 {0.06614}							
E	LOW AND REVERSE BRAKE CLEARANCE SPECIFICATION	—	mm {in}	1.500—1.700 {0.05906—0.06692}											
F	MEASUREMENT RESULT OF LOW AND REVERSE BRAKE CLEARANCE	—	mm {in}	OK/(NG)				(OK)/NG				OK/NG			
G	THICKNESS OF REMOVED SNAP RING	—	mm {in}	2.305 {0.09075}											
H	RANGE	D + G	mm {in}	4.184 {0.16472}											

bfw2za00000023

Secondary Gear and Output Gear Preload Measurement/Adjustment [FW6A-EL]

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	ANGULAR CONTACT BALL BEARING PRELOAD	—	N·m {kgf·cm, in·lbf}		←	←
B	TOTAL PRELOAD	—	N·m {kgf·cm, in·lbf}			
C	SECONDARY GEAR AND OUTPUT GEAR PRELOAD	B - A	N·m {kgf·cm, in·lbf}			
D	SECONDARY GEAR AND OUTPUT GEAR PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.8—3.7 {28.6—37.7, 24.8—32.7}		
E	MEASUREMENT RESULT OF SECONDARY GEAR AND OUTPUT GEAR PRELOAD	—	—	OK/NG	OK/NG	OK/NG
F	THICKNESS OF REMOVED SHIM	—	mm {in}			
G	MEDIAN VALUE OF SECONDARY GEAR AND OUTPUT GEAR PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	3.25 {33.1, 28.7}		
H	PRELOAD GAP	G - C	N·m {kgf·cm, in·lbf}			
I	SHIM THICKNESS GAP	H × 0.1 mm {0.00394 in} / 1.6 N·m {16.3 kgf·cm, 14.1 in·lbf}	mm {in}			
J	THICKNESS OF OPTIMUM SHIM	F + I	mm {in}			

azzzcw00000076

cardiagn.com

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	ANGULAR CONTACT BALL BEARING PRELOAD	—	N·m {kgf·cm, in·lbf}	1.2 {12.2, 10.6}	←	←
B	TOTAL PRELOAD	—	N·m {kgf·cm, in·lbf}	3.7 {37.7, 32.7}	4.4 {44.8, 38.9}	
C	SECONDARY GEAR AND OUTPUT GEAR PRELOAD	B - A	N·m {kgf·cm, in·lbf}	2.5 {25.5, 22.1}	3.2 {32.6, 28.3}	
D	SECONDARY GEAR AND OUTPUT GEAR PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.8—3.7 {28.6—37.7, 24.8—32.7}		
E	MEASUREMENT RESULT OF SECONDARY GEAR AND OUTPUT GEAR PRELOAD	—	—	OK/(NG)	(OK)/NG	OK/NG
F	THICKNESS OF REMOVED SHIM	—	mm {in}	0.855 {0.03366}		
G	MEDIAN VALUE OF SECONDARY GEAR AND OUTPUT GEAR PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	3.25 {33.1, 28.7}		
H	PRELOAD GAP	G - C	N·m {kgf·cm, in·lbf}	0.75 {7.6, 6.6}		
I	SHIM THICKNESS GAP	H × 0.1 mm {0.00394 in} / 1.6 N·m {16.3 kgf·cm, 14.1 in·lbf}	mm {in}	0.047 {0.00185}		
J	THICKNESS OF OPTIMUM SHIM	F + I	mm {in}	0.902 {0.03551}		

azzzcw00000077

Secondary Gear and Output Gear Preload Measurement/Adjustment [FW6AX-EL]

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	ANGULAR CONTACT BALL BEARING PRELOAD	—	N·m {kgf·cm, in·lbf}		←	←
B	TOTAL PRELOAD	—	N·m {kgf·cm, in·lbf}			
C	SECONDARY GEAR AND OUTPUT GEAR PRELOAD	B - A	N·m {kgf·cm, in·lbf}			
D	SECONDARY GEAR AND OUTPUT GEAR PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	1.6—3.4 {17—34, 15—30}		
E	MEASUREMENT RESULT OF SECONDARY GEAR AND OUTPUT GEAR PRELOAD	—	—	OK/NG	OK/NG	OK/NG
F	THICKNESS OF REMOVED SHIM	—	mm {in}			
G	MEDIAN VALUE OF SECONDARY GEAR AND OUTPUT GEAR PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.5 {25.5, 22.1}		
H	PRELOAD GAP	G - C	N·m {kgf·cm, in·lbf}			
I	SHIM THICKNESS GAP	H × 0.1 mm {0.00394 in} / 2.0 N·m {20.4 kgf·cm, 17.7 in·lbf}	mm {in}			
J	THICKNESS OF OPTIMUM SHIM	F + I	mm {in}			

bfw4ua00000001

cardiagn.com

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	ANGULAR CONTACT BALL BEARING PRELOAD	—	N·m {kgf·cm, in·lbf}	1.2 {12.2, 10.6}	←	←
B	TOTAL PRELOAD	—	N·m {kgf·cm, in·lbf}	2.6 {26.5, 23.0}	3.7 {37.7, 32.7}	
C	SECONDARY GEAR AND OUTPUT GEAR PRELOAD	B - A	N·m {kgf·cm, in·lbf}	1.4 {14.3, 12.4}	2.5 {25.5, 22.1}	
D	SECONDARY GEAR AND OUTPUT GEAR PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	1.6—3.4 {17—34, 15—30}		
E	MEASUREMENT RESULT OF SECONDARY GEAR AND OUTPUT GEAR PRELOAD	—	—	OK/(NG)	(OK)/NG	OK/NG
F	THICKNESS OF REMOVED SHIM	—	mm {in}	0.855 {0.03366}		
G	MEDIAN VALUE OF SECONDARY GEAR AND OUTPUT GEAR PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.5 {25.5, 22.1}		
H	PRELOAD GAP	G - C	N·m {kgf·cm, in·lbf}	1.1 {11.2, 9.7}		
I	SHIM THICKNESS GAP	H × 0.1 mm {0.00394 in} / 2.0 N·m {20.4 kgf·cm, 17.7 in·lbf}	mm {in}	0.055 {0.00217}		
J	THICKNESS OF OPTIMUM SHIM	F + I	mm {in}	0.91 {0.03583}		

bfw4ua00000002

Ring Gear and Differential Preload Measurement/Adjustment [FW6A-EL]

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	RING GEAR AND DIFFERENTIAL PRELOAD	—	N·m {kgf·cm, in·lbf}			
B	RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.0—3.1 {21—31, 18—27}		
C	MEASUREMENT RESULT OF RING GEAR AND DIFFERENTIAL PRELOAD	—	—	OK/NG	OK/NG	OK/NG
D	THICKNESS OF REMOVED SHIM	—	mm {in}			
E	MEDIAN VALUE OF RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.6 {27, 23}		
F	PRELOAD GAP	E - A	N·m {kgf·cm, in·lbf}			
G	SHIM THICKNESS GAP	F × 0.1 mm {0.00394 in} / 1.5 N·m {15.3 kgf·cm, 13.3 in·lbf}	mm {in}			
H	THICKNESS OF OPTIMUM SHIM	D + G	mm {in}			

bfw2za00000175

cardiagn.com

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	RING GEAR AND DIFFERENTIAL PRELOAD	—	N·m {kgf·cm, in·lbf}	2.5 {25.5, 22.1}	3.4 {34.7, 30.1}	
B	RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.0—3.1 {21—31, 18—27}		
C	MEASUREMENT RESULT OF RING GEAR AND DIFFERENTIAL PRELOAD	—	—	(OK)/NG	OK/(NG)	OK/NG
D	THICKNESS OF REMOVED SHIM	—	mm {in}		0.905 {0.03563}	
E	MEDIAN VALUE OF RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.6 {27, 23}		
F	PRELOAD GAP	E - A	N·m {kgf·cm, in·lbf}		-0.8 {-8.2, -7.1}	
G	SHIM THICKNESS GAP	F × 0.1 mm {0.00394 in} / 1.5 N·m {15.3 kgf·cm, 13.3 in·lbf}	mm {in}		-0.053 {-0.0021}	
H	THICKNESS OF OPTIMUM SHIM	D + G	mm {in}		0.852 {0.0335}	

bfw2za00000176

Ring Gear and Differential Preload Measurement/Adjustment [FW6AX-EL]

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	RING GEAR AND DIFFERENTIAL PRELOAD	—	N·m {kgf·cm, in·lbf}			
B	RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.1—3.2 {22—32, 19—28}		
C	MEASUREMENT RESULT OF RING GEAR AND DIFFERENTIAL PRELOAD	—	—	OK/NG	OK/NG	OK/NG
D	THICKNESS OF REMOVED SHIM	—	mm {in}			
E	MEDIAN VALUE OF RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.7 {28, 24}		
F	PRELOAD GAP	E - A	N·m {kgf·cm, in·lbf}			
G	SHIM THICKNESS GAP	F × 0.1 mm {0.00394 in} / 1.5 N·m {15.3 kgf·cm, 13.3 in·lbf}	mm {in}			
H	THICKNESS OF OPTIMUM SHIM	D + G	mm {in}			

bfw2za00001173

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	RING GEAR AND DIFFERENTIAL PRELOAD	—	N·m {kgf·cm, in·lbf}	2.8 {28.6, 24.8}	3.6 {36.7, 31.9}	
B	RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.1—3.2 {22—32, 19—28}		
C	MEASUREMENT RESULT OF RING GEAR AND DIFFERENTIAL PRELOAD	—	—	(OK)/NG	OK/(NG)	OK/NG
D	THICKNESS OF REMOVED SHIM	—	mm {in}		0.905 {0.03563}	
E	MEDIAN VALUE OF RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	2.7 {28, 24}		
F	PRELOAD GAP	E - A	N·m {kgf·cm, in·lbf}		-0.9 {-9.2, -8.0}	
G	SHIM THICKNESS GAP	F × 0.1 mm {0.00394 in} / 1.5 N·m {15.3 kgf·cm, 13.3 in·lbf}	mm {in}		-0.06 {-0.002}	
H	THICKNESS OF OPTIMUM SHIM	D + G	mm {in}		0.845 {0.0333}	

bfw2za00001174

cardiagn.com

Total End Play Measurement/Adjustment

Symbol	Item	Formula	Unit	First time			
A	TOTAL END PLAY ADJUSTMENT VALUE	—	mm{in}				
B	AVERAGE OF TOTAL END PLAY ADJUSTMENT VALUE	Average value of A	mm{in}				
C	THICKNESS OF SHIM (FZ01 19 2L1) FOR TOTAL END PLAY MEASUREMENT/ ADJUSTMENT	—	mm{in}				
D	RANGE	B + C	mm{in}				

azzzcw00000080

Description example

Symbol	Item	Formula	Unit	First time			
A	TOTAL END PLAY ADJUSTMENT VALUE	—	mm{in}	0.120 {0.00472}	0.110 {0.00433}	0.110 {0.00433}	0.120 {0.00472}
B	AVERAGE OF TOTAL END PLAY ADJUSTMENT VALUE	Average value of A	mm{in}	0.115 {0.00453}			
C	THICKNESS OF SHIM (FZ01 19 2L1) FOR TOTAL END PLAY MEASUREMENT/ ADJUSTMENT	—	mm{in}	3.010 {0.11850}			
D	RANGE	B + C	mm{in}	3.125 {0.12303}			

azzzcw00000081

cardiagn.com