
END COVER COMPONENT DISASSEMBLY

id051700661200

Structural view



bcw6ja00000250

1	8 bolts
2	Brake housing
3	2-6 brake piston
4	Springs and retainer component
5	Retaining plate
6	Drive plate
7	Driven plate
8	Retaining plate
9	Rear internal gear and reduction internal gear component
10	Thrust washer
11	Thrust needle bearing

12	Reduction sun gear
13	Thrust needle bearing
14	Reduction planetary gear
15	Thrust washer
16	Snap ring
17	Retaining plate
18	Drive plate
19	Driven plate
20	Springs and retainer component
21	R-3-5 brake piston
22	End cover

Disassembly Procedure

1. Perform a simple inspection of the 2-6 brake using the following procedure:
   (1) Blow compressed air into the oil passage shown in the figure and verify the operation condition of the 2-6 brake.

Warning


- **Always wear protective eye wear when using the air compressor. Otherwise, ATF or dirt particles blown off by the air compressor could get into the eyes.**

Caution

- **To prevent damage to parts, always use an air compressor which is adjusted to the indicated pressure.**

Compressed air pressure
0.39—0.44 MPa {4.0—4.4 kgf/cm^2, 57—63 psi}

- If there is a malfunction, verify the cause and repair the applicable part after disassembly.



bcw6ja00000251


2. Perform a simple inspection of the R-3-5 brake using the following procedure:
   (1) Blow compressed air into the oil passage shown in the figure and verify the operation condition of the R-3-5 brake.

Warning
- **Always wear protective eye wear when using the air compressor. Otherwise, ATF or dirt particles blown off by the air compressor could get into the eyes.**

Caution
- **To prevent damage to parts, always use an air compressor which is adjusted to the indicated pressure.**


Compressed air pressure
0.39—0.44 MPa {4.0—4.4 kgf/cm^2, 57—63 psi}

- If there is a malfunction, verify the cause and repair the applicable part after disassembly.



bcw6ja00000252


3. Remove the brake housing using the following procedure:



bcw6ja00000253

   (1) Loosen the bolts shown in the figure uniformly and remove them.


Caution
- **If the bolts are not loosened uniformly and removed, the brake housing will slant and parts could be damaged due to the spring force of the springs and retainer component in the brake housing.**



bcw6ja00000254

(2) Remove the brake housing.

1	8 bolts
2	Brake housing




bcw6ja00000255

4. Remove the 2-6 brake piston from the brake housing using the following procedure:
   (1) Blow compressed air into the oil passage shown in the figure.

Warning
- **Always wear protective eye wear when using the air compressor. Otherwise, ATF or dirt particles blown off by the air compressor could get into the eyes.**


Caution
- **To prevent damage to parts, always use an air compressor which is adjusted to the indicated pressure.**

Compressed air pressure
0.39—0.44 MPa {4.0—4.4 kgf/cm^2, 57—63 psi}




bcw6ja00000256

(2) Remove the 2-6 brake piston removed from the brake housing.




bcw6ja00000257

5. Remove the springs and retainer component.




bcw6ja00000258

6. Remove the retaining plate.




bcw6ja00000259

7. Remove the drive plates and driven plates.
A : Drive plate
B : Driven plate




bcw6ja00000028

8. Remove the retaining plate.



bcw6ja00000260

9. Remove the rear internal gear and reduction internal gear component.



bcw6ja00000026


10. Remove the reduction internal gear from the rear internal gear and reduction internal gear component using the following procedure:

(1) Remove the snap ring.




bcw6ja00000261

(2) Remove the reduction internal gear.




bcw6ja00000262

11. Remove the thrust washer.




bcw6ja00000263

12. Remove the thrust needle bearing.




bcw6ja00000264

13. Remove the reduction sun gear.




bcw6ja00000265

14. Remove the thrust needle bearing.




bcw6ja00000266

15. Remove the reduction planetary gear.




bcw6ja00000267

16. Remove the thrust washer.




bcw6ja00000268

17. Remove the snap ring using the following procedure:
    (1) Install the SST.



bcw6ja00000050




bcw6ja00000051

    (2) Set the SST and part to the press as shown in the figure.

Caution

- **Using the rubber plates, adjust the alignment surface of the end cover with the transaxle case so that it is level. Otherwise the parts could tip over during the procedure and get damaged.**

A : Press
B : Rubber plate




bcw6ja00000648

(3) Press the SST down using a press until there is no longer any spring force from the springs and retainer component applied to the snap ring.

Caution


- **If the SST is pressed excessively by the press, surrounding parts could be damaged.Stop pressing the SST down using a press if a gap appears between the snap ring and retaining plate.**

A : Snap ring
B : Retaining plate
C : Gap




bcw6ja00000649

(4) Remove the snap ring from the snap ring groove.



bcw6ja00000650

(5) Take the SST and part off the press.




bcw6ja00000053

(6) Remove the SST.




bcw6ja00000054


(7) Remove the snap ring removed from the snap ring groove.


bcw6ja00000269

18. Remove the retaining plate.



bcw6ja00000270

19. Remove the drive plates and driven plates.
A : Drive plate
B : Driven plate



bcw6ja00000055

20. Remove the springs and retainer component.



bcw6ja00000271

21. Remove the R-3-5 brake piston using the following procedure:
(1) Blow compressed air into the oil passage shown in the figure.

Warning
- **Always wear protective eye wear when using the air compressor. Otherwise, ATF or dirt particles blown off by the air compressor could get into the eyes.**


Caution
- **To prevent damage to parts, always use an air compressor which is adjusted to the indicated pressure.**

Compressed air pressure
0.39—0.44 MPa {4.0—4.4 kgf/cm^2, 57—63 psi}


bcw6ja00000272

(2) Remove the R-3-5 brake piston removed from the end cover.

22. Clean the disassembled parts. (See AUTOMATIC TRANSAXLE CLEANING.)
23. Perform the following inspection and replace a malfunctioning part with a new one.
    - Visual inspection of parts (See VISUAL INSPECTION OF PARTS.)
    - Thrust needle bearing inspection (See THRUST NEEDLE BEARING INSPECTION.)
    - Reduction planetary gear inspection (See REDUCTION PLANETARY GEAR INSPECTION.)
    - 2-6 brake inspection (See 2-6 BRAKE INSPECTION.)
    - R-3-5 brake inspection (See R-3-5 BRAKE INSPECTION.)
    - End cover inspection (See END COVER INSPECTION.)


bcw6ja00000273