MEASUREMENT/ADJUSTMENT VALUE INPUT SHEET

id051700665300

Differential Backlash Measurement/Adjustment

Symbol	Item	Formula	Unit	First time		Second time		Third time	
A	FRONT SIDE GEAR AND PINION GEAR BACKLASH	—	mm {in}						
B	REAR SIDE GEAR AND PINION GEAR BACKLASH	—	mm {in}						
C	FRONT DIFFERENTIAL BACKLASH	Average value of A	mm {in}						
D	REAR DIFFERENTIAL BACKLASH	Average value of B	mm {in}						
E	STANDARD DIFFERENTIAL BACKLASH	—	mm {in}	0.030—0.150 {0.0012—0.0059}					
F	MEASUREMENT RESULT OF FRONT DIFFERENTIAL BACKLASH	—	—	OK/NG		OK/NG		OK/NG	
G	MEASUREMENT RESULT OF REAR DIFFERENTIAL BACKLASH	—	—	OK/NG		OK/NG		OK/NG	
H	THICKNESS OF REMOVED FRONT THRUST WASHER	—	mm {in}						
I	THICKNESS OF REMOVED REAR THRUST WASHER	—	mm {in}						
J	MEDIAN VALUE OF DIFFERENTIAL BACKLASH SPECIFICATION	—	mm {in}	0.090 {0.0035}					
K	FRONT DIFFERENTIAL BACKLASH GAP	C - J	mm {in}						
L	REAR DIFFERENTIAL BACKLASH GAP	D - J	mm {in}						
M	FRONT THRUST WASHER THICKNESS GAP	K × 0.1 mm {0.004 in} / 0.08 mm {0.003 in}	mm {in}						
N	REAR THRUST WASHER THICKNESS GAP	L × 0.1 mm {0.004 in} / 0.08 mm {0.003 in}	mm {in}						
O	THICKNESS OF OPTIMUM FRONT THRUST WASHER	H + M	mm {in}						
P	THICKNESS OF OPTIMUM REAR THRUST WASHER	I + N	mm {in}						

bcw7za00000047

Description example

Symbol	Item	Formula	Unit	First time		Second time		Third time	
A	FRONT SIDE GEAR AND PINION GEAR BACKLASH	—	mm {in}	0.160 {0.00630}	0.170 {0.00669}	0.110 {0.00433}	0.100 {0.00394}		
B	REAR SIDE GEAR AND PINION GEAR BACKLASH	—	mm {in}	0.160 {0.00630}	0.150 {0.00591}	0.085 {0.0033}	0.075 {0.0030}		
C	FRONT DIFFERENTIAL BACKLASH	Average value of A	mm {in}	0.165 {0.00650}		0.105 {0.00413}			
D	REAR DIFFERENTIAL BACKLASH	Average value of B	mm {in}	0.155 {0.00610}		0.080 {0.0031}			
E	STANDARD DIFFERENTIAL BACKLASH	—	mm {in}	0.030—0.150 {0.0012—0.0059}					
F	MEASUREMENT RESULT OF FRONT DIFFERENTIAL BACKLASH	—	—	OK/(NG)		(OK)/NG		OK/NG	
G	MEASUREMENT RESULT OF REAR DIFFERENTIAL BACKLASH	—	—	OK/(NG)		(OK)/NG		OK/NG	
H	THICKNESS OF REMOVED FRONT THRUST WASHER	—	mm {in}	0.810 {0.0319}					
I	THICKNESS OF REMOVED REAR THRUST WASHER	—	mm {in}	0.795 {0.0313}					
J	MEDIAN VALUE OF DIFFERENTIAL BACKLASH SPECIFICATION	—	mm {in}	0.090 {0.0035}					
K	FRONT DIFFERENTIAL BACKLASH GAP	C - J	mm {in}	0.075 {0.0030}					
L	REAR DIFFERENTIAL BACKLASH GAP	D - J	mm {in}	0.065 {0.0026}					
M	FRONT THRUST WASHER THICKNESS GAP	K × 0.1 mm {0.004 in} / 0.08 mm {0.003 in}	mm {in}	0.094 {0.0037}					
N	REAR THRUST WASHER THICKNESS GAP	L × 0.1 mm {0.004 in} / 0.08 mm {0.003 in}	mm {in}	0.081 {0.0032}					
O	THICKNESS OF OPTIMUM FRONT THRUST WASHER	H + M	mm {in}	0.904 {0.0356}					
P	THICKNESS OF OPTIMUM REAR THRUST WASHER	I + N	mm {in}	0.876 {0.0345}					

bcw7za00000048

High Clutch Clearance Measurement/Adjustment

cardiagn.com

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}			
B	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}			
C	HIGH CLUTCH CLEARANCE	A - B	mm {in}			
D	HIGH CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.300—1.500 {0.05119—0.05905}		
E	MEASUREMENT RESULT OF HIGH CLUTCH CLEARANCE	—	—	OK / NG	OK / NG	OK / NG
F	THICKNESS OF REMOVED SNAP RING	—	mm {in}			
G	MEDIAN VALUE OF HIGH CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.400 {0.05512 }		
H	HIGH CLUTCH CLEARANCE GAP	C - G	mm {in}			
I	THICKNESS OF OPTIMUM SNAP RING	F + H	mm {in}			

bcw7za00000051

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}	1.605 {0.06319}	1.470 {0.05787}	
B	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}	0.055 {0.022}	0.090 {0.0035}	
C	HIGH CLUTCH CLEARANCE	A - B	mm {in}	1.550 {0.06102}	1.380 {0.05433}	
D	HIGH CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.300—1.500 {0.05119—0.05905}		
E	MEASUREMENT RESULT OF HIGH CLUTCH CLEARANCE	—	—	OK / (NG)	(OK) / NG	OK / NG
F	THICKNESS OF REMOVED SNAP RING	—	mm {in}	1.615 {0.06358}		
G	MEDIAN VALUE OF HIGH CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.400 {0.05512}		
H	HIGH CLUTCH CLEARANCE GAP	C - G	mm {in}	0.15 {0.059}		
I	THICKNESS OF OPTIMUM SNAP RING	F + H	mm {in}	1.765 {0.06949}		

bcw7za00000040

Low Clutch Clearance Measurement/Adjustment

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	CORRECTION VALUE OF LOW CLUTCH CLEARANCE	(SST WEIGHT- 98 N {10 kgf, 22 lbf}) × 0.00208 mm {0.0000819 in} (119.1508 N {12.15005 kgf, 26.78617 lbf} - 98 N {10 kgf, 22 lbf}) × 0.00208 mm {0.0000819 in}	mm {in}	0.04440 {0.00173}		
B	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}			
C	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}			
D	LOW CLUTCH CLEARANCE	B - C - 0.0440 {0.00173 in}	mm {in}			
E	LOW CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.330—1.530 {0.05237—0.06023}		
F	MEASUREMENT RESULT OF LOW CLUTCH CLEARANCE	—	—	OK / NG	OK / NG	OK / NG
G	THICKNESS OF REMOVED SNAP RING	—	mm {in}			
H	MEDIAN VALUE OF LOW CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.430 {0.05630}		
I	LOW CLUTCH CLEARANCE GAP	D - H	mm {in}			
J	THICKNESS OF OPTIMUM SNAP RING	G + I	mm {in}			

bcw7za00000033

cardiagn.com

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	CORRECTION VALUE OF LOW CLUTCH CLEARANCE	(SST WEIGHT- 98 N {10 kgf, 22 lbf}) × 0.00208 mm {0.0000819 in} (119.1508 N {12.15005 kgf, 26.78617 lbf} - 98 N {10 kgf, 22 lbf}) × 0.00208 mm {0.0000819 in}	mm {in}	0.04440 {0.00173}		
B	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}	2.320 {0.09134}	1.970 {0.07756}	
C	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}	0.595 {0.0234}	0.480 {0.0189}	
D	LOW CLUTCH CLEARANCE	B - C - 0.0440 {0.00173 in}	mm {in}	1.6810 {0.066181}	1.4456 {0.056913}	
E	LOW CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.330—1.530 {0.05237—0.06023}		
F	MEASUREMENT RESULT OF LOW CLUTCH CLEARANCE	—	—	OK /(NG)	(OK)/ NG	OK / NG
G	THICKNESS OF REMOVED SNAP RING	—	mm {in}	1.705 {0.06713}		
H	MEDIAN VALUE OF LOW CLUTCH CLEARANCE SPECIFICATION	—	mm {in}	1.430 {0.05630}		
I	LOW CLUTCH CLEARANCE GAP	D - H	mm {in}	0.2510 {0.009882}		
J	THICKNESS OF OPTIMUM SNAP RING	G + I	mm {in}	1.9560 {0.077008}		

bcw7za00000041

R-3-5 Brake Clearance Measurement/Adjustment

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}			
B	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}			
C	R-3-5 BRAKE CLEARANCE	A - B	mm {in}			
D	R-3-5 BRAKE CLEARANCE SPECIFICATION	—	mm {in}	1.030—1.230 {0.0406—0.0484}		
E	MEASUREMENT RESULT OF R-3-5 BRAKE CLEARANCE	—	—	OK / NG	OK / NG	OK / NG
F	THICKNESS OF REMOVED SNAP RING	—	mm {in}			
G	MEDIAN VALUE OF R-3-5 BRAKE CLEARANCE SPECIFICATION	—	mm {in}	1.130 {0.04449}		
H	R-3-5 BRAKE CLEARANCE GAP	C - G	mm {in}			
I	THICKNESS OF OPTIMUM SNAP RING	F + H	mm {in}			

bcw7za00000035

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	DIAL GAUGE VALUE WITH PISTON OPERATED	—	mm {in}	1.990 {0.07835}	1.890 {0.07441}	
B	DIAL GAUGE VALUE WITHOUT PISTON OPERATED	—	mm {in}	0.595 {0.0234}	0.740 {0.0291}	
C	R-3-5 BRAKE CLEARANCE	A - B	mm {in}	1.395 {0.05492}	1.150 {0.04528}	
D	R-3-5 BRAKE CLEARANCE SPECIFICATION	—	mm {in}	1.030—1.230 {0.0406—0.0484}		
E	MEASUREMENT RESULT OF R-3-5 BRAKE CLEARANCE	—	—	OK /(NG)	(OK)/ NG	OK / NG
F	THICKNESS OF REMOVED SNAP RING	—	mm {in}	2.140 {0.08425}		
G	MEDIAN VALUE OF R-3-5 BRAKE CLEARANCE SPECIFICATION	—	mm {in}	1.130 {0.04449}		
H	R-3-5 BRAKE CLEARANCE GAP	C - G	mm {in}	0.265 {0.0104}		
I	THICKNESS OF OPTIMUM SNAP RING	F + H	mm {in}	2.405 {0.09469}		

bcw7za00000042

2-6 Brake Clearance Measurement/Adjustment

cardiagn.com

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	STRAIGHT EDGE THICKNESS	—	mm {in}			
B	DISTANCE A	MEASUREMENT VALUE - A	mm {in}			
C	AVERAGE VALUE OF DISTANCE A	AVERAGE VALUE OF B	mm {in}			
D	DISTANCE B	—	mm {in}			
E	AVERAGE VALUE OF DISTANCE B	AVERAGE VALUE OF D	mm {in}			
F	2-6 BRAKE CLEARANCE	E - C	mm {in}			
G	2-6 BRAKE CLEARANCE SPECIFICATION	—	mm {in}	1.000—1.200 {0.03938—0.04724}		
H	MEASUREMENT RESULT OF 2-6 BRAKE CLEARANCE	—	—	OK / NG	OK / NG	OK / NG
I	THICKNESS OF REMOVED RETAINING PLATE	—	mm {in}			
J	MEDIAN VALUE OF 2-6 BRAKE CLEARANCE SPECIFICATION	—	mm {in}	1.100 {0.04449}		
K	2-6 BRAKE CLEARANCE GAP	F - J	mm {in}			
L	THICKNESS OF OPTIMUM RETAINING PLATE	I + K	mm {in}			

bcw7za00000036

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	STRAIGHT EDGE THICKNESS	—	mm {in}	39.76 {1.565}		
B	DISTANCE A	MEASUREMENT VALUE - A	mm {in}	3.160 {0.01244} / 3.150 {0.1240} / 3.140 {0.1236}	3.140 {0.1236} / 3.150 {0.1240} / 3.160 {0.1244}	
C	AVERAGE VALUE OF DISTANCE A	AVERAGE VALUE OF B	mm {in}	3.150 {0.1240}	3.150 {0.1240}	
D	DISTANCE B	—	mm {in}	4.380 {0.1724} / 4.370 {0.1720} / 4.360 {0.1717}	4.250 {0.1673} / 4.260 {0.1677} / 4.270 {0.1681}	
E	AVERAGE VALUE OF DISTANCE B	AVERAGE VALUE OF D	mm {in}	4.370 {0.1720}	4.260 {0.1677}	
F	2-6 BRAKE CLEARANCE	E - C	mm {in}	1.220 {0.04803}	1.110 {0.04370}	
G	2-6 BRAKE CLEARANCE SPECIFICATION	—	mm {in}	1.000—1.200 {0.03938—0.04724}		
H	MEASUREMENT RESULT OF 2-6 BRAKE CLEARANCE	—	—	OK / (NG)	(OK) / NG	OK / NG
I	THICKNESS OF REMOVED RETAINING PLATE	—	mm {in}	1.615 {0.06358}		
J	MEDIAN VALUE OF 2-6 BRAKE CLEARANCE SPECIFICATION	—	mm {in}	1.100 {0.04449}		
K	2-6 BRAKE CLEARANCE GAP	F - J	mm {in}	0.120 {0.00472}		
L	THICKNESS OF OPTIMUM RETAINING PLATE	I + K	mm {in}	1.735 {0.06831}		

bcw7za00000043

Low and Reverse Brake (Piston A) Clearance Measurement/Adjustment

cardiagn.com

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	DIAL GAUGE VALUE WITH PISTON A OPERATED	—	mm {in}			
B	DIAL GAUGE VALUE WITHOUT PISTON A OPERATED	—	mm {in}			
C	LOW AND REVERSE BRAKE (PISTON A) CLEARANCE	A - B	mm {in}			
D	LOW AND REVERSE BRAKE (PISTON A) CLEARANCE SPECIFICATION	—	mm {in}	2.130—2.330 {0.08386—0.09173}		
E	MEASUREMENT RESULT OF LOW AND REVERSE BRAKE (PISTON A) CLEARANCE	—	—	OK / NG	OK / NG	OK / NG
F	THICKNESS OF REMOVED SNAP RING	—	mm {in}			
G	MEDIAN VALUE OF LOW AND REVERSE BRAKE (PISTON A) CLEARANCE SPECIFICATION	—	mm {in}	2.230 {0.08780}		
H	LOW AND REVERSE BRAKE (PISTON A) CLEARANCE GAP	C - G	mm {in}			
I	THICKNESS OF OPTIMUM SNAP RING	F + H	mm {in}			

bcw7za00000037

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	DIAL GAUGE VALUE WITH PISTON A OPERATED	—	mm {in}	3.060 {0.1205}	2.850 {0.1122}	
B	DIAL GAUGE VALUE WITHOUT PISTON A OPERATED	—	mm {in}	0.595 {0.0234}	0.610 {0.0240}	
C	LOW AND REVERSE BRAKE (PISTON A) CLEARANCE	A - B	mm {in}	2.465 {0.09705}	2.240 {0.08819}	
D	LOW AND REVERSE BRAKE (PISTON A) CLEARANCE SPECIFICATION	—	mm {in}	2.130—2.330 {0.08386—0.09173}		
E	MEASUREMENT RESULT OF LOW AND REVERSE BRAKE (PISTON A) CLEARANCE	—	—	OK / (NG)	(OK) / NG	OK / NG
F	THICKNESS OF REMOVED SNAP RING	—	mm {in}	2.125 {0.08366}		
G	MEDIAN VALUE OF LOW AND REVERSE BRAKE (PISTON A) CLEARANCE SPECIFICATION	—	mm {in}	2.230 {0.08780}		
H	LOW AND REVERSE BRAKE (PISTON A) CLEARANCE GAP	C - G	mm {in}	0.235 {0.00925}		
I	THICKNESS OF OPTIMUM SNAP RING	F + H	mm {in}	2.360 {0.9291}		

bcw7za00000044

Low and Reverse Brake (Piston B1) Clearance Measurement/Adjustment

cardiagn.com

Symbol	Item	Formula	Unit	First time				Second time				Third time			
A	DIAL GAUGE VALUE WITH PISTON B1 OPERATED	—	mm {in}												
B	DIAL GAUGE VALUE WITHOUT PISTON B1 OPERATED	—	mm {in}												
C	LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE	A - B	mm {in}												
D	LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE AVERAGE VALUE	AVERAGE VALUE OF C	mm {in}												
E	LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE	—	mm {in}	1.500—1.700 {0.05906—0.06692}											
F	MEASUREMENT RESULT OF LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE	—	—	OK / NG				OK / NG				OK / NG			
G	THICKNESS OF REMOVED SNAP RING	—	mm {in}												
H	MEDIAN VALUE OF LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE SPECIFICATION	—	mm {in}	1.600 {0.06299}											
I	LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE GAP	D - H	mm {in}												
J	THICKNESS OF OPTIMUM SNAP RING	G + I	mm {in}												

bcw7za00000038

Description example

Symbol	Item	Formula	Unit	First time				Second time				Third time			
A	DIAL GAUGE VALUE WITH PISTON B1 OPERATED	—	mm {in}	2.470 {0.09724}	2.465 {0.09705}	2.470 {0.09724}	2.475 {0.09744}	2.170 {0.08543}	2.165 {0.08524}	2.170 {0.08543}	2.175 {0.08563}				
B	DIAL GAUGE VALUE WITHOUT PISTON B1 OPERATED	—	mm {in}	0.595 {0.0234}	0.600 {0.0236}	0.595 {0.0234}	0.590 {0.0232}	0.590 {0.0232}	0.595 {0.0234}	0.590 {0.0232}	0.585 {0.0230}				
C	LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE	A - B	mm {in}	1.875 {0.07382}	1.865 {0.07343}	1.875 {0.07382}	1.885 {0.07421}	1.580 {0.06220}	1.570 {0.06181}	1.580 {0.06220}	1.590 {0.06260}				
D	LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE AVERAGE VALUE	AVERAGE VALUE OF C	mm {in}	1.875 {0.07382}				1.580 {0.06220}							
E	LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE	—	mm {in}	1.500—1.700 {0.05906—0.06692}											
F	MEASUREMENT RESULT OF LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE	—	—	OK / (NG)				(OK) / NG				OK / NG			
G	THICKNESS OF REMOVED SNAP RING	—	mm {in}	2.125 {0.08366}											
H	MEDIAN VALUE OF LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE SPECIFICATION	—	mm {in}	1.600 {0.06299}											
I	LOW AND REVERSE BRAKE (PISTON B1) CLEARANCE GAP	D - H	mm {in}	0.275 {0.0108}											
J	THICKNESS OF OPTIMUM SNAP RING	G + I	mm {in}	2.400 {0.09449}											

bcw7za00000045

Secondary Gear and Output Gear End Play Measurement/Adjustment

carmanual.com

Symbol	Item	Formula	Unit	First time		
A	STRAIGHT EDGE THICKNESS	—	mm {in}			
B	DISTANCE A	MEASUREMENT VALUE - A	mm {in}			
C	AVERAGE VALUE OF DISTANCE A	AVERAGE VALUE OF B	mm {in}			
D	SST (49 G027 004) THICKNESS	—	mm {in}			
E	DEPTH MICROMETER MEASUREMENT VALUE	—	mm {in}			
F	DISTANCE B	A - D - E	mm {in}			
G	RANGE	C - F	mm {in}			

bcw7za00000039

Description example

Symbol	Item	Formula	Unit	First time		
A	STRAIGHT EDGE THICKNESS	—	mm {in}	39.76 {1.565}		
B	DISTANCE A	MEASUREMENT VALUE - A	mm {in}	20.15 {0.7933}	20.14 {0.7929}	20.16 {0.7937}
C	AVERAGE VALUE OF DISTANCE A	AVERAGE VALUE OF B	mm {in}	20.15 {0.7933}		
D	SST (49 G027 004) THICKNESS	—	mm {in}	15.00 {0.5906}		
E	DEPTH MICROMETER MEASUREMENT VALUE	—	mm {in}	5.82 {0.229}		
F	DISTANCE B	A - D - E	mm {in}	18.94 {0.7457}		
G	RANGE	C - F	mm {in}	1.21 {0.0476}		

bcw7za00000046

Ring Gear and Differential Preload Measurement/Adjustment

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	RING GEAR AND DIFFERENTIAL PRELOAD	—	N·m {kgf·cm, in·lbf}			
B	RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	0.83—1.51 {8.5—15, 7.3—13}		
C	MEASUREMENT RESULT OF RING GEAR AND DIFFERENTIAL PRELOAD	—	—	OK/NG	OK/NG	OK/NG
D	THICKNESS OF REMOVED SHIM	—	mm {in}			
E	MEDIAN VALUE OF RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	1.17 {12, 11}		
F	PRELOAD GAP	E - A	N·m {kgf·cm, in·lbf}			
G	SHIM THICKNESS GAP	F × 0.1 mm {0.004 in} / 0.75 N·m {7.6 kgf·cm, 6.6 in·lbf}	mm {in}			
H	THICKNESS OF OPTIMUM SHIM	D + G	mm {in}			

bcw7za00000049

cardiagn.com

Description example

Symbol	Item	Formula	Unit	First time	Second time	Third time
A	RING GEAR AND DIFFERENTIAL PRELOAD	—	N·m {kgf·cm, in·lbf}	0.70 {7.1, 6.2}	1.2 {12, 11}	
B	RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	0.83—1.51 {8.5—15, 7.3—13}		
C	MEASUREMENT RESULT OF RING GEAR AND DIFFERENTIAL PRELOAD	—	—	OK/(NG)	(OK)/NG	OK/NG
D	THICKNESS OF REMOVED SHIM	—	mm {in}	0.905 {0.0356}		
E	MEDIAN VALUE OF RING GEAR AND DIFFERENTIAL PRELOAD SPECIFICATION	—	N·m {kgf·cm, in·lbf}	1.17 {12, 11}		
F	PRELOAD GAP	E - A	N·m {kgf·cm, in·lbf}	0.47 {4.8, 4.2}		
G	SHIM THICKNESS GAP	F × 0.1 mm {0.004 in} / 0.75 N·m {7.6 kgf·cm, 6.6 in·lbf}	mm {in}	0.063 {0.0025}		
H	THICKNESS OF OPTIMUM SHIM	D + G	mm {in}	0.968 {0.0381}		

bcw7za00000050

Total End Play Measurement/Adjustment

Symbol	Item	Formula	Unit	First time			
A	TOTAL END PLAY ADJUSTMENT VALUE	—	mm{in}				
B	AVERAGE OF TOTAL END PLAY ADJUSTMENT VALUE	Average value of A	mm{in}				
C	THICKNESS OF SHIM (FZ11 19 2L1) FOR TOTAL END PLAY MEASUREMENT/ ADJUSTMENT	—	mm{in}				
D	RANGE	B + C	mm{in}				

bcw7za00000027

Description example

Symbol	Item	Formula	Unit	First time			
A	TOTAL END PLAY ADJUSTMENT VALUE	—	mm{in}	0.120 {0.00472}	0.110 {0.00433}	0.110 {0.00433}	0.120 {0.00472}
B	AVERAGE OF TOTAL END PLAY ADJUSTMENT VALUE	Average value of A	mm{in}	0.115 {0.00453}			
C	THICKNESS OF SHIM (FZ11 19 2L1) FOR TOTAL END PLAY MEASUREMENT/ ADJUSTMENT	—	mm{in}	2.710 {0.1067}			
D	RANGE	B + C	mm{in}	2.825 {0.1112}			

bcw7za00000028

cardiagn.com