TECHNICAL DATA

id055000800600

Item		Specification	Comment
Gap between front planetary gear pinion washer and planetary carrier	Maximum	0.82 mm {0.032 in}	—
Gap between rear planetary gear pinion washer and planetary carrier	Maximum	0.879 mm {0.0346 in}	—
Gap between reduction planetary gear pinion washer and planetary carrier	Maximum	0.82 mm {0.032 in}	—
Inner diameter of reduction planetary gear bush	Maximum	35.095 mm {1.3817 in}	—
Inner diameter of differential journal	Maximum	28.059 mm {1.1047 in}	—
Outer diameter of drive shaft (LH) journal	Minimum	27.944 mm {1.1002 in}	—
Outer diameter of drive shaft (RH) journal	Minimum	27.944 mm {1.1002 in}	—
Thickness of low clutch drive plate	Minimum	1.475 mm {0.05807 in}	Drive plate size: Outer diameter approx. 149.9 mm {5.902 in}
Thickness of high clutch drive plate	Minimum	1.475 mm {0.05807 in}	Drive plate size: Outer diameter approx. 111.7 mm {4.398 in}
Free length of high clutch springs and retainer component	Minimum	24.0 mm {0.0945 in}	Springs and retainer component size: Outer diameter approx. 78.5 mm {3.09 in}
Thickness of low and reverse brake drive plate	Minimum	1.580 mm {0.06220 in}	Drive plate size: Outer diameter approx. 162 mm {6.38 in}
Thickness of 2-6 brake drive plate	Minimum	1.475 mm {0.05807 in}	Drive plate size: Outer diameter approx. 160.4 mm {6.315 in}
Thickness of R-3-5 brake drive plate	Minimum	1.475 mm {0.05807 in}	Drive plate size: Outer diameter approx. 159.8 mm {6.291 in}
Inner diameter of low clutch hub bush	Maximum	24.661 mm {0.97091 in}	—
Inner diameter of high clutch hub bush	Maximum	16.138 mm {0.63535 in}	—
Oil pump side clearance (inner rotor)	Maximum	0.045 mm {0.0018 in}	—
Oil pump side clearance (outer rotor)	Maximum	0.050 mm {0.0020 in}	—
Inner diameter of oil pump (oil pump cover) bush	Maximum	44.006 mm {1.7325 in}	—
Low clutch clearance	Specification	1.330—1.530 mm {0.05237—0.06023 in}	—
High clutch clearance	Specification	1.300—1.500 mm {0.05119—0.05905 in}	—
Low and reverse brake (piston A) clearance	Specification	2.130—2.330 mm {0.08386—0.09173 in}	—
Low and reverse brake (piston B1) clearance	Specification	1.500—1.700 mm {0.05906—0.06692 in}	—
2-6 brake clearance	Specification	1.000—1.200 mm {0.03938—0.04724 in}	—
R-3-5 brake clearance	Specification	1.030—1.230 mm {0.0406—0.0484 in}	—
Differential backlash	Specification	0.030—0.150 mm {0.0012—0.0059 in}	—
Ring gear and differential preload	Specification	0.83—1.51 N·m {8.5—15 kgf·cm, 7.3—13 in·lbf}	—