TRANSMISSION/TRANSAXLE TECHNICAL DATA

id055000800100

Manual Transaxle

Item		Specification
Manual transaxle oil	Grade	API service GL-4
	Viscosity	SAE 75W-80
	Capacity (approx. quantity) (L {US qt, Imp qt})	SKYACTIV-G 1.5: 1.59 L {1.68 US qt, 1.40 Imp qt} SKYACTIV-D 1.5: 1.64 L {1.73 US qt, 1.44 Imp qt}

Gear Thrust Clearance

Measurement location	Specification (mm {in})	Maximum (mm {in})
3rd gear	0.208 {0.0082}	0.300 {0.0118}
4th gear	0.295 {0.0116}	0.373 {0.0147}
5th gear	0.269 {0.0106}	0.381 {0.0150}
6th gear	0.342 {0.0135}	0.461 {0.0181}
Secondary 1st gear	0.216 {0.0085}	0.313 {0.0123}
Secondary 2nd gear	0.307 {0.0121}	0.403 {0.0159}

Gear Inner Diameter

Measurement location	Specification (mm {in})	Maximum (mm {in})
3rd gear	41.510 {1.6343}	41.520 {1.6346}
4th gear	37.010 {1.4571}	37.020 {1.4575}
5th gear	37.010 {1.4571}	37.020 {1.4575}
6th gear	32.810 {1.2917}	32.820 {1.2921}
Secondary 1st gear	41.510 {1.6343}	41.520 {1.6346}
Secondary 2nd gear	37.010 {1.4571}	37.020 {1.4575}
Reverse idler gearbushing	16.025 {0.6309}	16.034 {0.6313}

Gear Shaft Runout

Measurement location	Maximum (mm {in})
Primary shaft	0.050 {0.0020}

Measurement location	Maximum (mm {in})
Secondary shaft	0.050 {0.0020}

Gear Shaft Outer Diameter

Measurement location		Specification (mm {in})	Minimum (mm {in})
Primary shaft	3rd gear assembly part	41.470 {1.6327}	41.460 {1.6323}
	4th gear assembly part	36.970 {1.4555}	36.960 {1.4551}
	5th gear assembly part	36.970 {1.4555}	36.960 {1.4551}
	6th gear assembly part	32.770 {1.2902}	32.760 {1.2898}
Secondary shaft	Secondary 1st gear assembly part	41.470 {1.6327}	41.460 {1.6323}
	Secondary 2nd gear assembly part	36.970 {1.4555}	36.960 {1.4551}
Reverse idler shaft	Reverse idler gear sliding part	15.975 {0.6289}	15.966 {0.6286}

Differential Case Journal Inner Diameter

Measurement location	Specification (mm {in})
Differential case journal	28.020—28.059 {1.1032—1.1046}

Drive Shaft Journal Outer Diameter

Measurement location	Minimum (mm {in})
Drive shaft journal (LH)	27.959 {1.1007}
Drive shaft journal (RH)	27.944 {1.1002}

Synchronizer Clearance

Measurement location	Specification (mm {in})	Minimum (mm {in})
Synchronizer ring (1GR)	0.990 {0.0390}	0.500 {0.0197}
Synchronizer ring (2GR)	0.990 {0.0390}	0.500 {0.0197}
Synchronizer ring (3GR)	1.000 {0.0394}	0.435 {0.0171}
Synchronizer ring (4GR)	1.000 {0.0394}	0.435 {0.0171}
Synchronizer ring (5GR)	1.000 {0.0394}	0.520 {0.0205}
Synchronizer ring (6GR)	1.000 {0.0394}	0.520 {0.0205}

Shift Fork and Clutch Hub Sleeve Clearance

Measurement location	Specification (mm {in})	Maximum (mm {in})
Shift fork and clutch hub sleeve	0.225 {0.0089}	0.400 {0.0157}

Differential Gear Backlash

Item	Specification (mm {in})
Pinion gear backlash	0.03—0.15 {0.002—0.005}

Bush Inner Diameter

Measurement location		Specification (mm {in})	Maximum (mm {in})
Transaxle case	Shift rod bushing (1GR/2GR)	14.048 {0.55307}	14.088 {0.55465}
	Shift rod bushing (3GR/4GR)	14.048 {0.55307}	14.088 {0.55465}
	Shift rod bushing (5GR/6GR)	14.048 {0.55307}	14.088 {0.55465}
	Control rod bushing	14.048 {0.55307}	14.088 {0.55465}
	Select lever bushing	14.048 {0.55307}	14.088 {0.55465}
	Shift lever bushing No.1	14.048 {0.55307}	14.088 {0.55465}
	Shift lever bushing No.2	14.031 {0.55240}	14.071 {0.55398}
Clutch housing	Shift rod bushing (1GR/2GR)	14.048 {0.55307}	14.088 {0.55465}
	Shift rod bushing (3GR/4GR)	14.048 {0.55307}	14.088 {0.55465}
	Shift rod bushing (5GR/6GR)	14.048 {0.55307}	14.088 {0.55465}
	Control rod bushing	14.048 {0.55307}	14.088 {0.55465}

Adjust Shim Size

Primary shaft (mm {in})

1.550 {0.06102}	1.500 {0.05906}	1.450 {0.05709}	1.400 {0.05512}
1.350 {0.05315}	1.300 {0.05118}	1.250 {0.04921}	1.200 {0.04724}
1.150 {0.04528}	1.100 {0.04331}	1.050 {0.04134}	1.000 {0.03937}
0.950 {0.03740}	0.900 {0.03543}	0.850 {0.03346}	0.800 {0.03150}
0.750 {0.02953}	0.700 {0.02756}	0.650 {0.02559}	0.600 {0.02362}

Differential (mm {in})

1.600 {0.06299}	1.550 {0.06102}	1.500 {0.05906}	1.450 {0.05709}
1.400 {0.05512}	1.350 {0.05315}	1.300 {0.05118}	1.250 {0.04921}
1.200 {0.04724}	1.150 {0.04528}	1.100 {0.04331}	1.050 {0.04134}
1.000 {0.03937}	0.950 {0.03740}	0.900 {0.03543}	0.850 {0.03346}
0.800 {0.03150}	-	-	-

Differential thrust washer size (mm {in})

0.95 {0.037}	0.90 {0.035}	0.85 {0.033}	0.80 {0.031}
0.75 {0.030}	-	-	-