## WHEEL AND TIRE SPECIFICATION

id021200800100

### Standard tire and wheel (15 inch wheel)

| Item | | | | Specification | | | |
|---|---|---|---|---|---|---|---|
| Wheel | Size | | | 15×5 1/2J | | | |
| | Material | | | Steel | Aluminum alloy | Steel | Aluminum alloy |
| | Inset | | (mm {in}) | 40 {1.6} | | | |
| | Pitch circle diameter | | (mm {in}) | 100 {3.94} | | | |
| Tire | Size | | | 185/65R15 88S | | 185/65R15 88T | |
| | Air pressure (kPa {bar, <psi>}) | Front | Up to 3 persons | 260 {2.6, <38>} | | 230 {2.3, <33>} or 240 {2.4, <35>} or 250 {2.5, <36>} or 260 {2.6, <38>}*1 | |
| | | | Full load | 270 {2.7, <39>} | | 260 {2.6, <38>} or 270 {2.7, <39>}*1 | |
| | | Rear | Up to 3 persons | 230 {2.3, <33>} | | 210 {2.1, <30>} or 230 {2.3, <33>}*1 | |
| | | | Full load | 320 {3.2, <46>} | | | |
| | Remaining tread | | (mm {in}) | 1.6 {0.063} | | | |
| Wheel and tire | Wheel and tire runout | Lateral direction | (mm {in}) | 2.5 {0.098} | 2.0 {0.079} | 2.5 {0.098} | 2.0 {0.079} |
| | | Radial direction | (mm {in}) | 1.5 {0.059} | | | |
| | Wheel and tire imbalance | Inside | (g {oz}) | Knock-type*2: 9 {0.3} max. | Knock-type*2: 9 {0.3} max. | Knock-type*2: 9 {0.3} max. | Knock-type*2: 9 {0.3} max. |
| | | Outside | (g {oz}) | | Adhesive-type*3: 15 {0.53} max. | | Adhesive-type*3: 15 {0.53} max. |
| | Lug nut tightening torque | | (N·m {kgf·m, ft·lbf}) | 108—147 {12—14, 80—108} | | | |

*1 : Verify that the tire pressures are correct by checking the label attached to the door frame which is visible when the driver's door is opened.

*2 : Do not install three or more weights. The weight of one balance weight must be 60 g {2.1 oz} or less, and the total weight of two balance weights must be 100 g {3.53 oz} or less.

*3 : Do not install three or more weights. Do not affix the weights such that they are parallel to each other or overlapping. The total weight of all the weights is 160 g {5.64 oz} or less.

### Standard tire and wheel (16 inch wheel)

| Item | | | | Specification |
|---|---|---|---|---|
| Wheel | Size | | | 16×5 1/2J |
| | Material | | | Aluminum alloy |
| | Inset | | (mm {in}) | 40 {1.6} |
| | Pitch circle diameter | | (mm {in}) | 100 {3.94} |
| Tire | Size | | | 185/60R16 86H |
| | Air pressure (kPa {bar, <psi>}) | Front | Up to 3 persons | 250 {2.5, <36>} or 260 {2.6, <38>}*1 |
| | | | Full load | 260 {2.6, <38>} or 270 {2.7, <39>}*1 |
| | | Rear | Up to 3 persons | 230 {2.3, <33>} |
| | | | Full load | 330 {3.3, <48>} |
| | Remaining tread | | (mm {in}) | 1.6 {0.063} |
| Wheel and tire | Wheel and tire runout | Lateral direction | (mm {in}) | 2.0 {0.079} |
| | | Radial direction | (mm {in}) | 1.5 {0.059} |
| | Wheel and tire imbalance | Inside | (g {oz}) | Knock-type*2: 9 {0.3} max. |
| | | Outside | (g {oz}) | Adhesive-type*3: 14 {0.49} max. |
| | Lug nut tightening torque | | (N·m {kgf·m, ft·lbf}) | 108—147 {12—14, 80—108} |

*1 : Verify that the tire pressures are correct by checking the label attached to the door frame which is visible when the driver's door is opened.

*2 : Do not install three or more weights. The weight of one balance weight must be 60 g {2.1 oz} or less, and the total weight of two balance weights must be 100 g {3.53 oz} or less.

*3 : Do not install three or more weights. Do not affix the weights such that they are parallel to each other or overlapping. The total weight of all the weights is 160 g {5.64 oz} or less.

**Temporary spare tire and wheel**

| Item | | | | Specification | | |
|---|---|---|---|---|---|---|
| Wheel | Size | | | 14 × 5J | 15 × 4T | |
| | Inset | | (mm {in}) | 40 {1.6} | | |
| | Pitch circle diameter | | (mm {in}) | 100 {3.94} | | |
| | Material | | | Steel | | |
| Tire | Size | | | 165/65R14 79M | T125/70D15 95M | T125/90R15 96M |
| | Air pressure | | (kPa {psi}) | — | 420 {60} | |
| | | | (kPa {bar, <psi>}) | 250 {2.5, <36>} | — | |
| | Remaining tread | | (mm {in}) | 1.6 {0.063} | | |
| Wheel and tire | Wheel and tire runout | Lateral direction | (mm {in}) | 2.5 {0.098} | | |
| | | Radial direction | (mm {in}) | 2.0 {0.079} | | |
| | Lug nut tightening torque | | (N·m {kgf·m, ft·lbf}) | 108—147 {12—14, 80—108} | | |